





- 3000 lumen brightness
- XGA resolution
- Network Control, Maintenance and Security, RJ-45
- Lamp access on top & easy, high performance filter access on side
- Wireless 802.11 Network operation
- Monitor loopthrough
- Remote mouse control
- HDTV ready, HDMI input
- Built-In Anti-theft security





8913-W DUKANE

ImagePro 8913-W Portable LCD projector

The ImagePro 8913-W is a LCD projector that can be used in a variety of applications. With sufficient brightness for classrooms and conference rooms the 8913-W is designed to be reliable and easy to maintain.

Computer-less presentations using your SD Card or USB

Flash Drive. Wireless operation using 802.11 b/g via an SD receiver. Can connect to 4 PC's wirelessly. Lamp and filter access points are conveniently located,



plus the new long life filter with 400 hours between maintainance makes this a wise multimedia investment.

Key features:

- XGA (1024 x 768) resolution
- 3000 ANSI lumens of brightness
- Network connection for control, maintenance, and security, RJ-45/wireless
- Easy maintenance in ceiling mount with lamp access on top & 400 hour filter access on side
- Monitor loopthrough & remote mouse control
- Built-In Anti-theft security
- Wireless 802.11 b/g operation
- Auto Vertical keystone correction
- HDTV ready & progressive scan with HDMI input
- Kensington lock slot & security bar
- Five Year Warranty and One Year Peace of Mind Service

8913-W Projection Table

Image Size 4:3		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
30	24	2.8	3.4
60	48	5.8	7.0
80	64	7.8	9.3
100	80	9.8	11 <i>.7</i>
120	96	11. <i>7</i>	14.1
150	120	14.7	17.6
200	160	19.5	23.5
300	240	29.3	35.3

1.5

Throw Ratio (distance to width),

Specifications subject to change without notice.

DUKANE

Dukane Corporation Audio Visual Products Division 2900 Dukane Drive St. Charles, Illinois 60174

Toll-free: 800-676-2485 Fax: 630-584-5156 avsales@dukcorp.com www.dukcorp.com/av



1.8

Specifications

Image Element Brightness

Resolution

Contrast

0.63" polysilicon active-matrix TFT x3

3000 ANSI lumens

(2500 lumens in Whisper Mode) 1024 x 768 pixels (H X V), XGA

400:1

8913-W

image width

Keystone Correction Digital, vertical +/-30 deg

horizontal +/-20 deg

Aspect Ratio 4:3, 16:9 selectable
Computer SVGA, VGA, XGA, SXGA, UXGA,

Compatibility and MAC13" and MAC16"
Video Compatibility NTSC, NTSC4.43, PAL, SECAM
Component Video, HDTV (1080i, 720p, 576i, 480i/p)
Image Control Freeze function, electronic

magnification and pan ol Using USB, Type B

Mouse Control
Projection Modes
Color Reproduction
Using USB, Type B
Front/rear/ceiling
24 bit (16.7 million)

Lamp 220W UHB

Lamp Life 2000 hours (typical) 3000 hours

(whisper mode)
1 speaker, 7 watt

Audio 1 speaker, 7 wat Throw Distance 34" to 423"

Inputs, Video
(1) Component, RCA x 3
(1) S-video, Mini DIN 4-pin
(1) Composite video, RCA x 1

(1) HDMI digital video (2) RGB, 15 pin D-sub

Inputs, Computer
Inputs, Audio
(2) RGB, 15 pin D-sub
(2) Stereo mini jack
(1) RCA x 2 (for video)
(1) Stereo mini jack
Outputs, Monitor
RGB, 15 pin D-sub

RS-232, 9 pin D-sub USB Mouse control, Type B

Wireless 802.11 b/g with SD card Network Connection LAN, RJ-45

Control

Other USB Type A, Storage, SD Card Slot Security Kensington lock slot & Security Bar

Fan Level 33dB, ultra quiet

29dB in Whisper Mode
Filter Service Filter cleaning at 400 hours

Operating Temperature 41-95 deg F

Power AC 100-120V, AC 220-240V

50/60 Hz, 350 watt

Size (WxHxD) 13.4" x 4.6" x 10.6"

Weight 8.8 lbs. Shipping Weight 18 lbs.

Carton Size 19" x 14" x 10"

Accessories Included Remote control, batteries, power cord,

RGB cable, RCA video cable,

operators manual and soft carry case.

Safety UL/C-UL, FCC Class B

Optional Accessories Lamp 456-8755G, Universal Ceiling Mount

RPM-U, Wireless card: VA08331

Filter; MU04951

Five (5) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply).Includes Dukane's FREE 1 year *Peace-of-Mind Loaner Program*.

