



USB 2.0 4 PORT HUB RHUB210

User Manual



System Requirements

PC

- Windows® 98SE, 2000, ME, XP
- USB 2.0 Compliant System

Mac

- Mac OS 8.6 to 9.x®, Mac OS X or greater
- USB 2.0 Compliant System

Features

- USB 1.1 and 2.0 Compliant
- Fully Backward Compatible with USB 1.1
- Up to 480 Mbps (Megabits-Per-Second) Data Transfer Rate
- 40 Times Faster Than The USB 1.1
- Four Independent, Fully Functional, Downstream Ports
- Hot Swappable Plug-n-Play
- 4 USB Type A Ports
- PC Power Management
- Power Adapter: DC 5V/2A

Hardware Installation

1. Plug the Hi-Speed USB 2.0 Cable (type B end) into the upstream port on the Hi-Speed USB 2.0 Hub.
2. Plug the Hi-Speed USB 2.0 Cable (type A end) into your computers Hi-Speed USB 2.0 Port.
Important Note : The Hub must be connected to a USB 2.0-compliant host in order to function in high-speed Mode (480Mbps data rate). If connected to a USB 1.1-compliant host, the Hub will operate only in low or full-speed mode (1.5/12Mbps)
3. Upon powering up your computer, the USB 2.0 hub will be recognized by the computer's operating system
4. Once complete, you are ready to plug all peripheral devices into your new USB 2.0 pocket hub

Specification

Ports	4 Type A USB ports
Output voltage(per port)	+5V DC
Output voltage(per port)	500mA (max.)
Operating Temperature	5~40 oC
Storage Temperature	-20-60 oC
Humidity	0~80% RH

Thank you for purchasing a quality Rosewill Product.

Please register your product at : www.rosewill.com for complete warranty information and future support for your product.