

Whisper-quiet Mini PC platform with an Intel Atom dual-core processor

To put it in a nutshell, the Shuttle XS35V2 is an extremely slim and ergonomic Mini PC that works highly energy-efficiently. With a power consumption that is barely not worth mentioning, its noise level is close to zero. The XS35V2 has an Intel Atom D525 dual-core processor (2x 1.8 GHz) beating at its heart while also using integrated GMA 3150 graphics. Because of its completely fanless case layout, it is virtually maintenance-free and noiseless. The 38mm thin case of the XS35V2 provides room for one slim-line optical drive and one 2.5in hard disk (a second hard drive can be fitted, if the optical drive is left out). WLAN (n) and a card reader are already built in. It sports an array of connectors too which include 5x USB, VGA, Gigabit LAN and audio ports.

Barebone XS 35V2

Slim PC



Fanless



Feature Highlights

Chassis	<ul style="list-style-type: none"> <input type="checkbox"/> Slim 1.5 litre chassis <input type="checkbox"/> Dimensions: 25.2 x 16.2 x 3.84 cm <input type="checkbox"/> Hole for the Kensington Lock <input type="checkbox"/> Optional: VESA75/100 mounting kit PV01
Operating system	<ul style="list-style-type: none"> <input type="checkbox"/> Without operating system (compatible with Windows 7, Windows XP and Linux)
CPU	<ul style="list-style-type: none"> <input type="checkbox"/> Intel ATOM 525 Dual Core (2x 1.8GHz)
Chipset	<ul style="list-style-type: none"> <input type="checkbox"/> Intel NM10 Express Chipset
Graphics	<ul style="list-style-type: none"> <input type="checkbox"/> Integrated Intel GMA3150 Graphics
Memory	<ul style="list-style-type: none"> <input type="checkbox"/> 1x SO-DIMM socket (204 pins) <input type="checkbox"/> Supports max. 4GB DDR3-667/800
Storage	<ul style="list-style-type: none"> <input type="checkbox"/> Supports one slimline DVD drive <input type="checkbox"/> Supports 2.5" SATA hard disk or SSD <input type="checkbox"/> With 4-in-1 card reader
Connectors and WLAN	<ul style="list-style-type: none"> <input type="checkbox"/> D-Sub VGA <input type="checkbox"/> 5x USB 2.0 (1x front, 4x rear) <input type="checkbox"/> Microphone input <input type="checkbox"/> Headphones output (Line-out) <input type="checkbox"/> Gigabit-LAN <input type="checkbox"/> WLAN 802.11 b/g/n
Power supply	<ul style="list-style-type: none"> <input type="checkbox"/> External 40W fanless power supply
Applications	<ul style="list-style-type: none"> <input type="checkbox"/> Basic and Home-Media

Images are only for illustration purposes.
The optical drive is not included.



©2011 by Shuttle Computer Handels GmbH (Germany). All information subject to change without notice. Pictures for illustration purposes only.

Shuttle Barebone XS35V2 - Product Features



Slim and stylish

Designed as a space-saver, this sleek 1.5 litre nettop PC only measures 3.8cm in width. It maximizes space whether it is placed upright using its stylish stand or affixed to the back of a display with the optional VESA mounting kit (PV01). Due to its small size and flexible design, this practical nettop offers exceptional functionality and is well-suited for home users, small offices, reception areas, classrooms, libraries, showrooms, call centres, public institutions and more.




Fanless and quiet

The Shuttle Barebone XS35V2 comes totally fanless making it perfect to be used in noise-sensitive environments such as living rooms, hospitals, libraries etc. As an additional benefit, fanless cases rarely gather dust on the inside and stay cleaner than others. So it's not only quiet and low in energy use, but also dust-free and virtually maintenance free.

**Intel Atom D525
Dual Core**

**DDR3
SO-DIMM**



The Atom processor integrates the graphics controller

Shuttle XS35V2 is equipped with Intel's new Atom D525 processor (1,8GHz, codenamed Pineview). It comes with both the memory controller and graphics core on-die which helps to keep heat dissipation and memory latency low. The CPU is connected to the Southbridge NM10, codenamed Tiger Point.


Dual Core. Do more.

Shuttle always uses the dual-core variant of Intel's Atom processors and thus integrates the Atom D525. This boosts the system performance significantly with particular regards to multi-threaded applications.

Highly energy-saving

The XS35V2 barely consumes, depending on system load, about 16-20 Watts. Running the device*) 5 days a week for eight hours a day, the annual consumption would amount to less than 40kWh which would mean just 8 Euros on the power bill (20 Euro ct/kWh) - way less than a conventional desktop PC draws.

*) Based on a configuration with 2GB of memory, 160GB hard disk and Windows 7





What does "Barebone" mean?

Shuttle's barebones line such as the XS35V2 is targeted at experienced users seeking to build a complete system to meet their individual requirements. The bulk of components is yet built in, simply the following hardware is to be installed upon purchase in this case:

- One 6.35cm/2.5" Serial ATA hard disk or Solid State Disk (SSD)
- One DDR3-667/800 SO-DIMM memory module (204 pins)
- USB keyboard and USB mouse
- Optional Slim-line DVD writer with 12.7mm height
- Operating system (Windows 7, Windows XP or Linux)



4-in-1 card reader

The built-in 4-in-1 card reader at the front side makes it easy to transfer files from your camera so you can share videos and photos on your XS35V2 with ease.



Kensington Lock

This is a small, metal-reinforced hole as part of an anti-theft system. As known from notebooks, this Mini-PC can also be safely locked by tying it to a solid object.

(The lock-and-cable apparatus is not included.)



Optional second hard disk (Accessory PHD2)

The optional accessory PHD2 supports a second 2.5" hard disk. Please note, that the bay for the optical drive will be occupied then.



Tiny power adapter

The external 40W power adapter is virtually noiseless and can easily be hidden behind the desk thanks to its tiny dimensions.

Dimensions: 89.5 x 37 x 26.5 mm (LWH) = 88ml



Easy installation

Remove just one screw to unmount the two chassis covers.



Optional VESA mount (Accessory PV01)

Its optional VESA75/100 wallmount allows it to be installed on to walls or just affixed on the rear side of a monitor which is particularly interesting for the industry segment, company buildings and public institutions.



24/7 nonstop operation

Shuttle XS35V2 is officially approved for 24/7 permanent operation. Thanks to its low power consumption and completely passively cooling, this PC runs highly reliable making it perfectly suitable for digital signage and POI/POS applications.

Conditions for permanent use:

- Ambient temperature while under load: 5-35°C
- Air humidity while under load: 10-80% (not condensing)
- Free circulation of air amongst the PC must be guaranteed
- Ventilation holes must be clear
- If a hard disk is installed, this must also be approved for permanent operation by its manufacturer (max. one hard disk)



Note on operating position

Please make sure the system is always placed upright using either its stand or the optional VESA mount. Ventilation holes must not be blocked to ensure sufficient cooling.

Shuttle Barebone XS35V2 Specifications


<i>Chassis</i>	<p>Dimensions without stand: 25.2 x 16.2 x 3.85 cm (DxHxW) = 1,57 litre</p> <p>Dimensions with stand: 25.2 x 18.5 x 10.04 cm (DxHxW)</p> <p>Weight: 2.1 kg net, 2.8 kg gross</p> <p>Hole for the Kensington Lock at the back panel</p> <p>Optional accessory: 75mm and 100mm VESA mounting kit (PV01)</p> <p>Warning: Please make sure the system is always placed upright using either its stand or the optional VESA mount.</p> <p>Ventilation holes must not be blocked to ensure sufficient cooling.</p>
<i>Operation System</i>	<p>This system comes without operating system.</p> <p>It is compatible with Windows 7, Windows XP and Linux</p>
<i>Processor</i>	<p>Intel Dual-Core Atom processor D525 (Codename: Pineview-D)</p> <p>45nm manufacturing process, FCBGA559</p> <p>Intel Hyper-Threading technology: 2-threads per core</p> <p>Intel 64 architecture, Core clock: 2x 1.8GHz, L2 Cache: 1024kB, TDP: max. 13W</p> <p>Integrated North Bridge with controller for memory and graphics</p>
<i>Cooling</i>	<p>Passive, completely fanless cooling</p>
<i>Chipset</i>	<p>Intel® NM10 Express Chipset Platform Controller Hub (PCH), Code name: Tiger Point</p>
<i>BIOS</i>	<p>AMI BIOS in a 2Mbit Flash ROM supports PnP, ACPI 3.0</p> <p>Supports external USB flash memory card boot up</p> <p>Supports Preboot eXecution Environment (PXE) to boot via network</p>
<i>Memory</i>	<p>Supports one module DDR3-667/800 (PC3-5300/6400), max. 4GB</p> <p>SO-DIMM slot with 204 pins</p> <p>Memory modules that are designed for higher frequencies can also be used.</p> <p>The installed modules then run at an actual frequency of 800 MHz.</p>
<i>Optical drive (opt.)</i>	<p>Optionally supports an optical DVD drive in slim line format</p> <p>Serial ATA interface, 12.7mm height, Slimline SATA connector</p>
<i>Hard disk drive</i>	<p>Supports one SATA hard disk or one SATA SSD drive in 6.35cm/2.5" format, max. 5400 RPM</p> <p>The SATA 2.0 interface supports up to 300MB/s data transfer speed</p> <p>Supports a drive with 9.5mm height (12.5mm is not supported)</p> <p>The optional accessory PHD2 supports a second 2.5" hard disk (the bay for the optical drive will be occupied then)</p>

<i>Integrated Graphics</i>	<p>The Graphics Processing Unit (GPU) is integrated into the processor</p> <p>Intel GMA 3150, 400MHz render clock frequency</p> <p>Intel Dynamic Video Memory Technology 4.0 (DVMT 4.0)</p> <p>Share system memory max. 256MB</p> <p>Supports DirectX 9 and 2D/3D instruction set, Pixel Shader 2.0</p> <p>MPEG2 hardware acceleration, Intel Clear Video / ProcAmp technology allows user adjustment of hue, saturation, brightness and contrast</p> <p>Analog VGA: supports up to 2048x1536, 60Hz resolution</p>
<i>Integrated Audio</i>	<p>IDT92HD81 Audio Codec with Azalia support</p> <p>Two analog audio connectors (3.5mm):</p> <ol style="list-style-type: none"> 1) Line out (head phone) 2) microphone input
<i>Card Reader</i>	<p>4-in-1 card reader at the front side</p> <p>Supports SDHC, SD, MS und MS-pro memory cards</p> <p>PCIe Interface</p>
<i>Wired Network</i>	<p>RJ45 connector supports Gigabit LAN at 10/100/1000 Mbit/sec.</p> <p>Supports Deep Sleep Mode (DSM)</p>
<i>Wireless Network</i>	<p>Supports IEEE 802.11b/g/n (Realtek RTL8188CE)</p> <p>Half size Mini-PCIe-Card</p>
<i>Connectors</i>	<p>VGA Analog Video (D-Sub 15 pol., analog)</p> <p>5x USB 2.0 (1x front, 4x rear)</p> <p>Network (LAN, RJ45)</p> <p>Audio Line-out (head phone)</p> <p>Microphone input</p> <p>DC input for power adapter</p>
<i>LEDs and Buttons</i>	<p>Power button</p> <p>Power LED (white), Hard disk LED (blue)</p>
<i>Power supply</i>	<p>External 40W AC/DC power adapter (fanless)</p> <p>AC Input: 100~240V AC, 50~60Hz</p> <p>Dimensions: 89.5 x 37 x 26.5 mm (LWH)</p>
<i>Certification and Compliance</i>	<p>EMI: CE, FCC, BSMI, C-Tick</p> <p>Safety: CB, BSMI, ETL</p> <p>Other compliances: RoHS, Eup Lot6</p>

Comparison: **Shuttle** Nettop Barebone PC XS35 Series

	Graphics	Processor	Memory (SO-DIMM)	Network
XS35	Integrated Intel GMA3150	Intel Atom 510 (2x 1.66GHz)	Max. 2GB DDR2-667/800	Fast Ethernet
XS35GT	Next-Generation NVIDIA ION	Intel Atom 510 (2x 1.66GHz)	Max. 2GB DDR2-667/800	Fast Ethernet
XS35V2	Integrated Intel GMA3150	Intel Atom 525 (2x 1.80GHz)	Max. 4GB DDR3-667/800	Gigabit LAN
XS35GTV2	Next-Generation NVIDIA ION	Intel Atom 525 (2x 1.80GHz)	Max. 4GB DDR3-667/800	Gigabit LAN

Shuttle Barebone XS35V2 – Connectors



- 1 4-in-1 card reader
- 2 USB connector
- 3 Power button with power and hard disk LED
- 4 Bay for optical slim drive *)
- 5 Stand

- A Microphone input
- B Head phone output (line out)
- C Network connector (RJ45)
- D 4x USB connectors
- E Hole for the Kensington lock
- F VGA connector
- G Connector for power adapter
- H Stand

*) Note: The optical drive is not included.



Warning:
Please make sure the system is always placed upright using either its stand or the optional VESA mount. Ventilation holes must not be blocked to ensure sufficient cooling.



Images are only for illustration purposes. The optical drive is not included.