

The Biggest Thing in Rack Mounted LCD Monitors

LCD-1900VR LCD-1900V



Active Matrix 19" Color LCD Monitors

- LCD-1900VR tilts 90° in rack for optimum viewing, occupies 9 rack units
- Hot key allows toggling between video, S-Video, component, and PC modes
- PIP: Picture in picture capability
- On-screen display for: brightness, contrast, back light, hue
- Low power consumption
- LCD-1900VR case made of durable metal
- LCD-1900V case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- LCD-1900VR: Response Time: 15ms / 10ms (rising/falling)
- LCD-1900V: Response Time: 25ms / 25ms (rising/falling)
- LCD-1900V has built-in removable desk stand and built-in interface for wall or arm mounting VESA 100mm FPMPI compliant
- Includes switching power supply 90-240V, 12V, 50W

Optional Accessories

- DC-1500 Factory approved car cord
- HM-400 Under-cabinet hinge mount
- WM-30 Wall mount bracket (fixed)
- WM-302 Wall mount with swing arm & 4-way adjustable



HM-400



WM-302

**For touch screen for LCD-1900VR: order LCD-1900VRTS
Touch screen not available for LCD-1900V.**

- Display: 19.0" TFT LCD active matrix
- Back Light: Built-in (CCFT)
- Input Signal: Composite NTSC/PAL (auto switching), component, S-Video, Analog RGB
- Resolution: SXGA 1280(H) x 1024(V) dots
- PC compatibility: IBM / MAC compatible
- Dot Pitch: 0.264(H) x 0.264(V)mm
- Brightness rating: 450 cd/m² (Nit)
- Colors: 16.7M
- Contrast Ratio: 500:1
- Number of Pixels: 1,310,720 dots
- Viewing angle L/R/T/B: 85/85/85/85 degrees
- Pixel Configuration: Stripe
- Input Signal Level: 1.0V P-P (positive) 75 Ohm
- LCD-1900VR: Dimensions (WHD): 19" x 15.75" x 2.5" (Occupies 9 RU)
- LCD-1900V: Dimensions w/o desk stand (WHD): 444 x 376 x 73mm / 17.5" x 14.8" x 2.9"
- LCD-1900V: Dimensions w/ desk stand (WHD): 444 x 426 x 215mm / 17.5" x 16.8" x 8.5"
- Actual visible screen size (WH): 338 x 270 mm / 14.75" x 11.75"
- Operating temperature: 50 ~ 104°F or 10 ~ 40°C
- Power Requirement: Regulated 12VDC, A (TBA), negative ground
- Power Consumption: 48 W (max), 3 W (power saving off mode)
- Includes switching power supply: 100 ~ 240VAC (auto-sensing), 50 ~ 60Hz, A (TBA)
- LCD-1900VR: Rear Terminal Connections: BNC video IN/OUT jacks, S-Video, 15-pin mini D-sub (female), 4-pin DC IN jack, RCA video IN, RCA L/R audio IN, headphone jack, 9-pin component IN jack
- LCD-1900V: Rear Terminal Connections: BNC video IN/OUT jack, RCA video IN, 3.5 stereo audio IN/OUT jacks, 2.1mm DC IN jack, S-Video jack, 15 pin mini D-sub (female), 9-pin component IN jack
- LCD-1900VR: Weight: Net: 8.6 kg. / 19 lbs.
Gross: 11.8 kg. / 26 lbs.
- LCD-1900V: Net: 7.5 kg / 16.5 lbs.
Gross: 10 kg. / 22 lbs.