



Xtra-Wide® Spotting Scope Instructions

Congratulations on the purchase of your Bushnell® Xtra-Wide® Spotting Scope, a versatile high-performance spotting scope offering an increased field of view. The Xtra-Wide® Spotting Scope offers hunters, birders and outdoor enthusiasts 87 feet field of view at 1,000 yards, nearly twice the field of view at 45x than any other spotting scope on the market. The Xtra-Wide® Spotting Scope features multi-coated lenses for exceptional resolution, brightness and clarity. The Xtra-Wide® Spotting Scope comes complete with an aluminum and rubber composite design and flip down lens cap and a protective case that can remain on the unit while in use.

FOCUSING

The focusing system is easy and accurate. Rotate the focusing wheel until the image seems to be in sharp, crisp focus. There is no need to overshoot or hunt for the correct focus. Once the image appears sharp, stop focusing - the image is in the best focus with minimum eyestrain.

SIGHTING

Your Xtra-Wide® Spotting Scope is equipped with a sighting line above the eyepiece. Simply aim the line at the object and look through the eyepiece and there it is!

ZOOM EYEPIECE

The Xtra-Wide® Spotting Scope provides a magnification range of 15 to 45 power. To change magnification, grasp and rotate the eyepiece to the desired magnification. It may be necessary to refocus the spotting scope after changing magnification, especially when going from 15 to 45 power.

CAUTION: DO NOT LOOK AT THE SUN THROUGH THIS SPOTTING SCOPE AS SEVERE DAMAGE TO YOUR EYES MAY RESULT!

TRIPOD ATTACHMENT

The Xtra-Wide® Spotting Scope has an integral tripod mount equipped with a video-pin hole. If your tripod has a video-pin hole, align the pin and the tripod screw to the appropriate holes on the spotting scope. The video-pin hole will prevent rotation of the spotting scope on the tripod during use.

CARE AND MAINTENANCE

Your Xtra-Wide® Spotting Scope does not require any maintenance beyond occasional cleaning. With a cloth, brush off the outside of the spotting scope to remove any dirt or dust. You can use a mild household cleaner - sparingly - to remove any stubborn dirt on the body of the spotting scope. Keep the optics clean; do not allow dust or water to stay on the glass. We recommend using a camera lens cleaner kit to clean the outside of the objective and eyepiece lenses. Follow the directions with the kit.

Do not disassemble the spotting scope. Unauthorized disassembly not only voids the warranty but also may cause damage from the lack of special tools and techniques.



Model # 78-5456

WARRANTY / REPAIR

LIFETIME LIMITED WARRANTY

Your Bushnell® spotting scope is warranted to be free of defects in materials and workmanship for the lifetime of the original owner. The Lifetime Limited Warranty is an expression of our confidence in the materials and mechanical workmanship of our products and is your assurance of a lifetime of dependable service. In the event of a defect under this warranty, we will, at our option, repair or replace the product, provided that you return the product postage prepaid. This warranty does not cover damages caused by misuse or improper handling, installation or maintenance of the product.

Any return made under this warranty must be accompanied by the items listed below:

- 1) A check in the amount of \$10.00 to cover the cost of handling
- 2) Name and address for product return
- 3) An explanation of the defect
- 4) Product should be well packed in a sturdy outside shipping carton to prevent damage in transit and return postage prepaid to the address listed below:

IN U.S.A. Send To:

Bushnell Performance Optics
8500 Marshall Drive
Lenexa, Kansas 66214

IN CANADA Send To:

Bushnell Performance Optics
25A East Pearce Street, Unit 1
Richmond Hill, Ontario L4B 2M9

For products purchased outside the United States and Canada please contact your local dealer for applicable warranty information. This warranty gives you specific legal rights. You may have other rights which vary from country to country.

©2001 Bushnell Performance Optics