



DVR4-Pro-Net™

Networkable 4 Channel DVR

Your home, office & business safety net!



Swann
BONUS

4 Security Warning Stickers
in this pack



- Networkable DVR for remote viewing over the web
- Set & forget with pre-installed, 160GB hard drive
- State of the art features including motion detection, alerts, on-screen programming
- Nannycam, monitor office, oversee yard, deter thieves & more
- High resolution MPEG4 switchable to MJPEG video format



MPEG4/MJPEG DVR Technology

- Compression format providing crystal clear images with real time performance

Multiplex

- Allow live display, record, playback, backup and network operation at the same time

Long-Recording Hours

- 500GB HDD can record more than 170 days (4CH, CIF Best Quality, 1.5IPS)

Backup Function

- Support network remote recording & backup

Remote Surveillance

- Remote surveillance with the licensed software AP and IE browser
- Web surveillance with 5 users simultaneously

Intelligent Motion Trigger Recording

- With advanced settings for motion detection, scheduled motion detection recording (4 different adjustable factors for the motion detection sensitivity) and convenient search function, customized security environment is achieved
- Alarm triggered recording will send alerts with images to the designated e-mails and FTP address
- Support pre-alarm recording (8Mb)

Covert Recording

- A mask replaces the live image with a blank screen, and the monitor shows nothing but recording is still on

AV Support

- Support 1 audio-in, 1 audio-out to record sounds
- Support VGA converter (optional)

General

- Support multi-language OSD
- System auto recovery after power reconnected
- Support daylight-saving function
- Support manual / timer / motion / alarm / remote recording functions
- Watermark function ensures authentication of the recorded images
- Support TCP/IP, PPPoE, DHCP and DDNS network connection



DVR4-Pro-Net™

Networkable 4 Channel DVR

Your home, office & business safety net!



Product Specifications

Video System:	NTSC / PAL (switchable)
Video Compression Format:	Frame: MJPEG ; CIF: MPEG4
Video Input:	4 Channels. Composite video signal Vp-p 75Ω BNC 4 Channels. Composite video signal Vp-p 75Ω BNC
Video Loop Out:	Composite video signal Vp-p 75Ω BNC
Video Output:	Main Monitor Output: Composite video signal Vp-p 75Ω BNC Call Monitor Output: Composite video signal Vp-p 75Ω BNC
Maximum Recording Rate	Frame: 720×480 pixels with 30 IPS <NTSC> / 720×576 pixels with 25 IPS <PAL> CIF: 352×240 pixels with 120 IPS <NTSC> / 352×288 pixels with 100 IPS <PAL>
Adjustable Recording Speed	Frame: 30, 15, 7, 3 IPS <NTSC> / 25, 12, 6, 3 IPS <PAL> CIF: 120, 60, 30, 15 IPS <NTSC> / 100, 50, 25, 12 IPS <PAL>
Image Quality Setting	Best, High, Normal and Basic
Hard Disk Storage	IDE type, ATA66, supported HDD*1, support HDD capacity over 400GB
HDD Quick Cleaning	Quick clean up the "index system" of the recorded files. 250GB under 2 seconds
Recording Mode	Manual / Timer / Motion / Alarm / Remote
Refresh Rate	120 IPS for NTSC / 100 IPS for PAL
Audio I/O	1 audio input, 1 audio output (Mono)
Motion Detection Area	16 × 12 grids per camera for all channels
Motion Detect Sensitivity	4 adjustable variables with precise calculation for motion detection
Pre-alarm Recording	Yes (8Mb)
Backup Device	Network remote backup

Web Transmitting / Compression Format Ethernet
Web Interface Remote Alarm Notification
Network Connection PTZ control Dwell Time (Sequential Channel Switch) Alarm I/O Digital Zoom Key Lock Video Loss Detection Camera Title Video Adjustable Date Display Format Power Source Power Consumption Operating Temperature Dimensions (mm) System Recovery Optional Peripheral

Motion JPEG 10/100 Base-T. Support remote control and live view via Ethernet Support licensed software AP and IE browser E-mail images, and upload images to FTP site's specific account Support TCP/IP, PPPoE, DHCP and DDNS function Support PELCO-D protocol
Programmable with adjustable dwell time 4 inputs, 1 output 2x digital zoom (live mode) Yes Yes Support up to 6 letters Hue / Color / Contrast / Brightness YY/MM/DD, DD/MM/YY, MM/DD/YY, and Off DC 19V 42 W 10°C~ 40°C (50°F ~104°F) 343mm (W) × 59mm (H) × 223mm (D) System auto recovery after power reconnected VGA converter

Package Contents

- DVR
- 4 x Security Stickers
- Manual
- Power Supply
- BNC to RCA Cable
- BNC Connectors

**Installed Seagate HDD
carries 5 year warranty**

