

WT2

Arrayable two-way compact theatre enclosure

features



- ▶ Arrayable compact trapezoid enclosure
- ▶ High SPL output capability
- ▶ 70° coverage angle
- ▶ Multi-laminate birch plywood construction
- ▶ Switchable active/passive operation
- ▶ Certified MAN quick-connect flying option

applications

- ▶ Theatre sound systems
- ▶ Club sound reinforcement
- ▶ Music playback in nightclubs

The WT2 is a powerful, compact theatre system which can be used as a stand-alone enclosure in a distributed system or arrayed in multiples. The switchable active/passive two-way cabinet is very efficient, combining smooth dynamic full-frequency performance with excellent articulation, utilising high power drive units for maximum SPL.

overall dimensions



technical specifications

TYPE	Compact two-way trapezoid, switchable active/passive
FREQUENCY RESPONSE (5)	70Hz-18kHz \pm 3dB -10dB @ 52Hz
DRIVERS	12" (300mm) / 3" (75mm) voice coil 1" (25mm) exit HF compression driver
RATED POWER (2)	LF/(LF + HF): 400W AES, 1600W peak HF: 60W AES, 240W peak
RECOMMENDED AMPLIFIER	400-600W into 4 ohms
SENSITIVITY (6)	LF/(LF + HF): 98dB HF: 107dB
MAXIMUM SPL (7)	123dB continuous, 129dB peak
NOMINAL IMPEDANCE	LF/(LF + HF) 8 ohms HF: 8 ohms
DISPERSION (-6dB)	70° horizontal, 40° vertical
CROSSOVER	2kHz active/passive
FINISH	Textured black paint
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 x Neutrik NL4
FITTINGS	10 x M8 threaded inserts 1 x mounting pole socket 2 x MAN blanking plates 2 x rear kelp fittings 2 x front lid fittings
DIMENSIONS	(W) 365mm x (H) 554mm x (D) 364mm (W) 14.4ins x (H) 21.8ins x (D) 14.3ins
WEIGHT	24.5kg (54lbs)

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2006 Martin Audio Ltd.



www.martin-audio.com

touring and theatre