



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SUPDMB710

Detachable PDU option for compatible SmartOnline UPS Systems



Highlights

- Converts compatible SmartOnline high-voltage UPS systems to provide North American 20 and 30A outputs
- For use with input voltages of 200-240 VAC
- Hardwired input / 2 L6-30R and 4 L6-20R output connections
- Manual bypass feature ensures maximum equipment availability

Description

The SUPDMB710 converts the output of SmartOnline SU8000RT3U and SU10000RT3U power modules to North American L6-20R and L6-30R output connections. Manual bypass feature ensures maximum availability of connected equipment while UPS maintenance occurs. Can accept input voltages of 200-240 VAC. Hardwire input / 2 L6-30R and 4 L6-20R output connections.

Applications

- Ideal for use with Tripp Lite's SU8000RT3U and SU10000RT3U power modules in 200-240V applications where hardwire input / C19 output connections are required

System Requirements

- For use with SmartOnline SU8000RT3U and SU10000RT3U Rack/Tower UPS systems in applications requiring a detachable PDU with manual bypass

Package Includes

- SUPDMB710 detachable PDU
- Mounting hardware
- Owner's Manual with warranty instructions

Features

- Converts compatible SmartOnline high-voltage UPS systems to provide North American 20 and 30A outputs
- For use with input voltages of 200-240 VAC
- Hardwired input / 2 L6-30R and 4 L6-20R output connections
- Manual bypass feature ensures maximum equipment availability

Specifications

SYSTEM OVERVIEW

Voltage compatibility	200/208/220/230/240 VAC
Frequency compatibility	60 Hz
OUTPUT	
Output nominal voltage	208/240 VAC
Outlet quantity / type	2 L6-30R, 4 L6-20R
Overload protection	2 double pole 30A breakers, 2 double pole 20A breakers
INPUT	
Input connection type	Hardwire
PHYSICAL	
Shipping weight (lbs)	9.75
Shipping weight (kg)	4.42
Shipping Dimensions (HWD/in)	12.25 x 9.25 x 8.25
Shipping Dimensions (HWD/cm)	31.1 x 23.5 x 21
Unit weight (lbs)	8.75
Unit weight (kg)	3.97
Unit Dimensions (HWD/in)	10.25 x 7.5 x 6.5
Unit Dimensions (HWD/cm)	26 x 19.1 x 16.5
Material of construction	Sheet metal
SPECIAL FEATURES	
Appearance	All-black color scheme
CERTIFICATIONS	
Certifications	Tested to UL1778 (USA), CSA (Canada)
WARRANTY	
Product Warranty Period	2 years

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4153.