

REMOTE VIEW



PC Internet Monitoring

# COMPLETE 21" CRT OBSERVATION SYSTEM WITH BUILT-IN DIGITAL VIDEO RECORDER & 4 CCD CAMERAS

## FEATURES

### Monitor

- High resolution (480 TV Lines) 21" Color Real Time quad monitor (30 fps) with built-in Digital Video Recorder
- 'Plug & Play' USB computer interface provides remote viewing via the internet\*
- View up to 4 Camera Locations in Real Time (30fps) simultaneously
- Built-in Multiplexer Function
- Dual Motion Sensing Function Camera & Pixel based sensing activity
- Playback recorded video in Quad or Full Screen
- On-Screen programming: date\*time\*camera
- Digital freeze with two time zoom capability
- Full screen or picture-in-picture sequential camera option
- Standby power switch enables monitor to be turned off while recording
- Multi-voltage system 100-240 volts
- Selectable dwell time
- Remote Control or Main Panel operation
- Two-way audio\*\*
- Alarm inputs to add additional alarm devices
- One alarm output to connect monitor to optional recording devices

### DVR

- 3 Record video settings (Normal, High & Best)
- 7 Selectable recording time selections
- Event list displays camera activity
- Security Password protected
- Supports 20 - 250 GB HDD
- High Quality Recording with Modified MJPEG Compression (5~20K byte/frame)
- Digital Recording and Playback allows for instant retrieval of recorded images



### CAMERA

- Professional Grade, Weather Resistant\*\*\* Cameras with CCD Image Sensors
- 3 x 1/4" CCD Color Cameras/ 1 x 1/4" CCD Color Dome Camera
- Built-in speaker and microphone to allow for two way audio communication (observation camera) one way audio (dome camera)
- Mounting Bracket included



 **LOREX**<sup>®</sup>

SG2ICD7444UQ-A80

[www.lorexcctv.com](http://www.lorexcctv.com)

# SPECIFICATIONS:

## Monitor:


|                        |                               |
|------------------------|-------------------------------|
| Picture Tube:          | 21" Color (diagonal)          |
| Horizontal Resolution: | More than 480 Lines           |
| Camera capable:        | 4 (DIN / BNC)                 |
| Audio inputs:          | 4 RCA                         |
| Quad Speed:            | 30 fps                        |
| Alarm Inputs/Outputs:  | 4/1                           |
| Input signal:          | 1 V p-p at 75 ohms terminated |
| Power source:          | Multi-voltage (100-240 volts) |
| Power Consumption:     | 105 watts                     |
| Operation Temperature: | 41°F - 104°F                  |
| Weight:                | 57 lbs (26 Kg)                |
| Color:                 | Grey                          |

## DVR


|                       |                                   |
|-----------------------|-----------------------------------|
| Hard Disk Storage:    | IDE Type, UTMA 66 above           |
| Video Compression:    | Modified MJPEG (5~20Kbyte/frame)  |
| HDD:                  | Default 80 GB (User optional)     |
| Video Resolution:     | 720 x 480                         |
| Recording Resolution: | 640 x 224                         |
| Record Modes:         | Alarm / External / Timer / Manual |
| Alarm history log:    | 1000 events                       |
| Security Protection:  | Password protection               |
| Display refresh rate: | 60 ips                            |
| Record refresh rate:  | 60 ips                            |

# DIMENSIONS:

## Monitor



## Camera



## Observation Camera

|                    |                                |
|--------------------|--------------------------------|
| Image Device:      | 1/4" CCD                       |
| Picture Elements:  | 510 H x 492 V                  |
| Lens:              | 3.6 mm                         |
| Resolution:        | 350 TV Lines                   |
| Illumination:      | 0.5 Lux @ F2.0                 |
| Power Requirement: | powered from monitor via cable |
| Operating Temp:    | 14F to 113F (-10°C ~ +45°C)    |

## Dome Camera

|                     |                                |
|---------------------|--------------------------------|
| Image Device:       | 1/4" CCD                       |
| Picture Elements:   | 510 H x 492 V                  |
| Lens:               | 3.6 mm                         |
| Resolution:         | 350 TV Lines                   |
| Illumination:       | 1.0 Lux @ F2.0                 |
| Power Requirement:  | powered from monitor via cable |
| Operating Temp:     | 14F to 113F (-10°C ~ +45°C)    |
| Operating Humidity: | 90% RH max.                    |

- \* Broadband Internet Service Recommended
- \*\* Dome Camera supports only listen-in audio at the monitor
- \*\*\* Not recommended for direct exposure to water, rain or snow.

# BACK JACK PANEL:



# PRODUCT INFORMATION:

|                     |   |
|---------------------|---|
| Model#:             | SG21CD7444UQ-A80                                    |
| Weight:             | 64 lbs /29 kgs                                      |
| Package Dimensions: | 21.5 X 26" X 22" / 546m X 660mm X 558mm (W x H x D) |
| UPC:                | 7-78597-07444-4                                     |
| Package Cube:       | 7.11ft / 0.192m                                     |

## Lorex Technology Inc.

300 Alden Road, Markham,  
Ontario L3R 4C1  
Canada.

3700 Koppers Street, Suite 504  
Baltimore, Maryland 21227,  
USA.

©2007 Lorex Technology Inc.

As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE