

New Holland Commercial Front Mower Specifications



MC22 MC28 MC35 G6030 G6035

MODEL	MC22	MC28	MC35	G6030	G6035
GROSS HORSEPOWER	22	28	35	30	36
ENGINE					
Engine type.....	Diesel.....				
Number of cylinders.....	3.....				
Displacement, cu. in. (L).....	61.3 (1.0)	81.1 (1.3)	101.4 (1.7)	91.3 (1.5)	101.4 (1.7)
Air cleaner.....	Dry, dual element.....				
Fuel tank capacity, gal. (L).....	13.3 (50.0).....				
Approved biodiesel blend.....	B5.....				

ELECTRICAL					
Voltage.....	12.....				
Alternator, amps.....	40.....				
Battery, cca.....	490.....				

TRANSMISSION					
Type.....	Hydrostatic.....				
Ranges.....	2.....				
4WD.....	Auto or full 4WD.....				
Direction control.....	Two separate foot pedals.....				
Cruise control.....	Optional.....				
Speed ranges (with large tire), mph (kph)					
Forward, min-max	0-10.7 (0-17.2)	0-10.7 (0-17.2)	0-10.7 (0-17.2)	0-15.2 (0-24.5)*	0-15.2 (0-24.5)*
Reverse, min-max	0-7.0 (0-11.3)	0-7.0 (0-11.3)	0-7.0 (0-11.3)	0-9.8 (0-15.8)*	0-9.8 (0-15.8)*

FRONT AXLE					
Type.....	Flanged.....				
Differential lock.....	Standard.....				
Brake.....	Wet disc.....				
Parking brake.....	Hand-engaged lever.....				
2WD rear axle	Optional	Optional	NA	NA	NA
Tread width (with standard tire), in. (cm)	39 (99.0)	39 (99.0)	NA	NA	NA
Turning radius, in. (cm)	28.7 (72.9)	28.7 (72.9)	NA	NA	NA
Turning angle	57°	57°	NA	NA	NA
Oscillation	9°	9°	NA	NA	NA
4WD rear axle	Optional	Optional	Standard	Standard	Standard
Drive type.....	Automatic or full-time.....				
Tread width (with standard tire), in. (cm).....	39.2 (99.6).....				
Turning radius, in. (cm).....	29.5 (74.9).....				
Turning angle.....	56°.....				
Oscillation.....	8°.....				

STEERING	
Type.....	Hydrostatic power.....

PTO	
Type.....	Independent.....
Speed (at engine rated speed), rpm.....	2209.....
Engagement.....	Mechanical.....

HYDRAULIC SYSTEM					
Type.....	Open center.....				
Pump capacity, gpm (lpm).....	1.9 (7.2)	2.4 (9.1)	2.4 (9.1)	2.4 (9.1)	2.4 (9.1)
Remote valve.....	Optional.....				

*measured with 24x13-12 and 20x8-10 tires.

New Holland Commercial Front Mower Specifications



MC22 MC28 MC35 G6030 G6035

MODEL	MC22	MC28	MC35	G6030	G6035
TIRES					
Rear			20 x 8.0-10 turf		
Front.....			23 x 10.5-12 turf or 24 x 13.0-12 turf.....		

ROLL OVER PROTECTIVE STRUCTURE.....Foldable ROPS.....

TRACTOR DIMENSIONS

(with standard tires), in. (cm)

Overall length			95.1 (241.6)		
Height (ROPS up)	76.0 (193.0)	76.0 (193.0)	76.0 (193.0)	76.0 (193.0)	76.2 (193.5)
Height (ROPS down)			48.2 (122.4)		
Minimum overall width	48.0 (121.9)	48.0 (121.9)	48.0 (121.9)	48.0 (121.9)	51.5 (131.0)
Minimum ground clearance	5.5 (13.9)	5.5 (13.9)	5.5 (13.9)	5.5 (13.9)	5.9 (15.0)
Wheelbase.....			49.2 (124.9)		

WEIGHT, lbs. (kg)

2WD	1550 (703.1)	1570 (712.1)	N/A	N/A	N/A
4WD	1630 (739.4)	1650 (748.4)	1650 (748.4)	1665 (755)	1698 (770)

MOWER DECKS

	60 inch	72 inch	84 inch
Cutting widths, in. (mm)	60 (1524)	72 (1829)	84 (2134)
Deck type options	side, rear, or flail	side or rear	rear
Blades	3	3	4
Cutting height, in. (mm)	1.5 to 4.5 (38 to 114)	1.5 to 4.5 (38 to 114)	.75 to 4 (19 to 102)
Gauge wheels		Semi-pneumatic front caster gauge wheels.....	
Anti-scalp rollers.....		Solid rear adjustable anti-scalp rollers.....	
Tilt-up capability for servicing		Standard.....	

OPTIONAL ATTACHMENTS AND ACCESSORIES

- 24 cu. ft. grass catcher
- 60 in. front quick-attach blade
- 60 in. front quick-attach rotary broom
- Front quick-attach debris blower
- 52 in. front quick-attach snow blower
- 62 in. front quick-attach snow blower
- 4 post ROPS with canopy
- Comfort soft cab

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.