



802.11g Wireless Outdoor Bridge

NWH9250

Product Overview

The NWH9250 is a 2.4GHz 802.11g Wireless Outdoor Bridge that compliant 802.11b/g standards. The NWH9250 covers a large operating distance for Wireless LANs and broadband Internet Access with transfer data rate up to 54Mbps. It links two or more separate networks (typically located in different buildings) to create a single expanded LAN quickly, simply, and economically. The NWH9250 delivers higher transmission rates than an E1 or T1 line, and eliminates the inconvenience of installing an expensive leased line or fiber-optic cable. The NWH9250 fully complies with the IEEE802.11b/g standard. Combining superior wireless technology and advanced features, the NWH9250 Wireless Outdoor Bridge is a reliable, high-performance, cost-effective solution for the most demanding wireless networking environments.



Key Features and Benefits

Superior Coverage and High Speed Transmission

Data rates up to 54Mbps, 5 times of 802.11b product
Features rugged construction and a weatherproof housing proven in outdoor installations exposed to wind, rain, and snow

Offers multiple mounting options for flexible placement to achieve the best possible alignment or coverage

Easy to Use Network Management Tools

Kick Start: If the DHCP server fails or the device is on a different subnet, the Advanced Discovery Protocol allows the NWH9250 to be found and configured.

Bridge Auto Learning: The NWH9250 can intelligently detect its peer bridges' MAC addresses via the advanced wireless technology, saving the user the hassle of entering MAC addresses.

Auto IP address assignment - the NWH9250 will automatically assign itself a new IP address should the DHCP server fail.

On-line firmware upgradability: allows the bridge's firmware to be upgraded via Web-based tool from a remote station without stopping the network.

DHCP client support: automatically obtains a new IP address from a DHCP server.

Remote Configuration

Allows administrators to manage the bridge from anywhere on the network. All that is required is that the bridge be on the same logical IP subnet as the management station.

Security Protection

WEP (Wired Equivalent Privacy): 64, 128 and 256-bit WEP encryption for secure wireless LAN data transmissions.

Detachable Antenna (Optional)

The detachable antenna design allows such options as connecting a high-gain antenna for better signal quality over a wider coverage area.

Outdoor Protection Solution for Harsh Weather

The Outdoor Protection Package bridge to be located outdoors, where it may be subjected to wind, rain, and snow.

Power Over Ethernet

PoE reduces power-cable expenses and increases location options by carrying both data and power to the bridge through a single Ethernet cable.



NATIONAL DATACOMM CORPORATION


Maximizing the Convenience of Networking



802.11g Wireless Outdoor Bridge

NWH9250

802.11g Wireless Outdoor Bridge Application Scenarios



Point-to-point Mode

Bridges in point-to-point mode connect two networks in different locations through a single wireless link. This allows two widely separated sites to share resources, including a single high-speed connection to the Internet.



Point-to-multipoint Mode

Bridges in point-to-multipoint mode connect three or more networks in scattered buildings through wireless links. This allows numerous sites in a wide area to share resources, including a single high-speed connection to the Internet.

Specifications

| | |
|-----------------------------------|---|
| Standards Compliance | IEEE802.11g, 11b |
| RF Spreading Method | Direct Sequence Spread Spectrum (DSSS) |
| Transmission Rate | 54/48/36/24/18/12/11/9/6/5.5/2/1Mbps with auto fallback 22Mbps (Optional) |
| RF Output Power | 802.11b: 17dBm (Typical) 802.11g: 14dBm (Typical) |
| Receive Sensitivity | 54 Mbps OFDM, 10% PER, -70 dBm 48 Mbps OFDM, 10% PER, -72 dBm 36 Mbps OFDM, 10% PER, -77 dBm 24 Mbps OFDM, 10% PER, -81 dBm 22 Mbps PBCC, 10% PER, -82 dBm 18 Mbps OFDM, 10% PER, -84 dBm 12 Mbps OFDM, 10% PER, -86 dBm 11 Mbps CCK, 8% PER, -84 dBm 9 Mbps OFDM, 10% PER, -89 dBm 6 Mbps OFDM, 10% PER, -90 dBm 5.5 Mbps CCK, 8% PER, -87 dBm 2 Mbps QPSK, 8% PER, -88 dBm 1 Mbps BPSK, 8% PER, -91 dBm |
| Security | 64/128/256-bit WEP; Wi-Fi Protected Access (WPA Q2 Support) |
| Software Support | Kick Start (Advance discovery protocol for easy to use); Web-based Tool; Bridge Auto Learning (Without the hassle of MAC number records); SNMP Support (Q2 Ready) |
| Environmental Requirements | Operating Temperature: -20° to 70°C Storage Temperature: -30° to 80°C Humidity: 5% to 95%, non-condensing |
| Dimensions | 165 X135 X 55 mm (6.52 X 5.34 X 2.17 in.) |
| Weight | 1.13 kg. |
| Power | Input voltage 12V DC; external power supply included (input voltage 100V to 240V AC) |
| Warranty | One year, limited |

* Product appearance and specifications are subject to change without prior notice.

National Datacomm Corporation

4F, No.24-2, Industry East 4th Road, Science Park
Hsin-Chu, Taiwan, R.O.C.
Tel: +886-3-5783966
Fax: +886-3-5777989
Email: sales@ndc.com.tw

NDC World Wide Web

www.ndclan.com
©2004 National Datacomm Corporation, Inc. All rights reserved.

P/N D-NWH9250 E01-0404



NATIONAL DATACOMM CORPORATION
Maximizing the Convenience of Networking