Large Screen LCD Monitors

Professional Monitors designed for public display, digital signage, financial, broadcast and transportation applications. These monitors are built specifically for the rigors of harsh industrial environments as well as extended operation applications. Monitors are rated at >50K hours MTBF(at 24/7 operation)

LCS2730 - LCS2740 27 inch Diagonal

- Resolution: 1366x768
- Brightness: 500 CD/M2
- Contrast Ratio: 1200:1
- 6.5ms Response Time
- RS232C RS485



LCS4230

- 42 inch Diagonal
- Resolution: 1920x1080p
- Brightness: 500CD/M2
- Contrast Ratio: 1200:1
- 6.5ms Response Time
- RS232C No Audio Amp



LCS4740

- 47 inch Diagonal
- Resolution: 1920x1080p
- Brightness: 500 CD/M2
- Contrast Ratio: 1200:1
- 6.5ms Response Time
- RS232C + Audio Amp



- LCS3230 LCS3240 32 inch Diagonal
- Resolution: 1366x768
- Brightness: 500 CD/M2
- Contrast Ratio: 1200:1
- 6.5ms Response Time
 RS232C RS485
 - RS232C RS485



LCS4240

- 42 inch Diagonal
- Resolution: 1920x1080p
- Brightness: 500 CD/M2
- Contrast Ratio: 1200:1
 6.5ms Response Time
- RS232C + Audio Amp





Common Featu

- Variable Black Level Adjustment
- Variable Back Light Adjustment
- Picture in Picture, Picture and Picture
- AutoAmbient Brightness Compensation
- Fanless Design for Quiet Operation
- Anti-Reflective coated LCD panels
- Composite and S-Video input
- 15 Pin VGA and DVI-D Input
- Component Video Input
- 176+ Degree H / V Viewing Angle
- Infrared and RS232 Control
- VESA Mounts 100/200MM
- Power: 100~240V AC 50/60HZ
- Approvals: cUL / FCC
- One Year Parts & Labor Warranty
- Extended Warranties Available



P.O. BOX 9219 info@ovideon.com

Features

ommon

Aurora, Illinois 60598 ph: 630.236.9917

LCS3730 37 inch Diagonal

- Resolution: 1920x1080p
- Brightness: 500 CD/M2
- Contrast Ratio: 1200:1
- 6.5ms Response Time
- •RS232C




LCS4730 47 inch Diagonal

- Resolution: 1920x1080p
- Brightness: 500 CD/M2
- Contrast Ratio: 1200:1
- 6.5ms Response Time
- RS232C No Audio Amp



OPTIONS

- Optical Touch Screen (42,47")
- Tempered Glass
- Bottom or Side Speakers (40ser)
- HD-SDI Input (42,47" 30 series)
- Audio Amp (42,47" 30 series)
- Open Frame Versions Available



* Specifications subject to change without prior notification