

Proxima DP6800 Projector

Technical and Functional Specifications

Display Technology	<ul style="list-style-type: none">● 1.3 in. polysilicon TFT LCD x3
Resolution	<ul style="list-style-type: none">● XGA (1024 x 768)
Resolutions Supported	<ul style="list-style-type: none">● VGA (640 x 480) Fit-to-View● SVGA (800 x 600) Fit-to-View● XGA (1024 x 768) native● SXGA (1280 x 1024) Fit-to-View
Brightness	<ul style="list-style-type: none">● 600 ANSI lumens (typical)
Contrast Ratio	<ul style="list-style-type: none">● 200:1 full on, full off
Computer Compatibility	<ul style="list-style-type: none">● IBM PC, PS/2, Pentium and compatibles● Powerbook and compatibles
Video Compatibility	<ul style="list-style-type: none">● NTSC, NTSC 4.3, PAL, PAL-M, SECAM
Sources	<ul style="list-style-type: none">● 2 Computer, 4 audio, 2 video, 2 S-video
H-Sync Range	<ul style="list-style-type: none">● 15.8 to 80 KHz
V-Sync Range	<ul style="list-style-type: none">● 50 to 85 Hz
Horizontal Resolution	<ul style="list-style-type: none">● 400 TV Lines
Image Size (Diagonal)	<ul style="list-style-type: none">● 1.8 ft to 23.5 ft (0.5 m to 7.2 m)
Lens	<ul style="list-style-type: none">● Power zoom and focus lens 1:5:1 ratio● Focal length: 48mm to 72mm, f/2.3 to f/3.0
Projection Distance (From Screen)	<ul style="list-style-type: none">● 4 ft to 35 ft (1.2 m to 10.7 m)
Keystone Correction	<ul style="list-style-type: none">● 8.8°
Number of Colors	<ul style="list-style-type: none">● 16.7 million
Lamp	<ul style="list-style-type: none">● 260 watt metal halide● Lamp life: 1500 hours to 50% brightness
Audio	<ul style="list-style-type: none">● 2 x 2-watt stereo
Remote Control	<ul style="list-style-type: none">● Wireless IR remote with mouse control & Laser pointer
Dimensions	<ul style="list-style-type: none">● 6.2 in. H x 16.3 in. W x 12.5 in L● (15.7 cm H x 41.5 cm W x 31.7 cm L)
Weight	<ul style="list-style-type: none">● 19 lbs. (8.6 kg)
Power Consumption	<ul style="list-style-type: none">● 370 watts
Power Requirements	<ul style="list-style-type: none">● 100 - 120V / 220 - 240V at 50/60 Hz
Operating Temperature (Sea Level)	<ul style="list-style-type: none">● 32° F (0° C) to 95° F (35° C)
Approvals	<ul style="list-style-type: none">● FCC Class A (U.S.)● C-UL (Canada), UL, CE
Warranty	<ul style="list-style-type: none">● Two years on parts and labor (excluding lamp)