



602 Cassette Deck

Date of manufacture : Jul 93 - Nov 96

Please note that this document contains the text from the original product brochure, and some technical statements may now be out of date



The NAD 602's primary features are audio excellence and ease of use, plus the ability to reproduce the full brilliance and dynamic range of CD recordings.

To achieve this, low-noise electronics plus Dolby B and C circuits enhance the 602's capability to record the full signal. Play Trim and HX Pro circuits give the 602 the advantage of being able to reproduce accurately a wide range of pre-recorded tapes even home recordings, with noise free brilliance.

The 602 automatically senses tape type and switches its internal electronics for optimum reproduction and ease of use. Two quiet DC motors, coupled to a belt driven balanced flywheel ensure flutter free capstan operation.

Speed accuracy		±1%
Wow and flutter		<0.06% JIS weighted, RMS
		<0.1% DIN weighted, peak
Frequency response		35Hz - 16kHz ±3dB
MPX filter response		-
Harmonic distortion		<0.3% at -10dB
THD at 0dB	Normal tape	<1%
	CrO ₂ , Metal	<1.5%
Signal/Noise ratio	Dolby off	56dB
	Dolby B	66dB
	Dolby C	76dB
Channel separation		35dB broadband
Erase		>70dB at 1kHz
Input sensitivity		40mV
Input impedance		10kΩ
Maximum input level		25V
Output level at 0dB		500mV
Output impedance		1kΩ
Remote		No
NAD Link		No
PHYSICAL SPECIFICATIONS		
Dimensions (W x H x D)		420 x 126 x 274mm
Net weight		4.4kg
Shipping weight		6.3kg

Dimensions are of unit's cabinet without attached feet; add up to 18mm for total height.

Dimension depth excludes terminals, sockets, controls and buttons.