




Installation is simplified with the Custom Hood Liner insert. All-in-one design includes everything you need to achieve a fully integrated appearance.







A.Installation height above the cooking surface 24–30"

B. The distance from bottom of range hood to top of range hood: 11"

CP35/CP37

HVI certified performance

Heat Sentry[™] detects excessive heat and adjusts speed to high automatically

Separate On/Off speed control gives you the convenience of automatically remembering favorite setting.

Standard stainless steel is not recommended for installations along saltwater coastal areas

CFM Reducer Kit for CP35 reduces max CFM to 250–300

Available only in the U.S.

Hood Sizes

Widths 28-7/16", 34-7/16", 40-7/16" on CP35; 46-7/16" on CP37 Depths 19-5/16" on CP35; 22-9/16" on CP37

Blower Included

Stocked	Brushed Standard Grade Stainless Steel (See Sidebar)		
Special Order	Not Available		
Features			
Light Type	Halogen, MR16; GU10-50W		
Number of Lamps	2		
Lighting Levels	2		
Lighting Lamps Included	Yes		
Control Type	Variable Speed, Rotary with Separate On/Off Control		
Control Features	Heat Sentry™		
Control Remote	Not Available		
Filter: Standard	Stainless Steel Baffle		
Filter: Options	Not Available		
	Special Order Features Light Type Number of Lamps Lighting Levels Lighting Lamps Included Control Type Control Features Control Remote Filter: Standard		

Blower (Included) Choose from 600 CFM or 1200 CFM

Internal Blower Model	CP35	CP37
Vertical CFM High/Low	600/190	1200/380
Vertical Sones High/Low	12.0/2.0	13.5/2.0

No

Accessories

Non-ducted Capability

Non-ducted Recirculating Kit
Decorative Trim
Liners
CFM Reducer Kit
Not Available
Not Available
ARP8, for CP35 only

Installation Requirements

Amps @ 120V CP35: 6 Amps, CP37: 9 Amps
Electrical Direct Wire

Duct Size: Internal Blower CP35: 8" Round, CP37: 10" Round

Duct Direction Vertical
Backdraft Damper Included





The Custom Hood Liner easy install system comes with liner, blower, filtration, controls, lighting and damper.



Rotary controls for two-level lighting and variable blower speeds enable the user to choose operating preferences.



BESTRANGEHOODS.COM

926 WEST STATE STREET HARTFORD, WISCONSIN 53027 800-558-1711, IN CANADA 866-737-7770