

Hood Type Dishwashers

WT65E with continuous water softener

The Electrolux Dishwashing range is produced for customers with the highest conceivable demands for good efficiency, economy and ergonomics for dishwashing operation. The product range comprises glasswashers, undercounter dishwashers, hood type dishwashers, rack type dishwashers, flight type dishwashers and pot and pan washers. The hood type dishwasher WT65E range consists of units with different voltages and has a capacity of 65 baskets per hour. The WT65E is available for cold or hot water connection, has insulated or uninsulated hood and manual hood opening.



Model 504156

EASY TO INSTALL

- The WT65E requires 10.6 kW for hot water supply connection.
- Only one cable for electrical connection.
- External connecting board, protected by a waterproof plastic box.
- Simple service from the front and from the side panels.
- Pre-arrangements for drain pump available as an optional accessory that is possible to install on site.
- Pre-arrangements automatic detergent dispenser. For machines without detergent dispenser it is possible to add it on site.
- Pre-arrangement for connection to an energy management device.
- Corner or straight flow installation.
- Available on request model pre-arranged for HACCP implementation (both basic as well as integrated system).

- Suitable to be connected to the tabling and roller conveyors (with appropriate kit) - included in Electrolux Handling System range - to create a functional and ergonomic lay-out.

EASY TO CLEAN

- Smooth surfaces and wash tank with rounded corners.
- Easily removable washing & rinsing arms, filters and rack support.
- Rack support guide pressed in the tank body.
- No pipes inside the washing chamber.
- Self cleaning cycle, easy to activate.
- Electronic control of the functions incorporating fault diagnosis system, number of cycles counter and number of drain cycles counter.
- Simple control panel with digital thermometers indicating both wash

and rinse temperatures.

- Four dishwashing programs: one for glass and lightly soiled items, one for normally soiled items, one for heavily soiled items and the fourth program is continuous.
- Height adjustable rounded feet.
- IPX5 water protection.

EASY TO USE

- Less hood friction thanks to a high sturdiness plastic guide.
- Double skin hood ceiling and completely closed and insulated back for less heat and noise dispersion.
- Pre-arrangement for connection to an Energy Management device.
- Available, on request, model pre-arranged for HACCP implementation (both basic as well as integrated system).
- High efficiency non-return (air gap class A) valve in water inlet circuit.



Electrolux

