

2K-Plus Filter Cartridge

Delivers premium quality water for foodservice, vending and OCS applications



2K-Plus Replacement Cartridge: EV9612-61

EV9612-61

BENEFITS

Provides sparkling clear, fresh, premium quality ingredient water for great tasting beverages

Everpure's unique filter blend using activated carbon reduces chlorine taste and odor and other offensive contaminants

KDF® Media inhibits microbial growth and provides bacteriostatic control plus scale inhibition

Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size

Reduces possible health contaminants such as asbestos fibers and Cryptosporidium and Giardia cysts

Sanitary cartridge replacement is simple, quick, and clean. Internal filter parts are never exposed to handling or contamination

NSF Certified under NSF/ANSI Standards 42 and 53

ī	M	ς	т	٨	ī	ī	٨	т	ī	٨	M	Т	ī	D	ς
ı	N	ა	- 1	А	L	L	А	- 1	П	U	N	- 1	ı	r	ა

Never use saddle valve for connection

Use 3/8" water line

Install vertically with cartridge hanging down

Allow 2-1/2" clearance below the cartridge for easy cartridge replacement

Flush 2K Plus cartridge by running water through filter for three minutes at full flow

OPERATION TIPS

Change cartridges on a regular 6 month preventative maintenance program

Change cartridges when capacity is reached or when pressure falls below 10 psi

Service flow rate must not exceed 0.5 gpm

Always flush the filter cartridge at time of installation and cartridge change

APPLICATION/SIZING

For foodservice, vending machine and office coffee service applications

Rated Capacity: 1,500 gallons (5,678L)

SPECIFICATIONS

Overall Dimensions: 10.25"H x 3.25"Diameter

Service Flow Rate: Maximum 0.5 gpm (1.9 Lpm)

Rated Capacity: 1,500 gallons

Pressure Requirements: 10 - 125 psi (0.7 - 8.6 bar), non-shock


Maximum Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

KDF® is the registered trademark of KDF Fluid Treatment, Inc.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

2K-Plus Filter Cartridge



WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction Mechanical Filtration Unit Particulate Reduction, Class I: 99.9+% reduction of particles one-half micron and larger in size Standard No. 53: Health Effects Mechanical Filtration Unit **Turbidity Reduction** Cvst Reduction Asbestos Reduction



Worldwide Headquarters: EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com

In Europe. Pentair Water Belgium B.V./B.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals BELGIUM TEL: +32.(o).14.283.500

FAX: +32.(o).14.283.505

In Iapan: Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN TEL: 81.(0)42.775.3011 FAX: 81.(0)42.775.3015