

MRS 100/225/225CC Reverse Osmosis System

Configurable system that delivers reverse osmosis or blended water for multiple foodservice applications





MRS-100 System	EV9970-07
MRS-225 System	EV9970-08
MRS-225CC System	EV9970-09
PRE-FILTER KIT	EV9795-81
6TO-BW Cartridge	EV9607-41
MR-100 Cartridge	EV9627-11
MR-225 Cartridge	EV9627-03
7CC-BW Cartridge	EV9627-05

BENEFITS

Improves equipment life and performance by removing at least 90%+ of all dissolved solids that cause scale build-up

Protects against taste and odor causing contaminants while removing dirt, particulates and dissolved minerals

Less frequent deliming of equipment means reduced maintenance and service costs

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

Wall mount design allows flexible installation

Reduces chlorine taste and odor and other offensive contaminants that can adversely affect taste of water and beverages

Reduces limescale build-up that can cause excessive machine downtime and increased maintenance costs. Plus, scale reduction reduces energy costs

INSTALLATION TIPS

Choose a mounting location suitable to support the full weight of the system when operating

Deliming of equipment prior to application is recommended

Never use saddle valve for connection

Use 3/8" (min.) water line

The water inlet must supply a minimum of 0.5 gpm

Install vertically with cartridge hanging down and allow 2 inches above and below unit for cover removal and service access.

Allow clearance to right of unit for optional pre-filter

Refer to Installation, Operation & Maintenance Manual for cartridge flushing and RO start-up

OPERATION TIPS

Change filter cartridges on a regular 6 month preventative maintenance program

Change RO cartridges on a regular 2 year preventative maintenance program

Change cartridges when capacity is reached

Always flush the filter cartridge at time of installation and cartridge change

APPLICATION/SIZING

Mineral Reduction System for foodservice applications

Ideal for: Flash steamers, conventional steamers, cheese melters, combi- ovens and coffee/espresso machines

Output capacity dependant on membrane selected:

100 gallons per day (379 lpd) 225 gallons per day (852 lpd)

For use in coffee, steam, reconstitution, ice and multiple applications.

S P E C I F I C A T I O N S

Overall Dimensions: 30"H (34"-CC Model) x 15"W (20.5" with Prefilter) x 8"D

Inlet and outlet connection: 3/8" OD tube connection

Wastewater line connection: 1/4" OD tube connection

Service Flow Rate:

Dependant on water pressure in storage tank and line size (s) to equipment

Pressure Requirements:

Operating:

25 - 80 psi (1.7 - 5.5 bar), non-shock

Maximum Static:

100 psi (6.9 bar), non-shock

Electrical connection required: 115 Volts AC, 60 Hertz, 1 Phase

Water Supply:

0.5 gpm (1.9L) @ 50-85 psi (280-595 Kpg)

Inlet Temperature:

40°F - 100°F (4-38°C)


Inlet TDS:

1,500 ppm max recommended

Operating Weight: 35 lbs. (not including storage tanks)

The contaminants or other substances removed or reduced by this system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

MRS 100/225/225CC



WARRANTY

MRS 100/225/225CC system (excluding replaceable elements) is covered by a limited warranty against defects in material and workmanship for a period of one year after the date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



Everpure offers a full line of water storage tanks. Contact your Everpure sales representative for more information.

<u>=V=??R=</u>

EVERPURE LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel. (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com

FAX 32-14-283505

In Europe EVERPURE EUROPE B.V./B.A. INDUSTRIEPARK WOLFSTEE TOEKOMSTLAAN 30 B-2200 HERENTALS BELGIUM TEL 32-14-283500

EVÉRPURE JAPAN LLC HASHIMOTO MN BLDG, 7F 3-25-1 HASHIMOTO SAGAMIHARA-SHI KANAGAWA 229-1103 TAPAN Tel. 81-(0)42-775-3011 FAX 81-(0)42-775-3015

Everpure 1040 Muirfield Drive Hanover Park, IL 60133 Phone: 630-307-3000 Fax: 630-307-3030