

COOPER LIGHTING - SURE-LITES®



RD SERIES

Two Injection Molded Thermoplastic Heads



RLM SERIES

Two High-Impact Thermoplastic Heads

Recessed Housing

EMERGENCY LIGHT


- Dual-voltage input 120/277VAC, 60Hz
- 20 gauge die-formed steel housing with white powder coat finish
- Heads match housing finish
- Knockout, conduit or cord set
- Supplied with hanger bars, T-Bar clips
- Single modular electrical connector
- Remote capability
- Line-latching, Solid-State voltage limited charger, Solid-State switching, low-voltage disconnect, brownout circuit, overload/short-circuit protection, test switch/power indicator light
- UL 924 Listed, Life Safety NFPA 101, NEC/OSHA, most state and local codes

DESCRIPTION

The RD Series is a recessed emergency lighting system designed for locations where aesthetics are of utmost importance. The housing is fully recessed in dry wall or grid ceiling installations. Designer pinchback heads rotate 358° and swivel 90° to 0°. Ideal for commercial and institutional environments where easy recessed installation and minimal maintenance are desired.

The RLM Series is a recessed system packaged in an attractive flame-resistant metal housing. It is the unit of choice for installations where a recessed product is desired and the size and cost of emergency lighting must be kept to a minimum without sacrificing dependability or light output.

DIMENSIONS




ELECTRICAL RATINGS

Model	Battery	Rated Wattage to 87 1/2% of rated D.C. Voltage					Lamp Information		
		DC Voltage	1 1/2 hours	2 hours	3 hours	4 hours	Type	Wattage	Number
RD1	SLC	6	18	15	10	8	Tungsten Halogen	6	29-12
RD3	SLC	6	27	24	18	14	Tungsten Halogen	12	29-66
RD4	SLC	12	54	-	-	-	Incandescent	9	029-86
RD6	SNC	6	15	12	8	6	Tungsten Halogen	6	29-12
RD7	SNC	6	24	18	12	10	Tungsten Halogen	12	29-66
RLM1	SLC	6	10.8	7.2	-	-	Incandescent	5.4	29-121
RLM2	SLC	6	18	15	10	8	Incandescent	9	29-84
RLM3	SLC	6	27	24	18	14	Incandescent	9	29-84
RLM4	SLC	12	54	-	-	-	Incandescent	9	029-86
RLM8	SNC	6	15	12	8	-	Incandescent	7.2	29-88
RLM9	SNC	6	24	18	12	10	Incandescent	7.2	29-88

SLC=Sealed Lead Calcium Battery
SNC=Sealed Nickel Cadmium Battery

ORDERING INFORMATION

SAMPLE NUMBER: RD1V



Energy Data

Model No.	Input Current (Max.):	
	120V	277V
RD1, RD3	.12A	.05A
RD4, RLM4	.30A	.13A
RD6	.06A	.03A
RD7	.07A	.04A
RLM1, RLM2, RLM3	.12A	.05A
RLM8	.06A	.03A
RLM9	.07A	.04A

⁽¹⁾ Consult your Cooper Lighting Representative. ⁽²⁾ Provision for one meter only.