

STAGE & THEATRICAL LIGHTING

CMY ZOOM-250

CONTROL FEATURES

USITT DMX-512
9 DMX channels
4 Digit L.E.D. Display
3 pin XLR serial input/output

NEW



OPTICAL SYSTEM

High Output Luminous-Efficiency parabolic mirror
Glass Dichroic reflector
8° - 22° Motorized zoom
150mm Fresnel Lens

LAMP SPECIFICATIONS

PHILIPS MSD-250/2 (250W, 8500°K, 2000HR)

COLOR

CMY Gradual Color Mixing
Dichroic Colors + White + UV
Continuous Color Scroll using color filters

SHUTTER/DIMMER

Mechanical Dimming 0-100%
Mechanical High Speed shutter & Pulse Effect

EFFECTS

180° Beam Shaper
Frost Filter

Rigging


1 x Hanging Yoke (Bracket)
1 x Base Plate

DIMENSIONS & WEIGHT

15"L x 18"W x 13.5"H
36 lbs

POWER SUPPLY

Fuse: 10A
Magnetic Ballast
Voltage: 115/208/230/240V AC, 50/60 Hz
Power consumption: 500VA



MOTORIZED ZOOM

8° - 22° Motorized zoom
of 150mm Fresnel Lens