



### Ordering Information

Catalog No.	Finishes	Mounting	Lamps
9530WH	Matte White	All Lytespan Track Systems	A19, 100W Max
9530BK	Matte Black		PAR16, PAR30 75W Max

### Features

- Lytespan attachment fitting:** Die-cast zinc alloy.
- Housing:** .40" aluminum
- Step baffle:** Compression-molded high heat phenolic with stepped conical surface for low brightness. Integral black finish.
- Lever:** Locks attachment fitting electrically and mechanically anywhere along the track.
- Movable brass Contact:** Extends for connection to 2nd circuit in Advent Lytespan Track.
- Swivel:** Die-cast zinc alloy. 350° horizontal adjustment.
- Pivot mounting:** Tensioned with built-in stop, provides 90° vertical adjustment.

### Electrical

Porcelain socket, medium base, nickel plated screw shell. No. 18 braided SF-1 leads.

### Finish

All painted finishes baked enamel.

### Labels

UL, I.B.E.W.

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

Lightolier a Genlyte company [www.lightolier.com](http://www.lightolier.com)  
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 © 2006 Genlyte Group LLC • A1006