

Energy savings, compact size

Philips Energy Advantage PL-C lamps offer significant energy savings in a compact size.

Save energy without changing a ballast

- Two wattages available—I4W and 2IW

 I4W is a direct replacement for a PL-C 18W lamp, saving 4 watts of energy
- $-21\mbox{\,W}$ is a direct replacement for a PL-C 26W lamp, saving 5 watts of energy
- Up to 22% energy savings when replacing the above 18W and 26W lamps*
- · No new ballast required

Broad range of color temperatures

Available in 2700K, 3500K and 4100K

High light output in a compact size

• 88% lumen maintenance

Excellent color rendering

• 82 CRI

*18 watt-14 watt=4 watt/18 watt=22% 26 watt-21 watt=5 watt/26 watt=19% Philips Energy Advantage PL-C Lamps featuring ALTO® Lamp Technology

Ideal for applications requiring maximum energy savings

ENERGY ADVANTAGE PL-C



† This lamp is better for the environment because of its reduced mercury content. All Philips ALTO® lamps give you end-of-life options which can simplify and reduce your lamp disposal costs depending on your state and local regulations.



Philips Energy Advantage PL-C Lamps featuring ALTO® Lamp Technology


Ordering, Electrical and Technical Data (Subject to change without notice)

| | Product Number | Ordering Code | Nom. Watts | Base | Pack. Qty. | Color Temp. (Kelvin) | MOL (ln.) | Rated Average 3-hr Start ² | Life (Hrs.) ^I I2-hr Start ³ | Approx. Initial Lumens ⁴ | Design Lumens ⁵ | CRI | Lumen Maint. |
|---|-------------------|------------------------------|---------------|--------|---------------|----------------------------|--------------|---|---|---|-------------------------------|-----|-----------------|
| • | 22034-3 | PL-C 18W/827/XEW/4P/ALTO 14W | 14 | G24q-2 | 10 | 2700K | 511/16 | 12,000 | 16,000 | 1100 | 1010 | 82 | 88% |
| • | 22040-0 | PL-C 18W/835/XEW/4P/ALTO 14W | 14 | G24q-2 | 10 | 3500K | 511/16 | 12,000 | 16,000 | 1100 | 1010 | 82 | 88% |
| • | 22041-8 | PL-C 18W/841/XEW/4P/ALTO 14W | 14 | G24q-2 | 10 | 4100K | 511/16 | 12,000 | 16,000 | 1100 | 1010 | 82 | 88% |
| • | 22042-6 | PL-C 26W/827/XEW/4P/ALTO 21W | 21 | G24q-3 | 10 | 2700K | 6½ | 12,000 | 16,000 | 1525 | 1400 | 82 | 88% |
| • | 22047-5 | PL-C 26W/835/XEW/4P/ALTO 21W | 21 | G24q-3 | 10 | 3500K | 6½ | 12,000 | 16,000 | 1525 | 1400 | 82 | 88% |
| • | 22048-3 | PL-C 26W/841/XEW/4P/ALTO 21W | 21 | G24q-3 | 10 | 4100K | 6½ | 12,000 | 16,000 | 1525 | 1400 | 82 | 88% |

- 1) Rated average life is the length of operation (in hours) at which point an average of 50% of a large sample of lamps will still be operational and 50% will not.
- 2) Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Lamp life is appreciably longer if lamps are started less frequently.
- 3) Average life under engineering data with lamps turned off and restarted once every 12 operating hours.
- 4) Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life, when the output is measured during operation on a reference ballast under standard laboratory conditions. For expected lamp lumen output, commercial ballast manufacturers can advise the appropriate ballast factor for each of their ballasts when they are informed of the designated lamp. The ballast factor is a multiplier applied to the designated lamp lumen output.
- 5) Design lumens are the approximate lamp lumen output at 40% of the lamp's rated average life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions.
- This lamp is better for the environment because of its reduced mercury content. All Philips ALTO® lamps give you end-of-life options which can simplify and reduce your lamp disposal costs depending on your state and local regulations.

88% Lumen Maintenance

Philips Energy Advantage PL-C Lamps




Rated Average Life

Philips Energy Advantage PL-C Lamps

■ Programmed Start Ballast



Rated Average Life in Hours



Dimensions

| | I4W | 21W |
|----|------------|-------------|
| Α | 3.9"/99mm | 5.2"/132mm |
| B- | 4.6"/117mm | 5.9"/150mm |
| С | 5.2"/I32mm | 6.5"/165mm |
| D | I.I"/28mm | ——I.I"/28mm |



© 2008 Philips Lighting Company. All rights reserved. Printed in USA 12/08

P-5974

www. philips.com

Philips Lighting Company
200 Franklin Square Drive
P.O. Box 6800
Somerset, NJ 08875-6800
I-800-555-0050
A Division of Philips Electronics North America Corporation

Philips Lighting 281 Hillmount Road Markham, Ontario Canada L6C 2S3 I-800-555-0050 A Division of Philips Electronics Ltd.