Tumble dryer

Instructions for installation and use G31VU G31V

۵ * ∭©

(j) INDESIT

Contents

Safety Advice	3 - 4
Electrical Requirements	5
Features - Get to know the main parts of your Dryer	6
Where to put and vent your Dryer	6
How to use your Dryer	7
Sorting your laundry	8
Items not suitable for drying	9
Items requiring special attention	10
The Controls	11
Guide to Drying Times	12
How to remove and clean the Fluff Filter	13
Caring for your Dryer	13
If something goes wrong	14
If it still won't work	15

Register your purchase now

Simply complete and return the **Registration Form** supplied with the appliance documents.

Retention of this Instruction Book

This Instruction Book must be kept handy for reference as it contains important details on the safe and proper use of the appliance.

If you sell or pass the appliance to someone else, or move house and leave it behind, make sure this Book is also provided so the new owner can become familiar with the appliance and safety warnings.

For your safety

IMPORTANT

Using your Tumble Dryer is easy.

Nevertheless, for your own safety and to get the best results it is important to know your Dryer by reading right through this handbook **before** using your dryer for the first time.

NEVER NEVER	 Allow children to play with or otherwise interfere with the dryer. Allow the air inlet at the back of the dryer, the air outlet or vent hose
	to be obstructed.
NEVER	 Direct the vent hose outlet towards the air intake at the back of the machine.
NEVER	Allow the tumble dryer to recycle exhaust air.
NEVER	Switch the machine off leaving a hot load in the drum.
NEVER	 Tumble dry without the filter in position.
NEVER	 Exceed the maximum load capacity recommended or place dripping wet items in the drum.
NEVER	• Use the dryer on a carpeted floor where the pile height would prevent air from entering the dryer from the base.
NEVER	 Allow lint to collect around the dryer.
NEVER	 Add liquid or sheet fabric conditioner to the dryer, use liquid conditioner in the final rinse of your wash.
NEVER	 Use the dryer for commercial drying, the dryer is only suitable for domestic use.
NEVER	 Dry Acrylics on the high heat setting.
NEVER	• Tumble dry articles that have NOT been well washed in water and detergent then well rinsed and spun.
NEVER	• Tumble dry articles that have had chemicals used for cleaning.
NEVER	• Dry articles that are contaminated with flammable substances such as: petrol, oil, paint, hair lacquer, creams, cooking fat or oil.
NEVER	• Tumble dry: rubber, foam rubber, plastic, plastic foam, nappy pants or liners, polythene or paper.
	Large, very bulky items including duvets and sleeping bags.
NEVER	 Never attempt to stand on top of your dryer, it is not designed for such use and you could injure yourself or damage the dryer by such
	abuse.
NEVER	 Switch electricity On or Off with wet hands.

IMPORTANT

A CHILD COULD CLIMB INTO OR TAMPER WITH AN UNATTENDED TUMBLE DRYER. WHEN THE MACHINE IS NOT IN USE SWITCH OFF, REMOVE THE PLUG AND CLOSE THE DOOR.

For your safety

- **ALWAYS** When the dryer is not in use, switch off at the wall, remove plug and close the door.
- **ALWAYS** Comply with the specified electrical requirements.
- ALWAYS Ensure that your dryer is installed correctly and has adequate ventilation. (see, "Where to put and vent your dryer.")
- ALWAYS Use the vent hose for optimum drying performance.
- ALWAYS Finish every programme with the cool tumble cycle provided on the control.
- ALWAYS Clean the filter, it is essential that the filter is kept clear of fluff after EACH drying cycle.
- ALWAYS Observe the rules for drying garments:

In particular woollen articles should not be dried in a tumble dryer unless they are labelled 'Superwash', 'Machine washable' or have the 'May be tumble dried' symbol: If in any doubt do not dry wool in the machine. Unlike other materials, the mechanism of wool

shrinkage is irreversible, i.e. it will not stretch back to the original size and shape.

ALWAYS • Buy genuine accessories and spares.



CAUTION: WHEN THE DRYER IS IN USE AVOID TOUCHING THE REAR OF THE DRYER AS IT MAY BE HOT.

Electrical Requirements

	WARNING: This appliance must be earthed!
Supply	REFER TO THE RATING PLATE FOR VOLTAGE AND CURRENT REQUIREMENTS. (see diagram for location.) The flexible mains lead is supplied fitted with a BS1363 plug and with a 13 amp BS1362 fuse. The plug should be connected to the mains supply via a suitable switched socket which is accessible after installing your dryer.
Changing the fuse	If it is necessary to fit a replacement fuse, it must be a 13 amp ASTA approved to BS1362 type.
Moulded plug	WARNING: The plug must not be used without a fuse cover.
	If a replacement fuse holder/cover is required, it must be of the same colour coding or wording as shown on the base of the plug. Replacements are available from your Spares stockist.
Changing the plug	The wires in the mains lead are coloured in accordance with the following: GREEN/YELLOW - EARTH BLUE - NEUTRAL BROWN - LIVE
Rewirable plug	If a replacement plug is to be fitted, the appropriate wire must be connected to the correct terminal, as follows:
EARTH EARTH I 3 AMP FUSE BLUE TO NEUTRAL CORD CLAMP	Connect: Green/Yellow to terminal marked Earth or Green or \downarrow Blue to terminal marked Neutral or N or Black Brown to terminal marked Live or L or Red. If the plug being replaced is a non-rewirable type then the cut-off plug must be disposed of safely. DO NOT leave where it can be inserted into a socket and create a shock hazard.
Changing the mains cable	Should the mains lead ever require replacing at any time please contact your nearest Service Centre. A charge will be made for the replacement of the mains lead or if you require a longer lead. The mains lead must only be replaced by a specially prepared cable obtainable from your Spares Stockist and fitted by a qualified electrician.
	NOTE: IF IN DOUBT ABOUT ANY OF THE ABOVE CONSULT A

QUALIFIED ELECTRICIAN.

Features - Get to know the main parts of your dryer



Where to put and vent your dryer

	 Your tumble dryer should NOT be located adjacent to a gas hob, cooker, heater, or eye level grill as flames from the burners could cause damage to your machine. The dryer should be placed where air can freely circulate around it, preferably near a window that can be opened to reduce the possibility of condensation occuring while the dryer is in use. When operating the dryer, there has to be adequate ventilation to avoid the back flow of gases into the room from appliances burning other fuels, including open fires. A vent hose is recommended for optimum performance. DO NOT operate the dryer in an enclosed environment, ensure the dryer is adequately ventilated. DO NOT allow clothes, towels etc., to hang down the front of the dryer into the airstream. This obstructs the airflow and may damage the dryer.
	 Ensure that the end of the hose is not directed towards the air intake grille at the rear of the dryer. NOTE: The vent hose should not exceed 2.4 metres in length, and should be kept free of any possible accumulation of fluff lint (and water) by frequently shaking it out. Always ensure that the hose is not squashed.
Window Vent Kit	A venting kit is available as an optional extra, which will take the moist air directly from the dryer and out through an open window. The venting kit is fitted to the front of the door.
Wall Hanging Kit	This allows the dryer to be mounted on a wall of suitable strength to take the weight. Alternatively it should be used when the dryer is mounted on top of a work surface to secure the dryer to the wall.
	WARNING: DO NOT DISCHARGE THE EXHAUST AIR INTO A FLUE WHICH IS USED FOR EXHAUSTING FUMES FROM OTHER APPLIANCES

BURNING GAS OR OTHER FUELS.

How to use your dryer



Never switch the dryer off with a hot load in the drum. You must terminate every programme with the Cool Tumble Phase.

Sorting your laundry

	2. See that belt, stri done this 3. It is imp	and dry t all zip ngs etc s for ea ortant	ying. os are c. are t ch iten to exti	closed ied loos n befor ract as	, ho sely e the mue	ne correct fa oks and eye in bows, you e washing sta ch water as u time and m	es are u will n age. possib	fasten Iormal	ed and ly have
	WARNING DRIPPING		THES	SHOUL	.D N	IEVER BE L	OADEI	כ	
		or are no	ot of a	type re		ied are suitat ing 'special a			
Maximum load size	if you are d maximum lo	rying ite bad sho ence is	ems of uld no that	man-m t excee man-m	ade d 2k	6lb) dry weig fibres (synth g (4.4lb) dry fibres requ	netic or weight	acryli	cs), the
		D DRYI		-		AS THIS CO NCE AND A	-		
Typical load		harts l	below			ms it takes t approximate			
	Clothes]	Household It	tems		
	Blouse	Cotton	150g	5oz]	Duvet cover	Cotton	•	3lb 5oz
		Other	100g	31/2oz		(Double)	Other	1000g	2lb 3oz
	Dress	Cotton	500g	1lb 2oz		Large Tableclot	h	700g	1lb 6oz
		Other	350g	12oz		Small Tableclot	h	250g	
	Jeans		700g	1lb 6oz	-	Tea Towel		100g	31/2oz
	10 Nappies		1000g	2lb 3oz	-	Bath Towel		700g	1lb 8oz
	Shirt	Cotton	300g	101/2oz		Hand Towel		350g	12oz

Other

T-Shirt

200g 7oz

125g

41/2oz

If you group small cotton or terry-towelling items with a synthetic fabric load they could be damp at the end of the drying cycle. If this happens simply give them an additional short period of drying to finish them off.

Double Sheet

Single Sheet

500g

350g

1lb 2oz

12oz

Wash Care Labels

Most of today's fabrics can be tumble dried in your Dryer with no trouble at all, but there are certain fabric finishes which should be dried away from direct heat.

The majority of garments now have wash-care labels on them, giving full washing and drying instructions. These should always be followed carefully especially when you are drying something for the first time.

Typical symbols are:



May be tumble dried



Do not tumble dry



Tumble dry at high heat setting

Tumble dry at low heat setting

Items not suitable for tumble drying

- Those containing foam rubber or rubber-like materials or plastic film (e.g. pillows, cushions, PVC rainwear), or any other articles which are inflammable or contain inflammable substances (e.g. towels contaminated with hair lacquer
- Fibreglass (e.g. some types of curtains)
- Items which have been dry cleaned
- Woollens. Woollen items need as much care in drying as they do in washing. The movement of the tumble-drying action causes the woollen fibre to shrink and distort.
- Garments with the ITCL Code (see 'Items Requiring Special Attention').



Do **not** tumble dry.

Large bulky items e.g. continental quilts, sleeping bags, pillows, cushions, double blankets and large bedspreads. These expand when drying and would prevent airflow through the Dryer.

WARNING: THE DRYER IS INTENDED FOR USE ONLY WHERE WATER SOLUTION IS USED FOR THE CLEANING PROCESS. MISUSE OF A TUMBLE DRYER MAY CREATE A FIRE HAZARD.

Items requiring special attention

Blankets and Bedspreads	The drying requirements of blankets and bedspreads will, of course, vary tremendously according to size and weight. Some, however are simply too big. if you have difficulty getting them into the Dryer, the machine will have difficulty drying them properly. Blankets (and Garments) made from Acrylic fibres (e.g. Acilan, Courtelle, Orion and Dralon) must be dried with special care on Low heat setting. Overdrying should be avoided to ensure heat creasing does not
	occur.

Permanently pleated or creased garments Your dryer will cope with such clothes very well, but you should always read the manufacturer's drying instructions attached to the garment before you begin.

- Starched articles Starched articles should be dried together in the same load to avoid the distribution of starch to non-starched items. You should use a slightly heavier starch solution than you would when drying the items on the washing line. Make sure that as much of the solution is removed from the load as possible before placing it in the Dryer. Remove the items from the dryer as soon as they reach ironing dampness. If they are overdried the starch will powder, leaving the fabric limp which rather defeats the purpose of the exercise!
- **Fabric conditioner** To make sure all your tumble dried clothes come out really fresh and soft we recommend you use a liquid fabric conditioner in the final rinse of your **wash.** A liquid fabric conditioner restores bounce and softness and helps eliminate static cling.

WARNING: ON NO ACCOUNT SHOULD LIQUID FABRIC CONDITIONER BE ADDED TO THE DRYER ITSELF.

Home Dry Cleaning Garments with the ITCL Code A may be cleaned using one of the Home Dry Cleaning Kits available. The instructions supplied with the Home Dry Cleaning Kit must be strictly followed.

The Controls

Setting the timer



G31VU

Turn the Timer clockwise to select the required drying time.

The drying time for both heat settings is controlled by the timer. All you have to do is turn the Timer Control clockwise slightly past the required time and then back to the required time.

Do not rotate the knob beyond 120 (maximum drying time) or past the zero stop. If you have selected more time than you require turn the knob anti-clockwise to select the correct time required.

This operation also starts the dryer, provided the door is closed and the machine is plugged in The "Guide to Drying Times" section will tell you how much time you'll need for various loads.

G31V

Turn the timer clockwise to select the required drying time.

The timer controls the drying time for both heat settings. All you have to do is turn the Timer Knob clockwise until it lines up with the required time.

Never wind the timer control anti-clockwise.

This operation also starts the dryer, provided the door is closed and the machine is plugged in. The "Guide To Drying Times" section will tell you how much time you'll need for various loads.

Door Release To open door, grip the handle and pull towards you.

If the door is opened while the Dryer is in use, the drying programme cuts out automatically and the machine stops. When the door is closed the Dryer will restart but you will not need to reset the Timer Control.

You can however reset the Timer Control at any stage, should you wish.

WARNING: CHILDREN HAVE BEEN KNOWN TO CLIMB INTO TUMBLE DRYERS AND INJURE THEMSELVES. ALWAYS ENSURE THAT THE MACHINE IS SWITCHED OFF AT THE MAINS WHEN THE DRYER IS NOT BEING USED.

Heat Selection Select the appropriate position for low heat or for high heat.

With the switch IN High Heat is selected With the switch OUT Low Heat is selected

The choice of FULL HEAT or LOW HEAT depends upon the fabric you wish to dry (see section "Sorting your Laundry").

Guide to Drying Times

Please note that the Drying Times stated below and on appliance control panel are a GUIDE only and drying times are affected by:

The amount of water remaining in the clothes after spinning litems such as towelling retain a lot of water after spinning, also the suggested wash programme for small items such as T-Shirts may sometimes incorporate a low spin speed which has the same effect.

The type of fabric Your drying load may contain the same type of fabric but of different thicknesses. Thinner items will take less time to dry. Some fabrics, such as those used for jeans are of closer texture than others and although light when dry will be heavy after washing and spinning.

The quantity of Single items of clothes or small loads may take disproportionally clothes to be dried longer to dry. It is more energy efficient to dry larger loads.

How dry you want the clothes As it takes longer to fully dry clothes than to have them ready for ironing, you may wish to remove some clothes when they are slightly damp, ready for ironing and then continue to dry the remainder until they are fully dry.

The heat setting The label on the garment should tell you the correct heat setting to select. See 'Wash Care Labels'.

The temperature of the room If the room in which the dryer is situated is cold, your clothes will take longer to dry than if the room is warm.

Bulky items Some bulky items such as padded jackets can be dried, with care, and we do advise that you remove these items several times, shake them and return them to the dryer. THERE ARE HOWEVER SOME ITEMS THAT WE DO NOT ADVISE YOU TO DRY. SEE 'ITEMS NOT SUITABLE FOR TUMBLE DRYING'

Drying Guide - approximate drying time in minutes (weights specified are when dry)

COTTONS			SYNTHET	ICS	ACRYLICS		
High Heat			High Heat		Gentle Heat		
	g times 800 - 1000rpm shing machine			s on reduced hing machine	Drying times on reduced spin in washing machine		
		Half load	Half load	Full load	Half load	Full load	
1 kg	2 kg	3 kg	1 kg	2 kg	1 kg	2 kg	
30 - 45	45 - 55	60 - 70	25 - 45	45 - 60	30 - 55	55 - 75	

Be careful not to overdry All fabrics contain a little natural moisture even when 'dry' and this natural moisture should not be lost if the clothes are to remain soft and fluffy. Clothes that are dried for too long tend to wrinkle and will need more ironing than usual giving you extra work that the dryer was designed to remove.

How to remove and clean the fluff filter

To remove the filter



A very important part of your dryer is the fluff filter at the front edge of the drum. It's there to trap the particles of lint and fluff which are normally blown away when clothes are dried on the washing-line.

if the filter is allowed to become blocked, the passage of warm air through the drum will be severely restricted. This means your clothes will take much longer than normal to dry and the cost of drying them will be increased. it may also damage your dryer.

WARNING: DO NOT OPERATE THE DRYER WITHOUT CLEANING THE FILTER AFTER EACH DRYING CYCLE. FAILURE TO CLEAN THE FILTER MAY RESULT IN A FIRE HAZARD.

Wash or vacuum clean the filter occasionally.

Don't be alarmed by the amount of fluff you may find on the filter. It's part of the wearing, washing and drying process.

WARNING: DO NOT OPERATE THE DRYER WITHOUT THE FILTER IN POSITION.

Caring for your Dryer

Your tumble dryer needs very little attention. The following simple steps will keep it performing well.

When finished Switch off electricity and remove plug.

After each load Always clean the filter and turn the drum by hand to check that small items like handkerchiefs do not get missed.

As necessary Clean exterior metal and plastic surfaces with a damp cloth or silicon polish only. Regularly check and clean if necessary, the vent hose and any permanent venting fixture to ensure that there has been no accumulation of fluff or lint during the drying process. Clean fluff from the area below the fluff filter and the rear vent tube.

Do not use abrasive cleaners, scouring agents, acids, chlorine bleach or metal polish to clean any part of the machine. These could damage the machine.

Lubrication Your tumble dryer uses special bearing components. Lubrication by the user is not necessary and must not be attempted.

We strongly recommend that all appliances are regularly checked for electrical and mechanical safety.

If something goes wrong

First, don't panic! There may be nothing wrong at all. Look for your problem below, then check the things we suggest. More often than not, this will give you the answer to your problem, and you'll be able to carry on without having to telephone your Service Office.

If after this you still cannot get your machine to work, follow the advice given on the next page.

Problem	Check these things first			
ʻlt won't start'	 Is the machine plugged in and switched on at the socket? Is the Timer Control set to required time? Is the door securely closed? Has the fuse blown? (Try plugging in another appliance to check) Have you used an extension lead? Many are not suitable. Try plugging the dryer directly into a socket to check. 			

'It is taking a long time to dry'	 Have you forgotten to clean the filter? It should be cleaned after each load. Have you selected the correct Heat setting for the type of fabric you are drying? Is the flexible Vent Hose blocked or kinked? Check it for foreign objects or condensate (water). Is the air inlet obstructed in any way? Permanent venting - is flap on the storm cover obstructed? Were the clothes 'excessively wet' when they were put in? Was the correct time selected? Have you overloaded the dryor?
Any other problem	8. Have you overloaded the dryer? Have you re-read this instruction book?

If it still won't work...

Contact the Service Office (0870 6070805)

if something is still wrong with your machine after you've been through the check-list on the previous page:

- 1. Switch off and unplug your machine from the mains.
- 2. Call your nearest Service Office or local importer on the telephone number provided on the guarantee card.

When you contact us we will want to know the following:

- 1. Your name, address and postcode.
- 2. Your telephone number.
- 3. Clear and concise details of the fault.
- 4. The model number and the serial number of your dryer.
- 5. The date of purchase enter the date here.

.....

Please make sure you have all these details ready when you call.

Spare parts

Please remember your new appliance is a complex piece of equipment.

'DIY" repairs or unqualified and untrained service people may put you in danger, could damage the appliance, and might mean you lose cover under the Parts Guarantee.

If you do experience a problem with the appliance don't take risks, call in our Service Engineer. Our Spare Parts are designed exclusively to fit your appliance. Do not use them for any other purpose as you may create a safety hazard.

Disposal of your product

To minimise the risk of injury to children please dispose of your product safely. The door and lid should be removed and mains cable cut off flush with the appliance ensuring that the mains plug can no longer be plugged into a mains socket. The items must then be disposed of safely.

This appliance conforms to the following EEC Directives. Low Voltage Equipment 72/23/EEC 93/68/EEC Electromagnetic Compatibility 89/336/EEC 92/31/EEC 93/68/EEC

(F