

# Bush Hog® TOUGH

## 1847QT Quick Attach Front-Push Loader

### Pin-On Attachments

- BUSH HOG® TOUGH FEATURES**
- TOUGH Boxed Boom Design**
- TOUGH Large Diameter Cross Tubes**
- TOUGH Robotic Welds**
- TOUGH High Strength Chrome Plated Cylinder Rods**
- TOUGH Bush Hog Made Buckets**
- TOUGH Powder Coat Paint**



MODEL	Specifications Based on 1997 ASAE STANDARDS	1847QT
<b>Tractor PTO HP Range</b>		12 - 25
<b>2WD/FWA</b>		2WD/FWA
<b>Maximum Lift Height</b> - Measured at Pivot Pin		76 inches
<b>Maximum Lift Height</b> - Under Level Bucket		71 inches
<b>Maximum Dump Angle</b>		50°
<b>Digging Depth</b>		2.5 inches
<b>Lift Capacity</b> to Maximum Height - At Pivot Pin		725 lbs
<b>Lift Capacity</b> to Maximum Height - 19.5 inches Forward of Pivot Pin		515 lbs
<b>Lift Capacity</b> to 59 inch Height - At Pivot Pin		800 lbs
<b>Lift Capacity</b> to 59 inch Height - 19.5 inches Forward of Pivot Pin		595 lbs
<b>Breakout Force</b> - At Pivot Pin		1340 lbs
<b>Breakout Force</b> - 19.5 inches - Forward of Pivot Pin		960 lbs
<b>Rollback Force</b> at Maximum Height - 19.5 inches Forward of Pivot Pin		1155 lbs
<b>Rollback Force</b> at 59 inch Height - 19.5 inches Forward of Pivot Pin		1330 lbs
<b>Rollback Force</b> at Ground Level - 19.5 inches Forward of Pivot Pin		1055 lbs
<b>Raising Time</b> (Ground Level to Full Height)		3.5 seconds
<b>Lowering Time</b> (Full Height to Ground Level)		2 seconds
<b>Bucket Dumping Time</b> (Full Rollback to Full Dump)		3.5 seconds
<b>Bucket Rollback Time</b> (Full Dump to Full Rollback)		2 seconds
<b>Hydraulics</b>	Two 1.5 inch Bore, 15.0 inch Stroke Double Acting Bucket Cylinders and Two 1.5 inch Bore, 15.0 inch Stroke Double Acting Lift Cylinders	
<b>Specifications Based on Tractor System of</b>	1875 PSI hyd. Pressure & 4 GPM pump capacity	
<b>Pin-On Buckets</b>	Available in 42, 48 and 60 inch widths	
<b>Options</b>	Forklift Attachment (36 inch tines), Bucket Level Indicator, and Grill Guards	
<b>Warranty</b>	1 year limited warranty	
<b>FEATURES</b>	Available in major tractor colors	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE