

# Bush Hog® TOUGH

## 3545 Quick Attach Mid-Mount Loaders

### Skid Steer Quick Attach System



#### BUSH HOG® TOUGH FEATURES

- TOUGH Boxed Boom Design
- TOUGH Large Diameter Cross Tubes
- TOUGH Robotic Welds
- TOUGH High Strength Chrome Plated Cylinder Rods
- TOUGH Steel Tube Hydraulic Lines
- TOUGH Pivot Pins With Recessed Grease Zerks
- TOUGH Bush Hog Made Buckets
- TOUGH Powder Coat Paint

MODEL	Specifications Based on 1997 ASAE STANDARDS	3545
Tractor PTO HP Range		40 - 60
2WD/FWA		2WD/FWA
Maximum Lift Height - Measured at Pivot Pin		120 inches
Maximum Lift Height - Under Level Bucket		110 inches
Maximum Dump Angle		45°
Digging Depth		3.5 inches
Lift Capacity to Maximum Height - At Pivot Pin		3000 lbs
Lift Capacity to Maximum Height - 31.5 inches Forward of Pivot Pin		1950 lbs
Lift Capacity to 59 inch Height - At Pivot Pin		3900 lbs
Lift Capacity to 59 inch Height - 31.5 inches Forward of Pivot Pin		2500 lbs
Breakout Force - At Pivot Pin		4300 lbs
Breakout Force - 31.5 inches - Forward of Pivot Pin		2750 lbs
Rollback Force at Maximum Height - 31.5 inches Forward of Pivot Pin		3550 lbs
Rollback Force at 59 inch Height - 31.5 inches Forward of Pivot Pin		4050 lbs
Rollback Force at Ground Level - 31.5 inches Forward of Pivot Pin		3550 lbs
Raising Time (Ground Level to Full Height)		5 seconds
Lowering Time (Full Height to Ground Level)		4 seconds
Bucket Dumping Time (Full Rollback to Full Dump)		5 seconds
Bucket Rollback Time (Full Dump to Full Rollback)		3 seconds
Hydraulics	Two 2.25 inch Bore, 23.13 inch Stroke Double Acting Bucket Cylinders and Two 2.5 inch Bore, 18.25 inch Stroke Double Acting Lift Cylinders	
Specifications Based on Tractor System of	2850 PSI hyd. pressure & 11. GPM pump capacity	
Regular Duty Skid Steer Buckets	Available in 72, 80 and 84 inch widths	
Commercial Grade Skid Steer Buckets	Available in 60, 72 and 84 inch widths	
Options	Forklift Attachment (48 inch tines), Round Bale Spear, Dual-Probe Bale Spear, Grapple Fork, Bucket Tine Teeth, Bolt-On Digging Teeth, Side Cutting Edges, Spill Guard Attachment, Hydraulic Self-Leveling, and Grill Guards	
Warranty	1 year limited warranty	
FEATURES	"Universal" skid steer quick attach system compatible with skid steer style attachments, Available in major tractor colors	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE