



OPEN AIR COOLERS

OPXS

Key Features

- Counter Top Open Air Unit
- Custom Designed for Easy Product Access
- Integrated Vertical Lighting in Each Post
- Electronic Temperature Control
- Automatic Defrost and Heated Drain Pan
- Adjustable Dual Position Shelves
- High Impact Graphics Available

Model	Doors	Capacity cu.ft (lt)	Shelves	Exterior Dimensions inches (mm)			Interior Dimensions inches (mm)			Power (V-Hz-Ph)	Amps	HP	Crated Weight lbs (kg)
				L	D	H	L	D	H				
OPXS	NA	2 1/2 (72)	2	17 3/4 (450)	17 3/8 (440)	36 1/4 (940)	15 (380)	13 5/8 (345)	21 5/8 (550)	115.60.1	3	1/5	93 (42.3)

Details

Cabinet Construction

- Exterior: Galvanized metal cabinet with impact-resistant, extruded plastic accent panels - gray.
- Large low-E double pane tempered thermal glass side panels for increased product visibility.
- Interior: Epoxy powder coated steel for increased durability and easy cleaning.
- High-density, CFC-free, polyurethane insulation.
- Four (4) low profile adjustable feet.

Shelving

- Two (2) heavy duty galvanized wire shelves: 14 1/4" x 10 5/8" (361 x 270).
- All shelves are dual position allowing for horizontal or gravity fed positions and are adjustable in 3/8" inch increments.

Lighting

- Fluorescent vertical lights mounted in each post and horizontal overhead light provide for maximum illumination of products.
- Utilizes a T8 bulb and an electronic ballast for increased energy efficiency and extended life.

Electrical

- Ready for connection to 115V/60Hz single phase 20 amp dedicated outlet.
- Includes an 8' cord and plug set.



NEMA 5-15R

Refrigeration System

- Self-contained environmentally-friendly refrigeration system using CFC-free R134A refrigerant.
- Self-contained heated drain pan and condensate evaporation system.
- Automatic self-defrost cycle.
- Electronic temperature control with digital readout maintains 34°F to 41°F (1°C to 5°C).
- Bottom mounted refrigeration unit slides out for easy maintenance and service.


Recommended Operating Conditions

- This unit is best suited for an environment where temperatures remain below 80°F (24°C) and humidity does not exceed 55%.
- Open air models should not be installed in any area where the air curtain will be frequently disrupted. This includes placement near an HVAC vent, open doorway, or fan.
- Areas with direct sunlight should also be avoided.

Options

- 208-230V/ 50Hz
- Custom Graphics
- Additional Shelves
- Various Cabinet Colors

Technical Drawing



OPXS



3235 Industry Drive • Suite C
North Charleston, SC 29418
Phone: 843-767-6855
Toll Free: 800-905-4768

Fax: 843-767-6858
Toll Free Fax: 800-906-4768
www.atcgroup.net
sales@atcgroup.net

WARRANTY

One year warranty on all parts and labor and an additional 4 year prorated warranty on compressor.