

## RANGE COMPOSITION

The range consists of 1 fan assisted model of 600 litres refrigeration cabinets that offer excellent standards in terms of performance and efficiency. These models come in fridge/freezer version in 304 AISI and is available with full doors.



## AU SERIES

## REFRIGERATORS/FREEZERS 600 LT ZANUSSI PROFESSIONAL

### FUNCTIONAL AND CONSTRUCTION FEATURES

- ◆ Internal and external structure in 304 AISI stainless steel, external base, top and back in galvanized steel. 150mm height-adjustable feet.
- ◆ Digital control panel allowing the easy and precise setting and control of the internal temperature.
- ◆ Completely automatic defrosting and automatic evaporation of defrost water.
- ◆ High standards of hygiene and ease of cleaning are guaranteed by the rounded internal corners of the cabinet and easily removable runners and grids (without the use of tools).
- ◆ The refrigeration unit can operate in tropical climates (+43°C ambient temperature).
- ◆ Excellent forced air cooling system that ensures the utmost uniformity of temperature in the cabinet and guarantees a perfect storage quality of the goods.
- ◆ High-density expanded polyurethane insulating foam, 60 mm in thickness, with cyclopentane injection, guarantees exceptional, long-term insulation and notable energy savings.
- ◆ The rational use of the internal space of the refrigerator guarantees a large storage area suitable to contain 2/1 GN grids.

- ◆ Reversible self-closing door, in positions less than 90°, with a stop at 95° and a maximum opening at 180°, equipped with a magnetic door seal to guarantee perfect closure. The pressed stainless steel recessed door handle without joints makes opening the cabinet extremely easy. All the doors are fitted as standard with locks and keys and a microswitch to switch off the fan when the door is opened.
- ◆ Stainless steel feet (plastic interior).

- ◆ A wide range of optional accessories are available.
- ◆ CFC and HCFC free.
- ◆ All models comply with the standards required by the main international approval bodies and are H marked.

CHARACTERISTICS	MODELS
	RS06DFX2F 726458
Operating temperature	
first compartment - min/max °C	-2 / 10
second compartment - min/max °C	-15 / -22
Operating mode	Ventilated
Type of stainless steel	
external	304 AISI
Gross capacity (D.I.N. 8952) - l.	300, 300
External dimensions - mm	
width	720
depth/with open doors	788, 1440
height	2000
N° and type of door	2x1/2
Door hinges	Right Side
N° and type of grids (included)	4, GN 2/1
Compressor power - HP	1/5
N° defrost in 24 hrs.	4/20'
Refrigerant type	R134a
Refrigerant quantity - g.	190, 210
Refrigeration power - W	523
Power - kW	
installed-electric	0.93
Net weight - kg.	139
Power supply - V, phases, Hz	230 V, 1, 50
<b>INCLUDED ACCESSORIES</b>	
2 S/S SIDE RUNNERS FOR 600-1300L REFRIG.	4
2/1 GN GREY "RILSAN" GRID	4

