REFRIGERATORS

Π	LEFRIDERAIURS	1896		1898	1899
FE	ATURES & SPECIFICATIONS	Bottom	1897	French Door	French Door
		Mount	Side-by-Side	Full Depth	Counter Depth
C/	APACITY	riount	Side by Side	i un Deptii	counter Depth
	al Fridge & Freezer (cu. ft.)	18.5	25.6	24.8	19.8
Tot	tal Fridge (cu. ft.)	12.9	16.0	17.5	14.4
	tal Freezer (cu. ft.)	5.6	9.6	7.3	5.4
101	di Fieezei (cu. it.)	5.0	9.0	1.5	5.4
RF	FRIGERATOR / FREEZER FEATURES				
		*	*	*	*
	lly adustable shelving	*	*	*	*
	llon size adjustable door storage	*	*	*	*
	aled vegetable crisper with adjustable humidity control		*	*	*
	li bin with adjustable temperature control	*	*	*	*
	spers and bins made of clear durable Lexan [™]		*		
	verage rack	*		*	*
	de out upper freezer basket	*	*	*	*
	parate fridge / freezer controls	-	*	Ŧ	Ť
	nartWater [™] ice / water filtration system through door		Ť	*	*
	ernal filtered water dispenser				
	ctory installed ice maker	Optional	Standard	Standard	Standard
	ergyStar	*	*	*	*
	erguide rating (KwH/year)	448	613	505	480
Sh	ipping weight (lb.)	325	450	400	325
CA	ABINET FEATURES				
Inj	ection molded fiberglass doors with enamel coating	•	•	•	•
Ad	justable rollers provide easy movement for cleaning	•	•	•	•
Sc	ulptured door handles	•	•	•	•
Со	il free back, clean-free condenser	•	•	•	•
Le	ft hand hinge	Optional	N/A	N/A	N/A
		-			
CC	DLORS				
Sta	andard colors - Black, White, Bisque	•	•	•	•
Pre	emium colors - Cayenne Pepper Red, Liberty Blue	•	•	•	•
Nickel Door Handles		Standard	Standard	Standard	Standard
Antique Brass or Antique Copper door handles		Optional	Optional	Optional	Optional
	kel, Antique Brass or Antique Copper door frames	Optional	Optional	Optional	Optional
	· · · · · · · · · · · · · · · · · · ·				
DII	MENSIONS				
А	Height to top of door	67-1/4 "	69-3/4"	69-7/8"	69-7/8"
	Height to top of hinge	66-1/2"	69-3/8"	69-7/8"	69-7/8"
В	Height to top of case	65-3/4"	68-3/4"	68-5/8"	68-5/8"
C	Depth not including door	28-1/4"	28"	29"	24"
D	Depth inlcuding door	33-3/4"	34"	34"	29"
E	Depth including door and handles	33-3/4"	34-1/2"	35-3/8"	30-3/8"
F	Depth with door(s) open 90 degrees	59-1/2"	50-1/2"	48-1/4"	43-1/4"
		52-1/2"	N/A		43-1/4
				54-5/8"	
	Width of case	29-1/4"	35-3/4"	35-5/8"	35-5/8"
I	Width with door(s)	30"	36-3/8"	36"	36"
	Width with door(s) open 90 degrees (not inc. handle)	32-1/4"	39-1/2"	42-7/8"	42-7/8"
	Side clearance from wall for doors to open 90 degrees	2-1/2"	4"	4"	4"
	Side clearance from wall to remove fresh food drawers	15 "	19 "	13-5/8"	13-5/8"
Cutout dimensions:					
	Width	30"	37 "	36"	36 "
	Height	67 "	70 "	70"	70 "
	Minimum depth	24 "	24"	24"	24"
	Ideal depth	28"	28 "	28"	24 "

MICROWAVES & WALL OVENS

FEATURES & SPECIFICATIONS	1895 Microwave	1880 Wall Oven
CAPACITY	2.1 cu. ft.	4.0 cu. ft.
DIMENSIONS		
Overall Dimensions:		
Height	14 "	28-7/8"
Width	24 "	29-7/8"
Depth	20-1/2"	23 "
Cabinet Cut-Out Dimensions (Minimum):		
Height	14-1/4 "	27-3/4"
Width	24-1/4 "	28-1/2"
Cabinet Width		30"
Depth	24 "	23-1/2"
Rear Stop Depth	15-1/2"	N/A
Power Source	120V, 15A	220V, 30A
Shipping Weight	65 lb.	200 lb.
Wall Oven Notes:		
Allow 5-1/4" minimum		
from bottom of cutout to floor.		
Allow 1-1/2" minimum from top of cutout to		
underside of countertop.		
Wall ovens can be installed two high.		

REFRIGERATOR DIMENSIONS



