

Precision Cooling
For *Business-Critical Continuity™*

Liebert XDC™ Refrigerant Chiller

Specifically Designed To Support The Modules In The Liebert XD System



The Liebert XDC Refrigerant Chiller is a part of Liebert's highly energy-efficient high heat density cooling system Liebert XD™.

The system can cool more than 30kW per rack and uses pumped refrigerant, which is ideal for use around electronic equipment.

Liebert XDC is specifically designed to support the Liebert XDO, XDV, XDH and CoolFrame modules. The XDC is an indoor unit that connects directly to the XD cooling modules and it provides refrigerant circulation and control while maintaining the refrigerant at a temperature always above the actual dewpoint.

The packaged unit includes Enclosure, Pumps, Heat Exchanger, Scroll Compressors, Receiver Tank, Controls, Valves and Piping. The XDC is available in an air cooled configuration with remote condenser.



Key Features

- Energy Efficient
- Floor Space Efficient
- Scalable
- Easy to Install

Technical Data

Nominal Capacity, 60 Hz	160 kW / 46 Ton
Nominal Capacity, 50 Hz	130 kW / 37 Ton
Input Voltage	460 V, 3 ph, 60 Hz 380/415 V, 3 ph, 50 Hz
Full load amps	79 A
Height	78" (1981 mm)
Width	74" (1879 mm)
Depth	34 5/8" (879mm)
Weight, empty	1800 lbs (817 kg)

Liebert XD Hydraulic System Schematic



The indoor Liebert Refrigerant Chiller is specifically designed to support the Liebert XD cooling modules. The XDC connects directly to the modules through the pumped refrigerant. When a building chilled water system is available, the Liebert XDP Pumping Unit is utilized as an interface between the pumped refrigerant circuit and the chilled water system. Both the XDC and the XDP units circulate the refrigerant to the XD modules, while maintaining the refrigerant at a temperature always above the actual dewpoint.

Liebert Corporation

1050 Dearborn Drive
P.O. Box 29186
Columbus, Ohio 43229
800 877 9222 Phone (U.S. & Canada Only)
614 888 0246 Phone (Outside U.S.)
614 841 6022 FAX

Via Leonardo Da Vinci 8
Zona Industriale Tognana
35028 Piove Di Sacco (PD)
Italy
39 049 9719 111 Phone
39 049 5841 257 FAX

Emerson Network Power Asia Pacific
7/F., Dah Sing Financial Centre
108 Gloucester Rd, Wanchai
Hong Kong
852 25722201 Phone
852 28029250 FAX

liebert.com

24 x 7 Tech Support

800 222 5877 Phone
614 841 6755 (outside U.S.)

While every precaution has been taken to ensure accuracy and completeness in this literature, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

© 2007 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice.

All names referred to are trademarks or registered trademarks of their respective owners.

© Liebert and the Liebert logo are registered trademarks of the Liebert Corporation.

SL-16670 (R12/07) Printed in USA

Emerson Network Power.
The global leader in enabling
Business-Critical Continuity™.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power
- Monitoring
- Outside Plant
- Power Switching & Controls
- **Precision Cooling**
- Racks & Integrated Cabinets
- Services
- Surge Protection

Emerson Network Power.com

Business-Critical Continuity, Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. ©2007 Emerson Electric Co.