So versatile, so light...so right TTAB-B12D

Tablet PC Configuration

CPU Pentium® M LV Pentium® M UV Celeron® M ULV CPU Speed 738 (1.40GHz) 723 (1GHz) 353 (900MHz) 758 (1.50GHz) 733 (1.10GHz) 373 (1GHz) 753(1.20GHz) 373 (1GHz) Chipset Intel® 855GME/915GMS* 852GM/915GMS* Cache Memory L2: 2MB L2: 512KB Main Memory 256MB RAM on board, one user expandable memory slot Security Kensington Lock Slot, BIOS Password, Cradle Lock Slot, Fingerprint (Optional) HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port, Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature	Model	TTAB-B12D/TTAB-A12D*		
T58 (1.50GHz) 733 (1.10GHz) 373 (1GHz) Chipset Intel® 855GME/915GMS* 852GM/915GMS* Cache Memory L2: 2MB L2: 512KB Main Memory 256MB RAM on board, one user expandable memory slot Security Kensington Lock Slot, BIOS Password, Cradle Lock Slot, Fingerprint (Optional) HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port, Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	СРИ	Pentium® M LV	Pentium® M ULV	Celeron® M ULV
Chipset Intel® 855GME/915GMS* 852GM/915GMS* Cache Memory L2: 2MB L2: 512KB Main Memory 256MB RAM on board, one user expandable memory slot Security Kensington Lock Slot, BIOS Password, Cradle Lock Slot, Fingerprint (Optional) HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	CPU Speed	738 (1.40GHz)	723 (1GHz)	353 (900MHz)
Chipset Intel® 855GME/915GMS* 852GM/915GMS* Cache Memory L2: 2MB L2: 512KB Main Memory 256MB RAM on board, one user expandable memory slot Security Kensington Lock Slot, BIOS Password, Cradle Lock Slot, Fingerprint (Optional) HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		758 (1.50GHz)	733 (1.10GHz)	373 (1GHz)
Cache Memory L2: 2MB L2: 512KB Main Memory 256MB RAM on board, one user expandable memory slot Security Kensington Lock Slot, BIOS Password, Cradle Lock Slot, Fingerprint (Optional) HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand			753(1.20GHz)	
Main Memory 256MB RAM on board, one user expandable memory slot Security Kensington Lock Slot, BIOS Password, Cradle Lock Slot, Fingerprint (Optional) HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Chipset	Intel® 855GME/915GMS*		852GM/915GMS*
Security Kensington Lock Slot, BIOS Password, Cradle Lock Slot, Fingerprint (Optional) HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Cache Memory	L2: 2MB		L2: 512KB
Cradle Lock Slot, Fingerprint (Optional) HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Main Memory	256MB RAM on board, one user expa		indable memory slot
HDD 2.5" 40GB / 60GB / 80GB Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Security	Kensington Lock Slot, BIOS Password,		
Video Graphics Integrated in 855GME / 852GM / 915GMS* Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port, Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0		Cradle Lock Slot, Fingerprint (Optional)		
Display 12.1" XGA TFT LCD with Electromagnetic Digitizer Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	HDD	2.5" 40GB / 60GB / 80GB		
Communication 10/100 Ethernet on MB, WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Video Graphics	Integrated in 855GME / 852GM / 915GMS*		
WLAN 802.11a/b/g, or b/g via Mini PCI, 56K V.92 Modem card, IrDA on MB I/O Ports VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port, Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Display	12.1" XGA TFT LCD with Electromagnetic Digitizer		
S6K V.92 Modem card, IrDA on MB	Communication	10/100 Ethernet on MB,		
VGA Out, DC-in, USB 2.0 x 2, IEEE1394, Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		WLAN 802.11a/b/g, or b/g via Mini PCI,		
Headphone out, Microphone in, Modem Port, LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		56K V.92 Modem card, IrDA on MB		
LAN Port , Docking Port, KBD Stand interface Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	I/O Ports	VGA Out, DC-in, USB 2.0 x 2, IEEE1394,		
Expansion Card Bus Slot for Type I/II, Mini-PCI, MDC Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		Headphone out, Microphone in, Modem Port,		
Audio AC-97 Rev 2.2 / 2.3* / Azalia* compliant, Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		LAN Port , Docking Port, KBD Stand interface		
Integrated Stereo Speakers, Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Expansion	Card Bus Slot for Type I/II, Mini-PCI, MDC		
Integrated full duplex microphone, Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Audio	AC-97 Rev 2.2 / 2.3* / Azalia* compliant,		
Array Microphone (Optional) Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		Integrated Stereo Speakers,		
Battery Lithium Ion (5400mAh @ 7.4V), 4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		Integrated full duplex microphone,		
4 hr battery life with 6-cell battery pack, Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		Array Microphone (Optional)		
Supports S3 Hot Swap Feature Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Battery	Lithium Ion (5400mAh @ 7.4V),		
Power Supply AC Adapter 42W, 12V DC out Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		4 hr battery life with 6-cell battery pack,		
Standard AC Adapter, Power Cord, Stylus Pen, Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		Supports S3 Hot Swap Feature		
Accessories Pen Tether, Quick Start Guide, Recovery CD, 6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Power Supply	AC Adapter 42W, 12V DC out		
6-Cell Battery Pack, Cleaning Cloth, Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Standard	AC Adapter, Power Cord, Stylus Pen,		
Detachable keyborad stand, User Manual Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Accessories	Pen Tether, Quick Start Guide, Recovery CD,		
Optional 10-Cell Extended Battery Pack, Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		6-Cell Battery Pack, Cleaning Cloth,		
Accessories External Battery Charger, Slim USB Keyboard, RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		Detachable keyborad stand, User Manual		
RF Mouse, Docking Cradle, Slipcover, Carrying Bag, Wire Stand Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Optional	10-Cell Extended Battery Pack,		
Carrying Bag, Wire Stand 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)	Accessories	External Battery Charger, Slim USB Keyboard,		
Dimension 9.13" x 11.92" x 0.73" (232 x 303 x 18.6mm)		RF Mouse, Dock	king Cradle, Slipcove	er,
		Carrying Bag, W	ire Stand	
Weight 3.08 lbs (1.4Kg) with 6-Cell Battery Pack	Dimension	9.13" x 11.92" x	0.73" (232 x 303 x	18.6mm)
	Weight	3.08 lbs (1.4Kg) with 6-Cell Battery Pack		

 * New TTAB-A12D with 915GMS Chipset is available on Q1 2005 according to Intel product roadmap.

*** Tatung Co. reserves the right to change specifications or other product information without notice.

*** Intel, Intel Inside, the Intel Inside logo, Intel Centrino, the Intel Centrino logo, Pentium and Celeron are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Microsoft, the Windows logo, and Windows XP are trademarks or registered trademarks of Microsoft Corporation or its subsidiaries in the United States and other countries.

Tablet PC Product Business Contact

United States: Tatung Science & Technology, Inc. 436 Kato Terrace Fremont, CA 94539 U.S.A. TEL: 510-687-9688 FAX: 510-687-9588 Sales: (800) 659-5902 email: sales @tsti.com







TTAB-B12D

- Lighter and Thinner
- Longer-lasting Battery
- Fingerprint Recognition
- Intelligent Light Sensor
- Array Microphone
- Reduced Parallax









Highlights of the Tablet PC

The Tangy Tablet PC runs Microsoft® Windows® XP Tablet PC Edition and features the capabilities of current Windowsbased applications, as well as digital handwriting and speech recognition, which allow you to use the PC even more easily.

Features

Lighter and Thinner

At 1.4kg (3.08 lbs) and 0.73 inches thick, the super-thin design makes taking your Tablet PC with you even easier.

Longer-lasting

The battery lasts up to 6 hours with 10-cell battery pack.

Fingerprint Recognition

The unique recognition system makes your Tablet even safer and more convenient for you.

Intelligent Light Sensor

The light sensor automatically adjusts the screen brightness in response to the environment, changing it to a comfortable level.

Array Microphone

The array microphone eliminates background noise, increasing your rate of speech recognition, so that even when making Internet calls, you can talk to your heart's content.


Reduced Parallax

Special measures to reduce the gap between the stylus tip and the on-screen ink make writing more truly natural.

Suddenly, it connects with all of your devices.

VGA Out, DC-in, PCMCIA, USB 2.0 x 2, IEEE1394, Headphone Out, Microphone in, Modem Port, LAN Port, Docking Port, Keyboard stand interface





Expandability

The **TTAB-B**12D is highly expandable. You may choose to purchase any of the following optional accessories to make using your Tablet PC even more convenient.

Connect your Tablet to an external keyboard.

 Easy to hook up to the Tablet and convenient to carry.







Connect your Tablet to the docking station.

- The Tablet can be rotated 90° on the docking station, allowing you to use the portrait or landscape setting.
- When you rotate the Tablet PC on the cradle, the on-screen image automatically rotates, too.



- The optical disk drive can be swapped out.
- When using the docking station, incline your Tablet to the four different viewing angles to find which is the most comfortable for you.

Handy, light-weight battery charger

You can charge the battery while the computer is in use and even charge an additional spare battery at the same time!

