

User Manual

LED Flashlight

Model No.:GD-3410



FC CE

Safety Cautions

- Clean the product with clean damp cloth but never with chemical solvents and cleaning agent.
- Charge the battery with the product's own charger but never with chargers of otherwise specifications and parameters, to avoid damaging the product.
- Our company will not bear any responsibility for unauthorized dismounting of the flashlight.
- The device is powered up by Li battery. If the battery is damaged or needs to be replaced, contact our company or our vendor. When leaving the device unused for a long time, remove the battery house, and make sure to recharge the battery every three month.
- Light directly to eyes is forbidden, as it may hurt the eyes.

Warning: The use of the product out of illegal purpose is forbidden. We are not liable for any claim and punishment raised from unauthorized use of the product.

Introduction

The flashlight module is provided with one 3W Cree Q4 to output 190LM light. With only one button, the light can cycle through strong-soft-weak-blink. The LED flashlight is powered by 26650 Li battery. The beam distance is 200m, which make it ideal for diving, hunting, military, police, and outdoor activities.

Features

- Versatile modules can be attached, including flashlight camera, GPS guard tour system, gas detector, infrared thermometer, vibration detector, high-pitch alarm, etc.

- Quick & easy installation with accessories and other modules through battery.
- 3 W CREE LED.
- Battery with overcharge, overdischarge, and short current protection, and can be used to provide power for mobile phone.
- Several batteries can be connected on the LED flashlight as required.

Technical Data

LED	LED type		Cree Q4
	Current	strong	800mA
		soft	520mA
		weak	220mA
		blink	200mA
	Voltage		4.2V
	Power		3W
Battery	Light Intensity		190LM
	Battery type		26650 Li battery*1
	Capacity		4000mAh
	Power		14.8wH
	Service life		>500 recharges
	Recharge voltage		4.2V
	Recharge time		4hrs

User Manual | LED Flashlight GD-3410

	Run time	Strong	5hrs
		Soft	7.5hrs
		Weak	18hrs
		Blink	20hrs
Size	34*155mm		
Rating	IP65		

Operations

Install Li battery. Gently press the on-off button to cycle through each light mode: strong-soft-weak-blink. The flashlight will remain in the mode in which it was in when last turned off. The flashlight will turn off when you press the switch once after ending blink mode.

Standard Components

- | | |
|------------------|---------------|
| 1 LED Flashlight | 1 Li-battery |
| 1 Charger | 1 User Manual |

Options

- **Battery**
26650 Li-battery 4000mAH with overcharge, overvoltage and overcurrent protection.
- **Battery Connector**
For connecting two 26650 batteries in parallel to increase battery quantities and capacity.
- **Charger Cap**

For recharge battery.

- **10W LED Flashlight**

1*Cree XM-L T6 LED outputting 1000 lumens to a distance of 500 meters.

- **UV Flashlight**

1W UV LED, 365nm wavelength, UV intensity: 1500μw/cm²".

- **Multi-color LED Flashlight**

1W RGB powerful LED. 7 types of pure colors.

- **720P Camera Flashlight**

3*Cree Q4 LEDs outputting 750lumens to a distance of 200m; records 720p video, 5mp photo.

- **1080P Camera Flashlight**

2*Cree Q4 LEDs outputting 500 lumens; records 1080p video, 8mp photo.

- **RFID Guard Tour System**

RFID induction, real-time data transfer through Wi-Fi 3G web.

- **Infrared Thermometer**

Range: -30 °C to 280 °C (-22 to 536 °F); D:S, 8:1.



北京国电科院检测科技有限公司
BEIJING GUODIAN NDT CO., LTD.

Building 309, Guodian New Energy Technology Research Institute, Future
Science and Technology Park, Changping District, Beijing, 102209, China

t: +86 10 56978358 +86 10 56978359

f: +86 10 56978357

Web: www.bjadsk.com