



X320

Compact Thermal Imager

EO Tech X320 – Ruggedized Ultra Compact Thermal Imager with 320 x 240 resolution and advanced features!

BENEFITS

- Simple one-button operation
- Greater scene detail with VGA 320 x 240 resolution
- Video port for simultaneous recording
- Covert operation with fully dimmable microdisplay
- Stows easily into pocket for quick extraction and agile operation in the field and on the run
- Customize camera features with provided user interface software

FEATURES

- 30 Hz frame rate
- 9 Hz model available
- Detect human activity up to 800 yards away
- 2x, 3x or 4x zoom
- White hot, black hot and 3 color modes
- Temperature measurement & cross hair enabled via supplied software CD
- Survives accidental drops and submersion
- Pocket-sized, weighing only 13 ounces (381 grams)
- Up to 6 hours runtime with two user-replaceable AA lithium batteries*
- Rugged design with integral rubber eye cup - 3-Year Warranty
- Tripod mount (1/4 - 20 thread)



Camera Kit Includes

- USB Cable
- User Interface Software
- Lens Cloth
- Neck/Wrist Straps
- User Manual
- AA Batteries*



COVERT SURVEILLANCE
CRIME SCENE INVESTIGATION
SEARCH & RESCUE
MECHANICAL INSPECTION
ELECTRICAL INSPECTION



FUGITIVE PURSUIT
OUTDOOR RECREATION
HUNTING
FARMING / RANCHING



*Compatible with AA alkaline batteries, but improved performance can be obtained with lithium-style batteries.



An **L3** Communications Company

X320 - Compact Thermal Imager



X320

Compact Thermal Imager

X320 TECHNICAL SPECIFICATIONS		
FEATURES		X320
FOCAL PLANE ARRAY	MATERIAL & STRUCTURE	Amorphous Silicon Microbolometer
	PIXEL COUNT (RESOLUTION)	320 x 240
	SPECTRAL RESPONSE	7 to 14 μ m (filter bandwidth)
	THERMAL SENSITIVITY	\leq 40 mK
THERMAL IMAGING PERFORMANCE	START-UP TIME	5 seconds (includes 2-second display of start-up logo)
	BRIGHTNESS/CONTRAST	Fully automatic
	RANGE TO DETECT HUMAN ACTIVITY	Up to 800 yards
	E-ZOOM	2X, 3X or 4X e-zoom as default on power push button
	INFRARED POLARITY	White hot, black hot, detection palettes and custom color modes
OPTICS	FOV (H x V)	12° x 9°
	FOCAL LENGTH (MM)	25 mm
	MINIMUM FOCUS DISTANCE	3 ft. (1 m)
VIDEO	OUTPUT FORMAT	Simultaneous NTSC output available on rear outlet jack
	VIEWFINDER DISPLAY	Color LCD (320 x 240 pixels)
	VIEWFINDER DIMMING	Integral to power on/off switch
POWER	POWER SOURCE	2 AA batteries (lithium recommended)
	OPERATING TIME	6 hours with lithium
	AUXILIARY POWER	12 VDC input on rear outlet jack
ENVIRONMENTAL CHARACTERISTICS	OPERATING TEMPERATURE	-4 °F to 140 °F (-20 °C to 60 °C)
	STORAGE TEMPERATURE	-4 °F to 176 °F (-20 °C to 80 °C)
	WATER & SHOCK RESISTANCE	Waterproof to 3 ft. (1 m) submersion, buoyant. Shockproof (MIL-STD-810G, Method 516.6).
	EMC COMPLIANCE	FCC Part 15 & CE Mark
PHYSICAL CHARACTERISTICS	SIZE	5 1/4" L x 4 1/2" W x 2" H (13.4 x 11.4 x 5.1 cm)
	WEIGHT	13 oz (381 g), batteries installed
	EYE CUP	Integral to camera body
ORDERING INFORMATION	CAMERA PART NUMBERS	30 Hz Camera - NTSC: 5002021-1 9 Hz Camera - NTSC: 5002020-1
CAMERA FEATURES	<ul style="list-style-type: none"> White hot, black hot, detection palettes and custom color modes On-screen battery level indicator Left- or right-hand operation with rugged slip-resistant grip 1/4 - 20 tripod mount 	<ul style="list-style-type: none"> Tactile battery loading feature for stealth nighttime operation External power input and video output jacks Long eye-relief viewfinder for use with glasses, face shields, masks, etc. Push-button control to activate feature set
STANDARD EQUIPMENT	<ul style="list-style-type: none"> 2 AA lithium batteries Neck strap & wrist strap 	<ul style="list-style-type: none"> Lens cover Lens cleaning cloth USB cable Interface software CD
OPTIONAL EQUIPMENT	<ul style="list-style-type: none"> MOLLE-Compatible soft pouch - 5002070 DVR cable 5002024 	<ul style="list-style-type: none"> BNC video cable - 5002068 A/C power adapter - 5002067

Specifications subject to change without notice.

Optional Equipment Example:



MOLLE-Compatible Soft Pouch

L-3 EOTech is ISO 9001:2000 certified.

This material consists of L-3 Warrior Systems general product information that does not contain controlled technical data as defined within the International Traffic in Arms (ITAR) Part 120.10 or Export Administration Regulations (EAR) Part 734.7-11.

1201 E. Ellsworth Road, Ann Arbor, MI 48108



An L3 Communications Company