



SHENZHEN KERCHAN TECHNOLOGY CO., LTD.

2/F, Building 1, Fu'an Industrial Park, Dayang, Fuyong Town, Bao'an District, Shenzhen

T: +86 755 82717421 82717429 F: +86 755 82717423 Web: www.szhyelec.com

Wireless Signage Display Price List

Model#: WSD9720C		specification	
		Delivery Time	10-15 Days
		Payment Term	T/T, Paypal
		Valid Time	15 Days
		Certificate	CE/FCC/Rohs
Main Function			
<p>1.Slot:USB2.0, DC 2.Auto Play: Auto play after plug the Memory Card or USB Driver 3.File Format: Support JPG, MPEG1/2/4, Divx, Xvid, M-Jpeg 4.WiFi: 802.11b/g (WEP/WPA/WPA2), built with Antenna 5.File Management: Upload or Delete the media files from local to sever 6.Playlist: Create or Delete playlist 7.Schedule: Schedule different playlist to be displayed in the timebucket 8. Preview: Preview created playlist, make sure all files is correct 9 Assign LCD: Assign LCD to different user 10.Group LCD: manage LCDs via different group 11. Smart Update: Only download the files which are new or changed; 12. Remote Setting: Setup volume, turn on / turn off time of each WSD, and reboot, erase memory, update the firmware of each WSD from server at anywhere by Internet connected PC</p>			
Assessoris		Panel Data	
<p>1. User Manual</p> 		Panel Size	7" TFT LED (154*86 mm)
		Display Ratio	16:9
		Resolution	800*480
		Color	16.7M
		Pixel Pitch (mm)	0.0642(W) x 0.1790(H)
		Brightness (nits)	250cd/m ²
		Contrast	300:1
		View Angle	140° / 120°
		Response Time	10ms
		Life (hrs)	50000
<p>2. Remote Controller</p> 		Specification	
		Material	Leather Pillow + Plastic Case (Suitable for Taxi)
		Installation	Taxi Headrest
		Unit Size	290*380*130mm
		Image Resolution	5000 x 5000p Max
		Video Resolution	720 x 480p Max
		Internal Memory	128MB to 1GB (Price didn't Include any Memory)
		Speaker	2 x 1W (at the side)
		Remote Controller	IR Remote Controller
		G-Sensor	Don't Support
		Menu Language	English, Germany, French, Spanish, Russian and Others
		Power Supply	12V DC, 2A
		Power Consumption	≦ 4.08W
		Power Supply	100-240V AC / 12V DC, 2A
		Working temperature	0°C~50°C
		Storage temperature	-20°C~60°C
		Working humidity	85%
		Packing	1pc/ctn, 36x31x15 CM, N.W.: 2kg, G.W.: 2.6kg
		Standard Color	black
Optional Accessories		Optional Function	
<p>1) 3G Router</p> 			