



iiyama's most recent addition to the widescreen monitor portfolio, the E2003WSV 20.1" panel is aimed at the user who appreciates the higher 1680x1050 screen resolution but lacks space for a 22". Improved features include an even faster 2ms response time for excellent results in gaming and video playback, increased brightness of 300 cd/m<sup>2</sup> and a sharp 2000:1 Dynamic Contrast Ratio delivering crisp, vivid images in any application. The smart black casing incorporates stereo speakers and the access controls for the On Screen Display Menu.

## 1. DISPLAY CHARACTERISTICS

DIAGONAL	20"; 51cm
PANEL	TN
DISPLAY AREA H X W	270.9 x 433.4 mm; " x "
RESPONSE TIME	2 ms
CONTRAST	2000 : 1 DCR
BRIGHTNESS	300 cd/m <sup>2</sup> typical
VIEWING ZONE	horizontal/vertical: 170° / 170°; right/left: 85° / 85°; up/down: 85° / 85°
DISPLAY COLOUR	16.7 million
PIXEL PITCH H X V	0.258 x 0.258 mm
NATIVE RESOLUTION	1680 x 1050 ( 1,8 megapixel)
HORIZONTAL SYNC	31 - 83 KHz
VERTICAL SYNC	56 - 75 Hz
BANDWIDTH	165 MHz
SYNCHRONIZATION	Separate Sync
ASPECT RATIO	16 : 10

## 2. INTERFACES CONNECTORS

ANALOG INPUT CONNECTOR	D-Sub
HEADPHONE CONNECTOR	Yes
OUTPUT CONNECTOR	headphone socket

## 3. SPECIAL FEATURES

APPLE - MAC	All iiyama monitors are compatible with Apple-Macintosh computers.
PLUG & PLAY	VESA DDC2B™
CONTROLS	On-Screen-Display in 10 languages (GB, F, D, I, ESP, JP, NL, PL, RU, CH) and 6 Front controls (Auto, Exit/Volume, Scroll down/Contrast, Scroll up/Brightness, Menu/Select, Power)
USER CONTROLS	auto adjust, luminance (brightness, contrast), geometry (clock, phase, V-position, H-position), colour temperature, OSD language, OSD position, OSD time out, recall, miscellaneous (sharpness, DDC/CI, display information, DCR, OD), volume
SPEAKERS	2 x 1 W (Stereo)
ANTI-THEFT-DEVICE	Kensington-lock™ prepared
ERGONOMICS	TCO '03, CE, MPR 3 (prEN50279), ISO 13406-2
SAFETY	TÜV GS, FCC-B, UL / C-UL, VCCI-B, GOST-R, CB
TILT ANGLE	22° up; 2° down
VESA MOUNTING	100 mm
COLOUR	Black
VISTA PREMIUM	Yes

## 4. ACCESSORIES

DRIVER	Windows 95 / 98 / 2000 / ME / XP / Vista
INCLUDED ACCESSORIES	power cable, D-Sub signal cable, audio cable, user manual, stand

## 5. POWER MANAGEMENT

POWER SUPPLY	AC 100 - 240 V, 50 / 60 Hz
POWER SUPPLY UNIT	internal
POWER USAGE	max. 49 W in normal use; max. 2 W in Power management mode
POWER MANAGEMENT	VESA DPMS, ENERGY STAR®

## 6. DIMENSIONS & WEIGHT

DIMENSIONS W X H X D	480 x 399 x 188 mm
WEIGHT	4.4 kg

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION ( ). ALL RIGHTS RESERVED.