

Z30 LED Controller



D.T.S. Code
03.LA.072 (RJ12 OUTPUT)
03.LA.077 (PLUG-IN OUTPUT)

User's Manual Rel 1.0 **GB**

D.T.S. Illuminazione srl - ITALY
<http://www.dts-lighting.it>



The Lighting Company

Made in Italy

Le informazioni contenute in questo documento sono state attentamente redatte e controllate. Tuttavia non è assunta alcuna responsabilità per eventuali inesattezze. Tutti i diritti sono riservati e questo documento non può essere copiato, fotocopiato, riprodotto per intero o in parte senza previo consenso scritto della D.T.S .

D.T.S si riserva il diritto di apportare senza preavviso cambiamenti e modifiche estetiche , funzionali o di design a ciascun proprio prodotto. D.T.S non assume alcuna responsabilità sull'uso o sull'applicazione dei prodotti o dei circuiti descritti.

The information contained in this publication has been carefully prepared and checked. However, no responsibility will be taken for any errors. All rights are reserved and this document cannot be copied, photocopied or reproduced, in part or completely, without prior written consent from D.T.S. D.T.S. reserves the right to make any aesthetic, functional or design modifications to any of its products without prior notice. D.T.S. assumes no responsibility for the use or application of the products or circuits described herein.

Les informations contenues dans le présent manuel ont été rédigées et contrôlées avec le plus grand soin. Nous déclinons toutefois toute responsabilité en cas d'éventuelles inexactitudes. Tous droits réservés. Ce document ne peut être copié, photocopié ou reproduit, dans sa totalité ou partiellement, sans le consentement préalable de D.T.S.

D.T.S. se réserve le droit d'apporter toutes modifications et améliorations esthétiques, fonctionnelles ou de design, sans préavis, à chacun de ses produits. D.T.S. décline toute responsabilité sur l'utilisation ou sur l'application des produits ou des circuits décrits.

Las informaciones contenidas en este documento han sido cuidadosamente redactadas y controladas. Con todo, no se asume ninguna responsabilidad por eventuales inexactitudes. Todos los derechos han sido reservados y este documento no puede ser copiado, fotocopiado o reproducido, total o parcialmente, sin previa autorización escrita de D.T.S.

D.T.S. se reserva el derecho a aportar sin previo aviso cambios y modificaciones de carácter estético, funcional o de diseño a cada producto suyo. D.T.S. no se asume responsabilidad de ningún tipo sobre la utilización o sobre la aplicación de los productos o de los circuitos descritos.

DESCRIPTION

Overview

Z30 is a power supply / DMX LED controllers designed to control the following D.T.S. LED products:

FOCUS LED projectors, MR16 LED lamps , DIVE 3

System

Z30 is fitted with 10 outputs of 3 channels each; max power of each output is 15W, max power of each channel is 5W. (5W RED, 5W GREEN, 5W BLUE)

Each output can supply and control an independent set-up of D.T.S. LED products at the same time, like one of the following:

- * max 3 x MR16 RGB LED lamps
- * max 1 x MR16 Full Color LED lamps
- * max 3 x FOCUS RGB LED projectors
- * max 1 x FOCUS Full Color LED projectors
- * max 1 x DIVE 3 FULL COLOUR

Interface

Z30 is fitted with a LED interface that lets you enter all functions of the internal menu.

DMX

Z30 LED CONTROLLER can be used in 2 DMX mode: 30 ch or 9 ch mode.

Operating system update

Z30 internal operating system can be updated via computer, through the dedicated D.T.S. RED BOX interface

Control

Z30 can be controlled by any DMX console.

Moreover, Z30 can be used in Master or Slave mode (max 32 slaves).

Construction

Z30 is housed in a sturdy metal case, that offers high resistance to knocks and mechanical stress.

Z30 is rack mountable.

The protection rating against external agents is Ip20.

Connections

DMX IN / OUT 2 XLR 5-pole by Neutrik and 2 XLR 3-pole by Neutrik.

LEDs connector output:

Two models available; RJ12 female connector (03.LA.072) / 6 poles plug-in screw connector (03.LA.077) .

(The Maximum distance between the Z30 and the last LED unit in the line should not exceed 60 meters).

MAIN ELECTRICAL CHARACTERISTICS

Input Voltage Range

Vin 90 - 260 Vac

Frequency

50 - 60 HZ

Power Consumption Range

16 - 200 W

Power Factor (Pf)

0.95 electronic PFC controller

Efficiency

90% typical

Output

Power Output Range : 10 outputs of 3 channels each (1,5 - 5W per channel)

Output Current : 350 mA @ 100% per channel

Output Voltage : Vout 12V

Max Load (output) per output : 3 x MR16 RGB LED lamps, 1 x MR16 Full Color LED lamps,
3 x FOCUS RGB LED projectors, 1 x FOCUS Full Color LED projectors, 1 x DIVE 3 full colour.

Min Load (output) per group: 1 x MR16 RGB LED lamp

Control Input

Control Signal : DMX 512

Dimming System :Constant Current PWM

Address Range : DMX 512 channels addressable by display

IMPORTANT SAFETY INFORMATION

Fire prevention:

Never locate the fixture on any flammable surface.
 Minimum distance from flammable materials: 10 cm
 Replace any blown or damaged fuses only with those of identical value

Prevention from electric shock:

High voltage is present inside the unit.
 Unplug the unit prior to performing any operation which involves touching the inside of the unit.
 This equipment must be grounded, do not connect to non-grounded supplies.
 The use of a thermal magnetic circuit breaker is recommended for each Z30.
 Use only AC supplies 90-260V, 50-60Hz
 The unit should never be located in position exposed to rain or in areas of extreme humidity.
 A good air ventilation is essential for proper equipment work.

Safety:

The external surface of the unit may exceed 50°C; never handle the unit until at least 5 minutes have elapsed since the unit was turned off.
 Never install the unit in an enclosed area lacking sufficient air flow.
 The ambient temperature should not exceed 40°C and should not be lower than -10°C

UNIT DIMENSION


Unit Dimensions
 (LxDxH)
 480 x 385 x 88 mm

Weight
 7,5 Kg



Packing Dimensions
 (LxDxH)
 490 x 390 x 90 mm

Weight
 8,5 Kg



INPUT/OUTPUT CONNECTIONS

03.LA.072 (RJ12 OUTPUT)



Mains Switch


Displays

Mains 90-260 Vac
50-60 Hz
Powercon female panel connector




10 x LEDs output
RJ12 Female panel connector



DMX IN-OUT connectors



- Pin 1 = RED +
- Pin 2 = RED -
- Pin 3 = GREEN +
- Pin 4 = GREEN -
- Pin 5 = BLUE +
- Pin 6 = BLUE -



6-pin Female (RJ12)



6-pin Male (Rj12)
Modular Plug

RJ12 : 6P6C

6P6C indicates 6 positions 6 cables

For application where IP65 rating is not necessary, Z30 LEDs cabling connection can be done with a standard UTP TIA/EIA 568-B2 category 5E cable.

The maximum distance between power supply and the last unit on the line should not exceed 60meters.

For IP65 rating application, D.T.S. reccomed the use of a IP65/68 cable as the 4X2XAWG24 multipolar black outdoor cable (D.T.S. Code: 0509C062).

The maximum distance between power supply and the last unit on the line should not exceed 60meters.

INPUT/OUTPUT CONNECTIONS

03.LA.077 (PLUG-IN OUTPUT)



Mains Switch


Displays

Mains 90-260 Vac
50-60 Hz
Powercon female panel connector




10 x LEDs output
6 poles plug-in screw connector

DMX IN-OUT connectors



- Pin 1 = RED +
- Pin 2 = RED -
- Pin 3 = GREEN +
- Pin 4 = GREEN -
- Pin 5 = BLUE +
- Pin 6 = BLUE -



1----PIN----6

6 poles plug-in screw connector

For application where IP65 rating is not necessary, Z30 LEDs cabling connection can be done with a standard UTP TIA/EIA 568-B2 category 5E cable.

The maximum distance between power supply and the last unit on the line should not exceed 60meters.

For IP65 rating application, D.T.S. reccomed the use of a IP65/68 cable as the 4X2XAWG24 multipolar black outdoor cable (D.T.S. Code: 0509C062).

The maximum distance between power supply and the last unit on the line should not exceed 60meters.

DMX SIGNAL CONNECTION:


The unit operates using a digital DMX 512 signal. Connection between the controller and the unit or between units must be carried out using a two pair screened \varnothing 0.5 mm cable and a CANNON XLR 3/5 pins connector.

Ensure that the conductors do not touch each other. Do not connect the cable ground to the XLR chassis. The plug housing must be isolated. Connect the mixer signal to the DMX IN of the Z30 plug and connect it to the next unit by connecting the DMX OUT plug on the first Z30 to the DMX IN plug of the second one.


This way, all the projectors are cascade connected.



Standard
DMX 512
controller



Standard
DMX 512
controller




P.S:

If the display showing the DMX address flashes, then one of the following errors has occurred:


- DMX signal not present
- DMX reception problem

For Installations where long distance DMX cable connections are needed, we suggest to use a DMX terminator.

The DMX terminator is a male XLR 3-5 pins connector with a 120 ohm resistor Between pin 2 and 3. The DMX terminator must be plugged into the last unit (DMX out panel connector) of the DMX line.



PLACE A 120 OHM RESISTOR BETWEEN PIN 2 AND 3 OF A MALE XLR CONNECTOR AND PLUG IT INTO THE DMX OUT PANEL CONNECTOR OF THE LAST UNIT CONNECTED TO THE DMX LINE



DMX ADDRESS

Z30 LED CONTROLLER can be used in 2 DMX mode: 30 ch or 9 ch mode.

If you want to use the Z30 in 30 channels mode, select the 30 CH mode from the MODE menu and set the following addresses on the mixer:

Projector 1 A001
 Projector 2 A031
 Projector 3 A061
 A....
 projector 6 A151

If you want to use the Z30 in 9 channels mode, select the 9 CH mode from the MODE menu and set the following addresses on the mixer:

Projector 1 A001
 Projector 2 A010 If you want to select the next projector, just add "9"
 Projector 3 A019
 A....
 projector 6 A046


Selecting the DMX address

- 1) Press the UP-DOWN key until you reach the required DMX address. The numbers on the display will start flashing (but the new DMX address hasn't yet been set).
- 2) Press ENTER to confirm your selection. The numbers on the display will stop flashing and the projector is now controlled by the new DMX address.

TIPS: if you keep pushed the UP or DOWN keys, the channels are calculated more quickly and you get a faster selection.

DISPLAY FUNCTIONS

Z30



DISPLAY FUNCTIONS

The Z30 display panel shows all the available functions. Using these functions, it is possible to change some of the parameters and add some functions. Changing the D.T.S. setting can vary the functions of the unit so that it does not respond to the DMX 512 signal used to control it. Carefully follow the instructions below before carrying out any variations or selections.

NOTE: the symbol  shows which key has to be pushed to obtain the desired function.

Z30 Software version 2.00

 Menu  Up-Down Global setting

SECURITY\ DEFAULT SETTING\ UPLOAD FIRMWARE\
DOWNLOAD FIRMWARE\ ABOUT

Security
This menu allow to select a security password to lock the user's settings

Default Setting:
To restore main settings

Upload firmware:
Upload the firmware by DMX
This menu allow to upgrade the unit's software by computer

Download firmware:
This menu allow to save unit's programs into computer

About:
Master pcb code, pcb revision, SW version

 ENTER  Up-Down



2.DISPLAY SETTING

- 1.Security
- 2.Default setting
- 3.Upload firmware
- 4.Download firmware
- 5.About...

Security

This menu allow to select a security password to lock the user's settings

 ENTER

Default setting:

To restore main settings

 ENTER

Upload firmware

Upload the firmware by DMX
This menu allow to upgrade the unit's software by computer

Download firmware

This menu allow to save unit's programs into computer

 ENTER

About

Master pcb code, pcb revision, SW version

 ENTER

  **Display Setting**  

Flip visual / Background colour / Backlight level / contrast level / Screen saver



Flip visual:
Reverses display's reading depending on the mounting position (On the ground or suspended).

Background color:
To select the colour of the display background

Backlight level:
Default=95%.

Contrast level:
Display contrast

Screen saver
This menu allow to activate the screen saver.



Flip visual:
Flip visual OFF (Default)
Flip visual ON



Background color:
Background NORMAL (Default)
Background REVERSE



Backlight level:
Back light intensity from 0% to 100% default 95%



Contrast level






Page under construction

Screen saver:
Screen saver TYPE (default disabled)
Screen saver TIME (default 10 sec.)



  **Mode setting**  

DMX MODE
To select DMX mode :
30 DMX ch or 9 DMX channel control



MODE SETTING




DMX mode setting
Full control map = 30 DMX ch (default)
Z1 type map = 9 DMX ch mode



LED Setup

Hardware test\ LED min setting\
LED max setting\ MR16 full color\
Output filter\ output delay\ PWM
Frequency.

PWM frequency value
This menu allow to adjust the PWM
frequency value (Hz) in order to
reduce flickering in the process of
your camera recordings



4.LED SETUP
1.Hardware test
2.Led MIN setting
3.Led MAX setting
4.MR16 full colour
5.Output filter

4.LED SETUP
6.Output delay
7.PWM frequency

HARDWARE TEST:
Hardware test OFF (default)
Hardware test ON



LED MIN SETUP



MIN level RED
MIN level GREEN
MIN level BLUE

LED MAX SETUP



MAX level RED
MAX level GREEN
MAX level BLUE

MR16 FULL COLOUR
MR16 limit OFF (Default)
MR16 limit ON



OUTPUT FILTER
Output filter OFF
Output filter ON (Default)



OUTPUT DELAY
No output delay
Short delay (default)
Long delay



PWM frequency

490Hz
1000Hz (default)
2000Hz
3000Hz
4000Hz
5000Hz
6000Hz
7000Hz
8000Hz
9000Hz
10000Hz



Measure

Lifetime \ voltage level \
temperature \ DMX tester

Lifetime
This menu show the total UNIT LIFE
TIME (reset not possible) and the
RGB life TIME (reset possible)

Voltage level
Internal voltage measure

Temperature
Internnal / External temperature
measure

DMX tester
DMX channels tester




MEASURE

5.MEASURE
1.Lifetime
2.Voltage level
3.Temperature
4.DMX tester

LIFETIME
Unit lifetime
LED Lifetime

Voltage level

Internal voltage measure

Temperature

Internnal / External temperature
measure

DMX tester

DMX channels tester






DMX PROTOCOL**Z30 RGB 30 CHANNELS MODE****60 CHANNELS****MODE (Default)**

1	RED	1	16	RED	6
2	GREEN	1	17	GREEN	6
3	BLUE	1	18	BLUE	6
4	RED	2	19	RED	7
5	GREEN	2	20	GREEN	7
6	BLUE	2	21	BLUE	7
7	RED	3	22	RED	8
8	GREEN	3	23	GREEN	8
9	BLUE	3	24	BLUE	8
10	RED	4	25	RED	9
11	GREEN	4	26	GREEN	9
12	BLUE	4	27	BLUE	9
13	RED	5	28	RED	10
14	GREEN	5	29	GREEN	10
15	BLUE	5	30	BLUE	10

DMX CHANNEL	1	Parameter: RED 1			
-------------	----------	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	2	Parameter: GREEN1			
-------------	----------	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	3	Parameter: BLUE 1			
-------------	----------	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	4	Parameter: RED 2			
-------------	----------	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	5	Parameter: GREEN 2			
-------------	----------	---------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	6	Parameter: BLUE 2			
-------------	----------	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	7	Parameter: RED 3			
-------------	----------	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	8	Parameter: GREEN 3			
-------------	----------	---------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	9	Parameter: BLUE 3			
-------------	----------	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	10	Parameter: RED 4			
-------------	-----------	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	11	Parameter: GREEN 4			
-------------	-----------	---------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	12	Parameter: BLUE 4			
-------------	-----------	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	13	Parameter: RED 5			
-------------	-----------	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	14	Parameter: GREEN 5			
-------------	-----------	---------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	15	Parameter: BLUE 5			
-------------	-----------	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	16	Parameter: RED 6			
-------------	-----------	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	17	Parameter: GREEN 6			
-------------	-----------	---------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	18	Parameter: BLUE 6			
-------------	-----------	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	19	Parameter: RED 7			
-------------	-----------	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	20	Parameter: GREEN 7			
-------------	-----------	---------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	21	Parameter: BLUE 7			
-------------	-----------	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	22	Parameter: RED 8			
-------------	----	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	23	Parameter: GREEN 8			
-------------	----	---------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	24	Parameter: BLUE 8			
-------------	----	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	25	Parameter: RED 9			
-------------	----	-------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	26	Parameter: GREEN 9			
-------------	----	---------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	27	Parameter: BLUE 9			
-------------	----	--------------------------	--	--	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	28	Parameter: RED 10
-------------	-----------	--------------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	29	Parameter: GREEN 10
-------------	-----------	----------------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX CHANNEL	30	Parameter: BLUE 10
-------------	-----------	---------------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
000-255					Proportional colour

DMX PROTOCOL**9 CHANNELS MODE**

- 1 SHUTTER**
- 2 DIMMER**
- 3 RED**
- 4 GREEN**
- 5 BLUE**
- 6 WHITE (Pre-programmed whites at different color temperatures)**
- 7 CTC**
- 8 COLOURS MACRO**
- 9 FUNCTIONS**

DMX CHANNEL	1	Parameter: SHUTTER
-------------	----------	---------------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
0-9	5				Black-out
10-19	14				Open
20-29	24				Black-out
30-119					Strobe at variable speed from slow to fast (3400ms-20ms)
120-149					Pulse open at variable speed from slow to fast (43s-100ms)
150-179					Pulse close at variable speed from slow to fast (43s-100ms)
180-204	192				Random Strobe (Master and RGB active)
205-229	218				Random Strobe (Full)
230-255	240				Open

DMX CHANNEL	2	Parameter: DIMMER
-------------	----------	--------------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
0-255					Proportional dimmer

DMX CHANNEL	3	Parameter: RED
-------------	----------	-----------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
0-255					Proportional colour

DMX CHANNEL	4	Parameter: GREEN
-------------	---	-------------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
0-255					Proportional colour

DMX CHANNEL	5	Parameter: BLUE
-------------	---	------------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
0-255					Proportional colour

DMX CHANNEL	6	Parameter: WHITE (Pre-programmed White at diff. color temperature)
-------------	---	---

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
0-55	23				No Function
56-105	80				Full (Red-Green-Blue at Full)
106-155	130				White DTS

IF CHANNEL 9 (FUNCTIONS) = CUSTOM WHITE RECALL (Dmx range value 0 - 79)

156-205	180				Custom White Recall
206-255	225				White CTC (Channel 7 CTC enabled 43 color temp. Correction Macros: 2000°K-7200°K)

IF CHANNEL 9 (FUNCTIONS) = CUSTOM WHITE CREATE (Dmx range value 80 - 160)

156-205	180				Custom White Create (RGB levels selectable by DMX)
206-255	225				White CTC (Channel 7 CTC enabled 43 color temp. Correction Macros: 2000°K-7200°K)

DMX CHANNEL	7	Parameter: CTC (Color temperature correction)
-------------	---	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function

IF CHANNEL 6 (White) = WHITE CTC (Dmx range value 206 - 255)

0-255	43 color temp. Correction Macros: 0 = 2000°K / 128 = 5500°K / 255 = 7200°K				
-------	---	--	--	--	--

IF CHANNEL 6 (White) = NO FUNCTION (Dmx range value 0 - 43)

0-255	Smooth RGB linear Hue correction				
-------	---	--	--	--	--

DMX CHANNEL	8	Parameter: COLOUR MACROS
-------------	----------	---------------------------------

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
0-14					No Function
15-29					Macro 1
30-44					Macro 2
45-59					Macro 3
60-74					Macro 4
75-89					Macro 5
90-104					Macro 6
105-119					Macro 7
120-134					Macro 8
135-149					Macro 9
150-164					Macro 10
165-179					Macro 11
180-194					Macro 12
195-209					Macro 13
210-225					Macro 14
226-239					Macro 15
240-255					Macro 16


DMX CHANNEL	9	Parameter: FUNCTIONS (Recall,Create and Store the Custom white)
-------------	----------	--

DMX range Value	Mid point DMX value	Move range (degrees)	Mode	Option	Function
0-79					Custom White Recall (Enable CH 6 for Custom white Recall)
80-160					Custom White Create (Enable CH 6 for Custom white Creation)
161-255					Custom White Store (Store the Custom White created)

WIRING DIAGRAMS


Z30 is available in 2 version with different LED output connectors:
 RJ12 female connectors (03.LA.072) and 6 poles plug-in screw connectors (03.LA.077) .

RJ12 Female panel connector on board :Z30 LED CONTROLLER (03.LA.072)



6-pin Female (RJ12)


RJ12 LED input male cable connector on board : Focus, Helios, MR16 led lamps



LEDS CONNECTOR PINOUT (Rj12)

- Pin 1 = RED +
- Pin 2 = RED -
- Pin 3 = GREEN +
- Pin 4 = GREEN -
- Pin 5 = BLUE +
- Pin 6 = BLUE -

6 poles plug-in screw connector on board :Z30 LED CONTROLLER (03.LA.077)




1-----PIN-----6

6 poles plug-in screw connector


LEDS CONNECTOR PINOUT 6 poles plug-in screw connector

- Pin 1 = RED +
- Pin 2 = RED -
- Pin 3 = GREEN +
- Pin 4 = GREEN -
- Pin 5 = BLUE +
- Pin 6 = BLUE -

M12 LED input Male cable connector on board: FOS 100 - FOS 33 TITAN



M12 LED output Female panel connector on board : Z10 / Z1 outdoor led controller




LEDS CONNECTOR PINOUT (M12)


- Pin 1 = RED +
- Pin 2 = RED -
- Pin 3 = GREEN +
- Pin 4 = GREEN -
- Pin 5 = BLUE +
- Pin 6 = BLUE -
- Pin 7 = Amber -**
- Pin 8 = Amber +**

LED UNITS WIRING CONNECTION


03.LA.072 (RJ12 OUTPUT)




6-pin Female (RJ12)




6-pin Female (RJ12)




MR16 RGB



MR16 RGB



MR16 RGB



6-pin Male (RJ12) Modular Plug



LEDs OUT 10

LEDs OUT 5

LEDs OUT 4

LEDs OUT 3

D.T.S. T-BOX
CODE 03.LA.001



INPUT

OUT 2

OUT 1

IMPORTANT:


The maximum number of MR16 / FOCUS RGB LED lamps connectable to each Z30 LEDs output is 3 pcs.

Never plug the cable coming from the Power supply into OUT 1 or OUT 2 of the T-BOX when other MR16 lamps are connected, because a wrong connection can seriously damage the lamps.

Never plug in a new MR16 lamp when the power supply is turned on.

LED UNITS WIRING CONNECTION

03.LA.072 (RJ12 OUTPUT)



6-pin Female (RJ12)




FOCUS FULL COLOUR



DIVE3 FULL COLOUR R




DIVE9 RGB R



IMPORTANT:

The maximum number of MR16 / FOCUS FULL COLOUR LED lamps, DIVE3 FULL COLOUR, DIVE9 RGB connectable to each Z30 LEDs output is 1 pcs.


Never plug in a new unit when the power supply is turned on.




DIVE9 RGB

LED UNITS WIRING CONNECTION

03.LA.072 (RJ12 OUTPUT)



6-pin Female (RJ12)




IMPORTANT:

DIVE6 FULL COLOUR and DIVE18 RGB unit are provided with 2 separated LED's input lines. DIVE6 FULL COLOUR and DIVE18 RGB unit need 2 x Z30 LED's output each.

Never plug in a new unit when the power supply is turned on.

LED UNITS WIRING CONNECTION

03.LA.077 (PLUG-IN OUTPUT)



1-----PIN-----6





LEDs OUT 10

LEDs OUT 4


LEDs OUT 3

LEDs OUT 2


LEDS OUTPUT



MR16 RGB



MR16 RGB



MR16 RGB


IMPORTANT:

The maximum number of MR16 / FOCUS RGB LED lamps connectable to each Z30 LEDs output is 3 pcs.

Never plug in a new MR16 lamp when the power supply is turned on.

LED UNITS WIRING CONNECTION

03.LA.077 (PLUG-IN OUTPUT)



1-----PIN-----6




LEDs OUT 10

LEDs OUT 4


LEDs OUT 3

LEDS OUTPUT 1

LEDS OUTPUT 2



DIVE3 FULL COLOUR



DIVE9 RGB R

IMPORTANT:

The maximum number of MR16 / FOCUS FULL COLOUR LED lamps, DIVE3 FULL COLOUR, DIVE9 RGB connectable to each Z30 LEDs output is 1 pcs.

Never plug in a new unit when the power supply is turned on.

NOTE

NOTE

NOTE

The information contained in this publication has been carefully prepared and checked. However, no responsibility will be taken for any errors. All rights are reserved and this document cannot be copied, photocopied or reproduced, in part or completely, without prior written consent from D.T.S.

D.T.S. reserves the right to make any aesthetic, functional or design modifications to any of its products without prior notice. D.T.S. assumes no responsibility for the use or application of the products or circuits described herein.

MADE IN ITALY



The Lighting Company

ISO 9001:2000

D.T.S quality system

Is certified to the

ISO 9001:2000 standard

D.T.S. Products are designed

And manufactured at the D.T.S

Plants in Italy

