# User's Manual

Intel i845-GE mainboard for Intel Socket 478 processor

#### **TRADEMARK**

All products and company names are trademarks or registered trademarks of their respective holders.

These specifications are subject to change without notice.

Manual Revision 1.0 May 01, 2003

## **DISCLAIMER OF WARRANTIES:**

THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE OF THE MANUFACTURER LIMITED WARRANTY. THE MANUFACTURER EXPRESSLY EXCLUDES ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, REGARDING ITS PRODUCTS; INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NONINFRINGEMENT. THIS DISCLAIMER OF WARRANTIES SHALL APPLY TO THE EXTENT ALLOWED UNDER LOCAL LAWS IN THE COUNTRY PURCHASED IN WHICH LOCAL LAWS DO NOT ALLOW OR LIMIT THE EXCLUSION OF THE IMPLIED WARRANTIES.

## 80 Port Frequently Asked Questions

Below is a list of some basic POST Codes, possible problems, and solutions. For more detailed information about POST Codes, refer to Appendix E in this manual.

POST CODE	Problem	Solution	
FFh or CFh	1.BIOS chip inserted incorrectly 2. Incorrect BIOS update version 3. Mainboard problem 4. Add-on card inserted incorrectly.	1. Reinsert the BIOS chip 2. Download the correct BIOS version update from the manufacturer's Web site. 3. Replace mainboard 4. Remove and replace the add-on card	
C1h - C5h	Memory module     inserted incorrectly     Memory compatibility     problem     Memory module     damaged	Reinsert memory     module     Replace memory     with correct type     Replace memory     module	
2Dh	Error occured in VGA     BIOS     VGA card inserted     incorrectly	Replace VGA card     Reinsert the VGA card	
26h	Overclock error	Clear CMOS or press the insert key to power on the system	
07h - 12h	Initial Keyboard     controller error     RTC error	Ensure that the keyboard and mouse are connected correctly.      Replace the RTC battery.	

## Table of Contents

	Page
Section 1	Introduction
	Components Checklist1-1
	Overview
	System Overview1-2
	Chipset Components1-3
	Intel Pentium 4 Processors1-4
	Accelerated Graphics Port1-6
	Ultra ATA66/1001-6
	Hardware Monitoring1-6
	Mainboard Form-Factor1-7
	I/O Shield Connector 1-8
	Power-On/Off(Remote) 1-8
	System Block Diagram1-9
Section 2	Features
	Mainboard Features2-1
Section 3	Installation
	Mainboard Layout
	Easy Installation Procedure
	CPU Installation
	Jumper Settings
	System Memory Configuration
	Expansion slots
	Device Connectors3-10
	External Modem Ring-in Power ON and
	Keyboard Power ON Function (KBPO)3-16
	STR (Suspend To RAM) Function
	Supports AGP Card 3 3V Protection 3-18

Section 4	Award BIOS Setup	
	Main Menu4-1	
	Standard CMOS Setup4-2	
	Advanced BIOS Features43	
	Advanced Chipset Features 4-8	
	Integrated Peripherals 4-11	
	Power Management Setup 4-16	
	PNP/PCI Configuration Setup 4-21	
	PC Health Status4-23	
	Frequency/Voltage Control 4-25	
	Defaults Menu4-28	
	Supervisor/User Password Setting 4-29	
	Exit Selecting4-30	
Section 5	Driver Installation	
	Easy Driver Installation 5-1	
	ALC650/655 Configuration Setup (6 Channel)5-2	
Appendix	Appendix A	
••	Realtek Media Player User's Guide A-1	
	Appendix B	
	Update Your System BIOS B-1	
	Appendix C	
	EEPROM BOIS Remover	
	Appendix D	
	GHOST 7 Quick User's Guide (Optional) D-1	
	Appendix E	
	POST Codes E-1	



# Section 1 INTRODUCTION

## Package Contents

#### **Contents**

- A. Mainboard
- B. User's manual
- C. Floppy disk drive cable
- D. Hard disk drive cable
- E. CD (drivers and utilities)


#### Deluxe Pack Items

- F. COM2 port cable
- G. Extra USB port cable

## Other Optional Items

H. SPD650 card

If you need the other optional item, please contact dealer for assistance.



#### Introduction

## System Overview

This board is designed with Intel® 845GE chipset. The Intel® 845GE chipset includes GMCH(FW82845GE), ICH4(FW82801DB) and FWH three chips. The Intel® 845GE chipset is designed for Intel's FC-PGA2 socket 478 package architecture and support the 4X capability of the AGP 2.0 Interface Specification. A new chipset component interconnect, the hub interface, is designed into the Intel® 845GE chipset to provide more efficient communication between chipset components.

Support of AGP 4X, 266/333/333+MHz DDR SDRAM and the hub interface provides a balanced system architecture for the Pentium® 4 in the Socket 478 architecture processor minimizing bottlenecks and increasing system performance. By increasing memory bandwidth to 2.128GB/s through the use of AGP 4X, the Intel® 845GE chipset will deliver the data throughput necessary to take advantage of the high performance provided by the powerful Pentium® 4 in the Socket 478 architecture processor.

The Intel® 845GE chipset architecture removes the requirement for the ISA expansion bus that was traditionally integrated into the I/O subsystem of Intel chipsets. This removes many of the conflicts experienced when installing hardware and drivers into legacy ISA systems. The elimination of ISA will provide true plug-and play for the Intel® 845GE platform.

Intel® 845GE chipset contains three core components: the Graphic Memory Controller Hub (GMCH), the I/O Controller Hub (ICH4) and the Firmware Hub (FWH). The GMCH integrates the data transfer rate of 400/533/533+MHz, Pentium® 4 processor bus controller, AGP 2.0 controller, 266/333/333+MHz DDR SDRAM controller and a high-speed hub interface for communication with the ICH4. The ICH4 integrates an Ultra ATA/66/100 controller, USB host controller, LPC interface controller, FWH interface controller, PCI interface controller, and a hub interface for communication with the GMCH. The Intel® 845GE chipset will provide the data buffering and interface arbitration required to ensure that system interfaces operate efficiently and provide the system bandwidth necessary to obtain peak performance the Pentium® 4 in the Socket 478 architecture.

## **Chipset Components**

The Intel® 845GE chipset consists of the Graphic Memory Controller Hub (GMCH), the I/O Controller Hub (ICH4) and the Firmware Hub (FWH).

#### • Graphic Memory Controller Hub (GMCH)

The GMCH provides the interconnect between the DDR SDRAM and the system logic. It integrates:

- Support for single processor with a data transfer rate of 400/533/533+MHz.
- 200/266/333/333+MHz DDR SDRAM interface supporting 2GB of DDR SDRAM.
- 4X 1.5V AGP interface (Only support 1.5V on AGP interface).
- Downstream hub link for access to the ICH4.

#### • I/O Controller Hub (ICH4)

The I/O controller Hub provides the I/O subsystem with access to the rest of the system. Additionally, it integrates many I/O functions. The ICH4 integrates:

- Upstream hub link for access to the GMCH
- 2 Channel Ultra ATA/33/66/100 Bus Master IDE controller
- USB controller
- SMBus controller
- FWH interface
- LPC interface
- PCI 2.2 interface
- Integrated System Management Controller

#### Introduction

## Intel Pentium 4 processors

Formally known as the Willamette, the Pentium<sup>™</sup> 4 is the next generation IA-32 processor from Intel. This next generation design is based upon a new microarchitecture that brings higher clock speeds and performance than previous processors could deliver. Among other advanced features the Pentium 4 offers Streaming SIMD extensions 2, Advanced Dynamic Execution, Hyper Pipelined Technology, and a data transfer rate of 400/533/533+MHz system bus.

#### **Streaming SIMD Extensions 2**

Building upon the foundations of core features of their previous line of processors the Pentium 4, this new version introduces Streaming SIMD Extensions 2 technology commonly referred to as SSE2. But what does this mean? SIMD stands for Single Instruction Multiple Data. Usually, processors process one data element in one instruction, called Single Instruction Single Data, or SISD. In contrast, with Single Instruction Single Data (SISD), SIMD has the ability to process more than one piece of data element during one instruction.

This technology is useful for 3D graphics applications that handle considerable amounts of floating-point numbers. With SIMD applications such as 3D graphics will be able to processor more data per instruction when equates to better performance. This technology adds 144 new instructions to the CPU core that can be used in a wide variety of applications. Software programmers can for example, take advantage of these new instructions and write more optimized code that take advantage of newer SIMD double-precision floating-point, integer, and cache ability instructions. In theory, this will enable better next generation services such as Interactive Digital TV to be produced.

## Advanced Dynamic Execution

Advanced Dynamic Execution describes the improved implementation and abilities over the older P6 processor line's out-of-order decoupled super scalar execution. Dynamic execution allows instructions to the processor to be executed without the need to do so in order. The ability to do this can add a significant performance increase versus ordered execution.

#### Hyper Pipelined Technology & 400/533/533+MHz System Bus

Hyper Pipelined Technology doubles the pipeline depth the Pentium 4 delivers to 20 stages. This significantly increases the performance and frequency capabilities. Pentium 4 also introduces a 400/533/533+MHz system bus as opposed to the 100 and 133MHz bus seen in previous Pentium III processors. This allows 3.2Gbytes per second of throughput while the Pentium III had a limited 1.06Gbyte/s throughput. Willamette will reportedly be introduced in the 0.18-micron using aluminum.

#### **Hyper-Threading Technology**

Hyper-Threading Technology is a new features in the IA-32 Intel Architecture that provides a performance boost for future Intel-32 processors based on the Intel NetBurst™ micro architecture. This technology enables a single processor to run two separate threads simultaneously, this arrangement looks like two processors. Hyper-Threading Technology makes a single physical processor appear as multiple logical processors, there is one copy of the architecture state for each logical processor, and the logical processor share a single set of physical execution resources. From a software or architecture perspective, this means operating systems and user programs can schedule processors or threads to logical processors as they would on conventional physical processors in a multi-processor system. From a micro architecture perspective, this means that instructions form logical processors will persist and execute simultaneously on shared execution resources.

For more information about all the new features the Pentium 4 delivers check out the Intel website at <a href="http://www.intel.com">http://www.intel.com</a>

#### Introduction

## Accelerated Graphics Port (AGP or A.G.P.)

Typically, 3D graphics rendering requires a tremendous amount of memory, and demands ever increasing throughput speed as well. As 3D products for the personal computer become more and more popular, these demands will only increase. This will cause a rise in costs for both end users and manufacturers. Lowering these costs as well as improving performance is the primary motivation behind AGP. By providing a massive increase in the bandwidth available between the video card and the processor, it will assist in relieving some of these pressures for quite sometime.

The board provides the AGP 2.0 interface. The AGP Interface Specification revision 2.0 enhances the functionality of the original AGP Interface Specification (revision 1.0) by allowing 4X data transfers (4 data samples per clock) and 1.5 volt (power supply) operation. The AGP 2.0 interface, along with SDRAM memory technology, allows graphics controllers to access main memory at over 1GB/s. In order to match the 4X AGP Card. The board used the Universal AGP connector. (1.5 volt AGP Card supports only).

## Ultra ATA/66/100

The ICH4 provides two channel Ultra ATA/66/100 Bus Master IDE controllers, that support Ultra ATA/66/100 protocols, perfect for such demanding applications as real-time video, multimedia, and high performance operating system. A new IDE cable is required for Ultra ATA/66/100. This cable is an 80 conductor cable; however the connectors are, of course, backwards compatible with ATA/33.

## Hardware Monitoring

Hardware monitoring allows you to monitor various aspects of your system operations and status. The features include CPU temperature, voltage and RPM of fan.

## Mainboard Form-Factor

The board is designed with Micro ATX form factor - the latest industry standard of chassis. The Micro ATX form factor is essentially a Baby-AT baseboard rotated 90 degrees within the chassis enclosure and a new mounting configuration for the power supply. With these changes the processor is relocated away from the expansion slots, allowing them all to hold full length add-in cards. Micro ATX defines a double height aperture to the rear of the chassis which can be used to host a wide range of onboard I/O. Only the size and position of this aperture is defined, allowing PC manufacturers to add new I/O features (e.g.; TV input, TV output, joystick, modem, LAN, audio, etc.) to systems. This will help systems integrators differentiate their products in the marketplace, and better meet your needs.

- By integrating more I/O down onto the board and better positioning the hard drive and floppy connectors material cost of cables and add-in cards is reduced.
- By reducing the number of cables and components in the system, manufacturing time and inventory holding costs are reduced and reliability will increase.
- By using an optimized power supply, it's possible to reduce cooling costs and lower acoustical noise. An ATX power supply, which has a sidemounted fan, allows direct cooling of the processor and add-in cards making a secondary fan or active heatsink unnecessary in most system applications.




Figure 2: Summary of Micro ATX chassis features

#### I/O Shield Connector

The board is equipped with an I/O back panel. Please use the appropriate I/O shield (figure 3).

RJ45 LAN
Parallel Port
Parallel Port
Parallel Port




Figure 3: I/O back panel layout


## Power-On/Off (Remote)

The board has a single 20-pin ATX and 4-pin ATX12V connector for power supplies (Figure 4). For power supplies that support the **Remote On/Off** feature, this should be connected to the mainboard front panel PW\_ON connector for the computer power On/Off button.

The board has been designed with "Soft Off" function. You can turn off the system two ways: pressing the front panel power On/Off button, using the "Soft Off" function (incorporated in the mainboard's onboard circuit controller) that can be controlled by an operating system such as Windows\*XP/ME/2000/98/95.

Note: For maintaining the DDR SDRAM power during STR (ACPI S3) function, it is strongly recommend to use power supplies that have a +5VSB current of (>=) 1A (1000mA). Please check the 5VSB's specification that has been printed on the power supply's outer case.

Note: The board requires a minimum of 250 Watt power supply to operate. Your system configuration (amount of memory, add-in cards, peripherals, etc.) may exceed the minimum power requirement but to ensure that adequate power is provided, use a 300 Watt (or greater) power supply.



## System Block Diagram





Figure 5: System Block Diagram



Page Left Blank

# Section 2 FEATURES

## Mainboard Features

#### Processor

- ◆ Socket 478 Intel<sup>®</sup> Pentium<sup>®</sup> 4 processor from 1.4 to 3.06GHz with 400/533/533+MHz Front Side Bus
- Supports Hyper-Threading Technology
   Enabling the functionality of Hyper-Threading Technology for your
   computer system requires ALL of the following platform Components:

**©CPU**: An Intel<sup>®</sup> Pentium 4 Processor with HT Technology.

**Chipset:** An Intel<sup>®</sup> Chipset that supports HT Technology.

**BIOS**: A BIOS that supports HT Technology and has it enabled.

**©OS**: An operating system that supports HT Technology.

#### Chipset

Intel 82845GE Chipset (82845GE+ICH4)

#### Built-in VGA

• Intel Extreme Graphics

## Main Memory

- Two 184-pin DDR DIMM sockets for PC1600/PC2100/PC2700 (DDR-200/ 266/333/333+) DIMMs
- Supports up to 2GB memory size

#### BIOS

- 4Mb Flash EEPROM with Award BIOS
  - ACPI v2.0 compliant
  - S3 (Suspend to DRAM) sleep-state support

#### **Features**

- SMBIOS (System Management BIOS) v2.2 compliant
- Supports Power failure recovery
- Capable to waked the computer up from specific states by LAN, Power switch, PME#, RTC alarm, USB, PS2 devices, Modem Ring-in COM#1...

#### Onboard PCI Devices

- ◆ LAN --> Embedded 10/100Mbps Fast Ethernet controller with (Optional) VIA 6105 LAN Chipset
- ◆ IDE --> Embedded IDE controller supports 2 IDE ports for up to 4 IDE devices
  - Supports ATA-100 with up to 100Mbps bandwidth

#### Legacy IO Controller

 Winbond W83627HF LPC IO controller with floppy, printer, game, serial and CIR/SIR interface

#### Audio

- Six channel audio with analog and digital output using ALC-650/655 AC'97
   CODEC
  - AC'97 v2.2 compliant
  - In 2-CH mode, supports Line-In (Blue), Line-Out (Green) and Mic-In (Pink) at rear panel
  - In 6-CH mode, supports Rear speaker-out (Blue), Front speaker-out (Green), Center&Subwoofer speaker-out (Pink) at rear panel
  - Supports CD-In, Aux-In and S/PDIF-In/out interface
  - Supports Line-out and Mic-In for front panel

#### Peripheral Interfaces

- PS/2 keyboard and mouse ports (at rear panel)
- One Parallel (printer) port (at rear panel)
- One RJ45 LAN connector (at rear panel)(Optional)
- Two Serial ports (1 at rear panel)
- One VGA ports (at rear panel)

- One game port (at rear panel)
- One floppy drive interface
- ◆ Two IDE interfaces with up to ATA-100 support
- Six USB2.0 ports (2 at rear panel)
- Three Fan connectors

#### Front Panel Controller

- Supports Reset & Soft-Off switches and KeyLock
- Supports HDD & Power LEDs
- · Supports PC speaker

## Expansion Slots

- ◆ One AGP slot supporting 1.5v 4X AGP card
  - AGP v2.0 compliant
- ◆ Three PCI bus sockets with Bus Master support
  - PCI v2.2 compliant

#### Other Features

- ◆ Magic Health USDM, a H/W monitoring software utility, for voltages, temperatures and fan-speeds sensing
- ◆ EZ Boot An easy way let end-user can choose to boot from hard drive, CD-ROM, floppy, ...
- Excellent Over clocking capabilities by
  - subtle voltage tuning on CPU, Memory, AGP
  - subtle frequency tuning on FSB
- Supports complete FSB/Memory and FSB/AGP, PCI Asynchronous scheme for over-clocking
- Supports AGP card 3.3V Protection
- P80P for system debugging (Optional)


## Form Factor

• 245 x 220 mm Micro ATX size


## **Features**

## Page Left Blank

## Section 3 INSTALLATION



## **Mainboard Layout**



## Easy Installation Procedure

The following must be completed before powering on your new system:

- 3-1. CPU Installation
- 3-2. Jumper Settings
- 3-3. System Memory Configuration
- 3-4. Expansion Slots
- 3-5. Device Connectors

## Section 3-1 CPU Installation




Figure 1

## Step 1

Open the socket by raising the actuation lever.




Figure 2

#### Step 2

Align pin 1 on the CPU with pin 1 on the CPU socket as shown in the illustration above. The CPU is keyed to prevent incorrect insertion. Don't force the processor into the socket. If it does not go in easily, check for misorientation and reinsert the CPU. Make sure the processor is fully inserted into the socket.

Pin 1



Figure 3

#### Step 3

Close the socket by lowering and locking the actuation lever.




Figure 5

#### Step 5

Install the cooling fan assembly. Press the two clips in the direction of the arrows shown in Figure 5 to secure the assembly to the CPU socket.



Figure 4

#### Step 4

Apply thermal compound to the top of the CPU and install the heatsink as shown.



Figure 6

#### Step 6


Plug the CPU fan into the CPU fan connector (FAN1).

The installation is complete.

#### NOTES:

- Damage to Intel Pentium<sup>TM</sup> 4 processors might result if installed with incorrect CPU fan and heatsink assemblies. Use Intel's design thermal solution shown in the illustrations above: an active heatsink; an extruded aluminum heatsink base; and a fan attached to the top on the fin array.
- Apply heatsink thermal compound or paste to the CPU to avoid CPU overheating and damage.
- In accordance with Intel Corp. specifications, do not install a CPU over 50 times to avoid bending the pins and damaging the CPU.

## Section 3-2 Jumper Settings



#### JBAT1 Clear CMOS data Jumper

If the CMOS data becomes corrupted or you forgot the supervisor or user password, clear the CMOS data to reconfigure the system back to the default values stored in the ROM BIOS.



Settings:

1-2: Normal (Default)

2-3: Clear CMOS

To CMOS Clear data, please follow the steps below.

- 1. Turn off the system.
- 2. Change the jumper from "1-2" to "2-3" position for a few seconds.
- 3. Replace the jumper on to the "1-2" position.
- 4. Turn on the system and hold down the <Del> key to enter BIOS setup.

# Section 3-3 System Memory Configuration

## Memory Layout

The mainboard accommodates two PC1600/2100/2700 184-pin DIMMs (Dual In-line Memory Modules):

- Supports up to 2.0GB of 200/266/333/333+ MHz DDR SDRAM.
- Supports up to 2 DDR DIMMs (refer to Table 1).
- Supports unbuffered non-ECC DIMMs only.
- Supports configurations defined in the JEDEC DDR DIMM specification

**NOTE:** The mainboard does not support double-sided x 16 DDR DIMMs. Use DDR SDRAM (Double-Data-Rate Synchronous DRAM) modules only.

Figure 7 and Table 1 show several possible memory configurations.

<figure 7=""></figure>	DDR DIMM 1	Bank 0/1	DDR
	DDR DIMM 2	Bank 2/3	DRAM

< Table 1>

Total Memory DDR DIMM 1 (Bank 0/1)		DDR DIMM 2 (Bank 2/3)	
= 1GB Maximum	DDR SDRAM* 64MB, 128MB, 256MB, 512MB, 1GB* X 1	None	
= 2GB Maximum	DDR SDRAM* 64MB, 128MB, 256MB, 512MB, 1GB* X 1	DDR SDRAM* 64MB, 128MB, 256MB, 512MB, 1GB* X 1	

<sup>\*</sup> DDR SDRAM supports 64, 128, 256, 512MB and 1GB DIMM modules using 512Mb technology.

#### NOTES:

 Using non-compliant memory with higher bus speeds (overclocking) may severely compromise the integrity of the system.

#### **DIMM Module Installation**

Figure 8 displays the notch on the DDR DIMM memory module.

DIMMs have 184 pins and one notch that matches with the DDR DIMM socket. DIMM modules are installed by placing the chip firmly into the socket and pressing straight down as shown in figure 9 until the white clips close and the module fits tightly into the DIMM socket (figure 10).




Figure 8 - DIMM notch





Figure 9 - DIMM module clips before installation



Figure 10 - DIMM module clip after installation

To remove the DIMM module press down the white clips and the module is released from the socket.

## 3-4 Expansion Slots



#### **AGP Slot**

The mainboard is equipped with an AGP slot. Make sure you install a card that supports the 1.5V specification.

#### **PCI Slots**


The mainboard is equipped with 5 PCI slots. It supports PCI cards that comply with the PCI specification.

## **Installing an Expansion Card**


The steps below assume that the mainboard is already installed in the system chassis.

- 1. Make sure the PC and all other peripheral devices connected to its has been powered down.
- 2. Disconnect all power cords and cables.
- 3. Remove the system unit cover.
- 4. Remove the bracket of the slot that you intend to use. (You need to remove the screw in order to remove the bracket.)
- 5. Align the card above the slot then press it down firmly until it is completely seated in the slot.
- 6. Secure the card to the chassis with the screw you removed in step 4.
- 7. Replace the system unit cover.
- 8. Power on the PC.
- 9. Enter the BIOS step program to make the necessary settings.
- 10. Save the settings and restart the PC.
- 11. Install the software drivers of the expansion cards, if necessary.


#### **AGP Card Installation Caution**



- AGP card component is blocked by DIMM socket lock.
- 2. AGP slot lock is not locked.







- 1. AGP card component is not blocked by DIMM socket lock.
- 2. AGP slot lock is locked.
- 3. AGP card edge connector is inserted properly.





- 1. AGP slot lock is not locked.
- 2. AGP card edge connector is not inserted properly.





- 1. AGP slot lock is locked.
- 2. AGP card edge connector is inserted properly.



## Section 3-5 Device Connectors




Figure 11 - I/O Ports



#### **FAN1 / FAN2 / FAN3:**

CPU/Power/Chassis Fan Power Connectors


FAN1:	FAN2:	FAN3:
CPU Fan	Power Fan	Chassis Fan
GND +12V Rotatior	GND +12V Rotation	GND +12V Rotation



WOL1: WOL (Wake On LAN) Connector Reserved for an NIC (Network Interface Card) to wake the system from power saving mode.








# IDE1/IDE2: Ultra DMA-66/100 Primary/Secondary IDE Connector (Blue)


This mainboard is equipped with 2 IDE disk connectors for connecting up to 4 ATA-100 IDE drives. It supports PIO and DMA mode operations for maximum data transfer rate of 100Mbps per channel.

**FLOPPY:** Floppy Controller Connector (Black) This mainboard is equipped with a floppy disk drive connector for connecting up to 2 floppy disk drives.



When use two IDE drives, one must be set to Master mode and the other one to Slave mode. Refer to your disk drive user's manual for information about selecting the proper drive switch settings.





ATX1: 20-pin ATX Power Connector

ATX2: 4-pin ATX12V Power Connector

The mainboard is equipped with a standard 20-pin ATX main power connector and a 4-pin +12V power connector for connecting an ATX12V power supply. The plugs of the power cables are designed to fit in only one orientation. Find the proper orientation then insert the plugs into the connectors until they fit in place.

#### Caution:

Be sure that the PW1 and PW12 Power Connector must be used simultaneously or else boot-up may not be possible.




The board requires a minimum of 250 Watt power supply to operate. Your system configuration (amount of memory, add-in cards, peripherals, etc.) may exceed the minimum power requirement but to ensure that adequate power is provided, use a 300 Watt (or greater) power supply.



#### FPCN1: Front Panel Audio Connector


When the jumpers are removed and this connector is used for front panel audio. The type of front panel line-out phone jack is normal close. Without phone plug inserted, the rear panel audio is enabled. With phone plug inserted, the rear panel audio is disabled.



#### Settings

Pins (5-6) & (9-10) Short (default): Only the Onboard Rear Audio Speaker can be used.

Pins (5-6) & (9-10) Open: Only Front Panel Audio Speaker can be used.





#### **COM2:** Serial Port Connector


The serial ports can be used with modems, serial printers, remote display terminals, and other serial device.







**SPDIF1:** Sony/Philips Digital InterFace This connector is the digital link between the motherboard and your devices, such as CD player, sampler or DAT recorder. It allows the digital transmission of audio data in SPDIF format.





CDIN1 / AUXIN1: CDIN1 and AUXIN1 Connectors The CD-IN and AUX-IN connectors are used to receive audio form a CD-ROM drive, TV tuner or






LED1: 80 Port Debug LED

Provides two digits LED light to show why system boots failed for quick and easy optimization.



80 Port Debug 7-segment LED display (Refer to Appendix E for POST codes)



#### USB2/3: USB Ports

The mainboard is equipped with Six onboard USB2.0/1.1 ports (2 at rear panel).


It is equipped with a 10-pin connector for connecting 4 additional external USB 2.0/1.1 ports. If you wish to use the additional USB ports, install the card-edge bracket to the system chassis then insert the connector that is attached to the USB port cables to the 10-pin connector.

It will help your device more efficient for the transfer speed up to 480Mbps.

#### CAUTION!


Please make sure the USB cable has the same pin assignment. The different pin assignment may be caused damage of system.

If you need the USB cable, please contact our retailer.



### USB port header pin descriptions


PIN#	Wire color	Signal Name	Comment
1	Red	Vcc	Cable Power
2	Black	Ground	Case Ground
3	White	-Data	Data
4	Black	Ground	Cable Ground
5	Green	+Data	Data
6	Green	+Data	Data
7	Black	Ground	Cable Ground
8	White	-Data	Data
9	Black	Ground	Case Ground
10	Red	Vcc	Cable Power



#### ◆ Power On/Off

This is connected to the power button on the case. Using the Soft-Off by Pwr-BTTN feature, you can choose either Instant Off (turns system off immediately), or 4 sec delay (push the button for 4 seconds before the system turns off). When the system is in 4 sec delay mode, suspend mode is enabled by pushing the button momentarily.

#### ◆ Turbo LED indicator



#### • IDE LED indicator

LED on when onboard PCI IDE Hard disks are being accessed.

#### • IR Connector

- 1. VCC
- 4. GND
- 2. CIRRX
- 5. IRTX
- 3. IRRX

#### KeyLock

Keyboard lock switch & power LED connector

- 1. Power LED(+) 4. KeyLock
- 2. N/C
- 5. GND
- 3. GND
- \* The power LED lights when the system is powered on and blinks in SLEEP Mode or STR Mode.

## • Speaker


Connect to the system's speaker for beeping

- 1. Speaker
- 3. GND
- 2. N/C
- 4. VCC

## • Reset

Closed to restart system.





## Section 3-6 External Modem Ring-in Power ON and Keyboard Power ON Functions (KBPO)

#### Modem-Ring Power ON Function

The I/O chipset provides the two serial ports with the External Modem Ring-in Power ON function. Once you connect an external modem to COM1 or COM2, the mainboard enables you to turn on the system through remote and host dial-up control.

#### Keyboard Power ON Function

The mainboard features a keyboard power on function that enables you to turn on the power supply using a keypress. Follow these instructions to enable the Keyboard Power ON function.

Step: Use the Keyboard Power ON function (KBPO) to turn on the system by using a key press, password, or hot key combination etc. as set in the BIOS Power Management Setup menu (refer to the BIOS Power Management Setup for details). The BIOS default setting is keyboard Hot key (<Ctrl> + <F1>). To power off the system, use the soft-OFF function under Windows XP/ME/2000/98. (refer to Windows online help).

#### NOTES:

- Intel ATX version 2.0 specification recommends you use a power supply that supplies >=2.0 A in 5.0 VSB. However, this mainboard supports a 5.0 VSB standby power supply > = 2A.
- We recommend you use the power supply with 1.0 A in 5.0 VSB, which supports PCI 2.2 specification for remote power-on and wake-up functions.

# 3-7 STR (Suspend To RAM) Function

This mainboard supports the STR (Suspend To RAM) power management scheme by maintaining the appropriate power states in the DDR SDRAM interface signals. The power source to the DDR SDRAM must be kept active during STR (ACPI S3). Advanced Configuration Power Interface (ACPI) provides many Energy Saving Features for operating systems that support Instant ON and OuickStart<sup>TM</sup> function.

- 1. Use the STR functionality to save system power, you are recommended to confirm the following requirements:
  - a. Install ACPI qualified add-on cards (such as AGP, LAN, and modem cards).
  - b. In BIOS under Power Management Setup (refer to Section 4), select "ACPI Suspend Type: S3(STR)" and "USB Wake-Up From S3: Enabled" (if you have a USB mouse or keyboard device).
  - c. Install Windows® XP/2000/ME/98SE.
  - d. Restart the system.
  - e. Open the Control Panel Power Management application, and click the Advanced tab. In the Power buttons section, select "Stand By" from the drop-down lists.
- To enable the STR function, click the START button and choose Shut Down. In the Shut Down Windows dialog box, select the Stand By option to enter STR mode.

The following lists the differences between STR power saving mode and Green (or Suspend) mode:

- a. STR is the most advanced Power Management mode.
- b. STR cuts all the power supplied to peripherals except to memory max. power saving.
- STR saves and keeps all on-screen data including any executed applications to DDR SDRAM.
- d. In STR mode, you must push the power button (connected to the onboard J3 pin), click your USB mouse buttons, or press your USB keyboard keys to wake up your system to the last display.

#### Installation

# 3-8 Supports AGP Card 3.3V Protection

The Intel® 845G chipset supports 1.5 volt AGP graphics cards only. Using a 3.3 volt AGP card in an Intel® 845G chipset-based board might damage the chipset on an 845G-equipped mainboard. However, this mainboard features a protection function that prevents the system from powering on when a 3.3V AGP card is inadvertently inserted into the AGP slot.

If this happens, we recommend you to follow these steps:

**Step 1:** Remove the 3.3V AGP card from the AGP slot.

**Step 2:** Unplug the ATX/ATX12V power cable.

**Step 3:** Insert a 1.5V AGP card into the AGP slot.

Step 4: Wait for 5 ~ 7 seconds and then plug in the ATX/ATX12V power cord again (or turn on the ATX/ATX12V power switch) to turn on your system.

**Note**: There should be an interval of  $5 \sim 7$  seconds between unplugging and plugging in the power cord, or turning the ATX/ATX12V power supply on and off.

# Section 4 AWARD BIOS SETUP

# Main Menu

Award's ROM BIOS provides a built-in Setup program which allows user to modify the basic system configuration and hardware parameters. The modified data is stored in a battery-backed CMOS, so that data will be retained even when the power is turned off. In general, the information saved in the CMOS RAM will stay unchanged unless there is a configuration change in the system, such as hard drive replacement or a device is added.

It is possible for the CMOS battery to fail causing CMOS data loss. If this happens you will need install a new CMOS battery and reconfigure your BIOS settings.

### To enter the Setup Program:

Power on the computer and press the <Del> key during the POST (Power On Self Test). The BIOS CMOS SETUP UTILITY opens. (Figure 1)




Figure 1: CMOS Setup Utility

The main menu displays all the major selection items. Select the item you need to reconfigure. The selection is made by moving the cursor (press any direction (arrow key ) to the item and pressing the 'Enter' key. An on-line help message is displayed at the bottom of the screen as the cursor is moved to various items which provides a better understanding of each function. When a selection is made, the menu of the selected item will appear so that the user can modify associated configuration parameters.

# 4-1 Standard CMOS Setup

Choose "STANDARD CMOS FEATURES" in the CMOS SETUP UTILITY Menu (Figure 2). Standard CMOS Features Setup allows the user to configure system settings such as the current date and time, type of hard disk drive installed, floppy drive type, and display type. Memory size is auto-detected by the BIOS and displayed for your reference. When a field is highlighted (use direction keys to move the cursor and the <Enter> key to select), the entries in the field can be changed by pressing the <PgUp> or the <PgUp> key.




Figure 2: Standard CMOS Setup

#### Notes:

- If the hard disk Primary Master/Slave and Secondary Master/Slave are set to Auto, then the hard disk size and model will be auto-detected.
- The "Halt On:" field is used to determine when to halt the system by the BIOS if an error occurs.
- Floppy 3 Mode support is a mode used to support a special 3.5-inch drive used in Japan. This is a 3.5-inch disk that stores 1.2 MB. The default setting for this is disabled.

### 4-2 Advanced BIOS Features

Selecting the "ADVANCED BIOS FEATURES" option in the CMOS SETUP UTILITY menu allows users to change system related parameters in the displayed menu. This menu shows all of the manufacturer's default values for the board.

Pressing the [F1] key displays a help message for the selected item.




Figure 3: BIOS Features Setup

### Virus Warning

During and after system boot up, any attempt to write to the boot sector or partition table of the hard disk drive halts the system and an error message appears.

You should then run an anti-virus program to locate the virus. Keep in mind that this feature protects only the boot sector, not the entire hard drive. The default is Disabled.

**Enabled**: Activates automatically when the system boots up causing a warning

message to appear when anything attempts to access the boot sector.

Disabled: No warning message appears when anything attempts to access the boot

sector.

**Note:** Many disk diagnostic programs that access the boot sector table can trigger the virus warning message. If you plan to run such a program, we recommend that you first disable the virus warning.

#### CPU L1 & L2 Cache

This controls the status of the processor's internal Level One and Level Two cache. The default is Enabled.

**Enabled:** This activates the processor's internal cache thereby increasing performance.

**Disabled**: This deactivates the processor's internal cache thereby lowering performance.

### **CPU Hyper-Threading**

Enables the CPU Hyper-Threading Technology.

Options: Enables, Disabled.

Note: Recommends enabling Hyper-Threading Technology on system with Windows XP and Linux 2.4 and disabling for legacy OS.

#### **Quick Power On Self Test**

This category speeds up the Power On Self Test (POST). The default is Enabled.

Enabled: This setting will shorten or skip of the items checked during POST.

Disabled: Normal POST.

#### **APIC Mode**

This item allows you to enable APIC (Advanced Programmable Interrupt Controller) functionality. APIC is an Intel chip that provides symmetric multiprocessing (SMP) for its Pentium systems.

Options: Enabled, Disabled.

### HDD S.M.A.R.T. Capability

The S.M.A.R.T. (Self-Monitoring, Analysis, and Reporting Technology) system is a diagnostics technology that monitors and predicts device performance. S.M.A.R.T. Software resides on both the disk drive and the host computer.

The disk drive software monitors the internal performance of the motors, media, heads, and electronics of the drive. The host software monitors the overall reliability status of the drive. If a device failure is predicted, the host software, through the Client WORKS S.M.A.R.T applet, warns the user of the impending condition and advises appropriate action to protect the data. The default is Disabled.

Options: Enabled, Disabled.

#### **Boot Up NumLock Status**

This controls the state of the NumLock key when the system boots. The default is On.

**On**: The keypad acts as a 10-key pad.

Off: The keypad acts like cursor keys.

### **Gate A20 Option**

This refers to the way the system addresses memory above 1 MB (extended memory). The default is Normal.

Normal: The A20 signal is controlled by the keyboard controller or chipset

hardware.

**Fast**: The A20 signal is controlled by Port 92 or chipset specific method.

### **Typematic Rate Setting**

This determines the keystrokes repeat rate. The default is Disabled.

Enabled: Allows typematic rate and typematic delay programming.

**Disabled**: The typematic rate and typematic delay will be controlled by the keyboard controller in your system.

### Typematic Rate (Chars/Sec)

This is the number of characters that will be repeated by a keyboard press. The default is 6.

Options:  $6 \sim 30$  characters per second.

### Typematic Delay (msec)

This setting controls the time between the first and the second character displayed by typematic auto-repeat. The default is 250.

Options: 250/500/750/1000 msec.

### **Security Option**

This category allows you to limit access to the System and Setup, or just to Setup. The default is Setup.

**System**: The system will not boot and access to Setup will be denied unless the

correct password is entered at the prompt.

**Setup**: The system will boot, but access to Setup will be denied unless the

correct password is entered at the prompt.

#### OS Select For DRAM > 64 MB

Some operating systems require special handling. Use this option only if your system has greater than 64 MB of memory. The default is Non-OS2.

OS2: Select this if you are running the OS/2 operating system with greater than 64 MB of RAM.

**Non-OS2**: Select this for all other operating systems and configurations.

# ▶ Boot Seq & Floppy Setup

Scroll to Boot Seq & Floppy Setup and press <Enter>. The following screen appears:

Phoenix - AwardBIOS CMOS Setup Utility Boot Seq & Floppy Setup			
First Boot Device	[Floppy] [HDD-0]	Item Help	
Second Boot Device Third Boot Device Boot Other Device	ISCSII [Enabled]	Menu Level ►►	
Swap Floppy Drive Boot Up Floppy Seek Report No FDD For WIN 95	[Disabled] [Enabled] [No]	Select Your Boot Device Priority	

#### First /Second/Third/Other Boot Device

The BIOS attempts to load the operating system from the devices in the sequence selected in these items.

Options: Floppy, LS120, HDD-0, SCSI, CDROM, HDD-1, HDD-2, HDD-3, ZIP100, USB-FDD, USB-ZIP, USB-CDROM, USB-HDD, LAN, Disabled.

#### **Boot Other Device**

When enabled, the system searches all other possible locations for an operating system if it fails to find one in the devices specified under the first, second, and third boot devices. The default is Enabled.

Options: Enabled, Disabled.

#### **Swap Floppy Drive**

This will swap your physical drive letters A & B if you are using two floppy disks. The default is Disabled.

**Enabled**: Floppy A & B will be swapped under the O/S.

**Disabled**: Floppy A & B will be not swapped.

#### **Boot Up Floppy Seek**

If this item is enabled, it checks the size of the floppy disk drives at start-up time.

You don't need to enable this item unless you have a legacy diskette drive with 360K capacity. The default is Disabled.

Options: Enabled, Disabled.

#### **Report No FDD For Win 95**

If you are running a system with no floppy drive under Windows 95, select Yes for this item to ensure compatibility with the Windows 95 logo certification.

Otherwise, select No.

**Yes**: The system has no floppy drive when you are using Windows 95.

**No**: The system has an operating system other than Windows 95.

# 4-3 Advanced Chipset Features

Choose the "ADVANCED CHIPSET FEATURES" option in the CMOS SETUP UTILITY menu to display following menu.




Figure 4: Chipset Features Setup

### **DRAM Timing Selectable**

For setting DRAM Timing, By SPD is follow Intel PC DDR SDRAM Serial Presence Detect Specification.

Options: Manual, By SPD.

### **CAS Latency Time**

Enables you to select the CAS latency time. The value is set at the factory depending on the DRAM installed. Do not change the values in this field unless you change specifications of the installed DRAM and DRAM clock from DRAM Timing Selectable. The default is by DRAM SPD.

Options: 1.5, 2, and 2.5.

### **Active to Precharge Delay**

This item specifies the number of clock cycles needed after a bank active command before a precharge can occur (sets the minimum RAS pulse width.). The default is by DRAM SPD.

Options: 5, 6, 7.

#### DRAM RAS# to CAS# Delay

This item sets the timing parameters for the system memory such as the CAS (Column Address Strobe) and RAS (Row Address Strobe). The default is by DRAM SPD. Options: 2, 3.

#### **DRAM RAS# Precharge**

This item refers to the number of cycles required to return data to its original location to close the bank or the number of cycles required to page memory before the next bank activate command can be issued. The default is by DRAM SPD. Options: 2, 3.

### System BIOS Cacheable

This item allows the system to be cached in memory for faster execution. The default is Enabled.

Options: Disabled, Enabled.

#### Video BIOS Cacheable

This item allows the video to be cached in memory for faster execution. The default is Disabled.

Options: Disabled, Enabled.

### **Delayed Transaction**

The mainboard's chipset has an embedded 32-bit post write buffer to support delay transactions cycles. Select Enabled to support compliance with PCI specification version 2.1. The default is Enabled.

Options: Disabled, Enabled.

#### **Command Per Clock**

Enabling this item improves performance. The default is Auto.

Options: Auto, Enabled, Disabled.

#### Fast CS#

When set to "Enabled" and SDRAM is idle, CS# is asserted in the same time the SDRAM tracking transitions to active state. The fast CS# timing is also applicable for pipelined assertion that follows page hit cycle.

Auto: This selection will Auto detect.

Disabled: Normal CS# mode (CS# active two clocks after internal SDRAM-start indication)

Enabled: Fast CS# mode (CS# active one clocks after internal SDRAM-start indication)

#### **Delay Prior to Thermal**

Set this item to enable the CPU Thermal function to engage after the specified time.

The default is 16 minutes.

Options: 4, 8, 16, 32 minutes.

# **AGP Aperture Size (MB)**

This item defines the size of the aperture if you use an AGP graphics adapter. It refers to a section of the PCI memory address range used for graphics memory. The default is 64 MB.

Options: 32, 64, 128, 256 MB.

# \*\* On-Chip VGA Settings \*\*

### On-Chip VGA

This item allows you to control the on-chip VGA.

Options: Enabled, Disabled.

### **On-Chip Frame Buffer Size**

This item allows you to control the on-chip frame buffer size.

Options: 1MB, 8MB.

# **On-Chip VGA Turbo Mode**

This item allows you to turn on/off on-chip VGA Turbo Mode.

Options: Auto, Enabled, Disabled.

### **Boot Display**

This item allows you to selcet the boot display device.

Options: Auto, CRT, TV, EFP.

#### **TV Format**

This item allows you to selcet the TV format.

# 4-4 Integrated Peripherals




Figure 5: Integrated Peripherals

#### Notes:

- If you do not use the Onboard IDE connector, then you will need to set that Onboard Primary PCI IDE: Disabled and Onboard Secondary PCI IDE: Disabled
- The Onboard PCI IDE cable should be equal to or less than 18 inches (45 cm.).

# **Init Display First**

If two video cards are used (1 AGP and 1 PCI) this specifies which one will be the primary display adapter. The default is PCI Slot.

Options: PCI Slot, AGP.

### VIA6105 Lan Boot ROM (Optional)

Enables and disables the onboard LAN Boot ROM. The default is Disabled. Options: Enabled, Disabled.

# ▶ Onboard IDE Device Setup

Scroll to Onboard IDE Device Setup and press <Enter>. The following screen appears:

Phoenix – AwardBIOS CMOS Setup Utility Onboard IDE Device Setup				
On-Chip Primary PCI IDE [Enabled]	Item Help			
IDE Primary Master PIO [Auto] IDE Primary Slave PIO [Auto]	Menu Level ►►			
IDE Primary Master UDMA [Auto] IDE Primary Slave UDMA [Auto]				
On-Chip Secondary PCI IDE [Enabled] IDE Secondary Master PIO [Auto]				
IDE Secondary Slave PIO [Auto]				
IDE Secondary Master UDMA [Auto] IDE Secondary Slave UDMA [Auto]				
IDE HDD Block Mode [Enabled]				

#### **On-Chip Primary PCI IDE**

The integrated peripheral controller contains an IDE interface with support for two IDE channels. Select Enabled (default) to activate each channel separately. Options: Enabled, Disabled.

### IDE Primary/Secondary Master/Slave PIO

The four IDE PIO (Programmed Input/Output) fields let you set a PIO mode (0-4) for each of the four IDE devices that the onboard IDE interface supports. From Modes 0 to 4 provide successively increased performance. In Auto mode, the system automatically determines the best mode for each device. The default is Auto. Options: Auto, Mode  $0 \sim 4$ .

### IDE Primary/Secondary Master/Slave UDMA

This allows you to select the mode of operation for the Ultra DMA-33/66/100 implementation is possible only if your IDE hard drive supports it and the operating environment includes a DMA driver (Windows 95 OSR2 or a third-party IDE bus master driver). If your hard drive and your system software both support Ultra DMA-33/66/100, select Auto to enable UDMA mode by BIOS or you can select mode by manual.

Options: Auto, Disabled.

#### **IDE HDD Block Mode**

IDE Block Mode allows the controller to access blocks of sectors rather than a single sector at a time. The default is Enabled.

Options: Enabled, Disabled.

# Onboard PCI Device Setup

Scroll to Onboard PCI Device Setup and press <Enter>. The following screen appears:

Phoenix - AwardBIOS CMOS Setup Utility Onboard PCI Device Setup				
USB Controller	[Enabled]	Item Help		
USB 2.0 Controller USB Keyboard Support USB Mouse Support	[Disabled] [Auto] [Disabled]	Menu Level ►►		
AC97 Audio Game Port Address	[Auto] [201]			
Midi Port Address x Midi Port IRO	[Disabled]			
Onboard LAN Device	[Enabled]			

#### **USB Controller**

Enables the all USB controller.

Options: Disabled, Enabled.

#### **USB 2.0 Controller**

Enables the EHCI (USB2.0) controller.

Options: Disabled, Enabled.

#### **USB Keyboard Support**

Your system contains a Universal Serial Bus (USB) controller and you have a USB keyboard. The default is Auto detect.

Options: Auto, Enabled, Disabled.

# **USB Mouse Support**

Your system contains a Universal Serial Bus (USB) controller and you have a USB Mouse . The default is Disabled.

Options: Enabled, Disabled.

#### AC97 Audio

This item allows you to decide to auto or disable the chipset family to support AC97 Audio. The function setting AC97 Audio Codec states. The system default is Auto.

Options: Auto, Disabled.

#### **Game Port Address**

Select an address for the Game port.

Options: 201 (default), 209, Disabled.

#### Midi Port Address

Select an address for the Midi port.

Options: 290, 300, 330, Disabled (default).

#### Midi Port IRQ

Select an interrupt for the Midi port.

Options: 5, 10 (default).

#### Onboard LAN Device (Optional)

Enables the onboard LAN feature.

Options: Enabled, Disabled.

# ▶ Onboard I/O Chip Setup

Scroll to Onboard I/O Chip Setup and press <Enter>. The following screen appears:

Phoenix – AwardBIOS CMOS Setup Utility Onboard I/O Chip Setup				
Onboard FDC Controller	[Enabled]	Item Help		
Onboard Serial Port 1 Onboard Serial Port 2	[3F8/IR04] [2F8/IR03]	Menu Level ►►		
UART Mode Select RxD , TxD Active	[Normal] [Hi,Lo]			
IR Transmission Delay UR2 Duplex Mode	[Enabled] [Half]			
Use IR Pins Onboard Parallel Port	[IR-Rx2Tx2] [378/IR07]			
Parallel Port Mode EPP Mode Select	[SPP] [FPP1.7]			
ECP Mode Use DMA	[3]			

#### Onboard FDC Controller

Select Enabled if your system has a floppy disk controller (FDC) installed on the system board and you wish to use it. If you install add-in FDC or the system has no floppy drive, select Disabled in this field.

Options: Enabled, Disabled.

#### Onboard Serial Port 1/2

Select an address and corresponding interrupt for the first and second serial ports. Options: 3F8/IRQ4, 2E8/IRQ3, 3E8/IRQ4, 2F8/IRQ3, Disabled, Auto.

#### **UART Mode Select**

This filed allows the users to configure what IR mode the 2nd serial port should use. The default is Normal.

Options: Normal, IrDA and ASKIR.

#### RxD, TxD Active

This field configures the receive and transmit signals generated from the IR port.

The default is Hi Lo (when UART Mode Select is not set to Normal).

Options: Hi Hi, Hi Lo, Lo Hi, and Lo Lo.

#### IR Transmission delay

This item allows you to enabled/disable IR transmission delay.

Options: Enabled, Disabled.

### **UR2 Duplex Mode**

This item allows you to select IR half/full duplex function.

Options: Half, Full.

#### **Use IR Pins**

This item allows you to select IR transmission routes, one is RxD2, TxD2 (COM

Port) and the other is IR-Rx2Tx2.

Options: IR-Rx2Tx2, RxD2, TxD2.

#### **Onboard Parallel Port**

This field allows the user to configure the LPT port.

Options: 378/IRQ7, 278/IRQ5, 3BC/IRQ7, Disabled.

#### **Parallel Port Mode**

This field allows the user to select the parallel port mode.

Options: SPP, EPP, ECP, ECP+EPP.

#### **EPP Mode Select**

This item allows you to determine the IR transfer mode of onboard I/O chip.

Options: EPP1.9, EPP1.7.

#### **ECP Mode USE DMA**

This field allows the user to select DMA1 or DMA3 for the ECP mode.

Options: DMA1, DMA3.

# 4-5 Power Management Setup

Choose the "POWER MANAGEMENT SETUP" in the CMOS SETUP UTILITY to display the following screen. This menu allows the user to modify the power management parameters and IRQ signals. In general, these parameters should not be changed unless it's absolutely necessary.




Figure 6: Power Management

# **ACPI Suspend Type**

This item allows you to select S1(POS) or S3(STR) function. When set to "S3(STR)" or "S1&S3" the following two fields become available.

Options: S1(POS), S3(STR), S1&S3.

#### Run VGABIOS if S3 Resume

This determines whether or not to enable the system to run the VGA BIOS when resuming from S3(STR) or S1&S3.

Options: Auto, Yes, No.

#### S3 KB Wake-up Function

This determines whether or not to enable keyboard/mouse activity to awaken the system from S3(STR) or S1&S3.

Options: AnyKey or Mouse, By PowerOn Func., AnyKey, Mouse.

#### **POWER ON Function**

Enables computer power on by keyboard, mouse, or hotkey activity. The default is HotKEY.

**Password:** Requires you to enter a password when using the keyboard

to power on. Set the password in the next field "KB Power ON

Password."

**HotKEY:** Enables you to use a hot key combination to power on the

computer. Set the hot key combination in the "Hot Key Power

ON" field.

**AnyKEY:** Enables you to set any keyboard activity to power on the

computer.

**BUTTONONLY:** Requires you to push the computer power button to power on

the system.

**Keyboard 98:** Enables you to set the Windows 98 key to power on the system.

# **Keyboard Power ON Password**

Press "Enter" to create a password that is required when you use the keyboard to power on the system. You must set the POWER ON Function to "Password" to be prompted for a password at power on.

### **Hot Key Power ON**

Enables you to set a hot key combination to be used for powering on the system.

The default is Ctrl-F1.

Options: Ctrl-F1 ~ Ctrl F12.

#### **PWRON After PWR-Fail**

This item enables your computer to automatically restart or return to its last operating status after power returns from a power failure.

**Off:** The system stays off after a power failure.

**Former-Sts:** The system returns to the state it was in just prior to the power

failure.

#### **Power Management**

Use this to select your Power Management selection. The default is User define.

Max.saving: Maximum power savings. Inactivity period is 1 minute in each mode.

Min.saving: Minimum power savings. Inactivity period is 1 hour in each mode.

**User define**: Allows user to define PM Timers parameters to control power saving

mode.

#### Video Off Method

This option allows you to select how the video will be disabled by the power management. The default is V/H Sync + Blank

V/H Sync + Blank: System turns off vertical and horizontal synchronization ports

and writes blanks to the video buffer.

**DPMS Support**: Select this option if your monitor supports the Display Power

Management Signaling (DPMS) standard of the Video

Electronics Standards Association (VESA). Use the software supplied for your video subsystem to select video power

management values.

**Blank Screen**: System only writes blanks to the video buffer.

# Video Off In Suspend

Lets you enable the video to power off in suspend mode.

No: Video power off not controlled by power management.

Yes: Video powers off after time shown in suspend mode setting.

# **Suspend Type**

Determines CPU status during power saving mode.

Stop Grant: CPU goes into idle mode during power saving mode.

PwrOn suspend: CPU and system remain powered on in suspend mode.

#### **MODEM Use IRQ**

Name the interrupt request (IRQ) line assigned to the modem (if any) on your system. Activity of the selected IRQ always awakens the system. Default is IRQ 3.

Options: N/A, 3, 4, 5, 7, 9, 10, 11

### **Suspend Mode**

enabled and after the set time of system inactivity, all devices except the CPU will be shut off.

Options: Disabled, 1, 2, 4, 8, 12, 20, 30, 40 Min and 1 Hour.

# Page 4-18

#### **HDD Power Down**

When enabled and after the set time of system inactivity, the hard disk drive will be powered down while all other devices remain active.

Options: Disabled,  $1 \sim 15$  Min.

### **Soft-Off by PWRBTN**

Use this to select your soft-off function. The default is Instant Off.

**Instant Off:** Turns off the system instantly.

**Delay 4 Second**: Turns off the system after a 4 second delay. If momentary press

of button, the system will go into Suspend Mode. Press the

power button again to make system back to work.

#### **CPU THRM-Throttling**

This item sets the percentage of time that the CPU is idled if CPU throttling is initiated by excess heat. The default setting is 50%.

Options: 12.5%, 25.0%, 37.5%, 50.0%, 62.5%, 75.0%, 87.5%.

#### PowerOn by PCI Card

An input signal form PME on the PCI card awakens the system from a soft off state. Options: Enabled, Disabled.

### Power On by Ring or WOL

When enabled, any modem or LAN activity awakens the system from power savings mode.

Options: Enabled, Disabled.

### **USB Wake-Up From S3**

When enabled, any USB activity awakens the system from power savings mode. Options: Enabled, Disabled.

#### **RTC Alarm Resume**

When enabled, you can set the date and time in the following two fields. Any event occurring at the specified date or time awakens the system from power savings mode.

# \*\* Reload Global Timer Events \*\*

# Primary/Secondary IDE 0/1

Any activity occuring on these channels awakens the system from power savings mode.

### FDD, COM, LPT Port

When enabled, any event occurring on these ports awakens the system from power savings mode.

# PCI PIRQ[A-D]#

When enabled, any event occurring on these PCI slots awakens the system from power savings mode.

# 4-6 PNP/PCI Configuration

The PNP/PCI configuration program is for the user to modify the PCI/ISA IRQ signals when various PCI/ISA cards are inserted in the PCI or ISA slots.

WARNING: Conflicting IRQ's may cause the system to not find certain devices.

Phoenix – AwardBIOS CMOS Setup Utility PnP/PCI Configurations				
× IRQ Resources  PCI/VGA Palette Snoop PCI Latency Timer(CLK) AGP SLOT INT Assignment SLOT1/AC97 INT Assignment SLOT2 INT Assignment SLOT3 INT Assignment SLOT4 INT Assignment	Autol Autol Autol Autol	Item Help  Menu Level ►  BIOS can automatically configure all the boot and Plug and Play compatible devices. If you choose Auto, you cannot select IRQ DMA and memory base address fields, since BIOS automatically assigns them		
		ESC:Exit F1:General Help F7: Optimized Defaults		

Figure 7: PNP/PCI Configuration Setup

## **Resources Controlled By**

Determines what controls system PNP/PCI resources. The default is Auto (ESCD).

Manual: PNP Card's resources are controlled manually. The "IRQ Resources" field

becomes available and you can set which IRQ-X and DMA-X are

assigned to PCI/ISA PNP or Legacy ISA Cards.

**Auto**: If your ISA card and PCI cards are all PNP cards, BIOS assigns the

interrupt resource automatically.

### PCI/VGA Palette Snoop

This item is designed to overcome problems that can be caused by some nonstandard VGA cards. This board includes a built-in VGA system that does not require palette snooping so you must leave this item disabled.

Options: Enabled, Disabled.

# PCI Latency Timer (CLK)

The latency timer defines the minimum amount of time, in PCI clock cycles, that the bus master can retain the ownership of the bus.

Options: 0-255.

### AGP SLOT/ AC97/IPCI Slot 1 ~ Slot 5/Onboard LAN NT Assignment

This setting enables the user to specify what IRQ will be assigned to the AGP/AC97/PCI Slot  $1 \sim$  PCI Slot 5/Onboard LAN devices in the chosen slot.

Options: Auto, 3, 4, 5, 7,9, 10, 11, 12, 14 & 15. The default is Auto.

#### Interrupt requests are shared as shown below:

	INT A	INT B	INT C	INT D	INT E	INT F	INT G	INT H
AGP Slot	V							
AC97		v						
Slot 1		v						
Slot 2			v					
Slot 3				v				
Slot 4					v			
Slot 5						v		
Onboard LAN (Optional)							V	
Onboard USB1	V							
Onboard USB2		v						
Onboard USB3			v					
USB 2.0				V				
SM BUS		v						

#### IMPORTANT!

If using PCI cards on shared slots, make sure that the drivers support "Shared IRQ" or that the cards don't need IRQ assignments. Conflicts will arise between the two PCI groups that will make the system unstable or cards inoperable.

# 4-7 PC Health Status




Figure 8: PC Health Status

#### Show PC Health in POST

When this function is enabled the PC Health information is displayed during the POST (Power On Self Test).

Options: Enabled, Disabled.

# **CPU Warning Temperature**

Sets the temperature at the time which the computer will respond to an overheating CPU. The default is Disabled.

Options: Disabled,  $50^{\circ}\text{C}/122^{\circ}\text{F} \sim 70^{\circ}\text{C}/158^{\circ}\text{F}$ .

# **Current CPU Temperature**

Displays the current CPU temperature.

### **Current System Temperature**

Displays the current system temperature.

# **Current CPU/Chassis/Power FAN Speed**

Displays the current speed of the CPU, chassis, and power fan speed in RPMs.

### Vagp (V)

The voltage level of Power supplied to AGP card.

# **BIOS**

# Vcore (V)

The voltage level of the CPU(Vcore).

### Vdimm(V)

The voltage level of the DRAM.

# VBAT(V)

The voltage level of the battery.

### ± 5V, ± 12V, 5VSB(V)

The voltage level of the switching power supply.

# **ACPI Shutdown Temperature**

This is the temperature that the computer will turn off the power to combat the effects of an overheating system. (requires ACPI to be enabled in Power Management BIOS and ACPI compliant operating system.) The default is Disabled. Options available are 60°C/140°F to 95°C/203°F in increments of 5°C.

# 4-8 Frequency/Voltage Control




Figure 9: Frequency/Voltage Control

#### **CPU Clock Ratio**

Use this item to select a multiplier for the system front side bus (FSB) frequency. The value of the multiplier must be set so that:

Multiplier x Front side Bus Frequency = CPU Clock Speed

For example, if you have a processor that is rated to run at 800 MHz and the system is running a front side bus frequency of 100 MHz, you should select a multiplier of 8 so that:

8 (Multiplier) x 100 MHz (front side bus) = 800 MHz (CPU clock)



Key in the DEC (decimalism) number for the CPU Clock Ratio.

## **Watching-Dog Function**

If you select enabled and overclock fail before POST code 26h, the system will reset automatically by default configuration.

Options: Enabled, Disabled.

#### **CPU FSB/SPEED**

Enables you to set the CPU frontside bus speed. The default is 100 MHz. Enables you to adjust CPU clock 1MHz by step. Pressing Enter displays the following screen:



Key in the DEC (decimalism) number for the CPU FSB/SPEED.

Note: Overclocking failure will cause system No display problem. At this moment, please press "*Insert*" key to back to the initial or default setting to boot up your system.

# **Memory Frequency**

Enables you to select a ratio of the Double Data Rate Synchronous DRAM to match the installed DRAM frequency 200/266/333/333+MHz. We recommend that you leave this item at the default value.

When the FSB is 400MHz the options will display 1:1 =>DDR200, 3:4 =>DDR266, 4:5=>DDR250, Auto =>DDR266.

When the FSB is 533MHz the options will display 1:1 =>DDR266, 3:4=>DDR354, 4:5 => DDR333, Auto =>DDR266.

When the FSB is 800MHz the options will display 1:1=>DDR400. (Use DDR400 memory to obtain the best CPU performance)

#### AGP/PCI Clock

Enables you to set the host clock to work concurrently with the PCI bus or the AGP bus. The default is AUTO.

**AUTO:** The system sets the item automatically.

AGP-FSB\*2/3 PCI-FSB/3: The system sets the host clock to work with the PCI

and AGP bus.

By subtle tuning item: The system sets the host clock according to the

number produced by the subtle tuning item.

#### AGP/PCI subtle tuning

Enables you to set the AGP/PCI frequency, enables you to subtle tuning AGP clock 1MHz by step. The default is 66 MHz. Pressing Enter displays the following screen:



Key in the DEC (decimalism) number for the AGP/PCI subtle tuning.

In the following items, "Default Voltage" indicates the original factory value, and "New Voltage" indicates the value that you assign.

# **CPU Vcore Voltage**

This item allows you to set the CPU Vcore voltage. The default is -0.075V.

Options: -0.100V to +0.350V in 0.025V increments. We recommend that you leave this at the default value.

# **AGP Voltage**

This item allows you to set the AGP slot voltage. The default is +0.00V.

Options: +0.00V to +0.70V in 0.10V increments. We recommend that you leave this at the default value.

# **DIMM Voltage**

This item allows you to set the DIMM slot voltage. The default is +0.00V.

Options: +0.00V to +0.70V in 0.10V increments. We recommend that you leave this at the default value.

#### Clock Generation for EMI

Scroll to Clock Generation for EMI and press <Enter>. The following screen appears:



#### **Auto Detect PCI CIk**

When enabled the mainboard automatically disables the clock source for a PCI slot which does not have a module in it, reducing EMI (ElectroMagnetic Interference). The default is Enabled.

### **Spread Spectrum Modulated**

If you enable spread spectrum, it can significantly reduce the EMI (ElectroMagnetic Interference) generated by the system.

### 4-9 Defaults Menu

Selecting "Defaults" from the main menu shows you two options which are described below

#### Load Fail-Safe Defaults

When you press <Enter> on this item you get a confirmation dialog box:

Load Fail-Safe Defaults (Y/N)? N

Pressing 'Y' loads the BIOS default values for the most stable, minimal-performance system operations.

# **Load Optimized Defaults**

When you press <Enter> on this item you get a confirmation dialog box:

Load Optimized Defaults (Y/N)? N

Pressing 'Y' loads the default values that are factory settings for optimal performance system operations.

# 4-10 Supervisor/User Password Setting

These items are used to install a password. A Supervisor password takes precedence over a User password, and the Supervisor limits the activities of a User. You can set either a supervisor or user password, or both of them:

**Supervisor password:** authorized to enter and change the options of the setup

menus.

**User password**: authorized to enter, but not authorized to change the

options of the setup menus.

When you select Set User/Supervisor Password, the following message appears prompting you to type a password:

#### **ENTER PASSWORD:**

Type the password, up to eight characters in length, and press <Enter>. The password typed now clears any previously entered password from CMOS memory. You will be prompted to confirm the password. Type the password and press <Enter>. You may also press <Esc> to abort the selection and not enter a password.

To disable a password, press <Enter> when you are prompted to enter the password. A message will confirm the password is disabled:

#### PASSWORD DISABLED.

Once the password is disabled, the system will boot and you can enter Setup freely. When a password has been enabled, you will be prompted to enter it every time you try to enter Setup. This prevents an unauthorized person from changing any part of your system configuration.

Additionally, when a password is enabled, you can also require the BIOS to request a password every time your system is rebooted. This prevents unauthorized use of your computer.

You determine when the password is required within the BIOS Features Setup menu "Security" option. If the Security option is set to "System", the password will be required both at boot and at entry to Setup. If set to "Setup", prompting only occurs when trying to enter Setup.

# 4-11 Exiting BIOS

# Save & Exit Setup

Pressing <Enter> on this item asks for confirmation:

### Save to CMOS and EXIT (Y/N)? Y

Pressing "Y" stores the selections made in the menus in CMOS – a special section of memory that stays on after you turn your system off. The next time you boot your computer, the BIOS configures your system according to the Setup selections stored in CMOS. After saving the values the system is restarted again.

# **Exit Without Saving**


Pressing <Enter> on this item asks for confirmation:

### Quit without saving (Y/N)? Y

This allows you to exit Setup without storing in CMOS any change. The previous selections remain in effect. This exits the Setup utility and restarts your computer.

# Section 5 Driver Installation

# Easy Driver Installation




Insert the bundled CD-disk, the main menu screen will appear. The main menu displays buttons that link you to the supported drivers, utilities and software.

- **Step 1:** Click "INTEL CHIPSET INF FILES" to install all components recommended.
- Step 2: Click "GRAPHICS DRIVER" to install graphical driver.
- Step 3: Click "AC'97 AUDIO DRIVER" to install Audio driver.
- Step 4: Click "VIA 6105 LAN" to install LAN driver. (Optional)


## **Drivers Installation**

# ALC650/655 Configuration Setup (6 Channel)


◆ To enable ALC650/655 Function




 Right-click Sound Effect button in the tool bar display currently selected Titles. Select Sound Manager.



Click Sound Effect button and select Environment from the drop-down menu.




3. Click **Equalizer** and setup the value of dB.




4. Click **Line in** and **Mic in** buttons to enable 6 channel function as this is required for the ALC650.


# **Drivers Installation**



5. The selected screen appears.



6. Click **Speaker Test** button and click on the speakers directly which show on the screen to test it.



7. General Information for user reference.


_				4					
11	PIL	ers	In	eta	•	21	•	$\mathbf{a}$	n
u	' I I V	<b>CI3</b>		эıа	•	aı	ч	v	

Page Left Blank

## Appendix A

### A-1 Realtek Media Player User's Guide

### **Realtek Media Player Platform**



### **Functional Descriptions**

### A. Playback Windows Display

Playback windows displays the following mode information:

- 1. Playback Time Display
- 2. Voice Cancellation Mode Display
- 3. Pitch Mode Display
- 4. Surround Sound Mode Display

#### **B.** Playback Function Controls

There are 8 selectable functions for the playback:

1. Volume control High/Low Adjustment Bar.

2. Pitch control 4-step High/Low Adjustment Bar.

3. Repeat mode Choice of Repeat, All Repeat, Random or No

Repeat Mode.

4. Mute On/Off Mode select.

5. Voice cancellation Voice Cancellation On/Off Mode select for

Karaoke.

6. Surround mode A total of 26 Surround Sound mode select as

shown in the table below.

Surround mode	
Stone corridor	
Alley	
Forrest	
City	
Mountain	
Quarry	
Plain	
Parking lot	
Sewer pipe	
Under water	
Drug	
Dizzy	
Psychological	

7. Skin change Media Player Skin Type select.

8. Open Open file formats including MP3, CDA, MDI, WAV

& WMA support.

### C. Playback Controls

The playback controls include "Play", "Pause", "Stop", "Previous", "Backward", "Forward", & "Next".

#### D. Seeking bar

Display Animated Playback Status

#### E. Title/Play List Windows

Display Currently Selected Title(s)

#### F. Title/Play List Edit Controls

There title/play list controls include "Add", "Del", "Clear", "Load", & "Store".

1. Add Add to the Title/Play List.

2. Del Remove form the Title/Play List.

3. Clear the Title/Play List.

4. Load Load Title/Play List.

5. Store Save Title/Play List.

#### G. Title/Play List Scroll bar

Scroll Up/Down the Title/Play List.

### **H. Recording Function Controls**

The recording function controls include "Input", "Save, "New", "Rec", "Stop",

& "Play".

1. Input Input soruce select.

2. Save Save to file.

3. New Open new file & select format includes Sampling

Rate, Sampling bit, Mono or Stereo.

4. Rec Start Rec.

5. Stop Stop Rec.

6. Play Playback Rec file.

### I. REC/Playback Time Display

Displays REC/Playback Time.

### J. Platform Display Panel Controls

The platform display panel control include "Minimize" & "Close".

1. Minimize Platform Display Panel.

2. Close Close/Exit Platform Display Panel.

### K. Equalizer Control Panel

The Equalizer Control Panel include "On/Off" & "Preset".

1. On/Off Enable/Disable Equalizer.

2. Preset Clear Equalizer setting to default value.

### Appendix B

### B-1 Update Your System BIOS

Download the xxxxx.EXE file corresponding to your model form the our website to an empty directory on your hard disk or floppy. Run the downloaded xxxxx.EXE file and it will self extract. Copy these extracted files to a bootable DOS floppy disk.

Note: The DOS floppy disk should contain NO device drivers or other programs.

- 1. Type "A:\AWDFLASH and press <Enter> Key.
- 2. You will see the following setup on screen.
- 3. Please key in the xxxxx.bin BIOS file name.

```
C)Award Software 2000 All Rights Reserved

For XXXX -W83627-6A69LPA9C-0 DATE: 05/11/2000

Flash Type -

File Name to Program :
```

4. If you want to save the previous BIOS data to the diskette, please key in [Y], otherwise please key in [N].

```
(C)Award Software 2000 All Rights Reserved

For XXXX-W83627-6A69LPA9C-0 DATE: 05/11/2000
Flash Type - XXXXX E82802AB /3.3V

File Name to Program : XXXXX.bin

Error Message: Do You Want To Save Bios (Y/N)
```

5. Key in File Name to save previous BIOS to file.

```
(C)Award Software 2000 All Rights Reserved

For XXXX-W83627-6A69LPA9C-0 DATE: 05/11/2000 Flash Type - XXXXX E8280ZAB /3.3V

File Name to Program : XXXXX.bin

File Name to Save : XXXXX.bin
```

6. Are you sure to program (y/n), please key in [Y] to start the programming.

```
FLASH MEMORY WRITER V7.88

(C)Award Software 2000 All Rights Reserved

For xxxx-W83627-6A69LPA9C-0 DATE: 05/11/2000
Flash Type - xxxxx E82802AB /3.3V

File Name to Program : xxxxx.bin
Checksum : 9335H
File Name to Save : xxxxx.bin
```

7. The programming is finished.

```
C) Award Software 2000 All Rights Reserved

For XXXX-W83627-6A69LPA9C-0 DATE: 05/11/2000
Flash Type - XXXXX E8280ZAB /3.3V

File Name to Program : XXXXX.bin
Checksum : 4804H
Verifying Flash Memory - 7FE00 OK


Whrite OK No Update Write Fail


F1: Reset F10: Exit
```

# Appendix C

### C-1 EEPROM BIOS Remover

Do not remove the BIOS chip, unless instructed by a technician and only with a PLCC IC extractor tool.





The BIOS socket may be damaged if using an improper method to replace the BIOS chip.

Page Left Blank

## Appendix D

### D-1 GHOST 7 Quick User's Guide (Optional)


Installation is very easy. You only need to copy the **Ghost7** folder or **Ghost.exe** to your hard disk.

#### Main Menu




### **Description of Menu**

Ghost clones and backs up Disk and Partition.



In which **Disk** indicates hard disk options **Partition** indicates partition options **Check** indicates check options

#### Disk



#### There are 3 hard disk functions:

- 1. Disk To Disk (disk cloning)
- 2. Disk To Image (disk backup)
- 3. Disk From Image (restore backup)

### Important!

- 1. To use this function, the system must have at least 2 disks. Press the **Tab** key to move the cursor.
- 2. When restoring to a destination disk, all data in that disk will be completely destroyed.

### **Disk To Disk (Disk Cloning)**


- 1. Select the location of the **Source drive**.
- 2. Select the location of the **Destination drive**.



3. When cloning a disk or restoring the backup, set the required partition size as shown in the following figure.




4. Click OK to display the following confirmation screen. Select Yes to start.




### Disk To Image (Disk Backup)

1. Select the location of the Source drive.



2. Select the location for storing the backup file.




3. Click **OK** to display the following confirmation screen. Select **Yes** to start.



### **Disk From Image (Restore Backup)**

1. Select the Restoring file.




2. Select the **Destination drive** of the disk to be restored.




3. When restoring disk backup, set the required partition size as shown in the following figure.



4. Click **OK** to display the following confirmation screen. Select **Yes** to start.



#### **Partition**



There are 3 partition functions:


- **1. Partition To Partition** (partition cloning)
- **2. Partition To Image** (partition backup)
- 3. Partition From Image (restore partition)

### **Partition To Partition (Partition Cloning)**

The basic unit for partition cloning is a "partition". Refer to "disk cloning" for the operating method.

### Partition To Image (Partition Backup)


1. Select the disk to be backed up.



2. Select the first partition to be backed up. This is usually where the operating system and programs are stored.



3. Select the path and file name to store the backup file.



- 4. Is the file compressed? There are 3 options:
  - (1) No: do not compress data during backup
  - (2) Fast: Small volume compression
  - (3) High: high ratio compression. File can be compressed to its minimum, but requiring longer execution time.




5. Select Yes to start performing backup.




### Partition From Image (Restore Partition)


1. Select the backup file to be restored.



2. Select the source partition.



3. Select the disk to be restored.



4. Select the partition to be restored.



5. Select Yes to start restoring.



#### Check

This function is to check possible error caused by defective FAT or track during backup or restoring.

#### **How to Reinstall Windows in 2 Minutes**

This chapter guides you how to setup your computer properly and, if necessary, reinstall Windows in 2 minutes. Ghost provides different methods to complete this task. The following two sections explain how to create an emergency Recover Floppy and Recover CD:

### **Emergency Recover Floppy**

Divide a hard disk into two partitions. The first partition is to store the operating system and application programs. The second partition is to back up the operating system and data. The size of the partition can be determined according to the backup requirements. For example, the **Windows** operating system needs 200MB of hard disk space, Plus complete **Office** programs require 360MB. The remaining space can be used to store data.

After installing **Windows**, use **Ghost** to create a backup area for the system and to store the file (Image file) in drive D. The file is named **Original.gho**. Then, create a recover floppy disk containing:

- Bootable files (Command.com, Io.sys, and MSDOS.SYS)
- Config.sys (configuration setup file)
- Autoexec.bat (auto-execution batch file)
- Ghost.exe (Ghost execution file)

There are two ways to create the content of the recover floppy for restoring:

(1) To load **Windows** automatically after booting, store the **Autoexec. bat** file with a command line:

Ghost.exe clone, mode=pload, src=d:\original.gho:2,dst=1:1 -fx -sure -rb Command Description: Runs the restore function automatically with the Image File. Stored in drive D. After execution, it will exit Ghost and boots the system.

Refer to the [Introducing Ghosts Functions] for details.

(2) After booting, the screen displays the Menu. Select Backup or Restore: Since the user may install other applications in the future, he/she may alter Autoexec.bat file to back up or restore the user-defined Image file as follows:

### Backup

Back up Windows and application programs as a file (Recent. gho). Command is:

Ghost -clone,mode=pdump,src=1:1,dst=d:\Recent.gho -fx - sure -rb

#### Restore

Restore types include [General Windows] and [Windows and Application Programs]. If you select [General Windows], the system is restored to the general Windows operation condition. The command is:

Ghost.exe -clone,mode=pload,src=d:\Original.gho,dst=1:1 -fx -sure -rb

If you select [Windows and Application Programs], the latest backup file (Recent.gho) is restored, skipping the installation and setup of application programs.

For description of related parameters, refer to [Introducing Ghosts Functions].

For more information about menu design, refer to Config.sys and Autoexec.bat under /Menu in the CD. You can also create a backup CD containing Ghost.exe and these two files.

#### **Recover CD**

The following is a simple guide to create a recover CD:

1. First, create a recover floppy disk contains the following with any copy program such as "Easy CD Create" (Note 2):

Bootable files (Command.com and Io.sys and MSDOS.SYS)

Config.sys (Configuration setup file)

Autoexec.bat (Auto-execution batch file)

Mscdex.exe (CD-Rom execution file)

Ghost.exe (Ghost execution file)

Oakcdrom.sys (ATAPI CD-ROM compatible driver)

The content of Config.sys is:

DEVICE=Oakcdrom.sys /d:idecd001

The content of Autoexec.bat includes:

MSCDEX.EXE /D:IDECD001 /L:Z

Ghost.exe clone,mode=load,src=z:\original.gho,dst=1 -sure -rb

2. Write the backup image file (original.gho) of the entire hard disk or partition into the recover CD. Use the Recover CD to boot up the system and restore the backup files automatically.

For description of related parameters, refer to [Introducing Ghosts Functions].

Note: For more details about copy the creation program and method to create a recover CD, please refer to the releated software and its associated operating manual.

Note: Ghost may be executed in interactive or in batch mode. Most of the Ghost switches are used to assist in batch mode operation. To list switches, type ghost.exe -h.

## Appendix E

## E-1 POST CODES (Optional)

POST (hex)	DESCRIPTION	
CFh	Test CMOS R/W functionality.	
C0h	Early chipset initialization:	
	- Disable shadow RAM	
	- Disable L2 cache (socket 7 or below)	
	- Program basic chipset registers	
C1h	Detect memory	
	- Auto-detection of DRAM size, type and ECC.	
	- Auto-detection of L2 cache (socket 7 or below)	
C3h	Expand compressed BIOS code to DRAM	
C5h	Call chipset hook to copy BIOS back to E000 & F000 shadow RAM.	
01h	Expand the Xgroup codes locating in physical address 1000:0	
02h	Reserved	
03h	Initial Superio_Early_Init switch.	
04h	Reserved	
05h	1. Blank out screen	
	2. Clear CMOS error flag	
06h	Reserved	
07h	1. Clear 8042 interface	
	2. Initialize 8042 self-test	
08h	1. Test special keyboard controller for Winbond 977 series Super I/O	
	chips.	
	2. Enable keyboard interface.	
09h	Reserved	
0Ah	1. Disable PS/2 mouse interface (optional).	
	2. Auto detect ports for keyboard & mouse followed by a port &	
	interface swap (optional).	
0D 0D1	3. Reset keyboard for Winbond 977 series Super I/O chips.	
0B-0Dh	Reserved	
0Eh	Test F000h segment shadow to see whether it is R/W-able or not. If test	
OF1.	fails, keep beeping the speaker.	
0Fh	Reserved	
10h	Auto detect flash type to load appropriate flash R/W codes into the run	
1.11.	time area in F000 for ESCD & DMI support.	
11h	Reserved	
12h	Use walking 1's algorithm to check out interface in CMOS circuitry.	
1.21.	Also set real-time clock power status, and then check for override.	
13h	Reserved	
14h	Program chipset default values into chipset. Chipset default values are MODBINable by OEM customers.	
15h	Reserved	
16h	Initial Early_Init_Onboard_Generator switch.	
17h	Reserved	

18h	Detect CPU information including brand, SMI type (Cyrix or Intel) and	
	CPU level (586 or 686).	
19-1Ah	Reserved	
1Bh	Initial interrupts vector table. If no special specified, all H/W	
	interrupts are directed to SPURIOUS_INT_HDLR & S/W	
	interrupts to SPURIOUS_soft_HDLR.	
1Ch	Reserved	
1Dh	Initial EARLY PM INIT switch.	
1Eh	Reserved	
1Fh	Load keyboard matrix (notebook platform)	
20h	Reserved	
21h	HPM initialization (notebook platform)	
22h	Reserved	
23h	Check validity of RTC value:	
2311	e.g. a value of 5Ah is an invalid value for RTC minute.	
	<ol> <li>Load CMOS settings into BIOS stack. If CMOS checksum fails, use</li> </ol>	
	default value instead.	
	3. Prepare BIOS resource map for PCI & PnP use. If ESCD is valid,	
	take into consideration of the ESCD's legacy information.	
	4. Onboard clock generator initialization. Disable respective clock	
	resource to empty PCI & DIMM slots.	
	5. Early PCI initialization:	
	-Enumerate PCI bus number	
	-Assign memory & I/O resource	
	-Search for a valid VGA device & VGA BIOS, and put it into C000:0.	
24-26h	Reserved	
27h	Initialize INT 09 buffer	
28h	Reserved	
29h	1. Program CPU internal MTRR (P6 & PII) for 0-640K memory	
	address.	
	2. Initialize the APIC for Pentium class CPU.	
	3. Program early chipset according to CMOS setup.	
	Example: onboard IDE controller.	
	4. Measure CPU speed.	
	5. Invoke video BIOS.	
2A-2Ch	Reserved	
2Dh	1. Initialize multi-language	
	2. Put information on screen display, including Award title, CPU type,	
	CPU speed	
2E-32h	Reserved	
33h	Reset keyboard except Winbond 977 series Super I/O chips.	
34-3Bh	Reserved	
3Ch	Test 8254	
3Dh	Reserved	
3Eh	Test 8259 interrupt mask bits for channel 1.	
3Fh	Reserved	
40h	Test 8259 interrupt mask bits for channel 2.	
41h	Reserved	
42h	Reserved	
7411	NOSCI VOG	

43h	Test 8259 functionality.		
44h	Reserved		
45-46h	Reserved		
47h	Initialize EISA slot		
48h	Reserved		
49h	1. Calculate total memory by testing the last double word of each 64K		
	page.		
	2. Program writes allocation for AMD K5 CPU.		
4A-4Dh	Reserved		
4Eh	1. Program MTRR of M1 CPU		
	2. Initialize L2 cache for P6 class CPU & program CPU with proper		
	cacheable range.		
	3. Initialize the APIC for P6 class CPU.		
	4. On MP platform, adjust the cacheable range to smaller one in case		
	the cacheable ranges between each CPU are not identical.		
4Fh	Reserved		
50h	Initialize USB		
51h	Reserved		
52h	Test all memory (clear all extended memory to 0)		
53-54h	Reserved		
55h	Display number of processors (multi-processor platform)		
56h	Reserved		
57h	1. Display PnP logo		
	2. Early ISA PnP initialization		
	-Assign CSN to every ISA PnP device.		
58h	Reserved		
59h	Initialize the combined Trend Anti-Virus code.		
5Ah	Reserved		
5Bh	(Optional Feature) Show message for entering AWDFLASH.EXE		
	from FDD (optional)		
5Ch	Reserved		
5Dh	1. Initialize Init Onboard Super IO switch.		
	2. Initialize Init Onbaord AUDIO switch.		
5E-5Fh	Reserved		
60h	Okay to enter Setup utility; i.e. not until this POST stage can users enter		
	the CMOS setup utility.		
61-64h	Reserved		
65h	Initialize PS/2 Mouse		
66h	Reserved		
67h	Prepare memory size information for function call: INT 15h ax=E820h		
68h	Reserved		
69h	Turn on L2 cache		
6Ah	Reserved		
6Bh	Program chipset registers according to items described in Setup & Auto-		
	configuration table.		
6Ch	Reserved		
6Dh	Assign resources to all ISA PnP devices.		
· <del></del>	<ol> <li>Auto assign ports to onboard COM ports if the corresponding item</li> </ol>		
	in Setup is set to "AUTO".		
	1		

6Eh	Reserved	
6Fh	Initialize floppy controller	
	2. Set up floppy related fields in 40:hardware.	
70-72h	Reserved	
73h	(Optional Feature) Enter AWDFLASH.EXE if:	
	-AWDFLASH is found in floppy drive.	
	-ALT+F2 is pressed	
74h	Reserved	
75h	Detect & install all IDE devices: HDD, LS120, ZIP, CDROM	
76h	Reserved	
77h	Detect serial ports & parallel ports.	
78h-79h	Reserved	
7Ah	Detect & install co-processor	
7B-7Eh	Reserved	
7Fh	1. Switch back to text mode if full screen logo is supported.	
	-If errors occur, report errors & wait for keys	
	-If no errors occur or F1 key is pressed to continue:	
	<ul> <li>Clear EPA or customization logo.</li> </ul>	
80h-81h	Reserved	
82h	1. Call chipset power management hook.	
	2. Recover the text fond used by EPA logo (not for full screen logo)	
	3. If password is set, ask for password.	
83h	Save all data in stack back to CMOS	
84h	Initialize ISA PnP boot devices	
85h	1. USB final Initialization	
	2. NET PC: Build SYSID structure	
	3. Switch screen back to text mode	
	4. Set up ACPI table at top of memory.	
	5. Invoke ISA adapter ROMs	
	6. Assign IRQs to PCI devices	
	7. Initialize APM	
	8. Clear noise of IRQs.	
86-92h	Reserved	
93h	Read HDD boot sector information for Trend Anti-Virus code	
94h	1. Enable L2 cache	
	2. Program boot up speed	
	3. Chipset final initialization.	
	4. Power management final initialization	
	5. Clear screen & display summary table	
	6. Program K6 write allocation	
	7. Program P6 class write combining	
95h	Program daylight saving	
	2. Update keyboard LED & typematic rate	
96h	1. Build MP table	
	2. Build & update ESCD	
	3. Set CMOS century to 20h or 19h	
	4. Load CMOS time into DOS timer tick	
	5. Build MSIRQ routing table.	
FFh	Boot attempt (INT 19h)	
	* · /	