

Address:#1403, BLOCK1,LIYUAN BUILDING NO.622.BULONG ROAD.LONGHUA XINQU.BAOAN DISTRICT SHENZHEN CITY.GUANGDONG PROVINCE .China

Tel:13537897340 Fax: 86-755-23322627 Email: colin_8866@hotmail.com Contact: Vicky

website: http://www.aglysecurity.com/ http://daping.en.alibaba.com/



Price List



www.aglysecurity.com									
Picture	Name	Model	Description	PRICE (USD/PCS)	Unit	MOQ	Note		
GSM+PSTN+CID	GSM - PSTN - SMS - TOUCH GSM Wireless Security Alarm System	DP-7016	Smart touch keypad with 4 line message LCD display Quad-band GSM communication, works with SIM card Calender, five personal emergency phone numbers One central monitoring	54	Set	50PCS			
Russian voice gsm alarm systm	Digital clock display cheaper GSM Alarm System with russian voice	DP-08G	 Smart touch keypad with 4 line message LCD display Quad-band GSM communication, works with SIM card Calender, five personal emergency phone numbers One central monitoring station phone number 	40	Set	10 PCS	russian voice is avaiable		
SECURITY ALONG HARM	Wireless Home Security GSM Alarm System with Built- in antenna	DP- 200C(Upda ted version with Communic ation Module;whi te/black for your choose)	included period of time, eliminating of need of	35	set	100PC S	russian voice andrussian user manual avaiable		
SECRETH MANAGEMENT OF THE SECRETH SECR	Wireless Home Security GSM Alarm System with Built- in antenna	DP- 200C(Upda ted version with Communic ation Module;whi te/black for your choose)	1.Work with GSM SIM card, and voice prompt, ease of use. 2.Two groups of Scheduled Arming and Disarming function. Each time disarmed you can select the included period of time, eliminating of need of	33	set	100PC S	russian voice andrussian user manual avaiable		

LCD Intelligent GSM alarm system	DP-500 (English &Spanish&Fr ench for choose)	1.8 wired defense zones,99 wireless defense zones,8 wireless remote controller to code 2.Static current: ≤ 50mA/15V, Working current:≤ 300mA/15V 3.Power adaptor:12V/2000MA 4.Wireless	48	Set	10 PCS
Wireless infards detector (pet)	DP-86R	1. MCU control 2. Low power alarm 3. Automatic temperature compensation technology 4. SMT design, anti-RFI & anti-EMI 5. Lowest consumption, Long service time of battery 6. Wireless alarm signal: 315MHz, 433 MHz Technical Parameter	4	PC	100PC S
Wireless magnetic door	DP-90	1. Static curren: ≤4.5mA 2. Alarm current: ≤10mA 3. Operating voltage: 3. Static Current Consumption: ≤5μA 4. Emission Current: ≤ 15mA 5.Operating Temperature: - 10 °C ~ 50 °C 6. Emission Distance: 100 m (Open field)	2.5	PC	100 PCS
Independent SMOKE DETECTOR wireless SMOKE DETECTOR	DP428	1.Unit Size:Ф107X44mm 2.Working Current: 1-Static Current: ≤10µA 2-Alarm Current: ≤12mA 3.Wireless frequece:433mhz 4.Operation Voltage: DC 9V Battery 5.Alarm Sound: ≥85dB(3m) 6.Ambient Temperature: - 10°C ~+60°C 7.Ambient Umidity	35	PC	500 PCS

NOTE:

- 1. Quotation is valid for one month.
- 2. Warranty: one year, wrong operation and damage would beyond the warranty.
- 3. G.W. & Size of Packing are only for reference
- 4. It's subject to our final confirmation.