Xerox[®] Phaser[®] 6600 Colour Printer and WorkCentre[™] 6605 Colour Multifunction Printer



Output Speed Colours	Phaser 6600N	Phaser 6600DN	WorkCentre 6605N	WorkCentre 6605DN
Output Speed - Colour an One-sided	Up to 35 ppm A4 (210) v 207 mm)		
Automatic Two-sided	N/A	Up to 24 ppm A4 (210 x 297 mm)	N/A	Up to 24 ppm A4 (210 x 297 mm)
Paper Handling - Input				
Duplex Automatic Docun	nent Feeder (DADF)			
Capacity ¹	N/A		50 sheets	
Sizes			Custom Sizes: 140 x 140	mm to 216 x 356 mm
Weights			Simplex: 50 to 125 gsm Duplex: 60 to 125 gsm	
Multipurpose Tray				
Capacity ¹	150 sheets			
Sizes	Custom Sizes: 76.2 x 127 mm to 216 x 356 mm			
Weights	60 to 216 gsm			
Media Types	Plain paper Hole punched Letterhead Coloured Lightweight Card stock Lightweight Glossy Card stock Heavyweight Glossy Card stock Heavyweight Glossy Card stock Labels Envelopes			
Tray 1				
Capacity ¹	550 sheets			
Sizes	Sizes: 148 x 210 mm to 216 x 356 mm			
Weights	60 to 216 gsm			

Media Types	Plain paper Hole punched Letterhead Coloured Lightweight Card stock Lightweight Glossy Card stock Heavyweight Card stock Heavyweight Glossy Card stock			
Tray 2 (Optional)				
Capacity ¹	550 sheets	550 sheets		
Sizes	Sizes: 148 x 210 mm to 21	6 x 356 mm		
Weights	60 to 216 gsm	60 to 216 gsm		
Media Types	Plain paper Hole punched Letterhead Coloured Lightweight Card stock Lightweight Glossy Card stock Heavyweight Card stock Heavyweight Glossy Card stock			
Paper Input Capacity	1			
Standard Capacity ¹	700 sheets			
Maximum Capacity ¹	1250 sheets			
Paper Output	Phaser 6600N	Phaser 6600DN	WorkCentre 6605N	WorkCentre 6605DN
Output Capacity ¹	250 sheets			
Automatic Two-sided Output	N/A	Standard	N/A	Standard
Print				
First-Page-Out Time	As fast as 9 seconds black and white / 10 seconds colour			
	As fast as 9 seconds black (and white / 10 seconds co	lour	
Print Resolution	Up to 600 x 600 x 4 dpi (1.			
Print Resolution Maximum Print Area				
	Up to 600 x 600 x 4 dpi (1)			
Maximum Print Area	Up to 600 x 600 x 4 dpi (1) 4.1 mm from all edges		age quality)	
Maximum Print Area Memory (Std/max)	Up to 600 x 600 x 4 dpi (1) 4.1 mm from all edges 256 MB / 768 MB		age quality)	
Maximum Print Area Memory (Std/max) Optional Hard Drive	Up to 600 x 600 x 4 dpi (1) 4.1 mm from all edges 256 MB / 768 MB 160 GB	200 x 1200 enhanced ima	age quality)	

Printing Features	PANTONE® Colour calibrated solid-colour simulations Saved settings Earth Smart settings Colour Corrections N-up Booklet layout Watermark Photo mode Collation Secure Print ² Saved Print ² Font/Form/Macro Storage ³ Apple AirPrint ⁴
Supported Operating Systems	Windows® XP SP1, Vista, 7, 2008 Server, 2003 Server Mac OS® 10.5 and later Various Linux and Unix distributions, including: IBM® AIX 5 HP-UX® 11i v2 Open SUSE 11 Red Hat Fedora Core 11-14 Ubuntu
Print Drivers	Windows® XP and later Mac OS® 10.5 and later Xerox® Global Print Driver® Xerox® Mobile Express Driver®
Font Capability	176 PostScript [®] fonts 88 PCL [®] fonts
Xerox [®] Mobile Express Driver [®] (X-MED)	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network and greatly reduce mobile support calls to IT. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management
Xerox® Globαl Print Driver® (X-GPD)	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bidirectional feedback device status, supplies, queue management

² Standard on WorkCentre 6605, requires optional Productivity Kit on Phaser 6600

³ Requires Productivity Kit (with 160 GB Hard Drive)

⁴ Requires minimum of Firmware 201301301313 for Phaser 6600 and minimum of Firmware 201301301321 for WorkCentre 6605.

Сору	Phaser 6600	WorkCentre 6605
Copy Speed	N/A	Simplex: Up to 35 ipm (images per minute) A4 Duplex: Up to 24 ipm A4
Document Scanner		Duplex Automatic Document Feeder with 50-sheet capacity
Document Scanner Size		Platen: Up to A4 DADF: Up to 216 x 356 mm
Sides (input:output)	_	1:1, 1:2, 2:2 and 2:1
Quantity		1 to 99
Resolution		Up to 600 x 600 dpi
First-copy-out Time		As fast as 13 seconds black and white / 16 seconds colour
Copy Feαtures		Reduce/Enlarge (25% - 400%) Lighter/Darker Colour Saturation Sharpness Colour Balance Auto Exposure 2-up Output AutoFit Cloning Collate (up to 50 pages)
Fax	Phaser 6600	WorkCentre 6605
Fax Speed	N/A	33.6 Kbps
Memory	_	4 MB
Resolution		Up to 300 x 300 dpi (Super Fine / Photo) resolution Up to 203 x 196 dpi (Fine) resolution Up to 203 x 98 dpi (Standard) resolution
Compression	_	MH, MR, MMR, JBIG
Walk-up Fax Features ^s		Reject Junk Fax Distinctive Ring Pattern Detection Fax Forward to Email and FTP/SMB Server ⁴ Fax Forwarding and Local Print Polling Receive Delayed Start (up too 24 hours) Broadcast Sending (up to 200 destinations) Fax Address Book (up to 200 speed dials) Secure Fax Receive
LAN Fax Features		Delayed Start (up to 24 hours) Broadcast Sending (up to 30 destinations) Zoom Auto Fit Rotation N-up Watermark Phonebook (Up to 500 speed dial numbers, up to 500 group dials, phonebook stored on PC)

⁴ Requires minimum of Firmware 201301301313 for Phaser 6600 and minimum of Firmware 201301301321 for WorkCentre 6605.

⁵ Analogue phone line required

Scan	Phaser 6600	WorkCentre 6605
Capability	N/A	Black and white and colour scanning
Input Speed - B/W		Simplex: Scan up to 22 ipm – A4 Duplex: Scan up to 7 ipm – A4
Input Speed - Colour		Simplex: Scan up to 13 ipm – A4 Scan up to 4 ipm – A4
Resolution (maximum)		Up to 1200 x 1200 dpi
Bit Depth		48-bit colour, 16-bit greyscale
Maximum Scan Area		Platen: Up to A4 DADF: Up to 216 x 356 mm
Network Filing Protocol		FTP SMB
File Formats		PDF TIFF (single and multi-page) JPEG
Scan Driver Compatibility		WIA TWAIN
Supported Scan Destinations		Scan to Computer via SMB Scan to Server via FTP Scan to Email with LDAP support Scan to USB Memory Device WSD Scanning
Scanning Solutions	'	
Xerox® Scan to PC Desktop Personal Edition	N/A	 A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools Nuance PaperPort – image viewing and file management software Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox[®] WorkCentre to individual desktops. For a complete list of scanning solutions, visit www.xerox.com
Security		
Security Features	Secure Fax Receive (WorkCentre 6605 only) Secure Print ⁶ 256-bit disk encryption and overwrite ⁷ Secure HTTPS (SSL, Secure LDAP ⁷) IPsec 802.1X Authentication IPv6 SNMPv3 Audit Log IP Filtering Scan to Email over SSL/TLS ⁴	

⁴ Requires minimum of Firmware 201301301313 for Phaser 6600 and minimum of Firmware 201301301321 for WorkCentre 6605.

⁶ Standard on WorkCentre 6605, requires optional Productivity Kit on Phaser 6600

⁷ Requires Productivity Kit (with 160GB Hard Drive)

Wi-Fi Security	1		1
	Authentication Method	Encryption	Hard Drive Required
	Open WPA PSK WPA PSK / WPA2 PSK	WEP 64/128 ASCII/HEX TKIP AES	No
	WPA Enterprise WPA Enterprise / WPA 2 Enterprise WPA Enterprise AuthenticationMethod options: PEAPVO MS-CHAPV2 EAP-TLS EAP-TTLS PAP EAP-TTLS CHAP	TKIP AES	Yes
Device Management			
Xerox CentreWare® Web			
	 A Web-based server application for network admini from any workstation, whether running Windows or Works with any SNMP-managed printer from any n Provides help with device discovery and installation well as basic accounting and asset management 	r UNIX or any other operating sy nanufacturer	stem
Xerox [®] CentreWare [®] Inter	rnet Services - Integrated Device Web Page		
Device Status	Web server embedded • Tray status/contents • Consumables status		
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete		
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft® Internet Explorer 7 Firefox® version 4 and above		
Xerox [®] Mobile Solutions			
Xerox® PrintBack	PrintBack takes the capabilities of the printer you already use, and extends them beyond your computer and out to your Apple iOS- or Android-based mobile device. When you're working offsite or away from your desk and receive an important document via your mobile device, simply use PrintBack to print it with your default printer back at your office or desk. Plus, it supports the most common office file types (Microsoft® Office documents, PDF, etc.) with uncompromised print quality.		
Xerox® Mobile Express Driver®	The Xerox® Mobile Express Driver is a single, universal printer driver that can be downloaded to a PC and used to print to virtually any PostScript device on the network, including printers made by other manufacturers. Instead of downloading individual printer drivers for each product in each office, users can download the single, simple, Mobil Express Driver.		
Device Specifications			
Duty Cycle			
	Up to 80,000 pages per month ⁸		
Recommended Monthly P	rint Volume		
	Up to 5,000 pages per month ⁹		

⁸ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

⁹ Average monthly print volume - expected regular monthly throughput.

Power Consumption	Phaser 6600		WorkCentre 6605		
220-240 VAC, 50/60 Hz, 5A					
Printing (average operations)	520 watts		560 watts		
Standby Mode	64 watts		72 watts	72 watts	
Sleep Mode	4 watts		5.9 watts	5.9 watts	
Warm up (from sleep)	As fast as 21 seconds		As fast as 25 seconds		
Warm up (from power on)	As fast as 40 seconds		As fast as 44 seconds		
Storage Temperature Range	0° to 35° C				
Operating Temperature Range	10° to 32° C				
Operating Humidity	10% to 85%				
Storage Humidity	5% to 85%				
Operating Altitude	Up to 3,100 metres				
Shipping Altitude	Up to 15,000 metres when pressurised at 70.9275 KPa or greater				
Sound Pressure Levels	Phaser 6600		WorkCentre 6605		
Printing / Copying	53 dB(A)		52 dB(A)		
Standby	29 dB(A)		29 dB(A)		
Sound Power Levels					
Printing / Copying	6.9 B		6.8 B		
Standby	4.5 B		4.4 B		
Dimensions and Weights (Unpackaged)	Width	Depth	Height	Weight (with CRUs)	
Phaser 6600	430 mm	488 mm	384 mm	25.5 kg	
WorkCentre 6605	430 mm	528 mm	560 mm	32.5 kg	
550-sheet Feeder	427 mm	485 mm	138 mm	2.6 kg	
Dimensions and Weights (Packaged)	Width	Depth	Height	Weight	
Phaser 6600	570 mm	686 mm	526 mm	30.5 kg	
WorkCentre 6605	570 mm	686 mm	706 mm	37.5 kg	
550-sheet Feeder	590 mm	544 mm	241 mm	5.2 kg	

Certifications			
	FCC Part 15 Class B, RoHS Directive 2002/95/EC, WEEE Directive 2002/96/EC, Low Voltage Directive 2006/95/EC, EN 60950-1, EN 60825-1 – Class 1 Laser Product, EMC Directive 2004/108/EC, EN 55022, Class B, EN 55024, Listed to UL/CSA 60950-1, FDA 21 CFR Part 1010, 1040 – Class 1 Laser Product, CB Report, IEC 60950-1, IEC 60825-1 – Class 1 Laser Product, Section 508 ADA		
	ENERGY STAR® (DN configuration), Microsoft WHQL, Adobe® PostScript®, PANTONE®, ECMA 370 Declaration (Nordic), GOST/NOM, GS Mark, Environmental Choice, Xerox® Green World Alliance, USB 2.0 Hi-Speed, WiFi Alliance (option), WLAN certified (option), Apple® Bonjour, IPv6 Ready logo, Citrix Ready, SAP, PTT (WorkCentre 6505 only)		
What Comes in the Box			
	Phaser 6600 or WorkCentre 6605 Starter Toner Cartridges – One of each (Cyan, Magenta, Yellow: 2,000 print capacity ¹⁰ ; Black: 3,000 print capacity ¹⁰) Quick Use Guide, Quick Install Guide Software and Documentation CD (with Drivers, User Manual and Warranty Statement) Scan Software (WorkCentre 6605 only) Power cord Fax cord (WorkCentre 6605 only)		
Supplies and Options	Description Order Number		
Standard-Capacity Print	Black: 3,000 pages	106R02248	
Cartridges ¹⁰	Cyan: 2,000 pages	106R02245	
	Magenta: 2,000 pages	106R02246	
	Yellow: 2,000 pages	106R02247	
High-Capacity Print	Black: 8,000 pages	106R02232	
Cartridges ¹⁰	Cyan: 6,000 pages	106R02229	
	Magenta: 6,000 pages	106R02230	
	Yellow: 6,000 pages	106R02231	
Routine Maintenance Items ¹¹	Imaging Unit Kit: Up to 60,000 pages	108R01121	
	Waste Cartridge: Up to 30,000 pages	108R01124	
	Fuser Assembly: Up to 100,000 pages	115R00076	
	Transfer Unit Kit: Up to 100,000 pages	108R01122	
	550-sheet Feeder	097504400	
	512 MB memory	097504269	
	Productivity Kit (160 GB Hard Drive)	097S04403	
	Wireless Networking Adaptor	097504409	

¹⁰ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

¹¹ Approximate pages. Declared yield based on an average job size of three A4 pages. Yield will vary depending on job run length and media size and orientation.



©2013 Xerox Corporation. All rights reserved. Contents of this publication may not be reproduced in any form without permission of Xerox Corporation. XEROX®, XEROX and Design®, CentreWare® and Phaser® are trademarks of Xerox Corporation in the United States and/or other countries. Adobe® and PostScript® 3^{rm} are registered trademarks or trademarks of Adobe Systems, Incorporated. PCL® is a registered trademark of Hewlett-Packard. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency (DN configuration). ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. All other trademarks are the property of their respective manufacturers. The information in this brochure is subject to change without notice. 2/13

