

## **Bullard EVA PAPR Pre-Operational Checklist:**

	•	
Initials	Task 1. Check the blower housing for visible signs of	
	damage or deterioration.	
	<ol><li>Check that the belt is free from damage and that the belt buckle functions properly.</li></ol>	(Indian)
	3. Remove the battery from the charger, checking that the green LED light is on to indicate a full charge.	
	<ol><li>Install the battery into the back of the blower by inserting it until it clicks.</li></ol>	
	5. Remove the filter cartridge from the packaging and ensure that it is appropriate for the application.	13. Verify that the low flow alarm is operational by covering the end of the breathing tube with your hand and waiting approximately 5 seconds.
	<ol><li>Inspect the filter cartridge (including the gasket seal) for damage.</li></ol>	14. Power off the blower by holding down the on/off switch for 3-4 seconds. This is indicated by a long beep and the shut down of the motor.
	<ol><li>Record the "in-service" date on the filter cartridge label.</li></ol>	15. Check that the hood and lens is free from damage.  If using a hood constructed with sealed seams, check that the seams are free from damage.
	<ol><li>Install the filter cartridge into the open filter retainer port on the blower housing. Ensure that the filter locking tab is fully engaged.</li></ol>	16. Check that a suspension is installed in the hood  (not applicable for RT Series). If using the 20SICH
	<ol><li>Check that the rubber gasket is in place in the breathing tube connection port.</li></ol>	or 20TICH, ensure that a hard hat is installed in the hood.
	10. Connect the breathing tube to the blower by screwing the male breathing tube adaptor into the female opening on the top of the blower housing.	17. Connect the hood by inserting the breathing tube approximately five inches into the air entry sleeve at the rear of the hood. Use the nylon clamp to secure the breathing tube to the plastic anchor plate on the hood for CC20 series or directly to the
	<ol> <li>Hold the Air Flow Indicator (PA1AFI for hoods and PA4AFI for masks) on the end of the breathing tube. Power on the blower by pressing the power</li> </ol>	hood for RT Series.
	switch on top of the blower for 1-2 seconds and a short beep sounds. Verify that the ball of the air flow indicator is above the pass line. If not, refer to the user manual for additional instruction.	18. For the loose-fitting facepiece, insert the breathing tube into the opening on the rear of the headpiece and twist clockwise to lock the breathing tube into place.
	12. Verify that the speed selection is operational by	You are now ready to don the respirator.
	toggling the on/off switch just until it beeps to indicate the change in speed. When the unit is first powered on, it operates at high speed (8.5 cfm), and when toggled to the lower speed it operates at 7.0 cfm.	Refer to the User Manual for donning and use information.

©2009 Bullard. All rights reserved. EVA is a trademark of Bullard.