



LATITUDE™
Air Cooled Screw Liquid Chillers



R134a

**150 - 385 TONS
(527 - 1354 kW)
2 and 3 Compressor
50 and 60 Hz
ASHRAE 90.1 Compliant**



**140-200 Tons
60Hz**



Table of Contents

Introduction.....	3
Specifications	4
Accessories and Options	7
Nomenclature.....	9
Temperatures and Flows	10
Water Pressure Drop.....	12
Standard Efficiency Ratings – English - 460V/60Hz.....	16
High Efficiency Ratings – English - 460V/60Hz.....	20
Standard Efficiency Ratings – SI - 460V/60Hz.....	24
High Efficiency Ratings – SI - 460V/60Hz	28
Standard Efficiency Ratings – SI - 400V/50Hz.....	32
High Efficiency Ratings – SI - 400V/50Hz	36
Standard Efficiency Ratings – English - 380V/60Hz.....	40
High Efficiency Ratings – English - 380V/60Hz.....	44
Standard Efficiency Ratings – SI - 380V/60Hz.....	48
High Efficiency Ratings – SI - 380V/60Hz	52
Physical Data (English - Standard Efficiency).....	56
Physical Data (English - High Efficiency).....	58
Physical Data (SI - Standard Efficiency).....	60
Physical Data (SI - High Efficiency)	62
Dimensions – English	64
Dimensions – SI.....	84
Isolator Locations – English.....	104
Isolator Locations – SI.....	108
Isolator Details.....	112
Electrical Data - 2 Comp Standard Efficiency.....	116
Electrical Data - 2 Comp High Efficiency	118
Electrical Data - 3 Comp Standard Efficiency.....	120
Electrical Data - 3 Comp High Efficiency	122
Electrical Notes.....	124
Power Wiring.....	125
Typical Control Wiring - Two Compressor.....	128
Typical Control Wiring - Three Compressor	130
Application Data	132
Guide Specifications	133

YORK YC/IV Air Cooled Screw Liquid Chillers



YORK has a proud history of innovation in both compressor design and variable-speed-drive (VSD) technology. The Latitude™ air cooled chiller uses the best of modern screw compressor design and manufacturing techniques and combines them with the latest in a long line of chiller variable speed drives. The result is superior control and industry leading efficiency at real world conditions. In addition, by slowing the speed of the chiller to match system requirements at off-design conditions, the chiller sound output is reduced when it is the most sensitive to neighbors – evenings and weekends.

With the introduction of the YCIV model air cooled chiller, system designers are given the Latitude™ to design around the traditional benefits of air cooled chillers and still offer building owners energy efficient system design. In the past, the choice to use an air cooled chiller came with the expectation of compromise, where simplicity of design and maintenance were traded for performance and efficiency. Now combining the best of both worlds can provide a design that truly delivers the lowest total cost of ownership.

Specifications

POWER AND ELECTRICAL

- Johnson Controls has over 25 years of experience designing variable speed drives specifically for chiller applications. The result is an extremely reliable air cooled chiller system that offers industry leading efficiency at real world operating conditions, valve-less compressor loading/unloading, excellent capacity control, high power factor and soft start.
- All controls and motor starting equipment necessary for unit operation shall be factory wired and function tested.
- VSD Power/Control Panel includes main power connection(s), VSD and fan motor contactors, current overloads, and factory wiring. Standard design includes NEMA 3R (IP55) rating, powder painted steel cabinet with hinged, latched, and gasket sealed outer doors equipped with wind struts for safer servicing.
- VSD section of power panel includes a dedicated inverter for each compressor.
- The panel includes control display access door so display and control features can be accessed without opening main cabinet doors.
- Two and three compressor models come standard with single point power connection. In addition, all models are supplied with a factory mounted and wired control transformer that will supply all unit control voltage from the main unit power supply. The transformer utilizes scheduled line voltage on the primary side and provides 115V/1Ø on secondary.
- The standard power panel is equipped with terminal block electrical connections at the point of incoming power. An optional factory mounted circuit breaker is available, at point of incoming single point connection, that provides the means to disconnect power and short circuit protection. The optional lockable operating handle extends through the power panel door so that power may be disconnected without opening any panel doors.
- Short Circuit Withstand Rating of the chiller electrical enclosure is 30,000 Amps for standard terminal block connection. Ratings IAW (in accordance with) UL508. (See Accessories and Options section: Can be increased to 65,000 Amps for 380, 400 & 460V).
- Compressor motors are powered by a variable speed drive. Therefore, motor current never exceeds the rated load amps (RLA), providing soft starts with no electrical inrush. This eliminates the motor heating and stress always found with conventional motor starters. In addition, by eliminating the heat build up during starting, the required off-time between starts is reduced to a maximum of two minutes.
- Many utility companies charge an additional fee

if power factor is below 0.95. These power factor adjustments/penalties can affect both regular tariff rates, as well as demand charges. All YCIV models have a full load power factor of 95% and maintain this level throughout the operating range. Specifications should always require the installing contractor to be responsible for additional cost to furnish and install power factor correction capacitors if they are not factory mounted and wired.

SEMI-HERMETIC YORK TWIN SCREW COMPRESSORS

Johnson Controls Engineered Systems' Chiller Design Team has developed a world class compressor with unequalled performance:

- Continuous function, microprocessor controlled, VSD provides valveless, smooth capacity control from 100% down to 10% of chiller capacity for two compressor chillers and 100% down to 7.5% for three compressor chillers. In addition, elimination of the slide valve and associated unloading components resulted in a 50% reduction in compressor moving parts.
- Compressors are direct drive, semihermetic, rotary twin-screw type, including: muffler, temperature actuated 'off-cycle' heater, rain-tight (IP55) terminal box, discharge shut-off service valve, and precision machined cast iron housing mounted on neoprene isolators.
- Reliable suction gas cooled, high efficiency, accessible hermetic compressor motor, full suction gas flow through 0.006" maximum mesh screen, with inherent internal thermal overload protection and external current overload on all three phases.
- Suction gas screen and serviceable, 0.5 micron full flow oil filter within the compressor housing.
- Cast iron compressor housing precisely machined for optimal clearances and superb efficiency. Entire compressor, from suction to discharge has a Design Working Pressure of 350 PSIG (24 bar) or higher.

REFRIGERANT CIRCUIT

- Independent refrigerant circuits per compressor, each using copper refrigerant pipe formed on computer controlled bending machines. This eliminates over 60% of system piping brazed joints as compared to designs that use fittings, resulting in a highly reliable and leak resistant system.
- Liquid line components include: liquid line shut-off valve with charging port, low side pressure relief device, high adsorption removable core filter-drier, sight glass with moisture-indicator, and electronic expansion valve.

- Discharge line provided with manual compressor shutoff service valve (See Options and Accessories for suction line valve). Suction line equipped with closed-cell insulation.
- Insulated external oil separators with no moving parts, 450 PSIG (31 bar) design working pressure, and UL listing. Refrigerant system differential pressure provides oil flow through service replaceable, 0.5 micron, full flow, cartridge type oil filter internal to compressor.
- Oil cooling provided by dedicated air cooled finned tube type heat exchanger located in the condenser section of the machine.
- A flash tank is located in each refrigerant circuit to increase the system efficiency. The design working pressure is 450 PSIG (31 bar).
- Suction lines, oil separators and flash tanks are covered with closed-cell insulation.

EVAPORATOR

- High efficiency, direct-expansion type cooler with refrigerant in tubes and chilled liquid through the baffled shell. Independent circuits provided for each compressor.
- Design working pressure of the shell waterside is 150 PSIG (10.3 bar), and 235 PSIG (16 bar) for the refrigerant side. Constructed and tested IAW applicable sections of ASME Pressure Vessel Code, Section VIII, Division (1). Water side exempt per paragraph U-1, ©, (6).
- Removable heads allow access to internally-enhanced, seamless, copper tubes. Water vent and drain connections included.
- The evaporator is equipped with a thermostatically controlled heater for protection to -20°F (-29°C) ambient, and shell is covered with 3/4" (19mm), flexible, closed-cell insulation, thermal conductivity of 0.26k (BTU/HR-Ft²-°F/in.) maximum.
- Water nozzles have grooves for mechanical (ANSI/AWWA C-606) couplings, and shall be insulated by Contractor after pipe installation. (See the Accessories and Options section for flange options).

CONDENSER SECTION

- Condenser fans are dynamically and statically balanced, direct drive, corrosion resistant glass fiber reinforced composite blades molded into low noise, full airfoil cross section, providing vertical air discharge from extended orifices. Guards of heavy gauge, PVC (polyvinyl chloride) coated.
- Standard and reduced sound level models have

condensers fitted with single speed fans. Low sound models have two speed fans fitted.

- The fan motors are the high efficiency, direct drive, 6 pole on standard sound models and 8 pole on reduced and low sound models, 3 phase, Class-"F", current overload protected, totally enclosed (TEAO) type with double sealed, permanently lubricated, ball bearings
- Fin and tube condenser coils of seamless, internally enhanced, high condensing coefficient, corrosion resistant copper tubes arranged in staggered rows and mechanically bonded to corrosion resistant aluminum alloy fins with full height fin collars. Design working pressure is 450 PSIG (31 bar).

MICROPROCESSOR CONTROLS

- Microprocessor control system provides automatic control of chiller operation including compressor start/stop and load/unload, anti-recycle timers, condenser fans, evaporator pump, evaporator heater, unit alarm contacts and run signal contacts.
- Chiller automatically resets to normal chiller operation after power failure.
- Unit operating software is stored in non-volatile memory. Field programmed set points are retained in lithium battery backed regulated time clock (RTC) memory for minimum 5 years.
- Alarm contacts are provided to remote alert contacts for any unit or system safety fault.
- Display and Keypad:
 - ♦ 80 character liquid crystal display that is both viewable in direct sunlight and has LED backlighting for nighttime viewing. One keypad and display panel is provided with every chiller.
 - ♦ Display and keypad is accessible through display access door without opening main control/electrical cabinet doors.
 - ♦ Display provides unit setpoints, status, electrical data, temperature data, pressures, safety lock-outs and diagnostics without the use of a coded display.
 - ♦ Descriptions in English (or available language options), numeric data in English (or Metric) units.
 - ♦ Sealed keypad shall include unit On/Off switch.
- Programmable Setpoints (within Manufacturer limits): display language; leaving chilled liquid temperature: setpoint, control range; local or remote control; units of measure; compressor lead/lag; and maximum chilled water setpoint reset temperature range.
- Display Data: Chiller liquid return and leaving temperatures, ambient, lead compressor identification, clock

Specifications (Continued)

and schedule, (variable) out of range, remote input indication, chilled liquid reset setpoint, and history data for last ten shutdown faults. Compressor suction, discharge, and oil pressures and temperatures, suction and discharge superheats, percent of full-load, operating hours, starts, and anti-recycle timer status. Status Messages for manual override, unit switch off, compressor run, run permissive, remote controlled shut down, no cooling load, daily/holiday shut down, anti-recycle timer.

- During extreme or unusual conditions (i.e. blocked condenser coils, ambient above scheduled maximum, etc.) the chiller control system will avoid safety shutdown by varying the chiller controls and cooling load output to stay online and avoid safety limits being reached. This allows maximum possible cooling capacity until the unusual condition is cleared and avoids costly shutdowns. The system monitors the following parameters and maintain the maximum cooling output possible without shutdown of the equipment: motor current, suction pressure and discharge pressure.
- System Safeties are provided for individual compressor systems to perform auto-reset shut down (manual reset required after the third trip in 90 minutes). Safeties include: high discharge pressure or temperature, low suction pressure, high / low motor current, high motor temperature, high pressure switch, high / low differential oil pressure, high oil temperature, low suction superheat, critical sensor malfunction, low or high current, phase loss/single phase power, overload of motor windings, and low voltage.
- Unit Safeties are provided for the chiller to perform auto-reset shut down for the following conditions: high or low ambient, low leaving chilled liquid temperature, under voltage, and flow switch operation.

COMPLETE FACTORY PACKAGE

- These air cooled chillers are shipped as a complete factory package. Each unit is completely assembled with all interconnecting refrigerant piping and internal wiring, ready for field installation:

- Each compressor is installed on its own independent refrigerant circuit, which is factory pressure tested, evacuated, then fully charged with R134a refrigerant and oil.
- After assembly, an operational test is performed with water flowing through the cooler to ensure each circuit operates correctly.
- Unit panels, structural elements, control boxes and heavy gauge structural base shall be constructed of galvanized steel. Unit panels, control boxes and structural base are finished with a baked on powder paint. All painted surfaces shall be coated with baked on powder paint which, when subject to ASTM B117, 1,000 hour, 5% salt spray test, yields minimum ASTM 1654 rating of "6".
- Design is IAW applicable sections of ASME Pressure Vessel Code, NFPA 70 (National Electrical Code), U.L. and cU.L. Standards, and ASHRAE/ANSI-15 Safety Code for Mechanical Refrigeration.
- Units are Rated (all) and Certified (140 - 200 tons) IAW ARI Standard 550/590-98.
- Design is IAW ASHRAE 90.1 Energy Standard for Building Except Low-Rise Residential Buildings and ARI 70 Sound Rating of Large Outdoor Refrigeration and Air Conditioning Equipment.
- YCIV chillers are designed within EN ISO 9001 and built within an EN ISO 9002 accredited manufacturing organization.
- All exposed power wiring routed through liquid-tight, UV-stabilized, non-metallic conduit.
- When required, chillers have the option available to conform with the following European Directives (50 Hz only):
 - ◆ Machinery Directive (89/9/EEC)
 - ◆ Low Voltage Directive (72/EEC, EN 600)
 - ◆ EMC Directive (89/6/EEC)
 - ◆ Pressure Equipment Directive (97/EC)
 - ◆ Safety Code for Mechanical Refrigeration (EN78)

Accessories and Options

SOUND REDUCTION OPTIONS – The standard chiller has fans that operate at normal speed, no compressor enclosure, and is typically used in non-sensitive sound areas such as industrial areas or locations with loud traffic background noise. One or more of the following sound reduction options may be employed by the system designer as normally generated machine noise is considered in the overall project design.

Ultra Quiet Fans (Factory Mounted) – With this option, the basic chiller is equipped with specially designed fans and motors to provide lower sound levels and retain appropriate airflow. The result is reduced fan generated noise with no adverse effect on the chiller capacity or efficiency performance.

Two-Speed Fans (Factory Mounted) – With this option, the basic chiller is equipped with fans designed with two operating speeds. At high ambient conditions the fans operate at the normal speed with sound levels equivalent to Ultra Quiet Fans. As the ambient temperature falls the fans automatically reduce to slow speed reducing sound levels. If very low sound is required at all ambient conditions normal fan speed can be inhibited.

Reduced Sound Option (Factory Mounted) – With this option the chiller is equipped with an unlined compressor enclosure. This option is typically used for daytime operation where background noise is lower than normal city traffic etc.

Low Sound Option (Factory Mounted) – This option is only available with the selection of Ultra Quiet Fans or Two-Speed Fans. The chiller is equipped with an acoustically lined compressor enclosure. This option is typically for locations near residential areas, hotels, or hospitals etc where background noise is limited. When paired with the Two-Speed Fan option the unit can operate at normal speed during the day, when background noise levels are noticeable, and at low speed in the evening and at night when background levels are lower.

SilentNight™ - Standard variable speed compressors result in a chiller system that has lower part load sound values than conventional air-cooled chillers. Over 99% of chiller operating hours occur when building loads are less than design and/or ambient temperatures are less than design. As a result, all YCIV model chillers will operate with less than full load sound output nearly all the time – this is especially important on evenings and weekends when neighbors are home the most. Due to time of day based sound regulations it may be desirable to force the chiller to a lower sound level on demand. The SilentNight™ control option provides a control input to limit sound output of the chiller based on time of day. This feature is programmable at the chiller panel or can be controlled remotely via signal (4-20mA or 0-10 VDC) from a BAS system.

CIRCUIT BREAKER – Power panel will come equipped with a factory mounted circuit breaker at point of incoming

single or multi-point connection that provides the following:

- Means to disconnect power mounted on chiller.
- Circuit breaker sized to provide the motor branch circuit protection, short circuit protection and ground fault protection for the motor branch-circuit conductors, the motor control apparatus and the motors. (Chiller mounted circuit breaker option sized for branch circuit protection eliminates the need to provide a separate 'line of sight' disconnect and separate branch circuit protection device.)
- Lockable operating handle that extends through power panel door so that power may be disconnected without opening any panel doors.
- Short Circuit Withstand Rating of the chiller electrical enclosure when using circuit breaker option is 380, 400, & 460V: 65,000 Amps. Rating IAW UL508.

CONDENSER COIL PROTECTION – Standard condenser coil construction materials include aluminum fins, copper tubes, and galvanized tube supports for generally good corrosion resistance. However, these materials are not adequate for all environments. The system designer can take steps to inhibit coil corrosion in harsh applications and enhance equipment life by choosing from these options based on project design parameters and related environmental factors. (**Factory Mounted**)

- **PRE-COATED FIN CONDENSER COILS** – The air cooled condenser coils are constructed of epoxy-coated aluminum fins. This can provide corrosion resistance comparable to copper-fin coils in typical seashore locations. Either these or the post coated coils (below), are recommended for units being installed at the seashore or where salt spray may hit the unit.
- **POST-COATED EPOXY DIPPED CONDENSER COILS** – The unit is built with dipped-cured epoxy condenser coils. This is another choice for seashore and other corrosive applications (with the exception of strong alkalis, oxidizers and wet bromine, chlorine and fluorine in concentrations greater than 100 ppm).
- **COPPER FIN CONDENSER COILS** – The unit constructed with copper tube condenser coils, which have copper fins. (This is not recommended for units in areas where they may be exposed to acid rain.)

PROTECTIVE CHILLER PANELS:

- **Wire Panels (full unit)** – UV stabilized black polyvinyl chloride coated, heavy gauge, welded wire mesh guards mounted on the exterior of the unit. Protects condenser coil faces and prevents unauthorized access to refrigerant components (compressors, pipes,

Accessories and Options (Continued)

cooler, etc.), yet provides free air flow. This can cut installation cost by eliminating the need for separate, expensive fencing. **(Factory mounted)**

- **Louvered Panels (condenser coils only)** – Painted steel to match unit panels, louvered panels are mounted over the exterior condenser coil faces on the sides of the unit to visually screen and protect coils. **(Factory mounted)**
- **Louvered Panels (full unit)** – Painted steel to match unit panels, to protect condenser coils from incidental damage, visually screen internal components, and prevent unauthorized access to internal components. **(Factory mounted)**
- **Louvered (Condensers)/Wire Panels (Mechanical)** – Louvered steel panels on external condenser coil faces, painted to match unit panels. Heavy gauge, welded wire-mesh, coated to resist corrosion, around base of machine to restrict unauthorized access. **(Factory Mounted)**

EVAPORATOR OPTIONS:

- **1-1/2" Insulation** – Double thickness insulation provided. **(Factory Mounted)**
- **Raised Face Flange Accessory** for cooler nozzles:
 - ♦ 150 PSIG (10.3 bar), welded flanges (field kit, matching pipe flange by contractor).
 - ♦ 150 PSIG (10.3 bar) companion weld flanges. (field kit - Not available with 460V units).
 - ♦ 150 PSIG (10.3 bar), ANSI/AWWA C-606 COUPLINGS (field kit, matching pipe flange by contractor).
- **Opposite Handed evaporator water connections** for ease of installation. Standard water connections are on the left-hand side of the unit, when viewed from the control panel end.

FLOW SWITCH ACCESSORY : Vapor proof SPDT, NEMA 3R switch, 150 PSIG (10.3 bar) DWP, 20°F to 250°F (-28.9°C to 121.1°C) with 1" NPT (IPS) connection for upright mounting in horizontal pipe (This flow switch or equivalent must be furnished with each unit). **(Field Mounted)**.

DIFFERENTIAL PRESSURE SWITCH - Alternative to the paddle-type flow switch. 3-45 PSIG (0.2-3 bar) range with 1/4" NPTE pressure connections. **(Field Mounted)**

BUILDING AUTOMATION SYSTEM INTERFACE:

- Chiller to accept 4 to 20mA or 0 to 10 VDC input to reset the leaving chilled liquid temperature. **(Factory Mounted)**

MULTI-UNIT SEQUENCE CONTROL:

Separate sequencing control center provided to permit control of up to eight chillers in parallel based of mixed liquid temperature (interconnecting wiring by others). **(Field Mounted)**

VIBRATION ISOLATION:

- **Neoprene Isolation** – Recommended for normal installations. Provides very good performance in most applications for the least cost. **(Field mounted)**
- **1" Spring Isolators** – Level adjustable, spring and cage type isolators for mounting under the unit base rails. 1" nominal deflection may vary slightly by application. **(Field mounted)**
- **2" Seismic Spring Isolators** – Restrained Spring-Flex Mountings incorporate a rugged welded steel housing with vertical and horizontal limit stops. Housings designed to withstand a minimum 1.0g accelerated force in all directions to 2" (51mm). Level adjustable, deflection may vary slightly by application. **(Field mounted)**

BUY AMERICAN ACT COMPLIANCE - In keeping with the "Buy America Act", products will be comprised of 50% or more U.S. content and manufactured (final assembly) in the U.S.A.


SERVICE ISOLATION VALVE – Service suction isolation added to unit for each refrigerant circuit. **(Factory Mounted)**

CHICAGO CODE RELIEF VALVE - Special relief valves per Chicago code. **(Factory Mounted)**

PRESSURE RELIEF (CE/PED) SERVICE VALVE KIT - Each relief valve is mounted on a sealable ball valve to aid maintenance. **(Factory Mounted)**

NOMENCLATURE

The Model Number denotes the following characteristics of the unit:



Temperatures and Flows

TEMPERATURE AND FLOWS (English Units)

MODEL NUMBER YCIV		LEAVING WATER TEMPERATURE (°F)		COOLER ³ FLOW (GPM)		AIR ON CONDENSER (°F)	
		MIN. ¹	MAX. ²	MIN.	MAX.	MIN.	MAX
50 Hz	60 Hz						
0600(S/P)	0157(S/P)	40	60	140	675	0	125
0590(E/V)	0157(E/V)	40	60	160	750	0	125
0650(S/P)	0177(S/P)	40	60	160	750	0	125
0630(E/V)	0177(E/V)	40	60	160	750	0	125
0720(S/P)	0187(S/P)	40	60	160	750	0	125
0700(E/V)	0187(E/V)	40	60	160	750	0	125
0760(E/V)	0197(E/V)	40	60	180	750	0	125
0770(S/P)	0207(S/P)	40	60	180	800	0	125
0800(E/V)	0207(E/V)	40	60	180	750	0	125
0840(S/P)	0227(S/P)	40	60	180	800	0	125
0830(E/V)	0227(E/V)	40	60	180	750	0	125
0920(S/P)	0247(S/P)	40	60	180	800	0	125
0930(E/V)	0247(E/V)	40	60	180	800	0	125
1000(S/P)	0267(S/P)	40	60	180	800	0	125
1050(E/V)	0267(E/V)	40	60	250	1200	0	125
1070(S/P)	0287(S/P)	40	60	250	1200	0	125
1120(E/V)	0287(E/V)	40	60	250	1200	0	125
1180(S/P)	0307(S/P)	40	60	300	1200	0	125
1220(E/V)	0327(E/V)	40	60	300	1200	0	125
1340(S/P)	0357(S/P)	40	60	300	1200	0	125
1380(E/V)	0357(E/V)	40	60	300	1200	0	125
1500(S/P)	0397(S/P)	40	60	300	1200	0	125

NOTES:

1. For leaving brine temperature below 40°F (4.4°C), contact your nearest Johnson Controls office for application requirements.
2. For leaving water temperature higher than 60°F (15.6°C), contact the nearest Johnson Controls office for application guidelines.
3. The evaporator is protected against freezing to -20°F (-28.8°C) with an electric heater as standard.

TEMPERATURE AND FLOWS (SI Units)

MODEL NUMBER YCIV		LEAVING WATER TEMPERATURE (°C)		COOLER ³ FLOW (l/s)		AIR ON CONDENSER (°C)	
		MIN. ¹	MAX. ²	MIN.	MAX.	MIN.	MAX
50 Hz	60 Hz						
0600(S/P)	0157(S/P)	4.4	15.6	8.8	42.6	-17.8	51.7
0590(E/V)	0157(E/V)	4.4	15.6	10.1	47.3	-17.8	51.7
0650(S/P)	0177(S/P)	4.4	15.6	10.1	47.3	-17.8	51.7
0630(E/V)	0177(E/V)	4.4	15.6	10.1	47.3	-17.8	51.7
0720(S/P)	0187(S/P)	4.4	15.6	10.1	47.3	-17.8	51.7
0700(E/V)	0187(E/V)	4.4	15.6	10.1	47.3	-17.8	51.7
0760(E/V)	0197(E/V)	4.4	15.6	11.4	47.3	-17.8	51.7
0770(S/P)	0207(S/P)	4.4	15.6	11.4	50.5	-17.8	51.7
0800(E/V)	0207(E/V)	4.4	15.6	11.4	47.3	-17.8	51.7
0840(S/P)	0227(S/P)	4.4	15.6	11.4	50.5	-17.8	51.7
0830(E/V)	0227(E/V)	4.4	15.6	11.4	47.3	-17.8	51.7
0920(S/P)	0247(S/P)	4.4	15.6	11.4	50.5	-17.8	51.7
0930(E/V)	0247(E/V)	4.4	15.6	10.1	47.3	-17.8	51.7
1000(S/P)	0267(S/P)	4.4	15.6	11.4	50.5	-17.8	51.7
1050(E/V)	0267(E/V)	4.4	15.6	11.4	50.5	-17.8	51.7
1070(S/P)	0287(S/P)	4.4	15.6	15.8	75.7	-17.8	51.7
1120(E/V)	0287(E/V)	4.4	15.6	15.8	75.7	-17.8	51.7
1180(S/P)	0307(S/P)	4.4	15.6	18.9	75.7	-17.8	51.7
1220(E/V)	0327(E/V)	4.4	15.6	18.9	75.7	-17.8	51.7
1340(S/P)	0357(S/P)	4.4	15.6	18.9	75.7	-17.8	51.7
1380(E/V)	0357(E/V)	4.4	15.6	18.9	75.7	-17.8	51.7
1500(S/P)	0397(S/P)	4.4	15.6	18.9	75.7	-17.8	51.7


NOTES:

1. For leaving brine temperature below 4.4°C, contact your nearest Johnson Controls office for application requirements.
2. For leaving water temperature higher than 15.6°C, contact the nearest Johnson Controls office for application guidelines.
3. The evaporator is protected against freezing to -28.8°C with an electric heater as standard.

Water Pressure Drop

ENGLISH UNITS


Pressure Drop Through Two Circuit YCIV Evaporators



COOLER	MODEL NUMBER YCIV	
	60Hz	50Hz
A	0157(S/P)	0600(S/P)
	0157(E/V)	0590(E/V)
B	0177(S/P/E/V)	0630(E/V), 0650(S/P)
	0187(S/P/E/V)	0700(E/V), 0720(S/P)
C	0197(E/V)	0760(E/V)
	0207(E/V)	0800(E/V)
	0227(E/V)	0830(E/V)
D	0207(S/P)	0770(S/P)
	0227(S/P)	0840(S/P)
	0247(S/P/E/V)	0920(S/P), 0930(E/V)
	0267(S/P)	1000(S/P)

SI UNITS

Pressure Drop Through Two Circuit YCIV Evaporators




COOLER	MODEL NUMBER YCIV	
	60Hz	50Hz
A	0157(S/P)	0600(S/P)
	0157(E/V)	0590(E/V)
B	0177(S/P/E/V)	0630(E/V), 0650(S/P)
	0187(S/P/E/V)	0700(E/V), 0720(S/P)
C	0197(E/V)	0760(E/V)
	0207(E/V)	0800(E/V)
	0227(E/V)	0830(E/V)
D	0207(S/P)	0770(S/P)
	0227(S/P)	0840(S/P)
	0247(S/P/E/V)	0920(S/P), 0930(E/V)
	0267(S/P)	1000(S/P)

Water Pressure Drop – continued

ENGLISH UNITS


Pressure Drop Through Three Circuit YCIV Evaporators



EVAP	YCIV MODELS	
	60Hz	50Hz
A	0267EA/VA	1050(E/V)
	0287SA/PA	1070(S/P)
	0287EA/VA	1120(E/V)
B	0307SA/PA	1180(S/P)
	0327EA/VA	1220(E/V)
	0357SA/PA	1340(S/P)
	0357EA/VA	1380(E/V)
	0397SA/PA	1500(S/P)

SI UNITS

Pressure Drop Through Three Circuit YCIV Evaporators



EVAP	YCIV MODELS	
	60Hz	50Hz
A	0267EA/VA	1050(E/V)
	0287SA/PA	1070(S/P)
	0287EA/VA	1120(E/V)
B	0307SA/PA	1180(S/P)
	0327EA/VA	1220(E/V)
	0357SA/PA	1340(S/P)
	0357EA/VA	1380(E/V)
	0397SA/PA	1500(S/P)

Standard Efficiency Ratings – English - 460V/60Hz

MODEL: YCIV0157S/P

S_IPLV = 13.2 P_IPLV = 14.5

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	149.1	131.5	12.3	148.0	141.8	11.4	146.7	152.6	10.6	145.4	164.1	9.8	143.9	176.0	9.1	142.2	189.4	8.4	138.9	202.0	7.7	133.5	212.3	7.1	127.9	223.1	6.5
42.0	153.7	132.5	12.6	152.5	142.6	11.7	151.2	153.5	10.9	149.8	165.0	10.1	148.2	177.0	9.3	146.5	190.5	8.6	142.7	202.7	7.9	137.0	213.2	7.3	131.3	223.9	6.6
44.0	158.3	133.5	12.9	157.1	143.6	12.0	155.7	154.4	11.1	154.3	165.9	10.3	152.6	177.9	9.6	150.8	191.5	8.8	146.5	203.4	8.1	140.6	214.0	7.4	134.7	224.7	6.8
45.0	160.7	134.0	13.1	159.4	144.1	12.1	158.1	154.9	11.3	156.5	166.4	10.4	154.9	178.4	9.7	153.0	192.0	8.9	148.4	203.7	8.2	142.5	214.3	7.5	136.5	225.0	6.9
46.0	163.1	134.6	13.2	161.8	144.6	12.3	160.4	155.4	11.4	158.8	166.9	10.6	157.1	178.9	9.8	155.2	192.5	9.0	150.4	204.0	8.3	144.3	214.7	7.6	138.3	225.4	6.9
48.0	167.9	135.7	13.5	166.6	145.7	12.6	165.1	156.5	11.7	163.5	167.9	10.8	161.7	180.0	10.0	159.7	193.6	9.3	154.3	204.7	8.5	148.1	215.4	7.8	141.8	226.3	7.1
50.0	172.8	137.0	13.8	171.4	146.9	12.8	169.9	157.7	11.9	168.2	169.0	11.1	166.4	181.1	10.3	164.3	194.7	9.5	158.2	205.4	8.7	151.9	216.1	7.9	145.5	227.0	7.3
52.0	177.8	138.4	14.0	176.4	148.2	13.1	174.8	158.9	12.2	173.1	170.2	11.3	171.2	182.3	10.5	168.6	195.6	9.7	162.2	206.1	8.9	155.8	216.8	8.1	149.2	227.6	7.4
55.0	185.4	140.6	14.4	184.0	150.3	13.5	182.3	160.8	12.6	180.5	172.1	11.7	178.5	184.1	10.8	175.0	196.8	10.0	168.3	207.2	9.2	161.7	217.8	8.4	151.7	218.9	7.8

MODEL: YCIV0177S/P

S_IPLV = 13.0

P_IPLV = 14.8

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	165.7	144.7	12.6	164.2	156.2	11.6	162.4	168.5	10.7	160.5	181.2	9.9	158.4	194.4	9.1	154.6	205.6	8.5	149.9	214.6	7.9	143.5	222.1	7.3	130.1	211.5	6.9
42.0	170.9	145.7	12.9	169.3	157.3	11.9	167.5	169.5	11.0	165.5	182.3	10.1	163.3	195.6	9.4	159.1	206.2	8.7	154.0	215.3	8.1	147.5	222.8	7.5	131.8	207.2	7.2
44.0	176.1	146.8	13.2	174.6	158.3	12.2	172.8	170.6	11.3	170.7	183.5	10.4	168.4	196.8	9.6	163.8	206.8	8.9	158.3	215.8	8.3	151.5	223.4	7.7	133.6	203.1	7.4
45.0	178.8	147.5	13.3	177.2	158.9	12.3	175.4	171.1	11.4	173.3	184.0	10.5	171.0	197.5	9.7	166.1	207.1	9.0	160.5	216.0	8.4	153.5	223.7	7.8	134.5	200.9	7.5
46.0	181.5	148.2	13.5	179.9	159.5	12.5	178.1	171.7	11.5	175.9	184.6	10.7	173.5	197.8	9.9	168.5	207.3	9.2	162.6	216.2	8.5	155.6	224.0	7.9	135.3	198.6	7.7
48.0	186.9	149.5	13.8	185.4	160.8	12.8	183.5	173.0	11.8	181.3	185.9	10.9	178.4	198.3	10.1	173.3	207.9	9.4	167.0	216.6	8.7	159.8	224.5	8.1	137.0	194.3	7.9
50.0	192.4	151.0	14.0	190.8	162.2	13.0	189.0	174.3	12.1	186.7	187.2	11.2	183.4	198.8	10.4	178.2	208.4	9.6	171.5	217.0	8.9	162.8	221.6	8.3	138.3	189.5	8.2
52.0	198.0	152.6	14.3	196.4	163.7	13.3	194.5	175.8	12.3	192.2	188.6	11.4	188.5	199.4	10.6	183.1	209.0	9.9	176.0	217.4	9.1	164.7	216.6	8.6	139.6	184.9	8.4
55.0	206.4	155.2	14.7	204.9	166.1	13.7	202.9	178.1	12.7	200.6	190.9	11.8	196.2	200.4	11.0	190.7	209.9	10.2	182.9	217.9	9.5	167.5	209.1	9.0	141.5	178.2	8.9

MODEL: YCIV0187S/P

S_IPLV = 13.1

P_IPLV = 14.9

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	180.3	156.2	12.6	178.8	168.2	11.7	177.1	181.1	10.8	175.3	194.7	10.0	173.4	208.9	9.3	171.1	224.9	8.6	166.1	236.3	7.9	159.4	245.3	7.3	152.8	253.9	6.8
42.0	185.9	157.4	12.9	184.4	169.4	12.0	182.6	182.3	11.1	180.7	195.8	10.3	178.7	210.1	9.5	176.4	226.2	8.8	170.5	236.8	8.1	163.7	245.8	7.5	156.9	254.5	7.0
44.0	191.7	158.8	13.2	190.0	170.7	12.3	188.2	183.5	11.4	186.3	197.1	10.5	184.2	211.3	9.8	181.7	227.5	9.0	175.1	237.3	8.3	168.0	246.3	7.7	160.9	255.1	7.1
45.0	194.6	159.6	13.4	192.9	171.4	12.4	191.1	184.2	11.5	189.1	197.7	10.7	186.9	212.0	9.9	184.3	228.0	9.1	177.4	237.5	8.4	170.2	246.5	7.8	163.0	255.4	7.2
46.0	197.5	160.4	13.5	195.8	172.1	12.5	193.9	184.9	11.6	191.9	198.4	10.8	189.7	212.7	10.0	186.9	228.3	9.2	179.7	237.7	8.5	172.5	246.7	7.9	165.1	255.6	7.3
48.0	203.5	162.1	13.8	201.7	173.7	12.8	199.8	186.3	11.9	197.6	199.8	11.0	195.3	214.1	10.2	191.9	228.9	9.4	184.5	238.1	8.7	177.0	247.1	8.1	169.5	256.1	7.5
50.0	209.5	163.8	14.1	207.7	175.3	13.1	205.7	187.8	12.2	203.5	201.3	11.3	201.1	215.5	10.5	196.8	229.3	9.7	189.3	238.4	9.0	181.6	247.5	8.3	171.2	249.6	7.8
52.0	215.7	165.8	14.3	213.8	177.1	13.3	211.7	189.5	12.4	209.4	202.8	11.5	206.9	217.0	10.7	201.9	229.8	9.9	194.1	238.9	9.2	186.3	247.9	8.5	172.9	242.8	8.0
55.0	225.2	169.0	14.7	223.2	180.0	13.7	221.0	192.2	12.8	218.6	205.4	11.9	215.9	219.6	11.0	209.6	230.6	10.2	201.5	239.5	9.5	193.4	248.5	8.8	175.7	233.3	8.5

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 kW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98
6. Certified IAW the ARI Water-Chilling Packages Using the Vapor Compression Cycle Certification Program, which is based on ARI Standard 550/590.

MODEL: YCIV0207S/P**S IPLV = 13.2****P IPLV = 14.7****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	194.8	168.3	12.7	192.9	182.2	11.7	190.9	197.4	10.8	188.7	213.5	9.9	186.4	230.3	9.1	181.9	244.1	8.4	176.0	254.8	7.8	168.7	261.6	7.3	149.2	238.0	7.1
42.0	200.9	169.6	13.1	199.0	183.3	12.0	196.8	198.2	11.1	194.6	214.3	10.2	192.1	231.2	9.4	187.1	244.4	8.7	180.7	254.7	8.0	173.2	261.8	7.5	151.0	232.8	7.3
44.0	207.2	171.2	13.3	205.2	184.5	12.3	202.9	199.3	11.4	200.5	215.2	10.4	197.6	231.3	9.6	192.4	244.6	8.9	185.4	254.4	8.3	177.7	261.8	7.7	152.8	227.3	7.6
45.0	210.4	172.0	13.5	208.3	185.2	12.5	206.0	199.8	11.5	203.6	215.7	10.6	200.4	231.4	9.8	195.0	244.7	9.0	187.9	254.3	8.4	180.0	261.8	7.8	153.7	224.5	7.7
46.0	213.6	173.0	13.6	211.5	185.9	12.6	209.1	200.4	11.6	206.6	216.3	10.7	203.2	231.5	9.9	197.8	244.8	9.1	190.3	254.1	8.5	182.0	260.9	7.9	154.6	221.8	7.8
48.0	220.2	175.1	13.9	218.0	187.6	12.9	215.5	201.8	11.9	212.9	217.5	11.0	208.9	231.7	10.2	203.3	245.0	9.4	195.3	253.7	8.7	184.0	254.4	8.2	156.2	216.6	8.1
50.0	226.9	177.4	14.1	224.5	189.6	13.2	222.0	203.5	12.2	219.2	218.9	11.2	214.8	232.1	10.4	208.8	245.0	9.6	200.4	253.2	9.0	186.1	247.7	8.5	157.8	211.5	8.4
52.0	233.7	180.1	14.4	231.3	191.8	13.4	228.6	205.3	12.4	225.7	220.5	11.5	220.7	232.5	10.7	214.2	244.6	9.9	205.5	252.8	9.2	188.1	241.3	8.8	159.3	206.5	8.6
55.0	244.3	184.7	14.7	241.7	195.6	13.8	238.8	208.5	12.8	235.4	222.5	11.9	229.8	233.6	11.1	222.4	244.2	10.3	213.4	252.2	9.6	191.0	232.5	9.3	161.6	199.2	9.0

MODEL: YCIV0227S/P**S IPLV = 12.9****P IPLV = 14.7****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	211.3	180.4	12.9	209.4	194.3	11.9	207.3	209.2	11.0	205.1	224.8	10.2	202.7	241.3	9.4	199.9	259.8	8.7	193.1	269.8	8.1	185.3	277.1	7.6	177.5	283.8	7.1
42.0	218.0	182.0	13.2	216.0	195.7	12.2	213.8	210.5	11.3	211.4	226.2	10.4	208.9	242.7	9.7	206.0	261.3	8.9	198.2	270.0	8.3	190.2	277.4	7.8	182.1	284.2	7.3
44.0	224.9	183.7	13.5	222.7	197.3	12.5	220.4	212.0	11.6	218.0	227.7	10.7	215.3	244.2	9.9	211.9	262.1	9.1	203.5	270.1	8.5	195.2	277.6	8.0	186.9	284.5	7.4
45.0	228.3	184.7	13.6	226.2	198.2	12.6	223.8	212.8	11.7	221.3	228.5	10.8	218.5	245.1	10.0	214.7	262.2	9.2	206.2	270.2	8.6	197.7	277.7	8.1	189.3	284.6	7.5
46.0	231.8	185.7	13.7	229.6	199.1	12.8	227.2	213.7	11.8	224.6	229.3	11.0	221.8	245.9	10.1	217.5	262.2	9.4	208.9	270.2	8.7	200.3	277.7	8.2	191.8	284.7	7.6
48.0	238.9	187.8	14.0	236.7	201.1	13.0	234.2	215.4	12.1	231.4	231.0	11.2	228.5	247.5	10.4	223.2	262.4	9.6	214.4	270.3	9.0	205.6	277.8	8.4	195.3	281.4	7.9
50.0	246.2	190.1	14.3	243.8	203.1	13.3	241.2	217.4	12.4	238.4	232.8	11.5	235.3	249.2	10.6	229.0	262.5	9.8	219.9	270.4	9.2	210.9	277.8	8.6	197.2	274.6	8.1
52.0	253.6	192.7	14.5	251.2	205.4	13.6	248.5	219.5	12.6	245.5	234.9	11.7	242.3	251.2	10.8	234.9	262.7	10.1	225.6	270.4	9.4	216.3	277.8	8.8	199.3	267.5	8.4
55.0	264.9	196.7	14.9	262.4	209.2	13.9	259.5	223.0	13.0	256.4	238.2	12.1	253.1	254.3	11.2	243.9	263.0	10.5	234.3	270.6	9.8	224.6	277.9	9.1	202.2	256.3	8.9

MODEL: YCIV0247S/P**S IPLV = 12.7****P IPLV = 14.8****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	231.8	198.8	12.8	229.8	213.8	11.9	227.6	229.8	11.0	225.2	246.7	10.2	222.7	264.4	9.4	219.7	284.3	8.7	213.4	297.6	8.1	206.3	308.8	7.6	199.1	319.5	7.1
42.0	239.1	200.6	13.1	236.9	215.6	12.1	234.6	231.5	11.3	232.1	248.4	10.4	229.5	266.1	9.7	226.4	286.1	8.9	219.3	298.4	8.3	211.9	309.5	7.8	204.4	320.4	7.2
44.0	246.5	202.6	13.4	244.3	217.4	12.4	241.9	233.3	11.5	239.2	250.2	10.7	236.4	268.0	9.9	232.9	287.5	9.1	225.3	299.1	8.5	217.6	310.3	7.9	208.9	318.7	7.4
45.0	250.2	203.7	13.5	248.0	218.4	12.6	245.5	234.3	11.7	242.8	251.2	10.8	239.9	268.9	10.0	236.1	287.8	9.2	228.3	299.4	8.6	220.5	310.7	8.0	210.1	315.4	7.6
46.0	254.0	204.8	13.7	251.7	219.4	12.7	249.2	235.2	11.8	246.5	252.1	10.9	243.5	269.9	10.1	239.2	288.2	9.4	231.4	299.7	8.7	223.4	311.1	8.1	211.3	311.8	7.7
48.0	261.7	207.1	13.9	259.4	221.6	13.0	256.7	237.3	12.0	253.9	254.1	11.2	250.8	271.9	10.4	245.7	288.9	9.6	237.6	300.4	8.9	229.4	311.7	8.3	213.6	304.4	7.9
50.0	269.6	209.5	14.2	267.1	223.9	13.2	264.4	239.5	12.3	261.4	256.2	11.4	258.2	274.0	10.6	252.2	289.6	9.8	243.9	301.1	9.2	235.5	312.4	8.5	215.8	296.4	8.2
52.0	277.6	212.2	14.4	275.1	226.4	13.5	272.2	241.9	12.5	269.1	258.5	11.7	265.8	276.2	10.8	258.9	290.4	10.1	250.3	301.8	9.4	241.7	313.0	8.8	217.8	288.1	8.5
55.0	289.9	215.9	14.8	287.2	230.3	13.9	284.2	245.7	12.9	281.0	262.2	12.0	277.4	279.7	11.2	269.0	291.7	10.4	260.2	302.9	9.7	251.2	314.1	9.1	220.5	275.9	9.0

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 kW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98
6. Certified IAW the ARI Water-Chilling Packages Using the Vapor Compression Cycle Certification Program, which is based on ARI Standard 550/590.

Standard Efficiency Ratings – English - 460V/60Hz

MODEL: YCIV0267S/P

S IPLV = 12.3

P IPLV = 14.9

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	252.3	217.0	12.8	250.2	233.1	11.9	247.9	250.3	11.0	245.4	268.3	10.2	242.7	287.2	9.5	239.6	308.5	8.7	233.9	325.1	8.1	227.3	340.0	7.6	220.8	354.7	7.1
42.0	260.2	219.0	13.1	258.0	235.2	12.1	255.6	252.2	11.3	252.9	270.4	10.4	250.1	289.2	9.7	246.8	310.7	9.0	240.4	326.4	8.3	233.6	341.3	7.8	226.8	356.2	7.2
44.0	268.2	221.2	13.3	265.9	237.3	12.4	263.3	254.3	11.5	260.6	272.4	10.7	257.6	291.5	9.9	254.0	312.6	9.2	247.1	327.6	8.5	240.1	342.6	7.9	231.8	354.5	7.4
45.0	272.2	222.5	13.5	269.9	238.4	12.5	267.3	255.5	11.6	264.5	273.6	10.8	261.4	292.5	10.0	257.5	313.2	9.3	250.5	328.3	8.6	243.4	343.2	8.0	233.0	350.2	7.5
46.0	276.3	223.6	13.6	273.9	239.5	12.7	271.3	256.6	11.8	268.4	274.7	10.9	265.3	293.6	10.1	261.0	313.9	9.4	253.9	328.9	8.7	246.7	344.0	8.1	234.2	345.8	7.7
48.0	284.6	226.1	13.9	282.1	242.0	12.9	279.4	258.9	12.0	276.4	276.9	11.2	273.1	296.0	10.4	268.2	315.2	9.6	260.9	330.1	8.9	253.4	345.2	8.3	236.7	336.8	8.0
50.0	293.1	228.7	14.1	290.5	244.5	13.2	287.7	261.3	12.3	284.6	279.3	11.4	281.1	298.4	10.6	275.5	316.5	9.8	267.9	331.5	9.1	260.2	346.5	8.5	239.1	327.9	8.2
52.0	301.7	231.6	14.4	299.1	247.1	13.4	296.1	264.0	12.5	292.9	281.8	11.6	289.3	300.9	10.8	282.9	317.8	10.0	275.1	332.8	9.4	267.2	347.8	8.7	241.5	319.2	8.5
55.0	315.0	234.9	14.8	312.1	251.1	13.8	309.0	268.1	12.9	305.6	286.0	12.0	301.9	304.8	11.1	294.2	320.1	10.4	286.1	334.8	9.7	277.9	349.8	9.0	244.8	307.1	9.0

MODEL: YCIV0287S/P

S IPLV = 13.0

P IPLV = 14.7

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	268.2	228.0	12.9	265.7	246.5	11.9	262.9	266.4	10.9	259.9	287.2	10.1	256.7	308.8	9.3	251.3	328.6	8.6	244.3	345.3	8.0	234.1	356.5	7.4	209.5	332.8	7.1
42.0	276.6	229.7	13.2	274.1	248.0	12.2	271.2	267.7	11.2	268.0	288.6	10.4	264.6	310.3	9.6	258.7	329.7	8.8	250.9	345.8	8.2	240.4	357.3	7.6	211.9	325.4	7.3
44.0	285.2	231.6	13.5	282.6	249.6	12.5	279.6	269.2	11.5	276.3	290.0	10.6	272.7	311.7	9.8	266.3	330.6	9.1	257.7	346.2	8.4	246.8	357.8	7.8	214.8	318.9	7.6
45.0	289.6	232.6	13.7	286.9	250.5	12.6	283.9	270.0	11.7	280.6	290.8	10.8	276.7	312.1	9.9	270.2	331.0	9.2	261.2	346.3	8.5	250.0	358.2	7.9	216.1	315.4	7.7
46.0	294.0	233.7	13.8	291.3	251.4	12.8	288.3	270.8	11.8	284.9	291.6	10.9	280.7	312.5	10.1	274.1	331.5	9.3	264.7	346.4	8.6	253.4	358.4	8.0	217.5	311.9	7.8
48.0	303.0	236.1	14.1	300.2	253.5	13.1	297.1	272.7	12.1	293.5	293.3	11.2	288.9	313.4	10.3	282.0	332.3	9.6	271.7	346.6	8.9	258.9	355.8	8.2	220.1	304.8	8.1
50.0	312.1	238.8	14.4	309.3	255.8	13.4	306.0	274.7	12.4	302.4	295.2	11.4	297.2	314.4	10.6	290.1	333.3	9.8	278.9	346.7	9.1	261.9	347.2	8.5	222.4	297.7	8.4
52.0	321.4	241.7	14.6	318.5	258.5	13.6	315.2	277.1	12.7	311.4	297.4	11.7	305.7	315.5	10.9	298.2	334.0	10.1	286.2	346.8	9.3	264.9	338.8	8.8	224.6	290.7	8.6
55.0	335.7	246.8	15.0	332.7	262.8	14.0	329.2	280.9	13.0	325.3	300.9	12.1	318.6	317.4	11.3	310.1	334.5	10.4	297.4	346.9	9.7	269.4	327.1	9.3	227.7	280.5	9.0

MODEL: YCIV0307S/P

S IPLV = 12.6

P IPLV = 14.6

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	298.0	251.5	13.0	295.2	272.2	12.0	292.2	294.8	11.0	289.0	318.9	10.1	285.6	344.0	9.3	279.8	366.7	8.6	271.4	384.3	8.0	260.3	394.8	7.5	229.5	358.3	7.2
42.0	307.4	253.3	13.3	304.5	273.7	12.3	301.3	296.0	11.3	297.9	320.0	10.4	294.3	345.1	9.6	287.9	367.5	8.8	278.6	384.1	8.2	267.2	395.1	7.7	232.1	349.9	7.5
44.0	317.0	255.6	13.6	314.0	275.5	12.6	310.6	297.5	11.6	307.1	321.3	10.7	302.9	345.6	9.8	296.2	368.1	9.1	286.0	383.8	8.4	274.2	395.1	7.9	235.1	342.1	7.7
45.0	321.9	256.9	13.8	318.8	276.5	12.8	315.4	298.3	11.8	311.7	322.0	10.8	307.3	345.8	10.0	300.4	368.5	9.2	289.7	383.6	8.5	277.7	395.0	8.0	236.5	338.1	7.8
46.0	326.9	258.2	13.9	323.7	277.6	12.9	320.2	299.2	11.9	316.4	322.7	11.0	311.7	346.1	10.1	304.7	368.8	9.3	293.5	383.3	8.7	280.1	392.1	8.1	237.9	334.0	8.0
48.0	336.9	261.3	14.2	333.6	280.0	13.2	329.9	301.2	12.2	326.0	324.5	11.2	320.6	346.9	10.4	313.4	369.4	9.6	301.2	382.7	8.9	283.2	382.4	8.4	240.7	326.4	8.3
50.0	347.2	264.7	14.5	343.7	282.9	13.5	339.9	303.5	12.5	335.8	326.6	11.5	329.8	347.7	10.7	322.0	369.6	9.8	309.0	382.1	9.1	286.4	372.5	8.7	243.0	318.5	8.5
52.0	357.7	268.6	14.7	354.1	286.1	13.7	350.1	306.2	12.7	345.8	328.8	11.8	339.1	348.7	10.9	330.3	369.0	10.1	317.0	381.4	9.4	289.6	362.8	9.0	245.3	311.0	8.8
55.0	373.9	275.3	15.0	370.0	291.6	14.1	365.8	310.9	13.1	360.8	332.0	12.2	353.5	350.8	11.3	343.0	368.4	10.5	329.2	380.5	9.8	294.2	349.6	9.5	248.8	300.0	9.2

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98

MODEL: YCIV0357S/P**S_IPLV = 13.5****P_IPLV = 15.1****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	336.3	288.0	12.8	333.4	309.9	11.9	330.1	333.5	11.0	326.6	358.2	10.2	322.9	384.1	9.4	318.6	413.2	8.7	309.3	432.1	8.1	298.3	446.9	7.6	287.4	460.8	7.1
42.0	346.9	290.6	13.1	343.8	312.4	12.2	340.4	335.8	11.3	336.7	360.5	10.4	332.8	386.5	9.7	328.3	415.8	8.9	317.7	433.0	8.3	306.3	447.8	7.7	295.0	462.0	7.2
44.0	357.7	293.3	13.4	354.5	315.0	12.4	350.9	338.3	11.5	347.1	363.1	10.7	342.9	389.0	9.9	338.1	418.1	9.1	326.3	433.8	8.5	314.6	448.7	7.9	302.8	463.1	7.4
45.0	363.2	294.8	13.6	359.9	316.4	12.6	356.3	339.6	11.7	352.3	364.3	10.8	348.1	390.4	10.0	342.7	418.5	9.2	330.7	434.1	8.6	318.7	449.1	8.0	304.8	459.0	7.5
46.0	368.8	296.5	13.7	365.4	317.8	12.7	361.7	341.0	11.8	357.6	365.7	10.9	353.3	391.7	10.1	347.2	418.9	9.3	335.1	434.5	8.7	322.9	449.5	8.1	306.7	454.4	7.6
48.0	380.1	299.7	14.0	376.6	320.9	13.0	372.7	343.8	12.1	368.5	368.5	11.2	363.9	394.5	10.4	356.5	419.7	9.6	344.0	435.2	8.9	331.5	450.3	8.3	310.2	444.4	7.9
50.0	391.6	303.2	14.2	387.9	324.2	13.3	383.9	347.0	12.3	379.5	371.4	11.4	374.8	397.4	10.6	366.0	420.5	9.8	353.1	435.9	9.2	340.2	450.9	8.5	313.5	433.3	8.2
52.0	403.4	307.0	14.5	399.6	327.7	13.5	395.4	350.3	12.6	390.8	374.5	11.7	385.9	400.4	10.8	375.7	421.3	10.1	362.4	436.7	9.4	349.2	451.6	8.8	316.5	421.3	8.5
55.0	421.3	312.6	14.9	417.2	333.5	13.9	412.9	355.6	13.0	408.1	379.9	12.0	402.9	405.5	11.2	390.4	422.8	10.4	376.6	437.8	9.7	362.8	452.6	9.1	320.4	402.9	8.9

MODEL: YCIV0397S/P**S_IPLV = 13.2****P_IPLV = 15.2****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	377.3	324.5	12.8	374.2	348.7	11.9	370.7	374.4	11.0	366.9	401.4	10.2	362.9	429.8	9.5	358.2	461.7	8.7	350.0	486.9	8.1	340.3	509.2	7.6	330.6	531.2	7.1
42.0	389.1	327.5	13.1	385.8	351.6	12.1	382.2	377.3	11.3	378.2	404.5	10.4	374.0	432.8	9.7	369.0	464.8	8.9	359.8	488.8	8.3	349.7	511.2	7.8	339.5	533.5	7.2
44.0	401.2	330.7	13.3	397.8	354.8	12.4	394.0	380.3	11.5	389.8	407.5	10.7	385.3	436.0	9.9	380.1	468.1	9.2	369.8	490.8	8.5	359.3	513.2	7.9	348.7	535.6	7.4
45.0	407.4	332.4	13.5	403.8	356.4	12.5	399.9	382.1	11.6	395.7	409.1	10.8	391.0	437.7	10.0	385.4	469.1	9.3	374.9	491.7	8.6	364.2	514.2	8.0	350.8	530.1	7.5
46.0	413.5	334.3	13.6	410.0	358.1	12.7	406.0	383.7	11.8	401.6	410.9	10.9	396.9	439.3	10.1	390.7	470.2	9.4	380.0	492.6	8.7	369.2	515.1	8.1	352.7	523.5	7.6
48.0	426.1	337.9	13.9	422.4	361.6	12.9	418.2	387.1	12.0	413.7	414.2	11.2	408.7	442.9	10.4	401.5	472.0	9.6	390.5	494.5	8.9	379.2	517.2	8.3	356.3	510.3	7.9
50.0	439.0	341.8	14.2	435.1	365.5	13.2	430.8	390.7	12.3	426.0	417.8	11.4	420.9	446.4	10.6	412.6	474.0	9.8	401.1	496.5	9.1	389.5	519.0	8.5	360.0	496.9	8.2
52.0	452.0	346.1	14.4	448.0	369.4	13.5	443.5	394.7	12.5	438.6	421.5	11.7	433.2	450.1	10.8	423.8	476.0	10.0	411.9	498.5	9.3	400.0	521.0	8.7	363.7	483.8	8.5
55.0	471.7	350.8	14.9	467.3	375.7	13.8	462.8	400.7	12.9	457.8	427.6	12.0	452.3	455.9	11.2	441.0	479.4	10.4	428.7	501.5	9.7	416.1	524.0	9.0	368.8	465.1	8.9

MODEL: YCIV0157E/V**E_IPLV = 13.5****V_IPLV = 14.6****NOTES:**

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KWt)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98

High Efficiency Ratings – English - 460V/60Hz

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
(°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	148.1	121.7	13.1	146.8	130.5	12.2	145.2	139.6	11.4	143.4	149.1	10.6	141.4	158.9	9.8	139.1	170.1	9.1	136.1	181.5	8.4	130.1	190.6	7.7	124.0	200.1	7.0
42.0	152.7	122.8	13.4	151.5	131.6	12.5	149.9	140.8	11.7	148.1	150.3	10.9	146.1	160.2	10.1	143.7	171.4	9.3	140.1	182.5	8.6	133.9	191.5	7.8	127.6	200.9	7.1
44.0	157.4	123.9	13.8	156.2	132.8	12.8	154.7	142.0	11.9	152.8	151.6	11.1	150.8	161.6	10.3	148.3	172.8	9.6	144.2	183.5	8.8	137.7	192.5	8.0	131.3	201.8	7.3
45.0	159.8	124.4	13.9	158.6	133.4	13.0	157.1	142.6	12.1	155.2	152.2	11.2	153.2	162.2	10.5	150.7	173.5	9.7	146.3	184.0	8.9	139.7	193.0	8.1	133.2	202.2	7.4
46.0	162.2	125.1	14.1	161.0	134.0	13.1	159.5	143.2	12.2	157.7	152.9	11.4	155.6	162.9	10.6	153.0	174.2	9.8	148.3	184.5	9.0	141.7	193.5	8.2	135.1	202.6	7.5
48.0	167.0	126.2	14.4	165.9	135.2	13.4	164.4	144.6	12.5	162.6	154.2	11.6	160.4	164.3	10.8	157.9	175.6	10.0	152.5	185.5	9.2	145.7	194.5	8.4	138.9	203.6	7.7
50.0	171.9	127.3	14.7	170.8	136.4	13.7	169.3	145.9	12.8	167.5	155.7	11.9	165.4	165.8	11.1	162.7	177.2	10.2	156.7	186.5	9.4	149.8	195.5	8.6	142.7	204.7	7.9
52.0	176.8	128.5	15.0	175.8	137.7	14.0	174.4	147.2	13.0	172.6	157.1	12.1	170.4	167.2	11.3	167.7	178.7	10.5	161.0	187.6	9.6	153.9	196.5	8.8	146.7	205.7	8.0
55.0	184.4	130.2	15.4	183.5	139.6	14.4	182.1	149.2	13.4	180.3	159.2	12.5	178.1	169.5	11.7	174.8	180.6	10.8	167.5	189.3	9.9	160.2	198.1	9.1	152.8	207.2	8.3

MODEL: YCIV0177E/V

E IPLV = 13.5

V IPLV = 14.7

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
(°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	157.1	131.4	13.0	156.3	137.3	12.3	155.0	147.6	11.4	153.5	158.6	10.6	151.9	170.1	9.8	150.0	183.2	9.1	147.0	195.7	8.4	142.2	207.3	7.7	136.2	217.9	7.0
42.0	162.5	128.7	13.6	161.3	138.3	12.6	159.9	148.5	11.7	158.3	159.4	10.9	156.6	171.0	10.1	154.7	184.1	9.3	151.2	196.5	8.6	146.1	207.9	7.9	139.9	218.6	7.2
44.0	167.6	129.9	13.9	166.3	139.3	12.9	164.8	149.5	12.0	163.2	160.4	11.2	161.5	171.9	10.4	159.4	185.0	9.6	155.6	197.2	8.8	150.1	208.5	8.1	143.6	219.3	7.4
45.0	170.2	130.5	14.0	168.9	139.9	13.1	167.4	150.1	12.2	165.7	160.9	11.3	163.9	172.4	10.5	161.8	185.5	9.7	157.8	197.6	8.9	152.1	208.8	8.2	145.5	219.6	7.4
46.0	172.8	131.2	14.2	171.4	140.5	13.2	169.9	150.6	12.3	168.2	161.4	11.4	166.4	172.9	10.6	164.3	186.0	9.8	160.0	198.0	9.0	154.1	209.1	8.3	147.5	219.9	7.5
48.0	178.0	132.6	14.5	176.7	141.8	13.5	175.1	151.8	12.6	173.4	162.5	11.7	171.5	174.0	10.9	169.1	186.9	10.0	164.6	198.7	9.2	158.3	209.7	8.4	151.4	220.5	7.7
50.0	183.4	134.1	14.8	182.0	143.1	13.8	180.4	153.0	12.9	178.6	163.7	12.0	176.6	175.1	11.1	173.9	187.8	10.3	169.2	199.6	9.5	162.5	210.3	8.7	154.4	218.2	7.9
52.0	188.9	135.7	15.0	187.5	144.6	14.1	185.8	154.4	13.2	183.9	165.0	12.3	181.9	176.3	11.4	178.7	188.7	10.5	173.9	200.5	9.7	166.8	210.9	8.9	156.2	212.7	8.2
55.0	197.4	138.4	15.4	195.8	147.0	14.5	194.1	156.6	13.6	192.2	167.0	12.7	190.0	178.3	11.8	186.2	190.2	10.9	180.8	201.5	10.0	173.3	211.9	9.2	158.8	204.8	8.7

MODEL: YCIV0187E/V

E IPLV = 13.2

V IPLV = 15.1

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
(°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	174.7	145.0	13.1	173.7	152.7	12.3	172.2	164.6	11.4	170.5	177.2	10.5	168.7	190.5	9.8	166.5	205.3	9.0	163.0	217.8	8.3	158.0	227.5	7.8	151.4	235.7	7.2
42.0	180.2	146.1	13.4	179.2	153.6	12.6	177.7	165.4	11.7	175.9	178.0	10.8	174.0	191.3	10.0	171.7	206.3	9.2	167.8	218.3	8.6	162.4	227.9	8.0	155.6	236.2	7.4
44.0	185.8	147.5	13.7	184.8	154.7	12.9	183.2	166.4	12.0	181.4	178.9	11.1	179.4	192.1	10.3	177.0	207.2	9.5	172.7	218.7	8.8	166.9	228.3	8.2	159.9	236.6	7.6
45.0	189.0	144.5	14.1	187.6	155.3	13.1	186.0	166.9	12.2	184.2	179.4	11.3	182.1	192.6	10.4	179.7	207.7	9.6	175.2	218.8	8.9	169.2	228.4	8.3	162.1	236.8	7.7
46.0	191.8	145.2	14.2	190.4	155.8	13.2	188.8	167.4	12.3	187.0	179.9	11.4	184.9	193.1	10.6	182.5	208.1	9.7	177.7	219.0	9.0	171.5	228.5	8.4	164.3	237.0	7.8
48.0	197.5	146.7	14.5	196.2	157.1	13.5	194.5	168.6	12.6	192.6	180.9	11.7	190.5	194.1	10.8	188.0	209.1	10.0	182.8	219.4	9.3	176.2	228.7	8.6	168.7	237.3	8.0
50.0	203.4	148.3	14.8	202.0	158.6	13.8	200.3	169.8	12.9	198.4	182.1	12.0	196.2	195.2	11.1	193.3	209.5	10.2	188.0	219.7	9.5	181.0	228.9	8.8	173.3	237.5	8.2
52.0	209.3	150.0	15.1	207.9	160.1	14.1	206.2	171.3	13.2	204.2	183.4	12.2	202.0	196.4	11.4	198.6	210.0	10.5	193.2	220.1	9.8	185.8	229.1	9.1	177.4	236.6	8.4
55.0	218.4	153.0	15.4	217.0	162.7	14.5	215.3	173.6	13.6	213.2	185.5	12.6	210.9	198.4	11.8	206.8	210.7	10.9	201.2	220.7	10.2	193.2	229.4	9.4	180.3	227.5	8.9

MODEL: YCIV0197E/V

E IPLV = 12.9

V IPLV = 15.0

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KWi)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98
6. Certified IAW the ARI Water-Chilling Packages Using the Vapor Compression Cycle Certification Program, which is based on ARI Standard 550/590.

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
(°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	189.8	153.1	13.4	188.2	165.6	12.4	186.4	179.5	11.4	184.5	194.4	10.5	182.5	210.2	9.6	180.1	227.8	8.8	176.4	243.2	8.1	169.4	250.7	7.6	162.4	257.3	7.1
42.0	195.8	154.3	13.7	194.1	166.4	12.7	192.2	180.0	11.7	190.3	194.8	10.8	188.1	210.6	9.9	185.6	228.4	9.1	181.3	242.8	8.4	174.0	250.6	7.8	166.7	257.5	7.3
44.0	201.9	155.8	14.0	200.1	167.5	13.0	198.2	180.8	12.0	196.1	195.4	11.1	193.9	211.0	10.2	191.3	228.9	9.3	186.2	242.3	8.6	178.7	250.3	8.0	171.2	257.5	7.5
45.0	205.0	156.6	14.2	203.2	168.2	13.2	201.3	181.3	12.2	199.1	195.7	11.2	196.8	211.2	10.4	194.2	229.1	9.5	188.7	242.1	8.7	181.1	250.1	8.1	173.5	257.4	7.6
46.0	208.1	157.6	14.3	206.3	168.8	13.3	204.3	181.8	12.3	202.2	196.0	11.4	199.8	211.5	10.5	197.1	229.4	9.6	191.2	241.8	8.9	183.6	249.9	8.3	175.8	257.3	7.7
48.0	214.5	159.6	14.6	212.6	170.4	13.6	210.6	182.9	12.7	208.3	196.9	11.7	205.8	212.2	10.8	203.0	230.0	9.9	196.4	241.2	9.1	188.5	249.4	8.5	180.5	256.9	7.9
50.0	221.0	162.1	14.8	219.1	172.3	13.9	216.9	184.3	12.9	214.5	198.1	12.0	212.0	213.1	11.1	209.0	230.9	10.1	201.6	240.6	9.4	193.5	248.8	8.7	185.3	256.5	8.1
52.0	227.7	164.8	15.0	225.7	174.5	14.2	223.4	186.1	13.2	221.0	199.4	12.3	218.3	214.2	11.3	215.2	231.7	10.4	206.9	240.1	9.7	198.5	248.2	9.0	190.2	255.9	8.4
55.0	237.9	169.6	15.3	235.8	178.3	14.5	233.4	189.1	13.6	230.8	201.8	12.7	228.0	216.1	11.7	223.7	231.3	10.8	214.9	239.4	10.1	206.3	247.4	9.4	197.7	255.0	8.7

MODEL: YCIV0207E/V

E_IPLV = 13.4

V_IPLV = 15.0

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	201.7	161.2	13.5	200.1	173.9	12.5	198.3	187.9	11.5	196.4	203.1	10.6	194.4	219.0	9.8	192.0	237.1	9.0	188.3	252.6	8.3	182.0	262.6	7.8	174.6	269.6	7.3
42.0	208.1	162.5	13.8	206.4	175.0	12.8	204.5	188.7	11.8	202.5	203.7	10.9	200.4	219.6	10.1	197.9	237.7	9.3	193.7	252.8	8.6	186.9	262.5	8.0	179.3	269.8	7.5
44.0	214.6	164.1	14.1	212.8	176.2	13.1	210.9	189.7	12.2	208.8	204.4	11.2	206.5	220.3	10.4	203.9	238.4	9.5	199.2	253.0	8.8	191.9	262.3	8.2	184.1	269.8	7.7
45.0	217.9	165.0	14.3	216.1	176.9	13.3	214.1	190.2	12.3	211.9	204.8	11.4	209.6	220.6	10.5	206.9	238.8	9.7	202.0	253.0	8.9	194.5	262.2	8.3	186.6	269.7	7.8
46.0	221.3	165.9	14.4	219.4	177.6	13.4	217.4	190.8	12.5	215.1	205.4	11.5	212.8	221.1	10.7	210.0	239.2	9.8	204.8	253.1	9.1	197.1	262.0	8.4	189.0	269.7	7.9
48.0	228.1	168.1	14.7	226.1	179.3	13.7	224.0	192.2	12.8	221.7	206.5	11.8	219.2	222.0	10.9	216.2	239.8	10.0	210.6	253.2	9.3	202.3	261.6	8.7	194.0	269.4	8.1
50.0	235.0	170.4	14.9	233.0	181.3	14.0	230.8	193.8	13.0	228.4	207.7	12.1	225.8	223.0	11.2	222.3	240.0	10.3	216.2	252.8	9.6	207.7	261.1	8.9	199.1	269.0	8.3
52.0	242.1	173.1	15.2	240.0	183.4	14.3	237.7	195.6	13.3	235.2	209.2	12.4	232.5	224.3	11.5	228.5	240.3	10.6	221.8	252.4	9.8	213.1	260.7	9.2	203.0	265.7	8.6
55.0	252.7	177.6	15.5	250.6	187.2	14.6	248.2	198.7	13.7	245.6	211.9	12.8	242.7	226.5	11.9	238.0	241.0	11.0	230.5	251.9	10.2	221.4	260.0	9.5	206.3	254.8	9.1

MODEL: YCIV0227E/V

E_IPLV = 13.1

V_IPLV = 15.0

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
(°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	209.5	167.1	13.4	207.9	179.8	12.5	206.1	193.4	11.6	204.2	208.1	10.7	202.1	223.5	10.0	199.8	241.0	9.2	197.2	259.1	8.5	190.9	269.7	7.9	183.3	277.2	7.4
42.0	216.1	168.5	13.7	214.5	181.0	12.8	212.6	194.6	11.9	210.6	209.1	11.0	208.4	224.5	10.2	205.9	242.0	9.4	203.2	260.3	8.7	196.1	269.8	8.1	188.3	277.4	7.6
44.0	222.9	170.1	14.1	221.2	182.3	13.1	219.2	195.8	12.2	217.1	210.2	11.3	214.9	225.6	10.5	212.2	243.1	9.7	209.4	261.4	8.9	201.5	269.9	8.3	193.4	277.4	7.8
45.0	226.4	171.0	14.2	224.6	183.1	13.3	222.6	196.4	12.3	220.4	210.8	11.5	218.1	226.1	10.6	215.4	243.7	9.8	212.4	261.7	9.0	204.2	269.8	8.4	196.0	277.5	7.9
46.0	229.8	171.9	14.4	228.0	183.9	13.4	226.0	197.1	12.5	223.8	211.4	11.6	221.4	226.8	10.8	218.6	244.2	9.9	215.2	261.7	9.2	206.9	269.8	8.6	198.6	277.5	8.0
48.0	236.9	173.9	14.7	235.0	185.6	13.7	232.9	198.7	12.8	230.6	212.8	11.9	228.1	228.0	11.0	225.2	245.5	10.2	221.0	261.7	9.4	212.5	269.8	8.8	203.9	277.4	8.2
50.0	244.0	176.0	14.9	242.1	187.5	14.0	239.9	200.3	13.1	237.6	214.2	12.2	235.0	229.3	11.3	232.0	246.8	10.4	226.9	261.7	9.7	218.1	269.7	9.0	209.3	277.4	8.4
52.0	251.1	178.3	15.2	249.2	189.5	14.3	247.0	202.1	13.3	244.6	215.9	12.4	242.0	230.8	11.6	238.9	248.2	10.7	232.9	261.7	9.9	223.9	269.6	9.3	214.8	277.2	8.7
55.0	262.1	182.1	15.6	260.1	192.9	14.6	257.8	205.1	13.7	255.3	218.6	12.8	252.5	233.3	12.0	249.2	250.5	11.0	242.1	261.8	10.3	232.7	269.6	9.6	223.2	277.1	9.0

MODEL: YCIV0247E/V

E_IPLV = 12.8

V_IPLV = 14.9

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98
6. Certified IAW the ARI Water-Chilling Packages Using the Vapor Compression Cycle Certification Program, which is based on ARI Standard 550/590.

High Efficiency Ratings – English - 460V/60Hz

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
(°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	232.7	192.6	13.1	230.8	206.9	12.2	228.7	222.3	11.3	226.4	238.6	10.5	223.9	255.8	9.7	221.1	275.2	9.0	216.9	292.5	8.3	210.2	305.1	7.8	202.9	316.2	7.2
42.0	240.0	194.4	13.4	238.0	208.6	12.5	235.8	223.9	11.6	233.4	240.2	10.8	230.8	257.3	10.0	227.9	276.8	9.2	223.2	293.8	8.5	216.0	305.8	8.0	208.5	317.0	7.4
44.0	247.4	196.3	13.7	245.4	210.4	12.8	243.1	225.6	11.9	240.6	241.8	11.0	237.9	259.0	10.2	234.7	278.3	9.4	229.7	294.9	8.7	221.9	306.4	8.2	213.0	315.2	7.6
45.0	251.2	197.4	13.9	249.1	211.4	12.9	246.8	226.5	12.0	244.2	242.7	11.1	241.4	259.9	10.3	238.1	278.9	9.6	232.8	295.2	8.9	225.0	306.8	8.3	214.3	311.7	7.7
46.0	255.1	198.5	14.0	252.9	212.3	13.1	250.5	227.4	12.1	247.9	243.6	11.3	245.1	260.7	10.5	241.5	279.6	9.7	236.0	295.5	9.0	228.0	307.1	8.4	215.6	308.1	7.9
48.0	262.8	200.8	14.3	260.6	214.5	13.3	258.1	229.4	12.4	255.4	245.4	11.5	252.4	262.6	10.7	248.4	280.9	9.9	242.4	296.1	9.2	234.2	307.7	8.6	218.0	300.5	8.2
50.0	270.8	203.3	14.5	268.5	216.8	13.6	265.9	231.5	12.7	263.1	247.5	11.8	260.0	264.5	11.0	255.5	282.2	10.1	248.9	296.8	9.4	240.5	308.3	8.8	220.2	292.4	8.5
52.0	278.9	205.9	14.8	276.5	219.2	13.9	273.8	233.8	12.9	270.9	249.6	12.0	267.7	266.6	11.2	262.8	283.6	10.4	255.5	297.5	9.7	246.9	308.9	9.0	222.2	284.1	8.8
55.0	291.2	209.7	15.2	288.7	223.1	14.2	285.9	237.5	13.3	282.8	253.1	12.4	279.5	269.8	11.6	273.9	286.0	10.7	265.7	298.6	10.0	256.7	309.9	9.3	225.0	272.3	9.2

MODEL: YCIV0267E/V E_IPLV = 13.3 V_IPLV = 14.9

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
(°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	264.2	211.7	13.5	261.9	228.6	12.5	259.3	246.9	11.5	256.4	266.4	10.6	253.3	286.8	9.8	249.7	309.7	9.0	244.9	331.1	8.3	234.7	343.0	7.7	224.5	353.9	7.1
42.0	272.6	213.3	13.8	270.3	229.9	12.8	267.6	248.0	11.8	264.6	267.4	10.9	261.3	287.9	10.1	257.6	310.9	9.2	251.8	331.4	8.5	241.3	343.4	7.9	230.7	354.6	7.3
44.0	281.2	215.2	14.1	278.8	231.4	13.1	276.0	249.2	12.1	272.9	268.5	11.2	269.5	288.9	10.4	265.6	312.2	9.5	258.9	331.4	8.8	247.9	343.6	8.1	237.1	355.1	7.5
45.0	285.5	216.3	14.3	283.1	232.3	13.3	280.3	249.9	12.3	277.2	269.1	11.4	273.7	289.5	10.5	269.7	312.7	9.6	262.4	331.4	8.9	251.3	343.7	8.2	240.3	355.3	7.6
46.0	289.9	217.4	14.4	287.4	233.2	13.4	284.6	250.7	12.5	281.4	269.8	11.5	277.9	290.1	10.6	273.8	313.4	9.8	266.0	331.5	9.0	254.7	343.8	8.3	243.5	355.5	7.7
48.0	298.8	219.9	14.7	296.3	235.3	13.7	293.4	252.4	12.8	290.1	271.2	11.8	286.5	291.4	10.9	282.2	314.7	10.0	273.3	331.4	9.2	261.7	343.8	8.5	250.2	355.6	7.9
50.0	307.8	222.7	15.0	305.3	237.6	14.0	302.3	254.4	13.1	299.0	273.0	12.1	295.2	293.0	11.2	290.8	316.1	10.3	280.7	331.3	9.5	268.8	343.8	8.8	256.9	355.8	8.1
52.0	317.0	225.8	15.3	314.5	240.3	14.3	311.5	256.6	13.3	308.0	274.9	12.4	304.2	294.7	11.5	299.6	317.8	10.5	288.2	331.3	9.7	276.0	343.8	9.0	263.8	355.8	8.3
55.0	331.1	231.1	15.6	328.5	244.8	14.7	325.4	260.5	13.8	321.9	278.2	12.8	317.9	297.6	11.9	312.4	319.0	10.9	299.8	331.4	10.1	287.1	343.7	9.4	274.4	355.8	8.7

MODEL: YCIV0287E/V E_IPLV = 12.9 V_IPLV = 14.8

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
(°F)	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	281.2	222.4	13.6	278.8	240.6	12.6	276.1	260.6	11.6	273.1	282.2	10.7	270.0	304.7	9.8	266.3	330.2	9.0	261.8	354.9	8.3	251.2	365.8	7.7	240.7	375.4	7.2
42.0	290.1	224.2	14.0	287.6	241.7	12.9	284.8	261.4	11.9	281.7	282.7	11.0	278.4	305.4	10.1	274.6	331.0	9.3	269.1	354.4	8.5	258.1	365.7	7.9	247.2	375.7	7.4
44.0	299.3	226.2	14.3	296.7	243.2	13.3	293.8	262.4	12.3	290.5	283.5	11.3	287.1	306.0	10.4	283.1	331.8	9.5	276.5	353.7	8.8	265.1	365.4	8.1	253.9	375.8	7.6
45.0	303.9	227.4	14.4	301.3	244.2	13.4	298.3	263.1	12.4	295.0	284.0	11.5	291.5	306.4	10.5	287.4	332.2	9.6	280.3	353.4	8.9	268.7	365.1	8.3	257.3	375.7	7.7
46.0	308.6	228.7	14.6	305.9	245.2	13.6	302.9	263.9	12.6	299.6	284.5	11.6	296.0	306.8	10.7	291.8	332.6	9.8	284.1	353.0	9.0	272.4	364.8	8.4	260.8	375.6	7.8
48.0	318.1	231.7	14.9	315.4	247.4	13.9	312.2	265.5	12.9	308.8	285.7	11.9	305.0	307.8	11.0	300.7	333.6	10.1	291.8	352.3	9.3	279.8	364.2	8.6	267.8	375.1	8.0
50.0	327.8	235.1	15.1	325.0	250.0	14.2	321.8	267.5	13.2	318.2	287.4	12.2	314.3	309.2	11.3	309.8	334.6	10.3	299.7	351.5	9.5	287.3	363.4	8.9	274.9	374.6	8.3
52.0	337.8	239.0	15.3	334.8	253.2	14.4	331.5	269.9	13.5	327.8	289.4	12.5	323.8	310.7	11.6	319.1	335.8	10.6	307.7	350.8	9.8	295.0	362.6	9.1	282.2	373.9	8.5
55.0	353.0	245.8	15.6	349.9	258.6	14.8	346.5	274.4	13.9	342.7	292.8	12.9	338.4	313.4	12.0	333.2	337.9	11.0	320.0	349.8	10.2	306.7	361.6	9.5	293.5	372.7	8.9

MODEL: YCIV0327E/V E_IPLV = 13.8 V_IPLV = 14.8

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	305.7	244.9	13.5	303.0	264.3	12.5	300.2	285.6	11.5	297.2	308.6	10.6	293.9	332.8	9.8	290.2	360.1	9.0	283.6	382.0	8.3	273.3	395.7	7.8	262.0	405.9	7.3
42.0	315.4	246.9	13.8	312.6	265.9	12.8	309.7	286.8	11.8	306.4	309.5	10.9	303.0	333.8	10.1	299.1	361.2	9.2	291.6	382.1	8.6	280.6	395.6	8.0	269.0	406.3	7.5
44.0	325.4	249.3	14.1	322.5	267.8	13.1	319.3	288.4	12.2	315.9	310.7	11.2	312.3	334.8	10.4	308.2	362.3	9.5	299.7	382.2	8.8	288.1	395.4	8.2	276.1	406.4	7.6
45.0	330.4	250.7	14.3	327.5	268.8	13.3	324.3	289.2	12.3	320.8	311.4	11.4	317.1	335.4	10.5	312.8	362.9	9.6	303.9	382.1	8.9	292.0	395.2	8.3	279.7	406.4	7.7
46.0	335.5	252.1	14.4	332.5	270.0	13.4	329.2	290.1	12.5	325.7	312.3	11.5	321.9	336.1	10.6	317.5	363.6	9.8	308.1	382.2	9.0	295.9	395.0	8.4	283.4	406.3	7.9
48.0	345.9	255.3	14.7	342.8	272.5	13.7	339.4	292.2	12.8	335.6	313.9	11.8	331.6	337.6	10.9	326.7	364.4	10.0	316.6	382.0	9.3	303.7	394.5	8.6	290.9	406.0	8.1
50.0	356.6	258.9	15.0	353.3	275.5	14.0	349.7	294.7	13.1	345.8	315.9	12.1	341.7	339.2	11.2	335.8	364.4	10.3	325.0	381.4	9.6	311.7	393.8	8.9	298.5	405.5	8.3
52.0	367.5	262.9	15.2	364.0	278.9	14.3	360.3	297.4	13.3	356.2	318.2	12.4	351.9	341.2	11.5	345.0	364.6	10.6	333.5	380.8	9.8	319.9	393.2	9.1	304.6	401.2	8.5
55.0	384.2	270.0	15.5	380.5	284.7	14.7	376.6	302.2	13.7	372.3	322.4	12.8	367.7	344.7	11.9	359.2	365.2	11.0	346.6	380.1	10.2	332.4	392.2	9.5	309.4	385.0	9.0

MODEL: YCIV0357E/V**E_IPLV = 12.2****V_IPLV = 15.3**

AIR TEMPERATURE ON - CONDENSER (°F)																											
LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	346.6	284.0	13.2	343.6	304.5	12.3	340.1	326.6	11.4	336.3	349.9	10.6	332.2	374.5	9.9	327.5	402.4	9.1	321.2	428.4	8.4	311.7	448.5	7.8	301.2	466.3	7.3
42.0	357.6	286.7	13.5	354.5	307.2	12.6	351.0	329.1	11.7	347.0	352.4	10.9	342.7	376.9	10.1	337.8	404.9	9.3	330.8	430.1	8.6	320.6	449.8	8.0	309.7	467.6	7.5
44.0	368.9	289.8	13.8	365.6	310.1	12.9	362.0	331.8	12.0	357.9	355.0	11.1	353.5	379.5	10.4	348.3	407.5	9.5	340.5	431.9	8.8	329.7	451.1	8.2	318.4	468.9	7.7
45.0	374.5	291.4	14.0	371.3	311.6	13.0	367.6	333.3	12.1	363.5	356.4	11.3	358.9	380.9	10.5	353.7	408.8	9.7	345.5	432.8	9.0	334.4	451.7	8.3	322.9	469.5	7.8
46.0	380.3	293.1	14.1	377.0	313.1	13.2	373.3	334.8	12.3	369.0	358.0	11.4	364.4	382.4	10.6	359.1	410.3	9.8	350.5	433.7	9.1	339.1	452.3	8.4	327.3	470.2	7.8
48.0	391.9	296.6	14.4	388.6	316.4	13.5	384.7	337.9	12.5	380.4	361.0	11.7	375.7	385.3	10.8	369.9	412.9	10.0	360.8	435.5	9.3	348.7	453.5	8.6	336.5	471.4	8.0
50.0	403.8	300.3	14.7	400.4	320.0	13.7	396.5	341.3	12.8	392.0	364.1	11.9	387.1	388.4	11.1	380.7	415.0	10.3	370.9	436.8	9.5	358.4	454.8	8.9	341.0	461.4	8.3
52.0	415.9	304.4	14.9	412.4	323.7	14.0	408.4	344.9	13.1	403.8	367.5	12.2	398.8	391.7	11.3	391.6	417.1	10.5	381.1	438.3	9.8	368.3	456.1	9.1	344.4	448.8	8.6
55.0	434.4	309.8	15.3	431.1	328.9	14.4	426.7	350.6	13.4	422.0	373.0	12.6	416.7	397.1	11.7	408.3	420.6	10.9	396.9	440.6	10.1	383.6	458.1	9.4	349.0	430.4	9.1

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 Kw)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98

Standard Efficiency Ratings – SI - 460V/60Hz

MODEL:YCIV0157S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	530.8	136.0	3.6	522.8	155.4	3.1	513.7	176.5	2.7	499.1	200.2	2.3	463.8	219.1	2.0	456.5	223.0	1.9
6.0	545.3	136.8	3.6	537.0	156.2	3.2	527.4	177.3	2.8	511.2	200.8	2.4	474.8	219.8	2.0	467.3	223.8	2.0
7.0	560.0	137.7	3.7	551.5	157.0	3.2	541.5	178.2	2.8	523.4	201.5	2.4	485.9	220.6	2.1	478.5	224.4	2.0
8.0	575.0	138.7	3.8	566.2	157.9	3.3	555.8	179.1	2.9	535.6	202.1	2.5	497.2	221.4	2.1	489.4	225.3	2.1
9.0	590.3	139.8	3.9	581.1	158.9	3.4	570.3	180.1	3.0	548.1	202.7	2.5	508.9	222.0	2.2	500.9	225.9	2.1
10.0	605.7	140.9	3.9	596.3	159.9	3.4	585.2	181.0	3.0	560.7	203.3	2.6	520.8	222.7	2.2	512.5	226.6	2.1
11.0	621.5	142.1	4.0	611.8	161.0	3.5	600.2	182.2	3.1	573.5	203.9	2.6	532.7	223.3	2.3	524.4	227.2	2.2
12.0	637.4	143.3	4.1	627.5	162.1	3.6	615.5	183.2	3.1	586.4	204.6	2.7	544.7	223.9	2.3	532.9	224.8	2.2
13.0	653.6	144.7	4.1	643.4	163.3	3.6	631.1	184.4	3.2	599.5	205.2	2.7	556.9	224.5	2.3	538.3	219.6	2.3

MODEL:YCIV0177S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	589.6	149.7	3.6	578.8	171.5	3.1	565.6	195.0	2.7	538.2	213.3	2.4	492.4	222.8	2.1	463.3	210.6	2.1
6.0	606.1	150.7	3.7	595.1	172.5	3.2	581.5	196.0	2.8	552.4	213.9	2.4	497.6	218.6	2.1	469.4	207.0	2.1
7.0	622.9	151.8	3.8	611.6	173.5	3.3	597.7	197.2	2.8	566.1	214.3	2.5	503.6	214.6	2.2	475.1	203.1	2.2
8.0	639.9	152.9	3.9	628.5	174.5	3.3	613.5	197.9	2.9	579.9	214.7	2.5	510.0	210.8	2.3	480.5	199.1	2.3
9.0	657.2	154.0	3.9	645.6	175.6	3.4	629.2	198.4	3.0	594.0	215.1	2.6	516.0	206.7	2.3	485.4	194.9	2.3
10.0	674.6	155.3	4.0	663.0	176.8	3.5	645.1	198.8	3.0	608.1	215.4	2.7	521.6	202.5	2.4	489.9	190.8	2.4
11.0	692.1	156.8	4.1	680.4	178.1	3.6	661.1	199.4	3.1	622.6	215.7	2.7	526.8	198.2	2.5	494.2	186.7	2.5
12.0	709.9	158.3	4.1	698.1	179.4	3.6	677.3	199.9	3.2	637.2	216.0	2.8	531.5	194.0	2.6	498.3	182.6	2.5
13.0	727.9	159.9	4.2	716.1	180.9	3.7	693.6	200.5	3.2	651.9	216.4	2.8	535.6	189.9	2.6	502.4	178.6	2.6

MODEL:YCIV0187S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	641.8	161.5	3.6	631.1	184.4	3.2	619.0	209.5	2.8	596.6	234.8	2.4	553.9	250.7	2.1	545.4	253.9	2.0
6.0	659.7	162.7	3.7	648.7	185.5	3.2	636.0	210.6	2.8	610.9	235.2	2.4	566.9	251.3	2.1	558.2	254.4	2.1
7.0	677.8	163.9	3.8	666.5	186.6	3.3	653.4	211.7	2.9	625.6	235.5	2.5	580.4	251.8	2.2	571.3	254.9	2.1
8.0	696.4	165.3	3.9	684.6	187.8	3.4	670.9	213.0	2.9	640.5	235.9	2.6	594.1	252.2	2.2	584.8	255.4	2.2
9.0	715.2	166.8	3.9	703.0	189.1	3.4	688.8	214.2	3.0	655.7	236.3	2.6	608.1	252.5	2.3	598.5	255.7	2.2
10.0	734.4	168.3	4.0	721.8	190.5	3.5	707.0	215.5	3.1	670.9	236.6	2.7	622.1	252.9	2.3	606.6	251.7	2.3
11.0	753.9	170.0	4.1	740.8	191.9	3.6	725.6	216.9	3.1	686.2	237.0	2.7	636.6	253.2	2.4	611.8	245.4	2.4
12.0	773.7	171.7	4.1	760.2	193.5	3.6	744.4	218.4	3.2	701.9	237.4	2.8	651.2	253.5	2.4	617.5	239.5	2.4
13.0	793.8	173.7	4.2	780.0	195.2	3.7	763.6	219.9	3.3	717.8	237.8	2.8	661.2	250.2	2.5	623.0	233.6	2.5

NOTES:

1. KW_o = Unit kW Cooling Capacity Output
2. KW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.15 l/s cooler water per ton, and 0.018 (m² – °C)/kW

MODEL:YCIV0207S/P**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	693.1	174.3	3.7	680.1	201.0	3.2	665.5	230.8	2.7	632.2	253.2	2.4	557.5	252.1	2.1	531.3	236.9	2.1
6.0	712.6	175.4	3.7	699.0	201.8	3.2	683.3	231.2	2.8	647.3	253.1	2.4	570.9	246.7	2.2	537.4	232.2	2.2
7.0	732.5	176.7	3.8	718.4	202.7	3.3	700.8	231.3	2.8	662.7	252.8	2.5	577.4	241.7	2.3	543.2	227.2	2.2
8.0	752.9	178.3	3.9	738.1	203.7	3.4	718.6	231.5	2.9	678.4	252.4	2.5	583.6	236.4	2.3	548.8	222.3	2.3
9.0	773.6	180.1	4.0	758.3	205.0	3.5	736.7	231.8	3.0	694.4	252.0	2.6	589.7	231.1	2.4	554.1	217.6	2.4
10.0	794.6	182.1	4.0	778.7	206.4	3.5	755.2	232.1	3.1	710.5	251.6	2.7	595.5	226.1	2.5	559.1	213.0	2.5
11.0	816.1	184.3	4.1	799.6	208.0	3.6	773.9	232.5	3.1	726.8	251.2	2.7	601.1	221.2	2.5	563.9	208.4	2.5
12.0	838.1	186.7	4.2	820.9	209.8	3.7	792.9	233.0	3.2	743.5	250.9	2.8	606.2	216.5	2.6	568.7	204.0	2.6
13.0	860.4	189.5	4.2	842.6	211.8	3.7	812.3	233.7	3.3	760.5	250.5	2.9	611.2	211.9	2.7	573.4	199.6	2.7

MODEL:YCIV0227S/P**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	752.2	186.5	3.7	738.8	212.9	3.2	723.6	242.0	2.8	693.5	268.4	2.4	643.3	281.4	2.2	633.5	283.7	2.1
6.0	773.4	188.0	3.8	759.5	214.2	3.3	743.6	243.3	2.9	710.2	268.5	2.5	658.6	281.7	2.2	648.3	284.1	2.2
7.0	795.1	189.5	3.9	780.6	215.6	3.4	763.9	244.8	2.9	727.2	268.6	2.6	674.1	281.9	2.3	663.6	284.3	2.2
8.0	817.1	191.3	3.9	802.1	217.0	3.4	784.7	246.2	3.0	744.5	268.7	2.6	690.0	282.0	2.3	679.1	284.4	2.3
9.0	839.7	193.2	4.0	824.0	218.7	3.5	805.9	247.7	3.1	762.0	268.7	2.7	706.0	282.1	2.4	692.1	282.7	2.3
10.0	862.6	195.2	4.1	846.3	220.4	3.6	827.6	249.2	3.1	779.7	268.8	2.7	722.5	282.1	2.4	698.4	276.5	2.4
11.0	886.0	197.3	4.1	869.1	222.3	3.6	849.6	251.0	3.2	797.8	268.9	2.8	739.2	282.1	2.5	704.8	270.1	2.5
12.0	909.5	199.6	4.2	892.3	224.2	3.7	872.1	252.8	3.2	816.2	269.0	2.9	753.8	280.5	2.5	710.7	263.3	2.5
13.0	933.5	202.1	4.3	915.7	226.3	3.8	895.1	254.7	3.3	834.8	269.1	2.9	760.7	273.7	2.6	717.4	256.8	2.6

MODEL:YCIV0247S/P**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	825.0	205.6	3.7	811.0	234.0	3.2	794.9	265.2	2.8	765.8	295.7	2.4	719.7	315.7	2.2	710.5	319.5	2.1
6.0	848.1	207.2	3.8	833.5	235.5	3.3	816.6	266.8	2.9	784.8	296.4	2.5	737.1	316.5	2.2	727.6	320.3	2.2
7.0	871.6	209.0	3.8	856.4	237.1	3.4	838.7	268.6	2.9	804.0	297.0	2.6	755.0	317.1	2.3	741.6	318.7	2.2
8.0	895.5	211.0	3.9	879.7	238.9	3.4	861.4	270.3	3.0	823.6	297.6	2.6	773.2	317.8	2.3	749.4	312.4	2.3
9.0	919.9	213.0	4.0	903.5	240.8	3.5	884.4	272.1	3.0	843.3	298.2	2.7	791.6	318.4	2.4	756.9	305.6	2.3
10.0	944.8	215.1	4.0	927.8	242.7	3.6	908.0	273.9	3.1	863.4	298.8	2.7	806.3	316.2	2.4	763.9	298.4	2.4
11.0	970.0	217.4	4.1	952.4	244.9	3.6	931.9	276.0	3.2	883.9	299.5	2.8	814.2	308.9	2.5	770.5	291.0	2.5
12.0	995.6	219.9	4.2	977.6	247.0	3.7	956.3	278.0	3.2	904.8	300.1	2.8	821.5	301.3	2.6	776.6	283.5	2.6
13.0	1021.7	221.9	4.3	1002.9	249.3	3.7	981.2	280.2	3.3	925.9	300.8	2.9	828.3	293.5	2.7	782.1	276.2	2.7

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.15 l/s cooler water per ton, and 0.018 (m² – °C)/kW

Standard Efficiency Ratings – SI - 460V/60Hz

MODEL:YCIV0267S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	898.1	224.4	3.7	883.4	254.8	3.2	866.4	288.2	2.8	838.4	322.8	2.4	796.3	349.6	2.2	787.8	354.9	2.1
6.0	923.0	226.2	3.8	907.7	256.6	3.3	889.9	290.2	2.9	859.6	323.9	2.5	816.0	350.8	2.2	807.2	356.2	2.1
7.0	948.4	228.2	3.8	932.5	258.5	3.4	913.9	292.1	2.9	881.1	325.0	2.6	836.1	352.0	2.3	823.0	354.5	2.2
8.0	974.1	230.3	3.9	957.7	260.5	3.4	938.4	294.1	3.0	902.9	326.1	2.6	856.7	353.2	2.3	830.7	346.5	2.3
9.0	1000.4	232.5	4.0	983.4	262.6	3.5	963.2	296.3	3.0	924.9	327.3	2.7	877.6	354.4	2.3	838.5	338.4	2.3
10.0	1027.2	234.8	4.0	1009.5	264.8	3.5	988.6	298.4	3.1	947.5	328.5	2.7	894.1	352.2	2.4	846.3	330.4	2.4
11.0	1054.4	237.3	4.1	1036.0	267.2	3.6	1014.5	300.6	3.2	970.4	329.6	2.8	902.4	343.6	2.5	854.0	322.4	2.5
12.0	1081.9	240.0	4.2	1063.1	269.6	3.7	1040.8	302.9	3.2	993.6	330.9	2.8	910.6	335.1	2.6	861.4	314.7	2.6
13.0	1110.1	241.5	4.2	1090.4	272.1	3.7	1067.6	305.4	3.3	1017.3	332.1	2.9	918.5	326.8	2.7	868.2	307.6	2.7

MODEL:YCIV0287S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	954.4	236.0	3.7	936.9	271.1	3.2	916.5	309.6	2.8	877.6	343.2	2.4	793.2	350.5	2.1	746.0	331.2	2.1
6.0	981.3	237.5	3.8	963.2	272.4	3.3	942.0	311.0	2.8	899.5	343.6	2.5	800.8	343.6	2.2	754.0	324.7	2.2
7.0	1008.7	239.2	3.9	990.1	273.8	3.4	967.5	312.0	2.9	921.4	343.8	2.5	809.9	337.1	2.3	763.4	318.9	2.2
8.0	1036.6	241.0	3.9	1017.4	275.2	3.4	992.9	312.7	3.0	943.6	344.0	2.6	820.0	330.9	2.3	772.1	312.5	2.3
9.0	1065.0	243.1	4.0	1045.3	276.9	3.5	1018.8	313.5	3.0	966.3	344.1	2.6	829.3	324.3	2.4	780.4	306.1	2.4
10.0	1093.8	245.4	4.1	1073.7	278.7	3.6	1045.2	314.4	3.1	989.4	344.2	2.7	838.5	317.7	2.5	787.8	299.7	2.5
11.0	1123.1	248.0	4.2	1102.5	280.7	3.6	1071.9	315.4	3.2	1012.6	344.3	2.8	847.0	311.1	2.5	794.9	293.5	2.5
12.0	1152.9	250.7	4.2	1131.8	282.9	3.7	1099.0	316.5	3.3	1036.2	344.4	2.8	855.1	304.7	2.6	801.6	287.2	2.6
13.0	1183.2	253.6	4.3	1161.7	285.3	3.8	1126.6	317.6	3.3	1060.1	344.5	2.9	862.0	298.3	2.7	808.3	281.1	2.7

MODEL:YCIV0307S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	1060.5	260.2	3.7	1041.2	300.1	3.2	1019.7	344.5	2.8	975.0	381.9	2.4	870.2	379.2	2.2	817.1	356.4	2.2
6.0	1090.3	262.0	3.8	1070.2	301.3	3.3	1046.9	345.3	2.8	998.2	381.7	2.5	878.4	371.1	2.2	826.0	349.2	2.2
7.0	1120.9	263.9	3.9	1099.9	302.6	3.4	1074.3	345.7	2.9	1022.0	381.3	2.5	888.4	363.6	2.3	835.5	342.1	2.3
8.0	1152.1	266.2	4.0	1130.1	304.1	3.5	1102.2	346.2	3.0	1046.2	380.8	2.6	897.9	355.6	2.4	844.5	334.7	2.4
9.0	1183.8	268.8	4.1	1161.0	305.9	3.5	1130.7	346.9	3.1	1070.9	380.2	2.7	907.5	347.9	2.4	853.1	327.6	2.4
10.0	1216.2	271.7	4.1	1192.5	307.9	3.6	1159.8	347.7	3.1	1095.9	379.6	2.7	916.7	340.3	2.5	860.8	320.7	2.5
11.0	1249.2	274.8	4.2	1224.5	310.3	3.7	1189.3	348.6	3.2	1121.1	379.1	2.8	925.4	333.0	2.6	868.4	313.9	2.6
12.0	1282.9	278.4	4.3	1257.3	312.9	3.7	1219.4	349.7	3.3	1147.0	378.5	2.9	933.7	326.0	2.7	875.7	307.2	2.7
13.0	1317.1	282.4	4.3	1290.6	315.7	3.8	1249.9	351.1	3.3	1173.3	378.0	2.9	941.3	319.2	2.8	883.0	300.7	2.7

NOTES:

1. KW_o = Unit kW Cooling Capacity Output
2. KW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.15 l/s cooler water per ton, and 0.018 (m² – °C)/kW

MODEL:YCIV0357S/P**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	1197.0	297.9	3.7	1176.3	339.5	3.2	1152.8	385.3	2.8	1110.2	429.5	2.4	1039.5	455.9	2.2	1025.5	460.9	2.1
6.0	1230.7	300.2	3.8	1209.2	341.6	3.3	1184.5	387.4	2.9	1137.3	430.2	2.5	1064.3	456.9	2.2	1049.7	461.9	2.2
7.0	1265.0	302.6	3.8	1242.6	343.9	3.4	1216.8	389.8	2.9	1165.0	430.9	2.5	1089.8	457.7	2.3	1074.7	462.8	2.2
8.0	1300.0	305.4	3.9	1276.7	346.4	3.4	1249.8	392.3	3.0	1193.1	431.5	2.6	1115.8	458.4	2.3	1087.6	455.1	2.3
9.0	1335.7	308.3	4.0	1311.6	348.9	3.5	1283.5	394.8	3.0	1221.8	432.2	2.7	1142.3	459.1	2.4	1099.0	446.1	2.3
10.0	1372.1	311.4	4.1	1347.0	351.7	3.6	1317.8	397.4	3.1	1250.7	432.9	2.7	1169.1	459.8	2.4	1109.6	436.2	2.4
11.0	1409.1	314.6	4.1	1383.1	354.6	3.6	1352.9	400.1	3.2	1280.3	433.5	2.8	1182.0	450.6	2.5	1119.3	425.5	2.5
12.0	1446.3	318.2	4.2	1419.9	357.8	3.7	1388.6	403.1	3.2	1310.4	434.2	2.8	1193.1	439.9	2.6	1128.3	414.4	2.6
13.0	1484.4	321.4	4.3	1456.9	361.0	3.8	1425.0	406.2	3.3	1340.9	434.9	2.9	1203.2	428.5	2.6	1136.4	403.3	2.6

MODEL:YCIV0397S/P**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	1343.1	335.5	3.7	1321.0	381.2	3.2	1295.4	431.2	2.8	1254.8	483.3	2.4	1192.2	523.5	2.2	1179.6	531.4	2.1
6.0	1380.7	338.2	3.8	1357.6	383.8	3.3	1330.9	434.0	2.9	1286.2	485.1	2.5	1221.4	525.5	2.2	1208.2	533.5	2.1
7.0	1419.0	341.1	3.8	1395.0	386.6	3.4	1367.0	437.0	2.9	1318.4	486.8	2.6	1251.4	527.3	2.2	1237.8	535.4	2.2
8.0	1458.1	344.2	3.9	1433.1	389.7	3.4	1403.9	439.9	3.0	1351.3	488.5	2.6	1282.0	529.1	2.3	1250.9	524.8	2.3
9.0	1497.8	347.6	4.0	1472.0	392.8	3.5	1441.5	443.2	3.0	1384.7	490.2	2.7	1313.2	530.8	2.3	1262.6	512.7	2.3
10.0	1538.4	351.0	4.0	1511.6	396.0	3.6	1479.9	446.4	3.1	1418.5	492.0	2.7	1344.9	532.7	2.4	1274.4	500.6	2.4
11.0	1579.6	354.7	4.1	1551.9	399.4	3.6	1519.1	449.7	3.2	1453.1	493.8	2.8	1358.8	520.8	2.5	1286.1	488.6	2.5
12.0	1620.2	358.5	4.2	1592.8	403.1	3.7	1559.0	453.1	3.2	1488.3	495.6	2.8	1371.2	508.0	2.6	1297.4	477.0	2.6
13.0	1662.5	360.8	4.3	1633.1	406.7	3.7	1599.6	456.7	3.3	1524.1	497.4	2.9	1383.3	495.4	2.6	1308.1	465.9	2.6

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.15 l/s cooler water per ton, and 0.018 (m² – °C)/kW

High Efficiency Ratings – SI - 460V/60Hz

MODEL:YCIV0157E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	527.1	125.7	3.8	517.8	142.0	3.3	505.5	159.6	2.9	490.0	180.2	2.5	451.1	196.7	2.2	443.3	200.1	2.1
6.0	542.0	126.7	3.9	532.6	143.2	3.4	520.3	160.8	3.0	503.0	181.1	2.6	462.9	197.4	2.2	454.9	200.9	2.1
7.0	557.0	127.7	4.0	547.7	144.3	3.5	535.2	162.0	3.1	516.0	182.0	2.6	475.0	198.2	2.2	466.7	201.6	2.2
8.0	572.2	128.8	4.0	563.0	145.5	3.5	550.4	163.2	3.1	529.3	182.9	2.7	487.0	199.2	2.3	478.7	202.4	2.2
9.0	587.6	129.9	4.1	578.6	146.6	3.6	565.9	164.4	3.2	542.6	183.8	2.8	499.2	200.1	2.3	490.5	203.4	2.3
10.0	603.1	130.9	4.2	594.3	147.8	3.7	581.5	165.8	3.2	556.1	184.8	2.8	511.8	201.0	2.4	503.0	204.3	2.3
11.0	618.9	132.0	4.3	610.2	149.0	3.8	597.4	167.1	3.3	569.7	185.7	2.9	524.6	201.9	2.4	515.5	205.2	2.4
12.0	634.8	133.1	4.3	626.4	150.2	3.8	613.5	168.4	3.4	583.4	186.7	2.9	537.5	202.8	2.5	528.3	206.1	2.4
13.0	650.9	134.2	4.4	642.7	151.5	3.9	629.9	169.8	3.4	597.3	187.7	3.0	550.6	203.7	2.5	541.2	207.0	2.5

MODEL:YCIV0177E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	561.0	131.9	3.8	552.5	150.2	3.3	542.5	170.5	2.9	527.1	193.7	2.5	494.1	213.9	2.2	486.2	217.8	2.1
6.0	576.9	132.9	3.9	568.1	151.1	3.4	557.6	171.3	3.0	540.8	194.4	2.6	505.9	214.6	2.2	498.0	218.4	2.1
7.0	593.0	133.9	4.0	583.9	152.0	3.5	573.0	172.2	3.1	554.8	195.0	2.6	518.3	215.1	2.3	510.0	219.0	2.2
8.0	609.4	135.1	4.1	600.0	152.9	3.6	588.7	173.1	3.1	569.0	195.7	2.7	530.8	215.7	2.3	522.3	219.6	2.2
9.0	626.1	136.3	4.1	616.5	154.0	3.7	604.7	174.1	3.2	583.5	196.4	2.8	543.5	216.2	2.4	534.8	220.2	2.3
10.0	643.1	137.6	4.2	633.2	155.1	3.7	621.1	175.1	3.3	598.3	197.2	2.8	556.5	216.8	2.4	546.5	219.8	2.3
11.0	660.4	139.0	4.3	650.2	156.3	3.8	637.7	176.2	3.3	613.3	198.0	2.9	569.7	217.3	2.5	552.4	214.9	2.4
12.0	678.1	140.5	4.4	667.6	157.6	3.9	654.7	177.3	3.4	628.6	198.8	2.9	583.1	217.9	2.5	558.1	210.0	2.5
13.0	696.0	142.1	4.4	685.2	159.0	3.9	672.0	178.5	3.5	644.1	199.6	3.0	596.6	218.4	2.6	563.6	205.3	2.6

MODEL:YCIV0187E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	623.4	146.4	3.8	614.0	167.5	3.3	602.4	190.9	2.9	585.1	216.1	2.5	549.2	232.7	2.2	540.6	235.6	2.1
6.0	640.9	147.4	3.9	631.3	168.3	3.4	619.4	191.6	3.0	600.4	216.4	2.6	562.9	233.1	2.3	554.1	236.1	2.2
7.0	658.7	148.5	4.0	648.9	169.1	3.5	636.6	192.4	3.0	616.1	216.7	2.6	576.8	233.4	2.3	567.8	236.4	2.2
8.0	676.6	149.6	4.1	666.7	170.1	3.6	654.2	193.3	3.1	632.0	217.0	2.7	591.0	233.7	2.4	581.8	236.7	2.3
9.0	694.9	150.9	4.1	684.8	171.1	3.6	671.9	194.2	3.2	648.3	217.3	2.8	605.5	233.9	2.4	596.0	237.0	2.4
10.0	713.4	152.3	4.2	703.1	172.2	3.7	690.0	195.2	3.3	664.8	217.7	2.8	620.2	234.1	2.5	610.4	237.2	2.4
11.0	732.2	153.7	4.3	721.7	173.5	3.8	708.3	196.2	3.3	681.4	218.0	2.9	635.0	234.3	2.5	625.1	237.4	2.5
12.0	751.3	155.3	4.4	740.7	174.8	3.9	727.0	197.4	3.4	698.3	218.4	3.0	650.2	234.5	2.6	633.7	233.4	2.5
13.0	770.6	157.1	4.4	759.9	176.2	3.9	745.9	198.7	3.5	715.5	218.8	3.0	665.6	234.6	2.7	639.4	227.8	2.6

NOTES:

1. KW_o = Unit kW Cooling Capacity Output
2. KW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.15 l/s cooler water per ton, and 0.018 (m² – °C)/kW

MODEL:YCIV0197E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	675.6	158.4	3.9	664.4	182.6	3.3	651.5	210.4	2.9	634.0	241.4	2.5	588.6	254.9	2.2	579.6	257.2	2.1
6.0	694.6	159.5	3.9	683.0	183.1	3.4	669.6	210.7	2.9	649.6	241.0	2.5	603.0	254.8	2.2	593.6	257.3	2.2
7.0	714.1	160.7	4.0	702.0	183.8	3.5	688.0	211.1	3.0	665.3	240.6	2.6	617.6	254.6	2.3	608.0	257.2	2.2
8.0	733.9	162.2	4.1	721.3	184.7	3.6	706.8	211.7	3.1	681.5	240.0	2.7	632.4	254.4	2.3	622.7	256.9	2.3
9.0	754.1	163.9	4.2	741.1	185.7	3.7	726.0	212.3	3.2	697.9	239.5	2.7	647.7	254.0	2.4	637.5	256.6	2.3
10.0	774.6	165.9	4.2	761.2	186.9	3.7	745.5	213.1	3.2	714.6	239.0	2.8	663.1	253.5	2.5	652.8	256.2	2.4
11.0	795.6	168.1	4.3	781.7	188.3	3.8	765.5	214.0	3.3	731.5	238.5	2.9	678.8	253.0	2.5	668.2	255.7	2.5
12.0	816.9	170.6	4.4	802.5	190.1	3.9	785.8	215.1	3.4	748.7	238.0	2.9	694.6	252.5	2.6	683.9	255.2	2.5
13.0	838.5	173.4	4.4	823.7	191.9	4.0	806.5	216.4	3.5	765.9	237.7	3.0	710.7	251.9	2.6	699.7	254.7	2.6

MODEL:YCIV0207E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	718.2	166.7	3.9	706.8	191.3	3.4	693.9	219.3	2.9	675.0	250.0	2.5	632.9	267.0	2.2	623.4	269.5	2.2
6.0	738.5	167.9	4.0	726.6	192.0	3.5	713.1	219.9	3.0	692.4	250.2	2.6	648.1	267.0	2.3	638.4	269.5	2.2
7.0	759.2	169.2	4.0	746.8	192.9	3.5	732.7	220.5	3.1	710.1	250.3	2.6	663.8	266.8	2.3	653.8	269.5	2.3
8.0	780.3	170.8	4.1	767.4	193.9	3.6	752.7	221.3	3.1	728.2	250.4	2.7	679.7	266.6	2.4	669.4	269.3	2.3
9.0	801.8	172.6	4.2	788.5	195.0	3.7	773.1	222.1	3.2	746.7	250.5	2.8	695.8	266.3	2.4	685.3	269.0	2.4
10.0	823.7	174.5	4.3	809.9	196.4	3.8	793.9	223.0	3.3	765.5	250.6	2.8	712.3	265.9	2.5	701.5	268.7	2.4
11.0	846.0	176.7	4.3	831.6	198.0	3.8	815.1	224.1	3.4	784.3	250.7	2.9	728.9	265.5	2.6	718.0	268.3	2.5
12.0	868.2	179.1	4.4	853.7	199.7	3.9	836.7	225.4	3.4	802.6	250.5	3.0	746.0	265.1	2.6	725.0	261.8	2.6
13.0	890.8	181.8	4.5	875.8	201.6	4.0	858.4	226.9	3.5	821.2	250.2	3.1	763.2	264.7	2.7	731.2	255.0	2.7

MODEL:YCIV0227E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	746.1	172.7	3.9	734.9	196.8	3.4	721.8	224.0	3.0	705.9	256.0	2.6	664.2	274.4	2.3	654.5	277.0	2.2
6.0	767.2	173.9	4.0	755.5	197.9	3.5	741.9	224.9	3.0	725.2	257.0	2.6	680.5	274.4	2.3	670.4	277.1	2.3
7.0	788.7	175.4	4.0	776.6	199.0	3.5	762.4	225.9	3.1	744.9	258.1	2.7	696.9	274.5	2.4	686.7	277.2	2.3
8.0	810.6	176.9	4.1	798.1	200.2	3.6	783.3	227.0	3.2	765.1	259.1	2.7	713.7	274.5	2.4	703.2	277.2	2.4
9.0	833.0	178.6	4.2	820.0	201.5	3.7	804.6	228.1	3.2	785.3	260.0	2.8	730.9	274.4	2.5	720.0	277.1	2.4
10.0	855.3	180.4	4.3	842.2	203.0	3.8	826.4	229.3	3.3	804.2	260.0	2.9	748.4	274.3	2.5	737.2	277.1	2.5
11.0	877.9	182.4	4.3	864.4	204.6	3.9	848.4	230.6	3.4	823.1	260.1	2.9	766.1	274.2	2.6	754.6	277.0	2.5
12.0	900.9	184.5	4.4	887.0	206.2	3.9	870.4	232.1	3.5	842.6	260.1	3.0	784.0	274.2	2.7	772.4	276.8	2.6
13.0	924.2	186.8	4.5	909.9	208.1	4.0	892.9	233.6	3.5	861.9	260.2	3.1	802.3	274.1	2.7	790.3	276.8	2.7

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 kW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

High Efficiency Ratings – SI - 460V/60Hz

MODEL:YCIV0247E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	828.3	199.0	3.8	815.0	226.2	3.3	799.5	256.6	2.9	777.0	289.8	2.5	733.7	312.2	2.2	724.3	316.2	2.2
6.0	851.5	200.6	3.9	837.7	227.7	3.4	821.5	258.0	3.0	797.5	290.9	2.6	751.7	312.9	2.3	742.1	316.9	2.2
7.0	875.2	202.4	3.9	860.9	229.2	3.5	844.0	259.5	3.0	818.3	292.0	2.6	770.1	313.5	2.3	756.5	315.1	2.3
8.0	899.4	204.3	4.0	884.5	230.9	3.5	867.0	261.1	3.1	839.6	293.1	2.7	789.0	314.1	2.4	764.6	308.6	2.3
9.0	924.0	206.3	4.1	908.5	232.7	3.6	890.3	262.7	3.2	860.3	293.9	2.7	808.2	314.6	2.4	772.2	301.7	2.4
10.0	949.1	208.5	4.2	933.1	234.6	3.7	914.2	264.5	3.2	881.2	294.5	2.8	823.3	312.2	2.5	779.4	294.4	2.5
11.0	974.5	210.8	4.2	958.0	236.7	3.7	938.5	266.3	3.3	902.3	295.1	2.9	831.3	304.8	2.6	786.1	287.0	2.6
12.0	1000.3	213.3	4.3	983.4	238.8	3.8	963.3	268.3	3.3	923.9	295.7	2.9	838.8	297.0	2.6	792.4	279.5	2.6
13.0	1026.6	215.3	4.4	1009.0	241.1	3.9	988.4	270.3	3.4	945.7	296.4	3.0	845.6	289.2	2.7	798.0	272.6	2.7

MODEL:YCIV0267E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	940.7	218.9	3.9	924.4	251.2	3.4	904.8	287.4	2.9	879.7	328.6	2.5	814.9	350.0	2.2	801.9	353.9	2.1
6.0	967.4	220.4	4.0	950.7	252.2	3.5	930.4	288.3	3.0	902.6	328.8	2.6	835.2	350.4	2.2	821.7	354.4	2.2
7.0	994.6	222.1	4.1	977.5	253.4	3.5	956.6	289.3	3.1	925.6	328.9	2.6	855.8	350.7	2.3	842.0	354.8	2.2
8.0	1022.3	223.9	4.1	1004.8	254.8	3.6	983.3	290.3	3.1	948.4	328.9	2.7	876.8	350.9	2.3	862.7	355.1	2.3
9.0	1050.5	226.0	4.2	1032.6	256.3	3.7	1010.5	291.5	3.2	971.8	328.9	2.8	898.2	351.0	2.4	883.6	355.2	2.3
10.0	1079.0	228.4	4.3	1060.9	258.0	3.8	1038.2	293.0	3.3	995.5	328.8	2.8	920.0	351.1	2.5	905.0	355.3	2.4
11.0	1108.1	231.0	4.4	1089.7	259.9	3.9	1066.5	294.5	3.4	1019.6	328.8	2.9	942.3	351.1	2.5	926.8	355.4	2.5
12.0	1137.7	233.9	4.4	1119.0	262.1	3.9	1095.2	296.1	3.4	1044.0	328.8	3.0	964.9	351.0	2.6	949.1	355.3	2.5
13.0	1167.7	237.0	4.5	1148.7	264.4	4.0	1124.5	298.0	3.5	1068.4	329.0	3.0	987.7	351.0	2.6	971.7	355.3	2.6

MODEL:YCIV0287E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	1001.1	230.1	3.9	984.0	265.1	3.4	964.1	304.9	2.9	940.0	351.6	2.5	872.8	371.8	2.2	859.2	375.2	2.2
6.0	1029.6	231.6	4.0	1011.9	265.9	3.5	991.2	305.6	3.0	964.6	351.7	2.6	894.2	371.8	2.3	880.2	375.4	2.2
7.0	1058.6	233.4	4.1	1040.4	266.9	3.6	1018.8	306.3	3.1	988.5	351.1	2.6	916.0	371.7	2.3	901.6	375.3	2.3
8.0	1088.2	235.5	4.2	1069.4	268.2	3.7	1047.0	307.0	3.2	1012.6	350.5	2.7	938.3	371.3	2.4	923.5	375.1	2.3
9.0	1118.3	237.9	4.3	1099.0	269.6	3.7	1075.9	307.9	3.2	1037.5	349.7	2.8	960.9	370.8	2.4	945.9	374.7	2.4
10.0	1149.0	240.7	4.3	1129.2	271.3	3.8	1105.3	309.2	3.3	1062.7	349.0	2.8	984.1	370.2	2.5	968.4	374.2	2.4
11.0	1180.1	243.9	4.4	1159.9	273.3	3.9	1135.3	310.5	3.4	1088.2	348.4	2.9	1007.7	369.5	2.6	991.7	373.5	2.5
12.0	1212.1	247.5	4.4	1191.2	275.8	4.0	1165.9	312.0	3.5	1114.2	347.8	3.0	1031.8	368.8	2.6	1015.3	372.8	2.6
13.0	1244.5	251.4	4.5	1223.0	278.5	4.0	1197.1	313.8	3.5	1140.4	347.3	3.1	1056.2	368.1	2.7	1039.4	372.1	2.6

NOTES:

1. KW_o = Unit kW Cooling Capacity Output
2. KW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.15 l/s cooler water per ton, and 0.018 (m² – °C)/kW

MODEL:YCIV0327E/V**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	1088.2	253.3	3.9	1070.0	290.7	3.4	1049.4	333.3	2.9	1017.6	378.6	2.5	949.6	402.1	2.2	935.1	405.8	2.2
6.0	1119.2	255.1	4.0	1100.1	291.8	3.5	1078.5	334.2	3.0	1043.2	378.7	2.6	972.3	402.2	2.3	957.5	406.0	2.2
7.0	1150.8	257.1	4.1	1130.9	293.2	3.5	1108.3	335.1	3.1	1069.5	378.6	2.6	995.6	402.1	2.3	980.3	406.0	2.3
8.0	1183.0	259.5	4.1	1162.4	294.7	3.6	1138.6	336.4	3.1	1096.4	378.6	2.7	1019.4	401.8	2.4	1003.5	405.8	2.3
9.0	1215.9	262.2	4.2	1194.4	296.6	3.7	1169.7	337.7	3.2	1123.7	378.5	2.8	1043.6	401.4	2.4	1027.4	405.5	2.4
10.0	1249.4	265.2	4.3	1227.1	298.7	3.8	1201.5	339.2	3.3	1151.6	378.5	2.8	1068.3	400.9	2.5	1051.6	405.0	2.4
11.0	1283.6	268.6	4.3	1260.4	301.1	3.8	1233.9	341.0	3.4	1179.4	378.3	2.9	1093.3	400.4	2.6	1076.4	404.5	2.5
12.0	1318.5	272.3	4.4	1294.4	303.8	3.9	1266.8	343.0	3.4	1207.0	377.9	3.0	1119.0	399.8	2.6	1087.7	395.4	2.6
13.0	1353.8	276.4	4.5	1329.1	306.7	4.0	1300.4	345.2	3.5	1235.1	377.6	3.1	1144.9	399.1	2.7	1096.9	385.2	2.7

MODEL:YCIV0357E/V**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP	KW _o	KW _i	COP
5.0	1234.1	293.3	3.8	1212.4	332.4	3.3	1186.6	375.7	2.9	1151.9	424.6	2.5	1089.0	459.9	2.2	1075.4	466.3	2.2
6.0	1269.1	295.9	3.9	1246.9	334.7	3.4	1220.2	377.9	3.0	1182.6	426.2	2.6	1116.8	461.0	2.3	1102.7	467.4	2.2
7.0	1304.7	298.6	4.0	1282.0	337.2	3.5	1254.5	380.3	3.1	1214.1	427.8	2.7	1145.1	462.2	2.3	1130.7	468.5	2.3
8.0	1341.0	301.5	4.0	1317.7	339.9	3.6	1289.3	383.0	3.1	1246.2	429.4	2.7	1174.2	463.3	2.4	1159.1	469.7	2.3
9.0	1377.9	304.7	4.1	1354.1	342.7	3.6	1325.0	385.6	3.2	1278.9	431.1	2.8	1203.7	464.4	2.4	1188.4	470.8	2.4
10.0	1415.4	308.0	4.2	1391.2	345.7	3.7	1361.2	388.4	3.3	1312.0	432.9	2.8	1234.0	465.5	2.5	1207.1	464.6	2.4
11.0	1453.6	311.5	4.3	1428.9	348.9	3.8	1398.1	391.4	3.3	1345.4	434.6	2.9	1264.5	466.7	2.5	1218.0	453.2	2.5
12.0	1492.3	315.3	4.3	1467.2	352.3	3.8	1435.7	394.5	3.4	1378.7	436.0	3.0	1295.8	467.8	2.6	1228.2	441.9	2.6
13.0	1531.8	318.0	4.4	1506.1	355.8	3.9	1473.9	397.8	3.4	1412.4	437.4	3.0	1310.2	457.9	2.7	1237.8	431.0	2.7

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.15 l/s cooler water per ton, and 0.018 (m² – °C)/kW

Standard Efficiency Ratings – SI - 400V/50Hz

MODEL: YCIV0600S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	528.8	133.1	3.6	520.9	152.2	3.2	511.8	172.8	2.8	497.4	196.1	2.4	462.2	214.6	2.0	455.0	218.5	2.0
6.0	543.2	134.0	3.7	535.0	152.9	3.2	525.5	173.7	2.8	509.5	196.7	2.4	473.3	215.3	2.1	465.8	219.2	2.0
7.0	557.9	134.9	3.8	549.4	153.8	3.3	539.5	174.5	2.9	521.7	197.3	2.5	484.5	216.0	2.1	476.8	219.9	2.0
8.0	572.9	135.8	3.8	564.1	154.6	3.4	553.7	175.4	2.9	533.9	197.9	2.5	495.5	216.9	2.2	487.9	220.6	2.1
9.0	588.0	136.8	3.9	578.9	155.6	3.4	568.2	176.3	3.0	546.3	198.5	2.6	507.2	217.5	2.2	499.2	221.3	2.1
10.0	603.4	137.9	4.0	594.1	156.6	3.5	583.0	177.3	3.1	558.9	199.1	2.6	519.0	218.1	2.2	510.8	222.0	2.2
11.0	619.1	139.1	4.1	609.5	157.6	3.6	598.0	178.4	3.1	571.6	199.7	2.7	531.0	218.7	2.3	522.6	222.6	2.2
12.0	635.0	140.3	4.1	625.1	158.7	3.6	613.2	179.4	3.2	584.5	200.3	2.7	542.9	219.3	2.3	532.1	221.1	2.3
13.0	651.2	141.6	4.2	641.0	159.8	3.7	628.7	180.5	3.2	597.5	201.0	2.8	555.1	219.9	2.4	537.5	215.9	2.3

MODEL: YCIV0650S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	587.3	146.6	3.7	576.4	167.9	3.2	563.2	190.9	2.8	536.0	208.9	2.4	491.4	218.9	2.1	462.3	206.9	2.1
6.0	603.7	147.6	3.8	592.6	168.9	3.3	579.1	192.0	2.8	550.1	209.5	2.5	496.5	214.8	2.2	467.9	203.3	2.2
7.0	620.4	148.6	3.8	609.2	169.9	3.3	595.2	193.1	2.9	563.9	210.0	2.5	502.4	210.9	2.2	474.0	199.7	2.2
8.0	637.4	149.7	3.9	626.0	170.9	3.4	611.2	193.9	3.0	577.7	210.4	2.6	508.8	207.2	2.3	479.4	195.7	2.3
9.0	654.7	150.8	4.0	643.0	171.9	3.5	626.8	194.3	3.0	591.8	210.7	2.6	514.8	203.2	2.4	484.4	191.6	2.4
10.0	672.0	152.0	4.1	660.4	173.1	3.5	642.6	194.8	3.1	605.9	211.0	2.7	520.5	199.0	2.5	488.9	187.6	2.4
11.0	689.4	153.4	4.1	677.8	174.4	3.6	658.6	195.3	3.2	620.3	211.4	2.8	525.7	194.9	2.5	493.2	183.6	2.5
12.0	707.1	154.9	4.2	695.4	175.6	3.7	674.7	195.8	3.2	634.8	211.7	2.8	530.6	190.8	2.6	497.4	179.6	2.6
13.0	725.1	156.4	4.3	713.3	177.0	3.7	691.0	196.4	3.3	649.5	212.0	2.9	534.7	186.7	2.7	501.5	175.7	2.7

MODEL: YCIV0720S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	639.4	158.1	3.7	628.8	180.6	3.2	616.7	205.2	2.8	594.6	230.0	2.4	551.9	245.6	2.1	543.3	248.7	2.1
6.0	657.2	159.2	3.8	646.3	181.6	3.3	633.7	206.2	2.9	608.9	230.4	2.5	564.8	246.2	2.2	556.2	249.2	2.1
7.0	675.3	160.5	3.9	664.0	182.7	3.4	651.0	207.3	2.9	623.5	230.8	2.5	578.2	246.7	2.2	569.2	249.7	2.2
8.0	693.7	161.8	3.9	682.0	183.9	3.4	668.4	208.5	3.0	638.4	231.1	2.6	591.9	247.1	2.3	582.6	250.2	2.2
9.0	712.5	163.2	4.0	700.4	185.1	3.5	686.2	209.8	3.1	653.5	231.5	2.7	605.8	247.4	2.3	596.2	250.6	2.2
10.0	731.6	164.7	4.1	719.0	186.5	3.6	704.3	211.0	3.1	668.7	231.8	2.7	619.9	247.8	2.4	605.6	247.6	2.3
11.0	751.0	166.3	4.1	738.0	187.9	3.6	722.8	212.3	3.2	683.9	232.2	2.8	634.3	248.1	2.4	610.8	241.4	2.4
12.0	770.7	168.0	4.2	757.3	189.4	3.7	741.6	213.7	3.2	699.5	232.6	2.8	648.9	248.4	2.5	616.4	235.6	2.5
13.0	790.7	169.9	4.3	776.9	191.0	3.8	760.7	215.3	3.3	715.3	233.0	2.9	660.2	246.2	2.5	621.8	229.7	2.5

NOTES:

1. kWo = Unit kW Cooling Capacity Output
2. KWi = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW
6. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

MODEL: YCIV0770S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	689.5	170.6	3.7	676.6	196.8	3.2	662.1	226.0	2.8	629.2	248.2	2.4	564.5	248.2	2.1	530.0	233.3	2.1
6.0	709.0	171.7	3.8	695.5	197.6	3.3	680.0	226.6	2.8	644.2	248.0	2.5	569.7	242.9	2.2	536.2	228.8	2.2
7.0	728.8	173.0	3.9	714.8	198.5	3.4	697.4	226.7	2.9	659.6	247.8	2.5	576.2	238.0	2.3	542.0	223.9	2.3
8.0	749.1	174.4	4.0	734.4	199.5	3.4	715.2	226.8	3.0	675.3	247.4	2.6	582.3	232.8	2.4	547.6	219.0	2.3
9.0	769.7	176.1	4.0	754.5	200.6	3.5	733.3	227.1	3.0	691.2	247.0	2.6	588.4	227.7	2.4	553.1	214.3	2.4
10.0	790.7	178.1	4.1	774.9	202.0	3.6	751.7	227.4	3.1	707.2	246.7	2.7	594.3	222.6	2.5	558.1	209.8	2.5
11.0	812.1	180.2	4.2	795.7	203.6	3.6	770.3	227.8	3.2	723.6	246.3	2.8	599.9	217.8	2.6	563.0	205.4	2.6
12.0	834.0	182.6	4.2	816.9	205.3	3.7	789.3	228.2	3.2	740.2	245.9	2.8	605.2	213.2	2.7	567.7	200.9	2.6
13.0	856.2	185.1	4.3	838.5	207.2	3.8	808.6	228.9	3.3	757.1	245.6	2.9	610.1	208.7	2.7	572.5	196.6	2.7

MODEL: YCIV0840S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	748.4	182.6	3.8	735.1	208.5	3.3	720.1	236.9	2.8	690.4	263.0	2.5	640.3	275.7	2.2	630.5	278.0	2.1
6.0	769.6	184.0	3.8	755.7	209.7	3.3	739.9	238.2	2.9	707.1	263.1	2.5	655.5	276.0	2.2	645.2	278.3	2.2
7.0	791.1	185.5	3.9	776.7	211.0	3.4	760.1	239.6	3.0	724.0	263.2	2.6	671.0	276.2	2.3	660.4	278.6	2.2
8.0	813.1	187.2	4.0	798.1	212.4	3.5	780.9	241.0	3.0	741.2	263.3	2.7	686.8	276.3	2.3	676.0	278.7	2.3
9.0	835.5	189.0	4.1	819.9	214.1	3.6	802.0	242.4	3.1	758.8	263.3	2.7	702.9	276.4	2.4	690.9	278.2	2.3
10.0	858.4	190.9	4.1	842.2	215.7	3.6	823.6	244.0	3.2	776.3	263.4	2.8	719.2	276.5	2.5	697.1	272.2	2.4
11.0	881.7	193.0	4.2	864.9	217.5	3.7	845.6	245.6	3.2	794.4	263.5	2.8	735.9	276.4	2.5	703.5	266.0	2.5
12.0	905.3	195.2	4.3	888.1	219.4	3.8	867.9	247.4	3.3	812.7	263.6	2.9	752.5	276.2	2.6	710.1	259.7	2.6
13.0	929.1	197.6	4.3	911.5	221.4	3.8	890.8	249.3	3.4	831.3	263.7	3.0	759.3	269.5	2.7	716.0	253.0	2.7

MODEL: YCIV0920S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	821.2	201.2	3.7	807.2	229.1	3.3	791.2	259.7	2.8	762.5	289.7	2.5	716.5	309.3	2.2	707.4	313.0	2.1
6.0	844.2	202.8	3.8	829.7	230.5	3.3	812.9	261.2	2.9	781.4	290.3	2.5	733.9	310.0	2.2	724.3	313.8	2.2
7.0	867.7	204.5	3.9	852.5	232.1	3.4	834.9	262.9	3.0	800.6	290.9	2.6	751.6	310.7	2.3	740.0	313.3	2.2
8.0	891.5	206.4	4.0	875.8	233.9	3.5	857.5	264.6	3.0	820.1	291.5	2.7	769.8	311.3	2.3	747.8	307.2	2.3
9.0	915.8	208.4	4.0	899.5	235.7	3.5	880.5	266.3	3.1	839.9	292.1	2.7	788.2	311.9	2.4	755.3	300.7	2.4
10.0	940.5	210.4	4.1	923.7	237.6	3.6	904.0	268.2	3.2	859.8	292.8	2.8	804.7	311.1	2.4	762.4	293.8	2.4
11.0	965.7	212.7	4.2	948.2	239.6	3.7	927.8	270.0	3.2	880.3	293.4	2.8	812.6	304.1	2.5	769.0	286.5	2.5
12.0	991.2	215.1	4.2	973.3	241.7	3.7	952.1	272.1	3.3	901.1	294.0	2.9	820.0	296.6	2.6	775.2	279.1	2.6
13.0	1017.2	217.0	4.3	998.6	243.9	3.8	976.9	274.2	3.3	922.2	294.7	2.9	826.9	289.0	2.7	780.9	272.0	2.7

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW
6. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

Standard Efficiency Ratings – SI - 400V/50Hz

MODEL: YCIV1000S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	894.3	219.6	3.7	879.6	249.4	3.3	862.6	282.2	2.9	834.9	316.1	2.5	793.0	342.4	2.2	784.6	347.5	2.1
6.0	919.1	221.4	3.8	903.8	251.2	3.3	886.1	284.0	2.9	856.0	317.2	2.5	812.6	343.6	2.2	803.8	348.8	2.2
7.0	944.5	223.3	3.9	928.6	253.0	3.4	909.9	286.0	3.0	877.4	318.3	2.6	832.6	344.8	2.3	821.7	348.8	2.2
8.0	970.2	225.4	4.0	953.7	255.0	3.5	934.4	287.9	3.0	899.1	319.4	2.7	853.0	345.9	2.3	829.3	341.0	2.3
9.0	996.3	227.5	4.0	979.4	257.0	3.5	959.2	290.0	3.1	921.3	320.5	2.7	873.9	347.1	2.4	837.1	333.1	2.4
10.0	1023.0	229.8	4.1	1005.4	259.2	3.6	984.6	292.1	3.2	943.6	321.7	2.8	892.6	346.7	2.4	844.9	325.2	2.5
11.0	1050.0	232.2	4.2	1031.8	261.5	3.7	1010.4	294.2	3.2	966.5	322.9	2.8	900.9	338.2	2.5	852.6	317.4	2.5
12.0	1077.5	234.8	4.2	1058.8	263.8	3.7	1036.6	296.5	3.3	989.7	324.0	2.9	909.1	329.9	2.6	860.1	309.8	2.6
13.0	1105.6	236.2	4.3	1086.0	266.3	3.8	1063.2	298.9	3.3	1013.3	325.3	2.9	917.1	321.7	2.7	867.0	302.7	2.7

MODEL: YCIV1070S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	949.5	231.0	3.8	932.1	265.4	3.2	911.8	303.1	2.8	873.5	336.2	2.4	791.6	344.8	2.2	743.1	325.2	2.1
6.0	976.3	232.5	3.8	958.3	266.7	3.3	937.2	304.4	2.9	895.5	336.6	2.5	799.7	338.3	2.2	752.1	319.4	2.2
7.0	1003.6	234.1	3.9	985.0	268.0	3.4	962.8	305.6	2.9	917.2	336.9	2.6	808.0	331.5	2.3	761.5	313.7	2.3
8.0	1031.4	235.8	4.0	1012.3	269.5	3.5	988.1	306.3	3.0	939.4	337.1	2.6	818.0	325.4	2.4	770.3	307.5	2.3
9.0	1059.7	237.8	4.1	1040.1	271.0	3.6	1013.9	307.0	3.1	962.0	337.2	2.7	827.4	319.0	2.4	778.7	301.3	2.4
10.0	1088.5	240.0	4.2	1068.4	272.8	3.6	1040.2	307.9	3.2	985.0	337.2	2.7	836.6	312.5	2.5	786.4	295.0	2.5
11.0	1117.8	242.5	4.2	1097.2	274.7	3.7	1066.9	308.9	3.2	1008.2	337.3	2.8	845.3	306.1	2.6	793.4	288.8	2.6
12.0	1147.6	245.2	4.3	1126.5	276.9	3.8	1094.0	309.9	3.3	1031.7	337.4	2.9	853.4	299.8	2.7	800.2	282.7	2.6
13.0	1177.9	248.0	4.4	1156.3	279.2	3.8	1121.6	311.1	3.4	1055.6	337.6	2.9	860.6	293.5	2.7	806.8	276.6	2.7

MODEL: YCIV1180S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1055.2	254.8	3.8	1036.1	294.0	3.3	1014.7	337.5	2.8	970.6	374.3	2.4	868.6	373.3	2.2	815.4	351.0	2.2
6.0	1084.9	256.5	3.9	1064.9	295.1	3.3	1042.0	338.3	2.9	993.7	374.1	2.5	876.5	365.3	2.3	824.1	343.8	2.2
7.0	1115.3	258.3	4.0	1094.4	296.3	3.4	1069.2	338.7	3.0	1017.4	373.7	2.6	885.7	357.6	2.3	833.7	336.9	2.3
8.0	1146.3	260.4	4.0	1124.5	297.7	3.5	1097.1	339.2	3.0	1041.6	373.3	2.6	896.0	350.3	2.4	842.6	329.7	2.4
9.0	1178.0	262.8	4.1	1155.3	299.4	3.6	1125.4	339.9	3.1	1066.2	372.7	2.7	905.5	342.6	2.5	851.2	322.6	2.5
10.0	1210.2	265.6	4.2	1186.6	301.4	3.7	1154.3	340.6	3.2	1091.1	372.1	2.8	914.9	335.1	2.6	859.2	315.8	2.5
11.0	1243.0	268.7	4.3	1218.5	303.7	3.7	1183.7	341.5	3.2	1116.3	371.6	2.8	923.7	327.9	2.6	866.8	309.2	2.6
12.0	1276.6	272.1	4.3	1251.1	306.1	3.8	1213.7	342.5	3.3	1142.1	371.0	2.9	932.2	321.0	2.7	874.2	302.6	2.7
13.0	1310.6	276.0	4.4	1284.3	308.9	3.9	1244.1	343.9	3.4	1168.3	370.5	3.0	939.9	314.3	2.8	881.4	296.1	2.8

NOTES:

1. kWo = Unit kW Cooling Capacity Output
2. KWi = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW
6. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

MODEL: YCIV1340S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1191.3	291.5	3.7	1170.8	332.4	3.3	1147.5	377.2	2.8	1105.5	420.8	2.5	1034.8	446.6	2.2	1020.8	451.5	2.1
6.0	1224.9	293.8	3.8	1203.5	334.4	3.3	1179.0	379.3	2.9	1132.5	421.5	2.5	1059.6	447.6	2.2	1045.0	452.5	2.2
7.0	1259.1	296.1	3.9	1236.8	336.6	3.4	1211.2	381.6	3.0	1160.1	422.2	2.6	1085.1	448.4	2.3	1070.0	453.4	2.2
8.0	1294.0	298.7	4.0	1270.8	339.0	3.5	1244.0	384.0	3.0	1188.2	422.8	2.6	1111.1	449.1	2.3	1085.2	447.5	2.3
9.0	1329.5	301.6	4.1	1305.4	341.5	3.5	1277.5	386.5	3.1	1216.8	423.4	2.7	1137.4	449.8	2.4	1096.7	438.8	2.4
10.0	1365.7	304.6	4.1	1340.7	344.2	3.6	1311.7	389.0	3.2	1245.7	424.1	2.8	1164.1	450.5	2.4	1107.5	429.2	2.4
11.0	1402.6	307.8	4.2	1376.7	347.0	3.7	1346.7	391.6	3.2	1275.0	424.8	2.8	1179.6	443.2	2.5	1117.3	418.9	2.5
12.0	1439.8	311.3	4.3	1413.4	350.1	3.8	1382.2	394.5	3.3	1305.0	425.4	2.9	1190.8	432.9	2.6	1126.4	408.1	2.6
13.0	1477.6	314.5	4.3	1450.3	353.2	3.8	1418.5	397.5	3.3	1335.5	426.1	3.0	1201.1	421.9	2.7	1134.7	397.2	2.7

MODEL: YCIV1500S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1337.3	328.4	3.7	1315.3	373.1	3.3	1289.8	422.2	2.9	1249.5	473.4	2.5	1187.1	512.7	2.2	1174.5	520.5	2.1
6.0	1374.7	331.0	3.8	1351.8	375.7	3.3	1325.2	424.9	2.9	1280.8	475.2	2.5	1216.1	514.6	2.2	1203.0	522.5	2.2
7.0	1412.9	333.8	3.9	1389.0	378.4	3.4	1361.1	427.8	3.0	1312.9	476.8	2.6	1246.0	516.4	2.3	1232.4	524.3	2.2
8.0	1451.9	336.8	4.0	1426.9	381.4	3.5	1397.9	430.7	3.0	1345.7	478.4	2.7	1276.5	518.2	2.3	1248.8	516.4	2.3
9.0	1491.4	340.1	4.0	1465.7	384.4	3.5	1435.3	433.8	3.1	1379.2	480.1	2.7	1307.7	519.9	2.4	1260.5	504.6	2.4
10.0	1531.8	343.5	4.1	1505.1	387.5	3.6	1473.6	436.9	3.2	1412.8	481.9	2.8	1339.2	521.7	2.4	1272.3	492.8	2.4
11.0	1572.9	347.0	4.2	1545.3	390.8	3.7	1512.7	440.1	3.2	1447.4	483.6	2.8	1356.6	512.7	2.5	1283.9	481.0	2.5
12.0	1613.6	350.8	4.2	1586.1	394.5	3.7	1552.4	443.5	3.3	1482.4	485.4	2.9	1369.0	500.1	2.6	1295.3	469.5	2.6
13.0	0.0	0.0	0.0	1626.5	398.0	3.8	1593.0	447.0	3.3	1518.1	487.2	2.9	1381.2	487.7	2.7	1306.2	458.5	2.7

NOTES:

1. kWo = Unit kW Cooling Capacity Output

2. KWi = Compressor kW Input

3. COP = Coefficient of Performance (includes condenser fan power)

4. LCWT = Leaving Chilled Water Temperature

5. Ratings based on 0.168 l/scooler water per ton, and 0.018 (m² – °C)/kW

6. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

High Efficiency Ratings – SI - 400V/50Hz

MODEL: YCIV0590E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	525.0	123.1	3.9	515.6	139.0	3.4	503.3	156.2	3.0	487.8	176.4	2.6	449.0	192.6	2.2	441.1	196.0	2.1
6.0	539.7	124.0	3.9	530.4	140.2	3.5	518.1	157.4	3.0	500.9	177.3	2.6	460.8	193.4	2.2	452.7	196.7	2.2
7.0	554.7	125.0	4.0	545.4	141.3	3.5	533.0	158.5	3.1	514.0	178.2	2.7	472.8	194.1	2.3	464.5	197.5	2.2
8.0	569.9	126.1	4.1	560.7	142.4	3.6	548.1	159.7	3.2	527.2	179.1	2.7	484.9	195.0	2.3	476.5	198.2	2.3
9.0	585.2	127.1	4.2	576.2	143.5	3.7	563.5	161.0	3.2	540.5	180.0	2.8	497.0	195.9	2.4	488.4	199.1	2.3
10.0	600.7	128.2	4.2	591.8	144.7	3.7	579.1	162.2	3.3	554.0	180.9	2.9	509.5	196.8	2.4	500.6	200.0	2.4
11.0	616.4	129.2	4.3	607.7	145.8	3.8	594.9	163.5	3.4	567.6	181.9	2.9	522.3	197.7	2.5	513.2	200.9	2.4
12.0	632.2	130.3	4.4	623.8	147.0	3.9	610.9	164.8	3.4	581.2	182.9	3.0	535.2	198.6	2.5	525.9	201.8	2.4
13.0	648.3	131.3	4.5	640.1	148.3	4.0	627.2	166.2	3.5	595.0	183.8	3.0	548.3	199.5	2.6	538.8	202.7	2.5

MODEL: YCIV0630E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	558.7	129.2	3.9	550.3	147.1	3.4	540.3	167.0	3.0	525.1	189.7	2.6	492.2	209.6	2.2	484.3	213.4	2.1
6.0	574.5	130.1	4.0	565.7	147.9	3.5	555.3	167.8	3.0	538.7	190.4	2.6	504.1	210.2	2.2	496.2	213.9	2.2
7.0	590.5	131.1	4.0	581.5	148.8	3.6	570.6	168.6	3.1	552.7	191.0	2.7	516.4	210.7	2.3	508.1	214.6	2.2
8.0	606.9	132.2	4.1	597.5	149.7	3.6	586.3	169.5	3.2	566.8	191.7	2.7	528.8	211.3	2.3	520.3	215.1	2.3
9.0	623.5	133.4	4.2	613.9	150.7	3.7	602.3	170.4	3.3	581.3	192.4	2.8	541.5	211.8	2.4	532.8	215.7	2.3
10.0	640.4	134.6	4.3	630.5	151.8	3.8	618.5	171.4	3.3	596.0	193.1	2.9	554.4	212.3	2.4	545.5	216.2	2.4
11.0	657.7	136.0	4.4	647.5	153.0	3.9	635.1	172.5	3.4	610.9	193.9	2.9	567.6	212.9	2.5	551.5	211.4	2.4
12.0	675.2	137.4	4.4	664.8	154.3	3.9	652.0	173.6	3.5	626.1	194.7	3.0	580.9	213.4	2.5	557.2	206.6	2.5
13.0	693.1	139.0	4.5	682.3	155.6	4.0	669.2	174.8	3.5	641.6	195.5	3.1	594.4	214.0	2.6	562.8	202.0	2.6

MODEL: YCIV0700E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	621.1	143.4	3.9	611.6	164.1	3.4	600.1	187.0	3.0	582.8	211.7	2.6	547.1	228.0	2.2	538.6	230.9	2.2
6.0	638.5	144.3	4.0	628.9	164.8	3.5	617.0	187.7	3.0	598.1	212.0	2.6	560.8	228.4	2.3	552.0	231.3	2.2
7.0	656.2	145.3	4.1	646.4	165.6	3.5	634.2	188.4	3.1	613.8	212.3	2.7	574.6	228.7	2.3	565.6	231.6	2.3
8.0	674.1	146.4	4.1	664.2	166.5	3.6	651.7	189.3	3.2	629.7	212.6	2.7	588.8	229.0	2.4	579.5	232.0	2.3
9.0	692.3	147.7	4.2	682.2	167.5	3.7	669.4	190.2	3.2	645.8	212.9	2.8	603.2	229.2	2.5	593.7	232.2	2.4
10.0	710.7	149.0	4.3	700.4	168.6	3.8	687.3	191.1	3.3	662.3	213.3	2.9	617.8	229.4	2.5	608.1	232.4	2.4
11.0	729.4	150.5	4.4	719.0	169.8	3.9	705.6	192.2	3.4	678.9	213.6	3.0	632.7	229.6	2.6	622.8	232.6	2.5
12.0	748.4	152.0	4.4	737.8	171.1	3.9	724.1	193.3	3.5	695.7	214.0	3.0	647.8	229.7	2.6	632.7	229.6	2.6
13.0	767.7	153.7	4.5	756.9	172.4	4.0	742.9	194.5	3.5	712.8	214.4	3.1	663.1	229.9	2.7	638.4	224.0	2.7

NOTES:

1. kWo = Unit kW Cooling Capacity Output
2. KWi = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW
6. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

MODEL: YCIV0760E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	672.7	155.1	3.9	661.6	178.9	3.4	648.7	206.1	2.9	631.4	236.7	2.5	586.1	249.7	2.2	577.1	252.0	2.2
6.0	691.7	156.1	4.0	680.1	179.4	3.5	666.7	206.4	3.0	647.0	236.3	2.6	600.4	249.7	2.3	591.1	252.1	2.2
7.0	711.0	157.3	4.1	699.0	180.0	3.6	685.1	206.8	3.1	662.9	235.8	2.6	614.9	249.6	2.3	605.4	252.0	2.3
8.0	730.8	158.7	4.2	718.3	180.9	3.6	703.9	207.3	3.1	678.8	235.3	2.7	629.7	249.3	2.4	620.0	251.8	2.3
9.0	750.9	160.4	4.2	737.9	181.8	3.7	723.0	207.9	3.2	695.2	234.8	2.8	645.0	249.0	2.4	634.8	251.6	2.4
10.0	771.3	162.3	4.3	758.0	183.0	3.8	742.4	208.8	3.3	711.9	234.3	2.8	660.3	248.5	2.5	650.0	251.1	2.4
11.0	792.1	164.4	4.4	778.4	184.3	3.9	762.2	209.6	3.4	728.8	233.8	2.9	675.9	248.0	2.6	665.4	250.7	2.5
12.0	813.3	166.8	4.4	799.1	186.0	3.9	782.4	210.6	3.4	745.9	233.3	3.0	691.8	247.5	2.6	681.0	250.2	2.6
13.0	834.9	169.5	4.5	820.2	187.8	4.0	803.0	211.8	3.5	763.0	233.0	3.1	707.8	247.0	2.7	696.9	249.6	2.6

MODEL: YCIV0800E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	715.1	163.2	3.9	703.9	187.3	3.4	691.1	214.8	3.0	672.4	245.0	2.6	630.3	261.6	2.3	620.8	264.1	2.2
6.0	735.3	164.3	4.0	723.6	188.0	3.5	710.2	215.4	3.0	689.7	245.2	2.6	645.5	261.6	2.3	635.9	264.1	2.3
7.0	755.9	165.6	4.1	743.7	188.9	3.6	729.7	216.0	3.1	707.4	245.3	2.7	661.1	261.5	2.4	651.2	264.1	2.3
8.0	776.9	167.1	4.2	764.2	189.8	3.7	749.5	216.7	3.2	725.4	245.4	2.8	677.0	261.3	2.4	666.7	264.0	2.4
9.0	798.4	168.8	4.3	785.1	191.0	3.8	769.8	217.5	3.3	743.7	245.5	2.8	693.1	261.0	2.5	682.6	263.7	2.4
10.0	820.2	170.7	4.3	806.4	192.3	3.8	790.5	218.4	3.3	762.5	245.6	2.9	709.5	260.7	2.5	698.7	263.4	2.5
11.0	842.4	172.9	4.4	828.1	193.8	3.9	811.6	219.5	3.4	781.3	245.8	3.0	726.1	260.3	2.6	715.2	263.0	2.5
12.0	864.5	175.1	4.5	850.1	195.4	4.0	833.1	220.7	3.5	799.5	245.5	3.0	743.1	259.9	2.7	723.9	257.8	2.6
13.0	887.0	177.7	4.5	872.1	197.2	4.0	854.8	222.1	3.6	818.1	245.3	3.1	760.3	259.5	2.7	730.1	251.0	2.7

MODEL: YCIV0830E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	743.0	169.0	3.9	731.8	192.7	3.4	718.8	219.4	3.0	703.0	250.7	2.6	661.8	268.9	2.3	652.0	271.4	2.2
6.0	764.0	170.2	4.0	752.3	193.7	3.5	738.8	220.3	3.1	722.2	251.7	2.7	678.0	268.9	2.3	667.8	271.6	2.3
7.0	785.4	171.7	4.1	773.3	194.8	3.6	759.2	221.2	3.2	741.8	252.8	2.7	694.3	269.0	2.4	684.1	271.6	2.3
8.0	807.2	173.1	4.2	794.7	196.0	3.7	780.0	222.3	3.2	761.9	253.8	2.8	711.1	269.0	2.5	700.6	271.6	2.4
9.0	829.4	174.8	4.3	816.5	197.2	3.8	801.2	223.4	3.3	782.3	254.8	2.9	728.2	268.9	2.5	717.3	271.6	2.5
10.0	851.7	176.5	4.3	838.7	198.7	3.8	822.9	224.6	3.4	801.1	254.8	2.9	745.6	268.9	2.6	734.4	271.5	2.5
11.0	874.2	178.4	4.4	860.8	200.2	3.9	844.9	225.8	3.4	820.0	254.9	3.0	763.3	268.8	2.6	751.8	271.4	2.6
12.0	897.1	180.5	4.5	883.2	201.8	4.0	866.8	227.3	3.5	839.3	254.9	3.1	781.0	268.7	2.7	769.5	271.3	2.6
13.0	920.3	182.6	4.5	906.1	203.6	4.1	889.1	228.7	3.6	858.7	255.0	3.1	799.3	268.6	2.8	787.3	271.3	2.7

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW
6. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

High Efficiency Ratings – SI - 400V/50Hz

MODEL: YCIV0930E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	824.5	194.8	3.8	811.2	221.5	3.4	795.7	251.2	2.9	773.5	283.8	2.5	730.4	305.9	2.2	721.2	309.7	2.2
6.0	847.7	196.4	3.9	833.8	222.9	3.4	817.7	252.6	3.0	793.8	284.9	2.6	748.4	306.5	2.3	738.8	310.5	2.2
7.0	871.3	198.1	4.0	856.9	224.4	3.5	840.1	254.0	3.1	814.6	286.0	2.7	766.7	307.1	2.3	754.9	309.8	2.3
8.0	895.3	199.9	4.1	880.5	226.0	3.6	863.0	255.6	3.1	835.8	287.1	2.7	785.5	307.7	2.4	763.0	303.6	2.4
9.0	919.9	201.9	4.1	904.5	227.8	3.7	886.3	257.2	3.2	856.8	287.9	2.8	804.7	308.2	2.5	770.6	296.9	2.4
10.0	944.8	204.0	4.2	928.9	229.6	3.7	910.1	258.9	3.3	877.5	288.5	2.8	821.6	307.2	2.5	777.9	289.9	2.5
11.0	970.3	206.2	4.3	953.8	231.6	3.8	934.4	260.7	3.3	898.6	289.1	2.9	829.7	300.0	2.6	784.7	282.6	2.6
12.0	995.9	208.6	4.4	979.1	233.6	3.9	959.0	262.6	3.4	920.1	289.7	3.0	837.3	292.4	2.7	791.0	275.3	2.7
13.0	1022.2	210.5	4.4	1004.7	235.9	3.9	984.2	264.6	3.5	941.9	290.4	3.0	844.2	284.8	2.8	796.8	268.3	2.8

MODEL: YCIV1050E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	935.9	214.3	3.9	919.5	246.0	3.4	900.1	281.3	3.0	875.5	321.9	2.5	811.1	342.9	2.2	798.1	346.7	2.2
6.0	962.5	215.7	4.0	945.8	247.0	3.5	925.6	282.3	3.0	898.2	322.2	2.6	831.3	343.3	2.3	817.8	347.2	2.2
7.0	989.5	217.3	4.1	972.5	248.1	3.6	951.7	283.3	3.1	921.3	322.3	2.7	851.9	343.6	2.3	838.0	347.6	2.3
8.0	1017.1	219.1	4.2	999.6	249.4	3.7	978.3	284.3	3.2	944.1	322.3	2.7	872.7	343.8	2.4	858.7	347.9	2.3
9.0	1045.2	221.1	4.3	1027.4	250.9	3.7	1005.4	285.5	3.3	967.3	322.3	2.8	894.2	343.9	2.4	879.6	348.1	2.4
10.0	1073.8	223.4	4.4	1055.6	252.5	3.8	1033.0	286.9	3.3	991.0	322.2	2.9	915.8	344.0	2.5	901.0	348.2	2.4
11.0	1102.8	225.9	4.4	1084.4	254.3	3.9	1061.2	288.3	3.4	1015.0	322.2	2.9	938.0	344.0	2.6	922.6	348.2	2.5
12.0	1132.3	228.7	4.5	1113.6	256.4	4.0	1089.8	289.9	3.5	1039.3	322.2	3.0	960.5	344.0	2.6	944.8	348.2	2.5
13.0	1162.3	231.7	4.6	1143.3	258.7	4.1	1119.1	291.7	3.6	1063.8	322.3	3.1	983.3	344.0	2.7	967.4	348.1	2.6

MODEL: YCIV1120E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	996.2	225.3	4.0	979.2	259.7	3.4	959.5	298.8	3.0	935.5	344.4	2.5	869.0	364.4	2.2	855.4	367.7	2.2
6.0	1024.5	226.7	4.1	1007.0	260.4	3.5	986.4	299.5	3.0	960.5	344.8	2.6	890.3	364.4	2.3	876.3	367.9	2.2
7.0	1053.4	228.4	4.2	1035.3	261.3	3.6	1013.9	300.0	3.1	984.3	344.2	2.7	912.1	364.3	2.3	897.7	367.9	2.3
8.0	1082.9	230.4	4.2	1064.2	262.5	3.7	1042.0	300.7	3.2	1008.6	343.5	2.7	934.3	363.9	2.4	919.5	367.6	2.3
9.0	1112.9	232.7	4.3	1093.7	263.9	3.8	1070.7	301.6	3.3	1033.1	342.9	2.8	956.7	363.5	2.5	941.8	367.2	2.4
10.0	1143.5	235.4	4.4	1123.7	265.6	3.9	1100.0	302.8	3.4	1058.1	342.2	2.9	979.9	362.9	2.5	964.3	366.8	2.5
11.0	1174.4	238.5	4.5	1154.4	267.5	3.9	1129.9	304.0	3.4	1083.6	341.5	3.0	1003.4	362.3	2.6	987.4	366.2	2.5
12.0	1206.4	241.9	4.5	1185.5	269.8	4.0	1160.4	305.5	3.5	1109.5	340.9	3.0	1027.4	361.6	2.7	1011.0	365.5	2.6
13.0	1238.7	245.7	4.6	1217.3	272.4	4.1	1191.4	307.2	3.6	1135.6	340.4	3.1	1051.7	360.9	2.7	1034.9	364.8	2.7

NOTES:

1. kWo = Unit kW Cooling Capacity Output
2. KWi = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW
6. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

MODEL: YCIV1220E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1082.7	247.9	3.9	1064.7	284.7	3.4	1044.3	326.4	3.0	1013.0	371.0	2.6	945.2	394.1	2.3	930.6	397.6	2.2
6.0	1113.5	249.6	4.0	1094.7	285.8	3.5	1073.2	327.3	3.0	1038.5	371.1	2.6	967.8	394.2	2.3	953.0	397.8	2.2
7.0	1145.0	251.6	4.1	1125.3	287.1	3.6	1102.8	328.3	3.1	1064.7	371.1	2.7	991.1	394.1	2.4	975.8	397.9	2.3
8.0	1177.1	253.9	4.2	1156.5	288.5	3.7	1133.0	329.5	3.2	1091.4	371.0	2.7	1014.9	393.9	2.4	999.0	397.7	2.4
9.0	1209.8	256.5	4.3	1188.4	290.3	3.8	1164.0	330.7	3.3	1118.6	370.9	2.8	1039.0	393.5	2.5	1022.8	397.4	2.4
10.0	1243.2	259.3	4.3	1221.0	292.3	3.8	1195.5	332.2	3.3	1146.4	370.9	2.9	1063.6	393.0	2.5	1047.0	397.0	2.5
11.0	1277.2	262.6	4.4	1254.2	294.7	3.9	1227.8	333.8	3.4	1174.3	370.9	3.0	1088.5	392.5	2.6	1071.6	396.5	2.5
12.0	1311.9	266.1	4.5	1288.1	297.2	4.0	1260.7	335.7	3.5	1201.8	370.4	3.0	1114.1	391.9	2.7	1085.7	389.4	2.6
13.0	1347.3	270.1	4.5	1322.6	300.0	4.1	1294.1	337.9	3.6	1229.8	370.1	3.1	1139.9	391.3	2.7	1095.0	379.4	2.7

MODEL: YCIV1380E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1228.4	287.0	3.9	1206.7	325.4	3.4	1181.0	367.8	3.0	1146.5	415.9	2.6	1083.9	450.5	2.3	1070.4	456.8	2.2
6.0	1263.2	289.6	4.0	1241.1	327.6	3.5	1214.5	370.0	3.0	1177.1	417.5	2.6	1111.7	451.6	2.3	1097.6	457.9	2.3
7.0	1298.8	292.2	4.0	1276.1	330.0	3.5	1248.7	372.3	3.1	1208.5	419.0	2.7	1139.9	452.8	2.4	1125.5	459.0	2.3
8.0	1334.9	295.0	4.1	1311.8	332.6	3.6	1283.4	374.9	3.2	1240.5	420.6	2.8	1168.8	453.8	2.4	1153.8	460.1	2.4
9.0	1371.6	298.1	4.2	1348.0	335.4	3.7	1318.9	377.4	3.2	1273.1	422.2	2.8	1198.3	454.9	2.5	1183.0	461.2	2.4
10.0	1409.1	301.3	4.3	1384.9	338.3	3.8	1355.0	380.2	3.3	1306.1	424.0	2.9	1228.4	456.0	2.5	1205.0	457.4	2.5
11.0	1447.1	304.6	4.3	1422.5	341.3	3.8	1391.8	383.1	3.4	1339.8	425.7	2.9	1258.9	457.1	2.6	1215.9	446.2	2.6
12.0	1485.7	308.3	4.4	1460.6	344.7	3.9	1429.2	386.1	3.4	1372.9	427.0	3.0	1290.1	458.2	2.6	1226.3	435.1	2.6
13.0	1525.2	311.0	4.5	1499.4	348.1	4.0	1467.3	389.3	3.5	1406.5	428.4	3.1	1308.1	450.8	2.7	1236.0	424.3	2.7

NOTES:

1. kWo = Unit kW Cooling Capacity Output

2. KWi = Compressor kW Input

3. COP = Coefficient of Performance (includes condenser fan power)

4. LCWT = Leaving Chilled Water Temperature

5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² - °C)/kW

6. ARI 550/590 does not provide certification for 50Hz ratings. The unique use of the YCIV variable speed drive allows compressor operation at the output speed regardless of the input power frequency. This allows for common unit/heat exchanger configurations between 60Hz and 50Hz with closely matching capacity.

Standard Efficiency Ratings – English - 380V/60Hz

MODEL: YCIV0157S/P

S IPLV = 13.4

P IPLV = 14.7

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	149.1	128.9	12.6	148.0	138.9	11.7	146.7	149.6	10.8	145.4	160.8	10.0	143.9	172.5	9.3	142.2	185.6	8.6	138.9	197.9	7.9	133.5	208.0	7.2	127.9	218.6	6.6
42.0	153.7	129.8	12.9	152.5	139.8	11.9	151.2	150.4	11.1	149.8	161.7	10.3	148.2	173.4	9.5	146.5	186.7	8.8	142.7	198.6	8.1	137.0	208.9	7.4	131.3	219.4	6.8
44.0	158.3	130.8	13.2	157.1	140.7	12.2	155.7	151.3	11.3	154.3	162.6	10.5	152.6	174.4	9.8	150.8	187.7	9.0	146.5	199.3	8.3	140.6	209.7	7.6	134.7	220.2	6.9
45.0	160.7	131.3	13.3	159.4	141.2	12.4	158.1	151.8	11.5	156.5	163.1	10.6	154.9	174.8	9.9	153.0	188.2	9.1	148.4	199.6	8.4	142.5	210.1	7.7	136.5	220.5	7.0
46.0	163.1	131.9	13.5	161.8	141.7	12.5	160.4	152.3	11.6	158.8	163.6	10.8	157.1	175.3	10.0	155.2	188.7	9.2	150.4	200.0	8.5	144.3	210.4	7.7	138.3	220.9	7.1
48.0	167.9	133.0	13.8	166.6	142.8	12.8	165.1	153.4	11.9	163.5	164.6	11.0	161.7	176.4	10.2	159.7	189.7	9.4	154.3	200.6	8.6	148.1	211.1	7.9	141.8	221.8	7.2
50.0	172.8	134.3	14.0	171.4	144.0	13.1	169.9	154.5	12.1	168.2	165.6	11.3	166.4	177.4	10.5	164.3	190.8	9.7	158.2	201.3	8.8	151.9	211.8	8.1	145.5	222.5	7.4
52.0	177.8	135.6	14.3	176.4	145.3	13.3	174.8	155.7	12.4	173.1	166.8	11.5	171.2	178.6	10.7	168.6	191.7	9.9	162.2	202.0	9.0	155.8	212.5	8.3	149.2	223.0	7.6
55.0	185.4	137.8	14.7	184.0	147.3	13.7	182.3	157.6	12.8	180.5	168.7	11.9	178.5	180.4	11.0	175.0	192.8	10.2	168.3	203.1	9.3	161.7	213.5	8.5	151.7	214.5	8.0

MODEL: YCIV0177S/P

S IPLV = 13.3

P IPLV = 15.0

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	165.7	141.8	12.8	164.2	153.1	11.8	162.4	165.1	10.9	160.5	177.6	10.1	158.4	190.5	9.3	154.6	201.5	8.6	149.9	210.4	8.0	143.5	217.6	7.5	130.1	207.3	7.1
42.0	170.9	142.8	13.1	169.3	154.1	12.1	167.5	166.1	11.2	165.5	178.7	10.3	163.3	191.6	9.6	159.1	202.1	8.9	154.0	211.0	8.2	147.5	218.3	7.6	131.8	203.1	7.3
44.0	176.1	143.9	13.4	174.6	155.2	12.4	172.8	167.2	11.5	170.7	179.8	10.6	168.4	192.9	9.8	163.8	202.6	9.1	158.3	211.5	8.4	151.5	218.9	7.8	133.6	199.1	7.5
45.0	178.8	144.5	13.6	177.2	155.7	12.6	175.4	167.7	11.6	173.3	180.4	10.7	171.0	193.5	9.9	166.1	202.9	9.2	160.5	211.7	8.6	153.5	219.3	7.9	134.5	196.9	7.7
46.0	181.5	145.2	13.7	179.9	156.3	12.7	178.1	168.3	11.8	175.9	180.9	10.9	173.5	193.9	10.0	168.5	203.2	9.3	162.6	211.9	8.7	155.6	219.5	8.0	135.3	194.7	7.8
48.0	186.9	146.5	14.0	185.4	157.6	13.0	183.5	169.5	12.0	181.3	182.1	11.1	178.4	194.4	10.3	173.3	203.7	9.6	167.0	212.3	8.9	159.8	220.0	8.2	137.0	190.4	8.1
50.0	192.4	148.0	14.3	190.8	158.9	13.3	189.0	170.8	12.3	186.7	183.4	11.4	183.4	194.9	10.6	178.2	204.3	9.8	171.5	212.6	9.1	162.8	217.2	8.5	138.3	185.7	8.3
52.0	198.0	149.5	14.6	196.4	160.4	13.6	194.5	172.2	12.6	192.2	184.9	11.6	188.5	195.4	10.8	183.1	204.8	10.1	176.0	213.0	9.3	164.7	212.2	8.8	139.6	181.2	8.6
55.0	206.4	152.1	15.0	204.9	162.8	13.9	202.9	174.5	13.0	200.6	187.0	12.0	196.2	196.4	11.2	190.7	205.7	10.4	182.9	213.5	9.7	167.5	204.9	9.2	141.5	174.7	9.0

MODEL: YCIV0187S/P

S IPLV = 13.3

P IPLV = 15.1

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	180.3	153.0	12.9	178.8	164.8	11.9	177.1	177.5	11.0	175.3	190.8	10.2	173.4	204.7	9.5	171.1	220.4	8.7	166.1	231.6	8.1	159.4	240.4	7.5	152.8	248.8	6.9
42.0	185.9	154.3	13.2	184.4	166.1	12.2	182.6	178.6	11.3	180.7	191.9	10.5	178.7	205.9	9.7	176.4	221.7	8.9	170.5	232.1	8.3	163.7	240.9	7.7	156.9	249.4	7.1
44.0	191.7	155.7	13.5	190.0	167.3	12.5	188.2	179.9	11.6	186.3	193.1	10.7	184.2	207.1	9.9	181.7	222.9	9.2	175.1	232.5	8.5	168.0	241.4	7.9	160.9	250.0	7.3
45.0	194.6	156.4	13.6	192.9	168.0	12.6	191.1	180.5	11.7	189.1	193.8	10.9	186.9	207.7	10.1	184.3	223.4	9.3	177.4	232.7	8.6	170.2	241.6	8.0	163.0	250.3	7.4
46.0	197.5	157.2	13.8	195.8	168.7	12.8	193.9	181.2	11.9	191.9	194.4	11.0	189.7	208.4	10.2	186.9	223.7	9.4	179.7	232.9	8.7	172.5	241.8	8.1	165.1	250.5	7.5
48.0	203.5	158.8	14.0	201.7	170.2	13.1	199.8	182.6	12.1	197.6	195.8	11.2	195.3	209.8	10.4	191.9	224.3	9.6	184.5	233.3	8.9	177.0	242.2	8.3	169.5	250.9	7.6
50.0	209.5	160.6	14.3	207.7	171.8	13.3	205.7	184.1	12.4	203.5	197.2	11.5	201.1	211.2	10.7	196.8	224.7	9.8	189.3	233.7	9.1	181.6	242.6	8.5	171.2	244.6	7.9
52.0	215.7	162.4	14.6	213.8	173.6	13.6	211.7	185.7	12.7	209.4	198.8	11.7	206.9	212.7	10.9	201.9	225.2	10.1	194.1	234.1	9.3	186.3	242.9	8.7	172.9	237.9	8.2
55.0	225.2	165.6	15.0	223.2	176.4	14.0	221.0	188.4	13.0	218.6	201.3	12.1	215.9	215.2	11.3	209.6	225.9	10.4	201.5	234.7	9.7	193.4	243.5	9.0	175.7	228.6	8.7

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KWi)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98
6. Certified IAW the ARI Water-Chilling Packages Using the Vapor Compression Cycle Certification Program, which is based on ARI Standard 550/590.

MODEL: YCIV0207S/P**S IPLV = 13.5****P IPLV = 14.9****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	194.8	164.9	13.0	192.9	178.5	12.0	190.9	193.4	11.0	188.7	209.2	10.1	186.4	225.7	9.3	181.9	239.3	8.6	176.0	249.7	8.0	168.7	256.4	7.5	149.2	233.3	7.2
42.0	200.9	166.2	13.3	199.0	179.6	12.3	196.8	194.3	11.3	194.6	210.0	10.4	192.1	226.6	9.5	187.1	239.5	8.8	180.7	249.6	8.2	173.2	256.6	7.6	151.0	228.1	7.5
44.0	207.2	167.7	13.6	205.2	180.8	12.6	202.9	195.3	11.6	200.5	210.9	10.6	197.6	226.7	9.8	192.4	239.7	9.1	185.4	249.4	8.4	177.7	256.6	7.8	152.8	222.7	7.7
45.0	210.4	168.6	13.7	208.3	181.5	12.7	206.0	195.8	11.7	203.6	211.4	10.8	200.4	226.8	9.9	195.0	239.8	9.2	187.9	249.2	8.5	180.0	256.5	8.0	153.7	220.0	7.8
46.0	213.6	169.5	13.9	211.5	182.2	12.9	209.1	196.4	11.9	206.6	211.9	10.9	203.2	226.8	10.1	197.8	239.9	9.3	190.3	249.0	8.6	182.0	255.7	8.1	154.6	217.4	8.0
48.0	220.2	171.6	14.2	218.0	183.8	13.1	215.5	197.8	12.1	212.9	213.1	11.2	208.9	227.1	10.4	203.3	240.1	9.6	195.3	248.6	8.9	184.0	249.3	8.4	156.2	212.3	8.2
50.0	226.9	173.9	14.4	224.5	185.8	13.4	222.0	199.4	12.4	219.2	214.5	11.5	214.8	227.4	10.6	208.8	240.1	9.8	200.4	248.2	9.1	186.1	242.8	8.7	157.8	207.3	8.5
52.0	233.7	176.5	14.6	231.3	187.9	13.7	228.6	201.2	12.7	225.7	216.0	11.7	220.7	227.9	10.9	214.2	239.7	10.1	205.5	247.7	9.4	188.1	236.5	9.0	159.3	202.4	8.8
55.0	244.3	181.1	14.9	241.7	191.7	14.0	238.8	204.4	13.1	235.4	218.1	12.1	229.8	228.9	11.3	222.4	239.3	10.5	213.4	247.1	9.8	191.0	227.9	9.4	161.6	195.2	9.2

MODEL: YCIV0227S/P**S IPLV = 13.2****P IPLV = 15.0****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	211.3	176.8	13.1	209.4	190.4	12.1	207.3	205.0	11.2	205.1	220.3	10.4	202.7	236.5	9.6	199.9	254.6	8.8	193.1	264.4	8.2	185.3	271.6	7.7	177.5	278.1	7.2
42.0	218.0	178.3	13.4	216.0	191.8	12.4	213.8	206.3	11.5	211.4	221.7	10.6	208.9	237.9	9.8	206.0	256.1	9.1	198.2	264.6	8.5	190.2	271.9	7.9	182.1	278.5	7.4
44.0	224.9	180.0	13.7	222.7	193.4	12.7	220.4	207.8	11.8	218.0	223.2	10.9	215.3	239.3	10.1	211.9	256.9	9.3	203.5	264.7	8.7	195.2	272.0	8.1	186.9	278.8	7.6
45.0	228.3	181.0	13.9	226.2	194.2	12.9	223.8	208.6	11.9	221.3	223.9	11.0	218.5	240.2	10.2	214.7	256.9	9.4	206.2	264.8	8.8	197.7	272.1	8.2	189.3	278.9	7.7
46.0	231.8	182.0	14.0	229.6	195.1	13.0	227.2	209.4	12.1	224.6	224.7	11.2	221.8	240.9	10.3	217.5	257.0	9.5	208.9	264.8	8.9	200.3	272.2	8.3	191.8	279.0	7.8
48.0	238.9	184.1	14.3	236.7	197.0	13.3	234.2	211.1	12.3	231.4	226.4	11.4	228.5	242.5	10.6	223.2	257.1	9.8	214.4	264.9	9.1	205.6	272.2	8.5	195.3	275.8	8.0
50.0	246.2	186.3	14.5	243.8	199.1	13.6	241.2	213.1	12.6	238.4	228.2	11.7	235.3	244.3	10.8	229.0	257.3	10.0	219.9	265.0	9.4	210.9	272.3	8.8	197.2	269.1	8.3
52.0	253.6	188.8	14.8	251.2	201.3	13.8	248.5	215.1	12.9	245.5	230.2	11.9	242.3	246.2	11.1	234.9	257.4	10.3	225.6	265.0	9.6	216.3	272.3	9.0	199.3	262.1	8.6
55.0	264.9	192.8	15.2	262.4	205.0	14.2	259.5	218.6	13.2	256.4	233.4	12.3	253.1	249.2	11.4	243.9	257.8	10.7	234.3	265.1	10.0	224.6	272.3	9.3	202.2	251.2	9.1

MODEL: YCIV0247S/P**S IPLV = 13.0****P IPLV = 15.1****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	231.8	194.8	13.0	229.8	209.5	12.1	227.6	225.2	11.2	225.2	241.7	10.4	222.7	259.1	9.6	219.7	278.6	8.9	213.4	291.6	8.3	206.3	302.6	7.7	199.1	313.1	7.2
42.0	239.1	196.6	13.3	236.9	211.3	12.4	234.6	226.9	11.5	232.1	243.4	10.6	229.5	260.8	9.9	226.4	280.4	9.1	219.3	292.4	8.5	211.9	303.4	7.9	204.4	314.0	7.4
44.0	246.5	198.5	13.6	244.3	213.1	12.7	241.9	228.6	11.7	239.2	245.2	10.9	236.4	262.6	10.1	232.9	281.7	9.3	225.3	293.1	8.7	217.6	304.1	8.1	208.9	312.4	7.6
45.0	250.2	199.6	13.8	248.0	214.0	12.8	245.5	229.6	11.9	242.8	246.2	11.0	239.9	263.6	10.2	236.1	282.1	9.4	228.3	293.4	8.8	220.5	304.5	8.2	210.1	309.1	7.7
46.0	254.0	200.7	13.9	251.7	215.0	12.9	249.2	230.5	12.0	246.5	247.1	11.1	243.5	264.5	10.3	239.2	282.4	9.5	231.4	293.7	8.9	223.4	304.8	8.3	211.3	305.6	7.8
48.0	261.7	202.9	14.2	259.4	217.2	13.2	256.7	232.5	12.3	253.9	249.0	11.4	250.8	266.5	10.6	245.7	283.1	9.8	237.6	294.4	9.1	229.4	305.5	8.5	213.6	298.3	8.1
50.0	269.6	205.3	14.5	267.1	219.4	13.5	264.4	234.7	12.5	261.4	251.1	11.6	258.2	268.5	10.8	252.2	283.8	10.0	243.9	295.1	9.3	235.5	306.1	8.7	215.8	290.5	8.4
52.0	277.6	208.0	14.7	275.1	221.8	13.7	272.2	237.0	12.8	269.1	253.3	11.9	265.8	270.7	11.0	258.9	284.6	10.3	250.3	295.8	9.6	241.7	306.7	8.9	217.8	282.3	8.7
55.0	289.9	211.6	15.1	287.2	225.7	14.1	284.2	240.8	13.2	281.0	256.9	12.2	277.4	274.1	11.4	269.0	285.9	10.6	260.2	296.8	9.9	251.2	307.8	9.2	220.5	270.4	9.2

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98
6. Certified IAW the ARI Water-Chilling Packages Using the Vapor Compression Cycle Certification Program, which is based on ARI Standard 550/590.

Standard Efficiency Ratings – English - 380V/60Hz

MODEL: YCIV0267S/P

S_IPLV = 12.5

P_IPLV = 15.2

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	252.3	212.7	13.0	250.2	228.4	12.1	247.9	245.3	11.2	245.4	262.9	10.4	242.7	281.5	9.7	239.6	302.4	8.9	233.9	318.6	8.3	227.3	333.2	7.7	220.8	347.6	7.2
42.0	260.2	214.7	13.3	258.0	230.5	12.4	255.6	247.2	11.5	252.9	265.0	10.6	250.1	283.5	9.9	246.8	304.5	9.1	240.4	319.9	8.5	233.6	334.5	7.9	226.8	349.1	7.4
44.0	268.2	216.8	13.6	265.9	232.5	12.6	263.3	249.2	11.7	260.6	267.0	10.9	257.6	285.6	10.1	254.0	306.3	9.3	247.1	321.1	8.7	240.1	335.8	8.1	231.8	347.4	7.6
45.0	272.2	218.0	13.7	269.9	233.6	12.8	267.3	250.4	11.9	264.5	268.1	11.0	261.4	286.7	10.2	257.5	306.9	9.4	250.5	321.7	8.8	243.4	336.4	8.2	233.0	343.2	7.7
46.0	276.3	219.2	13.9	273.9	234.7	12.9	271.3	251.4	12.0	268.4	269.2	11.1	265.3	287.8	10.3	261.0	307.6	9.6	253.9	322.3	8.9	246.7	337.1	8.3	234.2	338.8	7.8
48.0	284.6	221.6	14.1	282.1	237.1	13.2	279.4	253.7	12.2	276.4	271.4	11.4	273.1	290.1	10.6	268.2	308.8	9.8	260.9	323.5	9.1	253.4	338.3	8.5	236.7	330.1	8.1
50.0	293.1	224.1	14.4	290.5	239.6	13.4	287.7	256.1	12.5	284.6	273.7	11.6	281.1	292.4	10.8	275.5	310.1	10.0	267.9	324.9	9.3	260.2	339.6	8.7	239.1	321.4	8.4
52.0	301.7	227.0	14.7	299.1	242.2	13.7	296.1	258.7	12.7	292.9	276.2	11.9	289.3	294.9	11.0	282.9	311.5	10.2	275.1	326.1	9.5	267.2	340.8	8.9	241.5	312.8	8.7
55.0	315.0	230.2	15.1	312.1	246.1	14.1	309.0	262.7	13.1	305.6	280.2	12.2	301.9	298.7	11.4	294.2	313.7	10.6	286.1	328.1	9.9	277.9	342.8	9.2	244.8	300.9	9.1

MODEL: YCIV0287S/P

S_IPLV = 13.2

P_IPLV = 14.9

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	268.2	223.5	13.1	265.7	241.6	12.1	262.9	261.0	11.2	259.9	281.5	10.3	256.7	302.7	9.5	251.3	322.1	8.8	244.3	338.4	8.1	234.1	349.4	7.6	209.5	326.1	7.2
42.0	276.6	225.1	13.4	274.1	243.0	12.4	271.2	262.4	11.5	268.0	282.8	10.6	264.6	304.1	9.7	258.7	323.1	9.0	250.9	338.9	8.3	240.4	350.1	7.8	211.9	318.9	7.5
44.0	285.2	226.9	13.8	282.6	244.6	12.7	279.6	263.8	11.7	276.3	284.2	10.8	272.7	305.5	10.0	266.3	324.0	9.2	257.7	339.3	8.6	246.8	350.7	8.0	214.8	312.5	7.7
45.0	289.6	228.0	13.9	286.9	245.5	12.9	283.9	264.6	11.9	280.6	285.0	11.0	276.7	305.9	10.1	270.2	324.4	9.4	261.2	339.4	8.7	250.0	351.0	8.0	216.1	309.1	7.8
46.0	294.0	229.0	14.1	291.3	246.4	13.0	288.3	265.4	12.0	284.9	285.7	11.1	280.7	306.3	10.3	274.1	324.8	9.5	264.7	339.5	8.8	253.4	351.2	8.2	217.5	305.6	8.0
48.0	303.0	231.4	14.4	300.2	248.5	13.3	297.1	267.2	12.3	293.5	287.4	11.4	288.9	307.1	10.5	282.0	325.7	9.7	271.7	339.6	9.0	258.9	348.7	8.4	220.1	298.7	8.2
50.0	312.1	234.0	14.6	309.3	250.7	13.6	306.0	269.2	12.6	302.4	289.3	11.7	297.2	308.1	10.8	290.1	326.7	10.0	278.9	339.7	9.3	261.9	340.2	8.7	222.4	291.8	8.5
52.0	321.4	236.9	14.9	318.5	253.3	13.9	315.2	271.5	12.9	311.4	291.4	11.9	305.7	309.2	11.1	298.2	327.3	10.2	286.2	339.8	9.5	264.9	332.1	9.0	224.6	284.9	8.8
55.0	335.7	241.8	15.3	332.7	257.6	14.3	329.2	275.3	13.3	325.3	294.8	12.3	318.6	311.0	11.5	310.1	327.8	10.6	297.4	340.0	9.9	269.4	320.5	9.4	227.7	274.9	9.2

MODEL: YCIV0307S/P

S_IPLV = 12.9

P_IPLV = 14.9

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	298.0	246.4	13.2	295.2	266.7	12.2	292.2	288.9	11.2	289.0	312.5	10.3	285.6	337.1	9.5	279.8	359.4	8.8	271.4	376.6	8.1	260.3	386.9	7.6	229.5	351.1	7.4
42.0	307.4	248.3	13.6	304.5	268.2	12.5	301.3	290.1	11.5	297.9	313.6	10.6	294.3	338.2	9.8	287.9	360.2	9.0	278.6	376.5	8.4	267.2	387.2	7.8	232.1	342.9	7.6
44.0	317.0	250.5	13.9	314.0	270.0	12.8	310.6	291.6	11.8	307.1	314.8	10.9	302.9	338.6	10.0	296.2	360.8	9.2	286.0	376.2	8.6	274.2	387.2	8.0	235.1	335.3	7.9
45.0	321.9	251.7	14.0	318.8	270.9	13.0	315.4	292.4	12.0	311.7	315.5	11.0	307.3	338.9	10.2	300.4	361.1	9.4	289.7	375.9	8.7	277.7	387.1	8.1	236.5	331.3	8.0
46.0	326.9	253.1	14.2	323.7	272.0	13.1	320.2	293.2	12.1	316.4	316.3	11.2	311.7	339.2	10.3	304.7	361.4	9.5	293.5	375.7	8.8	280.1	384.3	8.2	237.9	327.3	8.1
48.0	336.9	256.1	14.5	333.6	274.4	13.4	329.9	295.1	12.4	326.0	318.0	11.5	320.6	339.9	10.6	313.4	362.0	9.8	301.2	375.1	9.1	283.2	374.7	8.5	240.7	319.9	8.4
50.0	347.2	259.4	14.7	343.7	277.2	13.7	339.9	297.5	12.7	335.8	320.0	11.7	329.8	340.7	10.9	322.0	362.2	10.0	309.0	374.4	9.3	286.4	365.0	8.8	243.0	312.2	8.7
52.0	357.7	263.2	15.0	354.1	280.3	14.0	350.1	300.1	13.0	345.8	322.2	12.0	339.1	341.8	11.1	330.3	361.6	10.3	317.0	373.8	9.6	289.6	355.6	9.2	245.3	304.8	9.0
55.0	373.9	269.8	15.3	370.0	285.8	14.4	365.8	304.7	13.4	360.8	325.3	12.4	353.5	343.8	11.5	343.0	361.0	10.7	329.2	372.9	10.0	294.2	342.6	9.6	248.8	294.0	9.4

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98

MODEL: YCIV0357S/P**S IPLV = 13.7****P IPLV = 15.4****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	336.3	282.3	13.1	333.4	303.7	12.1	330.1	326.9	11.2	326.6	351.0	10.4	322.9	376.4	9.6	318.6	404.9	8.9	309.3	423.4	8.2	298.3	437.9	7.7	287.4	451.6	7.2
42.0	346.9	284.7	13.4	343.8	306.1	12.4	340.4	329.1	11.5	336.7	353.3	10.6	332.8	378.7	9.8	328.3	407.4	9.1	317.7	424.3	8.4	306.3	438.9	7.9	295.0	452.8	7.4
44.0	357.7	287.5	13.7	354.5	308.7	12.7	350.9	331.5	11.7	347.1	355.8	10.9	342.9	381.2	10.1	338.1	409.8	9.3	326.3	425.1	8.7	314.6	439.7	8.1	302.8	453.8	7.6
45.0	363.2	288.9	13.8	359.9	310.1	12.8	356.3	332.9	11.9	352.3	357.1	11.0	348.1	382.6	10.2	342.7	410.2	9.4	330.7	425.4	8.8	318.7	440.1	8.2	304.8	449.8	7.7
46.0	368.8	290.5	13.9	365.4	311.4	13.0	361.7	334.2	12.0	357.6	358.4	11.1	353.3	383.9	10.3	347.2	410.5	9.5	335.1	425.8	8.9	322.9	440.5	8.3	306.7	445.3	7.8
48.0	380.1	293.7	14.2	376.6	314.5	13.2	372.7	337.0	12.3	368.5	361.1	11.4	363.9	386.6	10.6	356.5	411.3	9.8	344.0	426.5	9.1	331.5	441.3	8.5	310.2	435.5	8.1
50.0	391.6	297.1	14.5	387.9	317.7	13.5	383.9	340.0	12.6	379.5	364.0	11.7	374.8	389.5	10.8	366.0	412.1	10.0	353.1	427.2	9.3	340.2	441.9	8.7	313.5	424.6	8.3
52.0	403.4	300.9	14.8	399.6	321.1	13.8	395.4	343.3	12.8	390.8	367.0	11.9	385.9	392.4	11.0	375.7	412.9	10.3	362.4	427.9	9.6	349.2	442.5	8.9	316.5	412.9	8.6
55.0	421.3	306.4	15.2	417.2	326.8	14.2	412.9	348.5	13.2	408.1	372.3	12.3	402.9	397.4	11.4	390.4	414.3	10.6	376.6	429.0	9.9	362.8	443.6	9.3	320.4	394.8	9.1

MODEL: YCIV0397S/P**S IPLV = 13.4****P IPLV = 15.5****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	377.3	318.0	13.0	374.2	341.7	12.1	370.7	366.9	11.2	366.9	393.4	10.4	362.9	421.2	9.6	358.2	452.5	8.9	350.0	477.2	8.3	340.3	499.0	7.7	330.6	520.6	7.2
42.0	389.1	320.9	13.3	385.8	344.5	12.4	382.2	369.8	11.5	378.2	396.4	10.6	374.0	424.1	9.9	369.0	455.5	9.1	359.8	479.0	8.5	349.7	501.0	7.9	339.5	522.9	7.4
44.0	401.2	324.1	13.6	397.8	347.7	12.6	394.0	372.7	11.7	389.8	399.4	10.9	385.3	427.3	10.1	380.1	458.7	9.3	369.8	481.0	8.7	359.3	502.9	8.1	348.7	524.9	7.5
45.0	407.4	325.7	13.7	403.8	349.3	12.8	399.9	374.5	11.9	395.7	400.9	11.0	391.0	428.9	10.2	385.4	459.7	9.4	374.9	481.9	8.8	364.2	503.9	8.2	350.8	519.5	7.7
46.0	413.5	327.6	13.9	410.0	350.9	12.9	406.0	376.1	12.0	401.6	402.7	11.1	396.9	430.5	10.3	390.7	460.7	9.5	380.0	482.8	8.9	369.2	504.8	8.3	352.7	513.1	7.8
48.0	426.1	331.2	14.1	422.4	354.4	13.2	418.2	379.4	12.3	413.7	406.0	11.4	408.7	434.0	10.6	401.5	462.6	9.8	390.5	484.6	9.1	379.2	506.8	8.5	356.3	500.1	8.1
50.0	439.0	335.0	14.4	435.1	358.2	13.4	430.8	382.9	12.5	426.0	409.4	11.6	420.9	437.5	10.8	412.6	464.5	10.0	401.1	486.6	9.3	389.5	508.7	8.7	360.0	487.0	8.4
52.0	452.0	339.1	14.7	448.0	362.0	13.7	443.5	386.8	12.8	438.6	413.1	11.9	433.2	441.1	11.0	423.8	466.5	10.2	411.9	488.5	9.5	400.0	510.5	8.9	363.7	474.1	8.7
55.0	471.7	343.8	15.1	467.3	368.2	14.1	462.8	392.7	13.1	457.8	419.1	12.2	452.3	446.8	11.4	441.0	469.8	10.6	428.7	491.5	9.9	416.1	513.5	9.2	368.8	455.8	9.1

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 Kw)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98

High Efficiency Ratings – English - 380V/60Hz

MODEL: YCIV0157E/V

E IPLV = 13.8

V IPLV = 14.9

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	148.1	119.3	13.4	146.8	127.9	12.5	145.2	136.8	11.6	143.4	146.1	10.8	141.4	155.8	10.0	139.1	166.7	9.3	136.1	177.9	8.5	130.1	186.8	7.8	124.0	196.1	7.1
42.0	152.7	120.3	13.7	151.5	129.0	12.8	149.9	138.0	11.9	148.1	147.3	11.1	146.1	157.0	10.3	143.7	168.0	9.5	140.1	178.8	8.7	133.9	187.6	8.0	127.6	196.9	7.3
44.0	157.4	121.4	14.0	156.2	130.1	13.1	154.7	139.2	12.2	152.8	148.6	11.3	150.8	158.3	10.5	148.3	169.3	9.7	144.2	179.8	9.0	137.7	188.7	8.2	131.3	197.7	7.5
45.0	159.8	122.0	14.2	158.6	130.7	13.2	157.1	139.8	12.3	155.2	149.2	11.5	153.2	159.0	10.7	150.7	170.0	9.9	146.3	180.3	9.1	139.7	189.1	8.3	133.2	198.1	7.6
46.0	162.2	122.6	14.3	161.0	131.3	13.4	159.5	140.4	12.4	157.7	149.8	11.6	155.6	159.7	10.8	153.0	170.7	10.0	148.3	180.8	9.2	141.7	189.6	8.4	135.1	198.6	7.6
48.0	167.0	123.7	14.6	165.9	132.5	13.6	164.4	141.7	12.7	162.6	151.2	11.9	160.4	161.0	11.0	157.9	172.1	10.2	152.5	181.8	9.4	145.7	190.6	8.6	138.9	199.6	7.8
50.0	171.9	124.8	14.9	170.8	133.7	13.9	169.3	143.0	13.0	167.5	152.5	12.1	165.4	162.5	11.3	162.7	173.6	10.4	156.7	182.8	9.6	149.8	191.6	8.8	142.7	200.6	8.0
52.0	176.8	125.9	15.2	175.8	134.9	14.2	174.4	144.3	13.3	172.6	153.9	12.4	170.4	163.9	11.5	167.7	175.1	10.7	161.0	183.8	9.8	153.9	192.6	9.0	146.7	201.5	8.2
55.0	184.4	127.6	15.7	183.5	136.8	14.7	182.1	146.3	13.7	180.3	156.0	12.8	178.1	166.1	11.9	174.8	177.0	11.0	167.5	185.5	10.1	160.2	194.1	9.3	152.8	203.1	8.5

MODEL: YCIV0177E/V

E IPLV = 13.7

V IPLV = 14.9

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	157.1	128.7	13.3	156.3	134.6	12.5	155.0	144.6	11.6	153.5	155.4	10.8	151.9	166.7	10.0	150.0	179.5	9.3	147.0	191.8	8.5	142.2	203.1	7.8	136.2	213.6	7.1
42.0	162.5	126.2	13.8	161.3	135.5	12.8	159.9	145.6	11.9	158.3	156.2	11.1	156.6	167.5	10.3	154.7	180.4	9.5	151.2	192.5	8.7	146.1	203.7	8.0	139.9	214.2	7.3
44.0	167.6	127.3	14.1	166.3	136.5	13.2	164.8	146.6	12.2	163.2	157.2	11.4	161.5	168.4	10.6	159.4	181.3	9.7	155.6	193.3	9.0	150.1	204.3	8.2	143.6	214.9	7.5
45.0	170.2	127.9	14.3	168.9	137.1	13.3	167.4	147.1	12.4	165.7	157.7	11.5	163.9	168.9	10.7	161.8	181.8	9.9	157.8	193.6	9.1	152.1	204.6	8.3	145.5	215.2	7.6
46.0	172.8	128.6	14.4	171.4	137.7	13.5	169.9	147.6	12.5	168.2	158.2	11.7	166.4	169.4	10.8	164.3	182.2	10.0	160.0	194.0	9.2	154.1	204.9	8.4	147.5	215.5	7.7
48.0	178.0	129.9	14.7	176.7	138.9	13.8	175.1	148.7	12.8	173.4	159.2	11.9	171.5	170.5	11.1	169.1	183.2	10.2	164.6	194.8	9.4	158.3	205.5	8.6	151.4	216.1	7.9
50.0	183.4	131.4	15.0	182.0	140.3	14.1	180.4	150.0	13.1	178.6	160.4	12.2	176.6	171.6	11.4	173.9	184.0	10.5	169.2	195.6	9.6	162.5	206.1	8.8	154.4	213.8	8.1
52.0	188.9	133.0	15.3	187.5	141.7	14.3	185.8	151.3	13.4	183.9	161.7	12.5	181.9	172.8	11.6	178.7	184.9	10.7	173.9	196.4	9.9	166.8	206.7	9.0	156.2	208.5	8.4
55.0	197.4	135.6	15.7	195.8	144.1	14.8	194.1	153.5	13.8	192.2	163.7	12.9	190.0	174.7	12.0	186.2	186.4	11.1	180.8	197.5	10.2	173.3	207.7	9.3	158.8	200.7	8.8

MODEL: YCIV0187E/V

E IPLV = 13.5

V IPLV = 15.3

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	174.7	142.1	13.3	173.7	149.6	12.5	172.2	161.3	11.6	170.5	173.7	10.7	168.7	186.7	9.9	166.5	201.2	9.2	163.0	213.5	8.5	158.0	223.0	7.9	151.4	231.0	7.3
42.0	180.2	143.2	13.7	179.2	150.5	12.9	177.7	162.1	11.9	175.9	174.5	11.0	174.0	187.5	10.2	171.7	202.1	9.4	167.8	213.9	8.7	162.4	223.4	8.1	155.6	231.5	7.5
44.0	185.8	144.5	14.0	184.8	151.6	13.2	183.2	163.0	12.2	181.4	175.3	11.3	179.4	188.3	10.5	177.0	203.0	9.7	172.7	214.3	9.0	166.9	223.7	8.3	159.9	231.9	7.7
45.0	189.0	141.6	14.3	187.6	152.1	13.3	186.0	163.6	12.4	184.2	175.8	11.5	182.1	188.8	10.6	179.7	203.5	9.8	175.2	214.5	9.1	169.2	223.8	8.4	162.1	232.1	7.8
46.0	191.8	142.3	14.5	190.4	152.7	13.5	188.8	164.1	12.5	187.0	176.3	11.6	184.9	189.2	10.8	182.5	204.0	9.9	177.7	214.6	9.2	171.5	223.9	8.5	164.3	232.3	7.9
48.0	197.5	143.8	14.8	196.2	154.0	13.8	194.5	165.2	12.8	192.6	177.3	11.9	190.5	190.3	11.0	188.0	204.9	10.2	182.8	215.0	9.5	176.2	224.2	8.8	168.7	232.5	8.1
50.0	203.4	145.3	15.1	202.0	155.4	14.1	200.3	166.4	13.1	198.4	178.4	12.2	196.2	191.3	11.3	193.3	205.3	10.4	188.0	215.3	9.7	181.0	224.4	9.0	173.3	232.8	8.3
52.0	209.3	147.0	15.3	207.9	156.9	14.4	206.2	167.8	13.4	204.2	179.7	12.5	202.0	192.4	11.6	198.6	205.8	10.7	193.2	215.7	10.0	185.8	224.5	9.2	177.4	231.9	8.6
55.0	218.4	149.9	15.7	217.0	159.4	14.8	215.3	170.1	13.8	213.2	181.8	12.9	210.9	194.4	12.0	206.8	206.5	11.1	201.2	216.3	10.4	193.2	224.8	9.6	180.3	223.0	9.0

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KWi)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98
6. Certified IAW the ARI Water-Chilling Packages Using the Vapor Compression Cycle Certification Program, which is based on ARI Standard 550/590.

MODEL: YCIV0197E/V**E IPLV = 13.1****V IPLV = 15.2****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	189.8	150.0	13.7	188.2	162.3	12.6	186.4	175.9	11.6	184.5	190.5	10.7	182.5	206.0	9.8	180.1	223.2	9.0	176.4	238.4	8.3	169.4	245.7	7.7	162.4	252.2	7.2
42.0	195.8	151.2	14.0	194.1	163.1	12.9	192.2	176.4	11.9	190.3	190.9	11.0	188.1	206.3	10.1	185.6	223.8	9.3	181.3	238.0	8.5	174.0	245.6	8.0	166.7	252.4	7.4
44.0	201.9	152.7	14.3	200.1	164.2	13.3	198.2	177.1	12.3	196.1	191.4	11.3	193.9	206.8	10.4	191.3	224.3	9.5	186.2	237.5	8.8	178.7	245.3	8.2	171.2	252.3	7.6
45.0	205.0	153.5	14.4	203.2	164.8	13.4	201.3	177.6	12.4	199.1	191.8	11.5	196.8	207.0	10.6	194.2	224.6	9.7	188.7	237.3	8.9	181.1	245.1	8.3	173.5	252.2	7.7
46.0	208.1	154.4	14.6	206.3	165.5	13.6	204.3	178.1	12.6	202.2	192.1	11.6	199.8	207.3	10.7	197.1	224.8	9.8	191.2	237.0	9.0	183.6	244.9	8.4	175.8	252.1	7.8
48.0	214.5	156.4	14.9	212.6	167.0	13.9	210.6	179.3	12.9	208.3	193.0	11.9	205.8	208.0	11.0	203.0	225.4	10.1	196.4	236.4	9.3	188.5	244.4	8.7	180.5	251.8	8.1
50.0	221.0	158.8	15.1	219.1	168.8	14.2	216.9	180.6	13.2	214.5	194.2	12.2	212.0	208.9	11.3	209.0	226.2	10.3	201.6	235.8	9.6	193.5	243.8	8.9	185.3	251.3	8.3
52.0	227.7	161.5	15.3	225.7	171.0	14.4	223.4	182.4	13.5	221.0	195.4	12.5	218.3	209.9	11.6	215.2	227.1	10.6	206.9	235.3	9.8	198.5	243.3	9.2	190.2	250.8	8.5
55.0	237.9	166.2	15.6	235.8	174.7	14.8	233.4	185.3	13.9	230.8	197.8	12.9	228.0	211.8	12.0	223.7	226.6	11.0	214.9	234.6	10.3	206.3	242.4	9.5	197.7	249.9	8.9

MODEL: YCIV0207E/V**E IPLV = 13.6****V IPLV = 15.2****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	201.7	158.0	13.7	200.1	170.5	12.7	198.3	184.2	11.7	196.4	199.0	10.8	194.4	214.7	10.0	192.0	232.3	9.2	188.3	247.5	8.5	182.0	257.3	7.9	174.6	264.2	7.4
42.0	208.1	159.3	14.0	206.4	171.5	13.0	204.5	184.9	12.1	202.5	199.6	11.1	200.4	215.2	10.3	197.9	233.0	9.4	193.7	247.7	8.7	186.9	257.3	8.1	179.3	264.4	7.6
44.0	214.6	160.8	14.4	212.8	172.7	13.4	210.9	185.9	12.4	208.8	200.3	11.4	206.5	215.9	10.6	203.9	233.7	9.7	199.2	247.9	9.0	191.9	257.1	8.4	184.1	264.4	7.8
45.0	217.9	161.7	14.5	216.1	173.3	13.5	214.1	186.4	12.5	211.9	200.7	11.6	209.6	216.2	10.7	206.9	234.0	9.8	202.0	248.0	9.1	194.5	256.9	8.5	186.6	264.4	7.9
46.0	221.3	162.6	14.7	219.4	174.1	13.7	217.4	187.0	12.7	215.1	201.3	11.7	212.8	216.6	10.9	210.0	234.4	10.0	204.8	248.1	9.2	197.1	256.7	8.6	189.0	264.3	8.0
48.0	228.1	164.7	14.9	226.1	175.7	14.0	224.0	188.3	13.0	221.7	202.3	12.0	219.2	217.6	11.1	216.2	235.0	10.2	210.6	248.2	9.5	202.3	256.4	8.8	194.0	264.0	8.2
50.0	235.0	167.0	15.2	233.0	177.7	14.3	230.8	189.9	13.3	228.4	203.6	12.3	225.8	218.6	11.4	222.3	235.2	10.5	216.2	247.7	9.7	207.7	255.9	9.1	199.1	263.6	8.5
52.0	242.1	169.6	15.4	240.0	179.8	14.5	237.7	191.7	13.6	235.2	205.0	12.6	232.5	219.8	11.7	228.5	235.5	10.8	221.8	247.3	10.0	213.1	255.5	9.3	203.0	260.4	8.7
55.0	252.7	174.0	15.8	250.6	183.4	14.9	248.2	194.7	14.0	245.6	207.6	13.0	242.7	222.0	12.1	238.0	236.2	11.2	230.5	246.9	10.4	221.4	254.8	9.7	206.3	249.7	9.2

MODEL: YCIV0227E/V**E IPLV = 13.3****V IPLV = 15.3****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	209.5	163.7	13.7	207.9	176.2	12.7	206.1	189.6	11.8	204.2	203.9	10.9	202.1	219.1	10.1	199.8	236.1	9.4	197.2	254.0	8.6	190.9	264.3	8.1	183.3	271.6	7.5
42.0	216.1	165.1	14.0	214.5	177.4	13.0	212.6	190.7	12.1	210.6	204.9	11.2	208.4	220.0	10.4	205.9	237.1	9.6	203.2	255.1	8.9	196.1	264.5	8.3	188.3	271.8	7.7
44.0	222.9	166.7	14.3	221.2	178.7	13.3	219.2	191.9	12.4	217.1	206.0	11.5	214.9	221.0	10.7	212.2	238.3	9.9	209.4	256.2	9.1	201.5	264.5	8.5	193.4	271.9	7.9
45.0	226.4	167.6	14.5	224.6	179.4	13.5	222.6	192.5	12.6	220.4	206.6	11.7	218.1	221.6	10.8	215.4	238.8	10.0	212.4	256.5	9.2	204.2	264.5	8.6	196.0	271.9	8.1
46.0	229.8	168.5	14.6	228.0	180.3	13.7	226.0	193.2	12.7	223.8	207.2	11.8	221.4	222.2	11.0	218.6	239.4	10.1	215.2	256.5	9.3	206.9	264.4	8.7	198.6	271.9	8.2
48.0	236.9	170.4	14.9	235.0	181.9	14.0	232.9	194.7	13.0	230.6	208.5	12.1	228.1	223.4	11.2	225.2	240.6	10.4	221.0	256.5	9.6	212.5	264.4	9.0	203.9	271.9	8.4
50.0	244.0	172.5	15.2	242.1	183.7	14.2	239.9	196.3	13.3	237.6	210.0	12.4	235.0	224.8	11.5	232.0	241.9	10.6	226.9	256.4	9.8	218.1	264.3	9.2	209.3	271.8	8.6
52.0	251.1	174.8	15.5	249.2	185.7	14.5	247.0	198.0	13.6	244.6	211.6	12.7	242.0	226.2	11.8	238.9	243.2	10.9	232.9	256.4	10.1	223.9	264.3	9.4	214.8	271.7	8.8
55.0	262.1	178.5	15.8	260.1	189.1	14.9	257.8	201.0	14.0	255.3	214.2	13.1	252.5	228.6	12.2	249.2	245.5	11.3	242.1	256.6	10.5	232.7	264.2	9.8	223.2	271.5	9.2

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98
6. Certified IAW the ARI Water-Chilling Packages Using the Vapor Compression Cycle Certification Program, which is based on ARI Standard 550/590.

High Efficiency Ratings – English - 380V/60Hz

MODEL: YCIV0247E/V

E IPLV = 13.0

V IPLV = 15.2

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	232.7	188.7	13.4	230.8	202.8	12.4	228.7	217.8	11.5	226.4	233.8	10.7	223.9	250.7	9.9	221.1	269.7	9.2	216.9	286.7	8.5	210.2	299.0	7.9	202.9	309.9	7.4
42.0	240.0	190.5	13.7	238.0	204.4	12.7	235.8	219.4	11.8	233.4	235.4	11.0	230.8	252.2	10.2	227.9	271.2	9.4	223.2	287.9	8.7	216.0	299.7	8.1	208.5	310.7	7.6
44.0	247.4	192.4	14.0	245.4	206.2	13.0	243.1	221.0	12.1	240.6	237.0	11.2	237.9	253.8	10.4	234.7	272.7	9.6	229.7	289.0	8.9	221.9	300.3	8.3	213.0	308.9	7.8
45.0	251.2	193.5	14.1	249.1	207.1	13.2	246.8	222.0	12.2	244.2	237.9	11.4	241.4	254.7	10.5	238.1	273.3	9.7	232.8	289.3	9.0	225.0	300.6	8.4	214.3	305.5	7.9
46.0	255.1	194.5	14.3	252.9	208.1	13.3	250.5	222.9	12.4	247.9	238.7	11.5	245.1	255.5	10.7	241.5	274.0	9.9	236.0	289.6	9.1	228.0	301.0	8.5	215.6	302.0	8.0
48.0	262.8	196.7	14.5	260.6	210.2	13.6	258.1	224.8	12.6	255.4	240.5	11.8	252.4	257.3	10.9	248.4	275.2	10.1	242.4	290.2	9.4	234.2	301.6	8.7	218.0	294.5	8.3
50.0	270.8	199.2	14.8	268.5	212.4	13.9	265.9	226.9	12.9	263.1	242.5	12.0	260.0	259.2	11.2	255.5	276.5	10.3	248.9	290.9	9.6	240.5	302.2	9.0	220.2	286.6	8.6
52.0	278.9	201.8	15.1	276.5	214.8	14.1	273.8	229.1	13.2	270.9	244.6	12.3	267.7	261.2	11.4	262.8	277.9	10.6	255.5	291.5	9.8	246.9	302.8	9.2	222.2	278.4	8.9
55.0	291.2	205.5	15.5	288.7	218.6	14.5	285.9	232.8	13.6	282.8	248.1	12.7	279.5	264.4	11.8	273.9	280.3	10.9	265.7	292.6	10.2	256.7	303.7	9.5	225.0	266.8	9.4

MODEL: YCIV0267E/V

E IPLV = 13.5

V IPLV = 15.2

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	264.2	207.4	13.7	261.9	224.0	12.7	259.3	242.0	11.7	256.4	261.1	10.8	253.3	281.0	10.0	249.7	303.5	9.2	244.9	324.5	8.4	234.7	336.1	7.8	224.5	346.9	7.3
42.0	272.6	209.1	14.1	270.3	225.3	13.0	267.6	243.0	12.0	264.6	262.0	11.1	261.3	282.1	10.3	257.6	304.7	9.4	251.8	324.8	8.7	241.3	336.5	8.0	230.7	347.6	7.5
44.0	281.2	210.9	14.4	278.8	226.8	13.4	276.0	244.2	12.4	272.9	263.1	11.4	269.5	283.1	10.5	265.6	305.9	9.7	258.9	324.8	8.9	247.9	336.7	8.3	237.1	348.0	7.7
45.0	285.5	211.9	14.6	283.1	227.6	13.5	280.3	244.9	12.5	277.2	263.7	11.6	273.7	283.7	10.7	269.7	306.5	9.8	262.4	324.8	9.0	251.3	336.8	8.4	240.3	348.2	7.8
46.0	289.9	213.1	14.7	287.4	228.5	13.7	284.6	245.7	12.7	281.4	264.4	11.7	277.9	284.3	10.8	273.8	307.1	9.9	266.0	324.8	9.2	254.7	336.9	8.5	243.5	348.4	7.9
48.0	298.8	215.5	15.0	296.3	230.5	14.0	293.4	247.4	13.0	290.1	265.8	12.0	286.5	285.6	11.1	282.2	308.4	10.2	273.3	324.8	9.4	261.7	337.0	8.7	250.2	348.5	8.1
50.0	307.8	218.3	15.3	305.3	232.8	14.3	302.3	249.3	13.3	299.0	267.6	12.3	295.2	287.1	11.4	290.8	309.8	10.5	280.7	324.7	9.7	268.8	336.9	8.9	256.9	348.7	8.3
52.0	317.0	221.3	15.5	314.5	235.4	14.6	311.5	251.5	13.6	308.0	269.4	12.6	304.2	288.8	11.7	299.6	311.4	10.7	288.2	324.7	9.9	276.0	336.9	9.2	263.8	348.7	8.5
55.0	331.1	226.5	15.9	328.5	239.9	15.0	325.4	255.3	14.0	321.9	272.6	13.0	317.9	291.6	12.1	312.4	312.6	11.2	299.8	324.7	10.3	287.1	336.8	9.6	274.4	348.6	8.8

MODEL: YCIV0287E/V

E IPLV = 13.2

V IPLV = 15.1

AIR TEMPERATURE ON - CONDENSER (°F)

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	281.2	217.9	13.9	278.8	235.8	12.8	276.1	255.4	11.8	273.1	276.5	10.9	270.0	298.6	10.0	266.3	323.6	9.2	261.8	347.8	8.4	251.2	358.5	7.9	240.7	367.9	7.3
42.0	290.1	219.7	14.2	287.6	236.9	13.2	284.8	256.2	12.1	281.7	277.1	11.2	278.4	299.3	10.3	274.6	324.3	9.4	269.1	347.3	8.7	258.1	358.4	8.1	247.2	368.2	7.5
44.0	299.3	221.7	14.5	296.7	238.4	13.5	293.8	257.2	12.5	290.5	277.8	11.5	287.1	299.9	10.6	283.1	325.2	9.7	276.5	346.7	8.9	265.1	358.1	8.3	253.9	368.3	7.7
45.0	303.9	222.9	14.7	301.3	239.3	13.7	298.3	257.8	12.6	295.0	278.3	11.7	291.5	300.3	10.7	287.4	325.6	9.8	280.3	346.3	9.1	268.7	357.8	8.4	257.3	368.2	7.8
46.0	308.6	224.2	14.9	305.9	240.3	13.8	302.9	258.6	12.8	299.6	278.8	11.8	296.0	300.7	10.9	291.8	326.0	10.0	284.1	345.9	9.2	272.4	357.5	8.5	260.8	368.0	8.0
48.0	318.1	227.0	15.1	315.4	242.4	14.1	312.2	260.2	13.1	308.8	280.0	12.1	305.0	301.7	11.2	300.7	326.9	10.2	291.8	345.2	9.5	279.8	356.9	8.8	267.8	367.6	8.2
50.0	327.8	230.4	15.4	325.0	245.0	14.4	321.8	262.2	13.4	318.2	281.7	12.4	314.3	303.0	11.5	309.8	327.9	10.5	299.7	344.4	9.7	287.3	356.1	9.0	274.9	367.1	8.4
52.0	337.8	234.2	15.6	334.8	248.1	14.7	331.5	264.5	13.7	327.8	283.6	12.7	323.8	304.4	11.8	319.1	329.1	10.8	307.7	343.7	10.0	295.0	355.3	9.3	282.2	366.4	8.6
55.0	353.0	240.9	15.9	349.9	253.4	15.1	346.5	268.9	14.1	342.7	286.9	13.2	338.4	307.1	12.2	333.2	331.2	11.2	320.0	342.8	10.4	306.7	354.4	9.7	293.5	365.2	9.0

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98

MODEL: YCIV0327E/V**E IPLV = 14.1****V IPLV = 15.0****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	305.7	240.0	13.7	303.0	259.0	12.7	300.2	279.9	11.7	297.2	302.4	10.8	293.9	326.1	10.0	290.2	352.9	9.2	283.6	374.3	8.5	273.3	387.8	7.9	262.0	397.8	7.4
42.0	315.4	242.0	14.1	312.6	260.6	13.1	309.7	281.0	12.1	306.4	303.3	11.1	303.0	327.1	10.3	299.1	353.9	9.4	291.6	374.4	8.7	280.6	387.7	8.1	269.0	398.2	7.6
44.0	325.4	244.3	14.4	322.5	262.4	13.4	319.3	282.6	12.4	315.9	304.5	11.4	312.3	328.1	10.6	308.2	355.1	9.7	299.7	374.5	9.0	288.1	387.5	8.3	276.1	398.3	7.8
45.0	330.4	245.6	14.5	327.5	263.4	13.5	324.3	283.4	12.5	320.8	305.2	11.6	317.1	328.7	10.7	312.8	355.7	9.8	303.9	374.5	9.1	292.0	387.3	8.5	279.7	398.2	7.9
46.0	335.5	247.0	14.7	332.5	264.6	13.7	329.2	284.3	12.7	325.7	306.0	11.7	321.9	329.3	10.8	317.5	356.3	9.9	308.1	374.5	9.2	295.9	387.1	8.6	283.4	398.2	8.0
48.0	345.9	250.2	15.0	342.8	267.1	14.0	339.4	286.3	13.0	335.6	307.7	12.0	331.6	330.8	11.1	326.7	357.1	10.2	316.6	374.4	9.5	303.7	386.6	8.8	290.9	397.8	8.2
50.0	356.6	253.7	15.2	353.3	270.0	14.3	349.7	288.8	13.3	345.8	309.6	12.3	341.7	332.5	11.4	335.8	357.1	10.5	325.0	373.7	9.7	311.7	386.0	9.1	298.5	397.4	8.4
52.0	367.5	257.7	15.5	364.0	273.3	14.6	360.3	291.5	13.6	356.2	311.9	12.6	351.9	334.3	11.7	345.0	357.3	10.8	333.5	373.2	10.0	319.9	385.3	9.3	304.6	393.2	8.7
55.0	384.2	264.6	15.8	380.5	279.0	14.9	376.6	296.2	14.0	372.3	315.9	13.0	367.7	337.8	12.1	359.2	357.9	11.2	346.6	372.5	10.4	332.4	384.3	9.7	309.4	377.3	9.2

MODEL: YCIV0357E/V**E IPLV = 12.4****V IPLV = 15.6****AIR TEMPERATURE ON - CONDENSER (°F)**

LCWT (°F)	75.0			80.0			85.0			90.0			95.0			100.0			105.0			110.0			115.0		
	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER	TONS	KW	EER
40.0	346.6	278.3	13.5	343.6	298.4	12.5	340.1	320.0	11.7	336.3	342.9	10.8	332.2	367.0	10.0	327.5	394.3	9.3	321.2	419.8	8.6	311.7	439.6	8.0	301.2	457.0	7.4
42.0	357.6	281.0	13.8	354.5	301.0	12.8	351.0	322.5	11.9	347.0	345.4	11.1	342.7	369.4	10.3	337.8	396.8	9.5	330.8	421.5	8.8	320.6	440.8	8.2	309.7	458.3	7.6
44.0	368.9	284.0	14.1	365.6	303.9	13.1	362.0	325.2	12.2	357.9	347.9	11.4	353.5	371.9	10.5	348.3	399.3	9.7	340.5	423.3	9.0	329.7	442.0	8.4	318.4	459.5	7.8
45.0	374.5	285.5	14.2	371.3	305.4	13.3	367.6	326.6	12.4	363.5	349.3	11.5	358.9	373.2	10.7	353.7	400.6	9.8	345.5	424.1	9.1	334.4	442.6	8.5	322.9	460.1	7.9
46.0	380.3	287.3	14.4	377.0	306.9	13.4	373.3	328.1	12.5	369.0	350.8	11.6	364.4	374.8	10.8	359.1	402.0	10.0	350.5	425.0	9.2	339.1	443.2	8.6	327.3	460.8	8.0
48.0	391.9	290.7	14.7	388.6	310.1	13.7	384.7	331.2	12.8	380.4	353.7	11.9	375.7	377.6	11.1	369.9	404.7	10.2	360.8	426.8	9.5	348.7	444.4	8.8	336.5	462.0	8.2
50.0	403.8	294.3	14.9	400.4	313.6	14.0	396.5	334.4	13.0	392.0	356.8	12.2	387.1	380.6	11.3	380.7	406.7	10.5	370.9	428.1	9.7	358.4	445.7	9.0	341.0	452.1	8.5
52.0	415.9	298.3	15.2	412.4	317.3	14.2	408.4	338.0	13.3	403.8	360.2	12.4	398.8	383.9	11.6	391.6	408.8	10.7	381.1	429.5	9.9	368.3	447.0	9.3	344.4	439.8	8.8
55.0	434.4	303.6	15.6	431.1	322.3	14.7	426.7	343.6	13.7	422.0	365.5	12.8	416.7	389.1	11.9	408.3	412.2	11.1	396.9	431.8	10.3	383.6	449.0	9.6	349.0	421.8	9.3

NOTES:

1. kW = Compressor Input Power
2. EER = Chiller EER (includes power from compressors, fans, and control panels 0.8 KW)
3. LCWT = Leaving Chilled Water Temperature
4. Ratings based on 2.4 GPM cooler water per ton
5. Rated IAW ARI Standard 550/590-98

Standard Efficiency Ratings – SI - 380V/60Hz

MODEL: YCIV0157S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	528.8	133.1	3.6	520.9	152.2	3.2	511.8	172.8	2.8	497.4	196.1	2.4	462.2	214.6	2.0	455.0	218.5	2.0
6.0	543.2	134.0	3.7	535.0	152.9	3.2	525.5	173.7	2.8	509.5	196.7	2.4	473.3	215.3	2.1	465.8	219.2	2.0
7.0	557.9	134.9	3.8	549.4	153.8	3.3	539.5	174.5	2.9	521.7	197.3	2.5	484.5	216.0	2.1	476.8	219.9	2.0
8.0	572.9	135.8	3.8	564.1	154.6	3.4	553.7	175.4	2.9	533.9	197.9	2.5	495.5	216.9	2.2	487.9	220.6	2.1
9.0	588.0	136.8	3.9	578.9	155.6	3.4	568.2	176.3	3.0	546.3	198.5	2.6	507.2	217.5	2.2	499.2	221.3	2.1
10.0	603.4	137.9	4.0	594.1	156.6	3.5	583.0	177.3	3.1	558.9	199.1	2.6	519.0	218.1	2.2	510.8	222.0	2.2
11.0	619.1	139.1	4.1	609.5	157.6	3.6	598.0	178.4	3.1	571.6	199.7	2.7	531.0	218.7	2.3	522.6	222.6	2.2
12.0	635.0	140.3	4.1	625.1	158.7	3.6	613.2	179.4	3.2	584.5	200.3	2.7	542.9	219.3	2.3	532.1	221.1	2.3
13.0	651.2	141.6	4.2	641.0	159.8	3.7	628.7	180.5	3.2	597.5	201.0	2.8	555.1	219.9	2.4	537.5	215.9	2.3

MODEL: YCIV0177S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	587.3	146.6	3.7	576.4	167.9	3.2	563.2	190.9	2.8	536.0	208.9	2.4	491.4	218.9	2.1	462.3	206.9	2.1
6.0	603.7	147.6	3.8	592.6	168.9	3.3	579.1	192.0	2.8	550.1	209.5	2.5	496.5	214.8	2.2	467.9	203.3	2.2
7.0	620.4	148.6	3.8	609.2	169.9	3.3	595.2	193.1	2.9	563.9	210.0	2.5	502.4	210.9	2.2	474.0	199.7	2.2
8.0	637.4	149.7	3.9	626.0	170.9	3.4	611.2	193.9	3.0	577.7	210.4	2.6	508.8	207.2	2.3	479.4	195.7	2.3
9.0	654.7	150.8	4.0	643.0	171.9	3.5	626.8	194.3	3.0	591.8	210.7	2.6	514.8	203.2	2.4	484.4	191.6	2.4
10.0	672.0	152.0	4.1	660.4	173.1	3.5	642.6	194.8	3.1	605.9	211.0	2.7	520.5	199.0	2.5	488.9	187.6	2.4
11.0	689.4	153.4	4.1	677.8	174.4	3.6	658.6	195.3	3.2	620.3	211.4	2.8	525.7	194.9	2.5	493.2	183.6	2.5
12.0	707.1	154.9	4.2	695.4	175.6	3.7	674.7	195.8	3.2	634.8	211.7	2.8	530.6	190.8	2.6	497.4	179.6	2.6
13.0	725.1	156.4	4.3	713.3	177.0	3.7	691.0	196.4	3.3	649.5	212.0	2.9	534.7	186.7	2.7	501.5	175.7	2.7

MODEL: YCIV0187S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	639.4	158.1	3.7	628.8	180.6	3.2	616.7	205.2	2.8	594.6	230.0	2.4	551.9	245.6	2.1	543.3	248.7	2.1
6.0	657.2	159.2	3.8	646.3	181.6	3.3	633.7	206.2	2.9	608.9	230.4	2.5	564.8	246.2	2.2	556.2	249.2	2.1
7.0	675.3	160.5	3.9	664.0	182.7	3.4	651.0	207.3	2.9	623.5	230.8	2.5	578.2	246.7	2.2	569.2	249.7	2.2
8.0	693.7	161.8	3.9	682.0	183.9	3.4	668.4	208.5	3.0	638.4	231.1	2.6	591.9	247.1	2.3	582.6	250.2	2.2
9.0	712.5	163.2	4.0	700.4	185.1	3.5	686.2	209.8	3.1	653.5	231.5	2.7	605.8	247.4	2.3	596.2	250.6	2.2
10.0	731.6	164.7	4.1	719.0	186.5	3.6	704.3	211.0	3.1	668.7	231.8	2.7	619.9	247.8	2.4	605.6	247.6	2.3
11.0	751.0	166.3	4.1	738.0	187.9	3.6	722.8	212.3	3.2	683.9	232.2	2.8	634.3	248.1	2.4	610.8	241.4	2.4
12.0	770.7	168.0	4.2	757.3	189.4	3.7	741.6	213.7	3.2	699.5	232.6	2.8	648.9	248.4	2.5	616.4	235.6	2.5
13.0	790.7	169.9	4.3	776.9	191.0	3.8	760.7	215.3	3.3	715.3	233.0	2.9	660.2	246.2	2.5	621.8	229.7	2.5

NOTES:

1. kWo = Unit kW Cooling Capacity Output
2. KWi = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW

MODEL: YCIV0207S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	689.5	170.6	3.7	676.6	196.8	3.2	662.1	226.0	2.8	629.2	248.2	2.4	564.5	248.2	2.1	530.0	233.3	2.1
6.0	709.0	171.7	3.8	695.5	197.6	3.3	680.0	226.6	2.8	644.2	248.0	2.5	569.7	242.9	2.2	536.2	228.8	2.2
7.0	728.8	173.0	3.9	714.8	198.5	3.4	697.4	226.7	2.9	659.6	247.8	2.5	576.2	238.0	2.3	542.0	223.9	2.3
8.0	749.1	174.4	4.0	734.4	199.5	3.4	715.2	226.8	3.0	675.3	247.4	2.6	582.3	232.8	2.4	547.6	219.0	2.3
9.0	769.7	176.1	4.0	754.5	200.6	3.5	733.3	227.1	3.0	691.2	247.0	2.6	588.4	227.7	2.4	553.1	214.3	2.4
10.0	790.7	178.1	4.1	774.9	202.0	3.6	751.7	227.4	3.1	707.2	246.7	2.7	594.3	222.6	2.5	558.1	209.8	2.5
11.0	812.1	180.2	4.2	795.7	203.6	3.6	770.3	227.8	3.2	723.6	246.3	2.8	599.9	217.8	2.6	563.0	205.4	2.6
12.0	834.0	182.6	4.2	816.9	205.3	3.7	789.3	228.2	3.2	740.2	245.9	2.8	605.2	213.2	2.7	567.7	200.9	2.6
13.0	856.2	185.1	4.3	838.5	207.2	3.8	808.6	228.9	3.3	757.1	245.6	2.9	610.1	208.7	2.7	572.5	196.6	2.7

MODEL: YCIV0227S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	748.4	182.6	3.8	735.1	208.5	3.3	720.1	236.9	2.8	690.4	263.0	2.5	640.3	275.7	2.2	630.5	278.0	2.1
6.0	769.6	184.0	3.8	755.7	209.7	3.3	739.9	238.2	2.9	707.1	263.1	2.5	655.5	276.0	2.2	645.2	278.3	2.2
7.0	791.1	185.5	3.9	776.7	211.0	3.4	760.1	239.6	3.0	724.0	263.2	2.6	671.0	276.2	2.3	660.4	278.6	2.2
8.0	813.1	187.2	4.0	798.1	212.4	3.5	780.9	241.0	3.0	741.2	263.3	2.7	686.8	276.3	2.3	676.0	278.7	2.3
9.0	835.5	189.0	4.1	819.9	214.1	3.6	802.0	242.4	3.1	758.8	263.3	2.7	702.9	276.4	2.4	690.9	278.2	2.3
10.0	858.4	190.9	4.1	842.2	215.7	3.6	823.6	244.0	3.2	776.3	263.4	2.8	719.2	276.5	2.5	697.1	272.2	2.4
11.0	881.7	193.0	4.2	864.9	217.5	3.7	845.6	245.6	3.2	794.4	263.5	2.8	735.9	276.4	2.5	703.5	266.0	2.5
12.0	905.3	195.2	4.3	888.1	219.4	3.8	867.9	247.4	3.3	812.7	263.6	2.9	752.5	276.2	2.6	710.1	259.7	2.6
13.0	929.1	197.6	4.3	911.5	221.4	3.8	890.8	249.3	3.4	831.3	263.7	3.0	759.3	269.5	2.7	716.0	253.0	2.7

MODEL: YCIV0247S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	821.2	201.2	3.7	807.2	229.1	3.3	791.2	259.7	2.8	762.5	289.7	2.5	716.5	309.3	2.2	707.4	313.0	2.1
6.0	844.2	202.8	3.8	829.7	230.5	3.3	812.9	261.2	2.9	781.4	290.3	2.5	733.9	310.0	2.2	724.3	313.8	2.2
7.0	867.7	204.5	3.9	852.5	232.1	3.4	834.9	262.9	3.0	800.6	290.9	2.6	751.6	310.7	2.3	740.0	313.3	2.2
8.0	891.5	206.4	4.0	875.8	233.9	3.5	857.5	264.6	3.0	820.1	291.5	2.7	769.8	311.3	2.3	747.8	307.2	2.3
9.0	915.8	208.4	4.0	899.5	235.7	3.5	880.5	266.3	3.1	839.9	292.1	2.7	788.2	311.9	2.4	755.3	300.7	2.4
10.0	940.5	210.4	4.1	923.7	237.6	3.6	904.0	268.2	3.2	859.8	292.8	2.8	804.7	311.1	2.4	762.4	293.8	2.4
11.0	965.7	212.7	4.2	948.2	239.6	3.7	927.8	270.0	3.2	880.3	293.4	2.8	812.6	304.1	2.5	769.0	286.5	2.5
12.0	991.2	215.1	4.2	973.3	241.7	3.7	952.1	272.1	3.3	901.1	294.0	2.9	820.0	296.6	2.6	775.2	279.1	2.6
13.0	1017.2	217.0	4.3	998.6	243.9	3.8	976.9	274.2	3.3	922.2	294.7	2.9	826.9	289.0	2.7	780.9	272.0	2.7

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW

Standard Efficiency Ratings – SI - 380V/60Hz

MODEL: YCIV267S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	894.3	219.6	3.7	879.6	249.4	3.3	862.6	282.2	2.9	834.9	316.1	2.5	793.0	342.4	2.2	784.6	347.5	2.1
6.0	919.1	221.4	3.8	903.8	251.2	3.3	886.1	284.0	2.9	856.0	317.2	2.5	812.6	343.6	2.2	803.8	348.8	2.2
7.0	944.5	223.3	3.9	928.6	253.0	3.4	909.9	286.0	3.0	877.4	318.3	2.6	832.6	344.8	2.3	821.7	348.8	2.2
8.0	970.2	225.4	4.0	953.7	255.0	3.5	934.4	287.9	3.0	899.1	319.4	2.7	853.0	345.9	2.3	829.3	341.0	2.3
9.0	996.3	227.5	4.0	979.4	257.0	3.5	959.2	290.0	3.1	921.3	320.5	2.7	873.9	347.1	2.4	837.1	333.1	2.4
10.0	1023.0	229.8	4.1	1005.4	259.2	3.6	984.6	292.1	3.2	943.6	321.7	2.8	892.6	346.7	2.4	844.9	325.2	2.5
11.0	1050.0	232.2	4.2	1031.8	261.5	3.7	1010.4	294.2	3.2	966.5	322.9	2.8	900.9	338.2	2.5	852.6	317.4	2.5
12.0	1077.5	234.8	4.2	1058.8	263.8	3.7	1036.6	296.5	3.3	989.7	324.0	2.9	909.1	329.9	2.6	860.1	309.8	2.6
13.0	1105.6	236.2	4.3	1086.0	266.3	3.8	1063.2	298.9	3.3	1013.3	325.3	2.9	917.1	321.7	2.7	867.0	302.7	2.7

MODEL: YCIV287S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	949.5	231.0	3.8	932.1	265.4	3.2	911.8	303.1	2.8	873.5	336.2	2.4	791.6	344.8	2.2	743.1	325.2	2.1
6.0	976.3	232.5	3.8	958.3	266.7	3.3	937.2	304.4	2.9	895.5	336.6	2.5	799.7	338.3	2.2	752.1	319.4	2.2
7.0	1003.6	234.1	3.9	985.0	268.0	3.4	962.8	305.6	2.9	917.2	336.9	2.6	808.0	331.5	2.3	761.5	313.7	2.3
8.0	1031.4	235.8	4.0	1012.3	269.5	3.5	988.1	306.3	3.0	939.4	337.1	2.6	818.0	325.4	2.4	770.3	307.5	2.3
9.0	1059.7	237.8	4.1	1040.1	271.0	3.6	1013.9	307.0	3.1	962.0	337.2	2.7	827.4	319.0	2.4	778.7	301.3	2.4
10.0	1088.5	240.0	4.2	1068.4	272.8	3.6	1040.2	307.9	3.2	985.0	337.2	2.7	836.6	312.5	2.5	786.4	295.0	2.5
11.0	1117.8	242.5	4.2	1097.2	274.7	3.7	1066.9	308.9	3.2	1008.2	337.3	2.8	845.3	306.1	2.6	793.4	288.8	2.6
12.0	1147.6	245.2	4.3	1126.5	276.9	3.8	1094.0	309.9	3.3	1031.7	337.4	2.9	853.4	299.8	2.7	800.2	282.7	2.6
13.0	1177.9	248.0	4.4	1156.3	279.2	3.8	1121.6	311.1	3.4	1055.6	337.6	2.9	860.6	293.5	2.7	806.8	276.6	2.7

MODEL: YCIV307S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1055.2	254.8	3.8	1036.1	294.0	3.3	1014.7	337.5	2.8	970.6	374.3	2.4	868.6	373.3	2.2	815.4	351.0	2.2
6.0	1084.9	256.5	3.9	1064.9	295.1	3.3	1042.0	338.3	2.9	993.7	374.1	2.5	876.5	365.3	2.3	824.1	343.8	2.2
7.0	1115.3	258.3	4.0	1094.4	296.3	3.4	1069.2	338.7	3.0	1017.4	373.7	2.6	885.7	357.6	2.3	833.7	336.9	2.3
8.0	1146.3	260.4	4.0	1124.5	297.7	3.5	1097.1	339.2	3.0	1041.6	373.3	2.6	896.0	350.3	2.4	842.6	329.7	2.4
9.0	1178.0	262.8	4.1	1155.3	299.4	3.6	1125.4	339.9	3.1	1066.2	372.7	2.7	905.5	342.6	2.5	851.2	322.6	2.5
10.0	1210.2	265.6	4.2	1186.6	301.4	3.7	1154.3	340.6	3.2	1091.1	372.1	2.8	914.9	335.1	2.6	859.2	315.8	2.5
11.0	1243.0	268.7	4.3	1218.5	303.7	3.7	1183.7	341.5	3.2	1116.3	371.6	2.8	923.7	327.9	2.6	866.8	309.2	2.6
12.0	1276.6	272.1	4.3	1251.1	306.1	3.8	1213.7	342.5	3.3	1142.1	371.0	2.9	932.2	321.0	2.7	874.2	302.6	2.7
13.0	1310.6	276.0	4.4	1284.3	308.9	3.9	1244.1	343.9	3.4	1168.3	370.5	3.0	939.9	314.3	2.8	881.4	296.1	2.8

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW

MODEL: YCIV357S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1191.3	291.5	3.7	1170.8	332.4	3.3	1147.5	377.2	2.8	1105.5	420.8	2.5	1034.8	446.6	2.2	1020.8	451.5	2.1
6.0	1224.9	293.8	3.8	1203.5	334.4	3.3	1179.0	379.3	2.9	1132.5	421.5	2.5	1059.6	447.6	2.2	1045.0	452.5	2.2
7.0	1259.1	296.1	3.9	1236.8	336.6	3.4	1211.2	381.6	3.0	1160.1	422.2	2.6	1085.1	448.4	2.3	1070.0	453.4	2.2
8.0	1294.0	298.7	4.0	1270.8	339.0	3.5	1244.0	384.0	3.0	1188.2	422.8	2.6	1111.1	449.1	2.3	1085.2	447.5	2.3
9.0	1329.5	301.6	4.1	1305.4	341.5	3.5	1277.5	386.5	3.1	1216.8	423.4	2.7	1137.4	449.8	2.4	1096.7	438.8	2.4
10.0	1365.7	304.6	4.1	1340.7	344.2	3.6	1311.7	389.0	3.2	1245.7	424.1	2.8	1164.1	450.5	2.4	1107.5	429.2	2.4
11.0	1402.6	307.8	4.2	1376.7	347.0	3.7	1346.7	391.6	3.2	1275.0	424.8	2.8	1179.6	443.2	2.5	1117.3	418.9	2.5
12.0	1439.8	311.3	4.3	1413.4	350.1	3.8	1382.2	394.5	3.3	1305.0	425.4	2.9	1190.8	432.9	2.6	1126.4	408.1	2.6
13.0	1477.6	314.5	4.3	1450.3	353.2	3.8	1418.5	397.5	3.3	1335.5	426.1	3.0	1201.1	421.9	2.7	1134.7	397.2	2.7

MODEL: YCIV397S/P

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1337.3	328.4	3.7	1315.3	373.1	3.3	1289.8	422.2	2.9	1249.5	473.4	2.5	1187.1	512.7	2.2	1174.5	520.5	2.1
6.0	1374.7	331.0	3.8	1351.8	375.7	3.3	1325.2	424.9	2.9	1280.8	475.2	2.5	1216.1	514.6	2.2	1203.0	522.5	2.2
7.0	1412.9	333.8	3.9	1389.0	378.4	3.4	1361.1	427.8	3.0	1312.9	476.8	2.6	1246.0	516.4	2.3	1232.4	524.3	2.2
8.0	1451.9	336.8	4.0	1426.9	381.4	3.5	1397.9	430.7	3.0	1345.7	478.4	2.7	1276.5	518.2	2.3	1248.8	516.4	2.3
9.0	1491.4	340.1	4.0	1465.7	384.4	3.5	1435.3	433.8	3.1	1379.2	480.1	2.7	1307.7	519.9	2.4	1260.5	504.6	2.4
10.0	1531.8	343.5	4.1	1505.1	387.5	3.6	1473.6	436.9	3.2	1412.8	481.9	2.8	1339.2	521.7	2.4	1272.3	492.8	2.4
11.0	1572.9	347.0	4.2	1545.3	390.8	3.7	1512.7	440.1	3.2	1447.4	483.6	2.8	1356.6	512.7	2.5	1283.9	481.0	2.5
12.0	1613.6	350.8	4.2	1586.1	394.5	3.7	1552.4	443.5	3.3	1482.4	485.4	2.9	1369.0	500.1	2.6	1295.3	469.5	2.6
13.0	0.0	0.0	0.0	1626.5	398.0	3.8	1593.0	447.0	3.3	1518.1	487.2	2.9	1381.2	487.7	2.7	1306.2	458.5	2.7

NOTES:

1. kWo = Unit kW Cooling Capacity Output
2. kWi = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW

High Efficiency Ratings – SI - 380V/60Hz

MODEL: YCIV0157E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	525.0	123.1	3.9	515.6	139.0	3.4	503.3	156.2	3.0	487.8	176.4	2.6	449.0	192.6	2.2	441.1	196.0	2.1
6.0	539.7	124.0	3.9	530.4	140.2	3.5	518.1	157.4	3.0	500.9	177.3	2.6	460.8	193.4	2.2	452.7	196.7	2.2
7.0	554.7	125.0	4.0	545.4	141.3	3.5	533.0	158.5	3.1	514.0	178.2	2.7	472.8	194.1	2.3	464.5	197.5	2.2
8.0	569.9	126.1	4.1	560.7	142.4	3.6	548.1	159.7	3.2	527.2	179.1	2.7	484.9	195.0	2.3	476.5	198.2	2.3
9.0	585.2	127.1	4.2	576.2	143.5	3.7	563.5	161.0	3.2	540.5	180.0	2.8	497.0	195.9	2.4	488.4	199.1	2.3
10.0	600.7	128.2	4.2	591.8	144.7	3.7	579.1	162.2	3.3	554.0	180.9	2.9	509.5	196.8	2.4	500.6	200.0	2.4
11.0	616.4	129.2	4.3	607.7	145.8	3.8	594.9	163.5	3.4	567.6	181.9	2.9	522.3	197.7	2.5	513.2	200.9	2.4
12.0	632.2	130.3	4.4	623.8	147.0	3.9	610.9	164.8	3.4	581.2	182.9	3.0	535.2	198.6	2.5	525.9	201.8	2.4
13.0	648.3	131.3	4.5	640.1	148.3	4.0	627.2	166.2	3.5	595.0	183.8	3.0	548.3	199.5	2.6	538.8	202.7	2.5

MODEL: YCIV0177E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	558.7	129.2	3.9	550.3	147.1	3.4	540.3	167.0	3.0	525.1	189.7	2.6	492.2	209.6	2.2	484.3	213.4	2.1
6.0	574.5	130.1	4.0	565.7	147.9	3.5	555.3	167.8	3.0	538.7	190.4	2.6	504.1	210.2	2.2	496.2	213.9	2.2
7.0	590.5	131.1	4.0	581.5	148.8	3.6	570.6	168.6	3.1	552.7	191.0	2.7	516.4	210.7	2.3	508.1	214.6	2.2
8.0	606.9	132.2	4.1	597.5	149.7	3.6	586.3	169.5	3.2	566.8	191.7	2.7	528.8	211.3	2.3	520.3	215.1	2.3
9.0	623.5	133.4	4.2	613.9	150.7	3.7	602.3	170.4	3.3	581.3	192.4	2.8	541.5	211.8	2.4	532.8	215.7	2.3
10.0	640.4	134.6	4.3	630.5	151.8	3.8	618.5	171.4	3.3	596.0	193.1	2.9	554.4	212.3	2.4	545.5	216.2	2.4
11.0	657.7	136.0	4.4	647.5	153.0	3.9	635.1	172.5	3.4	610.9	193.9	2.9	567.6	212.9	2.5	551.5	211.4	2.4
12.0	675.2	137.4	4.4	664.8	154.3	3.9	652.0	173.6	3.5	626.1	194.7	3.0	580.9	213.4	2.5	557.2	206.6	2.5
13.0	693.1	139.0	4.5	682.3	155.6	4.0	669.2	174.8	3.5	641.6	195.5	3.1	594.4	214.0	2.6	562.8	202.0	2.6

MODEL: YCIV0187E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	621.1	143.4	3.9	611.6	164.1	3.4	600.1	187.0	3.0	582.8	211.7	2.6	547.1	228.0	2.2	538.6	230.9	2.2
6.0	638.5	144.3	4.0	628.9	164.8	3.5	617.0	187.7	3.0	598.1	212.0	2.6	560.8	228.4	2.3	552.0	231.3	2.2
7.0	656.2	145.3	4.1	646.4	165.6	3.5	634.2	188.4	3.1	613.8	212.3	2.7	574.6	228.7	2.3	565.6	231.6	2.3
8.0	674.1	146.4	4.1	664.2	166.5	3.6	651.7	189.3	3.2	629.7	212.6	2.7	588.8	229.0	2.4	579.5	232.0	2.3
9.0	692.3	147.7	4.2	682.2	167.5	3.7	669.4	190.2	3.2	645.8	212.9	2.8	603.2	229.2	2.5	593.7	232.2	2.4
10.0	710.7	149.0	4.3	700.4	168.6	3.8	687.3	191.1	3.3	662.3	213.3	2.9	617.8	229.4	2.5	608.1	232.4	2.4
11.0	729.4	150.5	4.4	719.0	169.8	3.9	705.6	192.2	3.4	678.9	213.6	3.0	632.7	229.6	2.6	622.8	232.6	2.5
12.0	748.4	152.0	4.4	737.8	171.1	3.9	724.1	193.3	3.5	695.7	214.0	3.0	647.8	229.7	2.6	632.7	229.6	2.6
13.0	767.7	153.7	4.5	756.9	172.4	4.0	742.9	194.5	3.5	712.8	214.4	3.1	663.1	229.9	2.7	638.4	224.0	2.7

NOTES:

1. kWo = Unit kW Cooling Capacity Output
2. KWi = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW

MODEL: YCIV0197E/V**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	672.7	155.1	3.9	661.6	178.9	3.4	648.7	206.1	2.9	631.4	236.7	2.5	586.1	249.7	2.2	577.1	252.0	2.2
6.0	691.7	156.1	4.0	680.1	179.4	3.5	666.7	206.4	3.0	647.0	236.3	2.6	600.4	249.7	2.3	591.1	252.1	2.2
7.0	711.0	157.3	4.1	699.0	180.0	3.6	685.1	206.8	3.1	662.9	235.8	2.6	614.9	249.6	2.3	605.4	252.0	2.3
8.0	730.8	158.7	4.2	718.3	180.9	3.6	703.9	207.3	3.1	678.8	235.3	2.7	629.7	249.3	2.4	620.0	251.8	2.3
9.0	750.9	160.4	4.2	737.9	181.8	3.7	723.0	207.9	3.2	695.2	234.8	2.8	645.0	249.0	2.4	634.8	251.6	2.4
10.0	771.3	162.3	4.3	758.0	183.0	3.8	742.4	208.8	3.3	711.9	234.3	2.8	660.3	248.5	2.5	650.0	251.1	2.4
11.0	792.1	164.4	4.4	778.4	184.3	3.9	762.2	209.6	3.4	728.8	233.8	2.9	675.9	248.0	2.6	665.4	250.7	2.5
12.0	813.3	166.8	4.4	799.1	186.0	3.9	782.4	210.6	3.4	745.9	233.3	3.0	691.8	247.5	2.6	681.0	250.2	2.6
13.0	834.9	169.5	4.5	820.2	187.8	4.0	803.0	211.8	3.5	763.0	233.0	3.1	707.8	247.0	2.7	696.9	249.6	2.6

MODEL: YCIV0207E/V**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	715.1	163.2	3.9	703.9	187.3	3.4	691.1	214.8	3.0	672.4	245.0	2.6	630.3	261.6	2.3	620.8	264.1	2.2
6.0	735.3	164.3	4.0	723.6	188.0	3.5	710.2	215.4	3.0	689.7	245.2	2.6	645.5	261.6	2.3	635.9	264.1	2.3
7.0	755.9	165.6	4.1	743.7	188.9	3.6	729.7	216.0	3.1	707.4	245.3	2.7	661.1	261.5	2.4	651.2	264.1	2.3
8.0	776.9	167.1	4.2	764.2	189.8	3.7	749.5	216.7	3.2	725.4	245.4	2.8	677.0	261.3	2.4	666.7	264.0	2.4
9.0	798.4	168.8	4.3	785.1	191.0	3.8	769.8	217.5	3.3	743.7	245.5	2.8	693.1	261.0	2.5	682.6	263.7	2.4
10.0	820.2	170.7	4.3	806.4	192.3	3.8	790.5	218.4	3.3	762.5	245.6	2.9	709.5	260.7	2.5	698.7	263.4	2.5
11.0	842.4	172.9	4.4	828.1	193.8	3.9	811.6	219.5	3.4	781.3	245.8	3.0	726.1	260.3	2.6	715.2	263.0	2.5
12.0	864.5	175.1	4.5	850.1	195.4	4.0	833.1	220.7	3.5	799.5	245.5	3.0	743.1	259.9	2.7	723.9	257.8	2.6
13.0	887.0	177.7	4.5	872.1	197.2	4.0	854.8	222.1	3.6	818.1	245.3	3.1	760.3	259.5	2.7	730.1	251.0	2.7

MODEL: YCIV0227E/V**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	743.0	169.0	3.9	731.8	192.7	3.4	718.8	219.4	3.0	703.0	250.7	2.6	661.8	268.9	2.3	652.0	271.4	2.2
6.0	764.0	170.2	4.0	752.3	193.7	3.5	738.8	220.3	3.1	722.2	251.7	2.7	678.0	268.9	2.3	667.8	271.6	2.3
7.0	785.4	171.7	4.1	773.3	194.8	3.6	759.2	221.2	3.2	741.8	252.8	2.7	694.3	269.0	2.4	684.1	271.6	2.3
8.0	807.2	173.1	4.2	794.7	196.0	3.7	780.0	222.3	3.2	761.9	253.8	2.8	711.1	269.0	2.5	700.6	271.6	2.4
9.0	829.4	174.8	4.3	816.5	197.2	3.8	801.2	223.4	3.3	782.3	254.8	2.9	728.2	268.9	2.5	717.3	271.6	2.5
10.0	851.7	176.5	4.3	838.7	198.7	3.8	822.9	224.6	3.4	801.1	254.8	2.9	745.6	268.9	2.6	734.4	271.5	2.5
11.0	874.2	178.4	4.4	860.8	200.2	3.9	844.9	225.8	3.4	820.0	254.9	3.0	763.3	268.8	2.6	751.8	271.4	2.6
12.0	897.1	180.5	4.5	883.2	201.8	4.0	866.8	227.3	3.5	839.3	254.9	3.1	781.0	268.7	2.7	769.5	271.3	2.6
13.0	920.3	182.6	4.5	906.1	203.6	4.1	889.1	228.7	3.6	858.7	255.0	3.1	799.3	268.6	2.8	787.3	271.3	2.7

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW

High Efficiency Ratings – SI - 380V/60Hz

MODEL: YCIV0247E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	824.5	194.8	3.8	811.2	221.5	3.4	795.7	251.2	2.9	773.5	283.8	2.5	730.4	305.9	2.2	721.2	309.7	2.2
6.0	847.7	196.4	3.9	833.8	222.9	3.4	817.7	252.6	3.0	793.8	284.9	2.6	748.4	306.5	2.3	738.8	310.5	2.2
7.0	871.3	198.1	4.0	856.9	224.4	3.5	840.1	254.0	3.1	814.6	286.0	2.7	766.7	307.1	2.3	754.9	309.8	2.3
8.0	895.3	199.9	4.1	880.5	226.0	3.6	863.0	255.6	3.1	835.8	287.1	2.7	785.5	307.7	2.4	763.0	303.6	2.4
9.0	919.9	201.9	4.1	904.5	227.8	3.7	886.3	257.2	3.2	856.8	287.9	2.8	804.7	308.2	2.5	770.6	296.9	2.4
10.0	944.8	204.0	4.2	928.9	229.6	3.7	910.1	258.9	3.3	877.5	288.5	2.8	821.6	307.2	2.5	777.9	289.9	2.5
11.0	970.3	206.2	4.3	953.8	231.6	3.8	934.4	260.7	3.3	898.6	289.1	2.9	829.7	300.0	2.6	784.7	282.6	2.6
12.0	995.9	208.6	4.4	979.1	233.6	3.9	959.0	262.6	3.4	920.1	289.7	3.0	837.3	292.4	2.7	791.0	275.3	2.7
13.0	1022.2	210.5	4.4	1004.7	235.9	3.9	984.2	264.6	3.5	941.9	290.4	3.0	844.2	284.8	2.8	796.8	268.3	2.8

MODEL: YCIV0267E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	935.9	214.3	3.9	919.5	246.0	3.4	900.1	281.3	3.0	875.5	321.9	2.5	811.1	342.9	2.2	798.1	346.7	2.2
6.0	962.5	215.7	4.0	945.8	247.0	3.5	925.6	282.3	3.0	898.2	322.2	2.6	831.3	343.3	2.3	817.8	347.2	2.2
7.0	989.5	217.3	4.1	972.5	248.1	3.6	951.7	283.3	3.1	921.3	322.3	2.7	851.9	343.6	2.3	838.0	347.6	2.3
8.0	1017.1	219.1	4.2	999.6	249.4	3.7	978.3	284.3	3.2	944.1	322.3	2.7	872.7	343.8	2.4	858.7	347.9	2.3
9.0	1045.2	221.1	4.3	1027.4	250.9	3.7	1005.4	285.5	3.3	967.3	322.3	2.8	894.2	343.9	2.4	879.6	348.1	2.4
10.0	1073.8	223.4	4.4	1055.6	252.5	3.8	1033.0	286.9	3.3	991.0	322.2	2.9	915.8	344.0	2.5	901.0	348.2	2.4
11.0	1102.8	225.9	4.4	1084.4	254.3	3.9	1061.2	288.3	3.4	1015.0	322.2	2.9	938.0	344.0	2.6	922.6	348.2	2.5
12.0	1132.3	228.7	4.5	1113.6	256.4	4.0	1089.8	289.9	3.5	1039.3	322.2	3.0	960.5	344.0	2.6	944.8	348.2	2.5
13.0	1162.3	231.7	4.6	1143.3	258.7	4.1	1119.1	291.7	3.6	1063.8	322.3	3.1	983.3	344.0	2.7	967.4	348.1	2.6

MODEL: YCIV0287E/V

AIR TEMPERATURE ON - CONDENSER (°C)																		
LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	996.2	225.3	4.0	979.2	259.7	3.4	959.5	298.8	3.0	935.5	344.4	2.5	869.0	364.4	2.2	855.4	367.7	2.2
6.0	1024.5	226.7	4.1	1007.0	260.4	3.5	986.4	299.5	3.0	960.5	344.8	2.6	890.3	364.4	2.3	876.3	367.9	2.2
7.0	1053.4	228.4	4.2	1035.3	261.3	3.6	1013.9	300.0	3.1	984.3	344.2	2.7	912.1	364.3	2.3	897.7	367.9	2.3
8.0	1082.9	230.4	4.2	1064.2	262.5	3.7	1042.0	300.7	3.2	1008.6	343.5	2.7	934.3	363.9	2.4	919.5	367.6	2.3
9.0	1112.9	232.7	4.3	1093.7	263.9	3.8	1070.7	301.6	3.3	1033.1	342.9	2.8	956.7	363.5	2.5	941.8	367.2	2.4
10.0	1143.5	235.4	4.4	1123.7	265.6	3.9	1100.0	302.8	3.4	1058.1	342.2	2.9	979.9	362.9	2.5	964.3	366.8	2.5
11.0	1174.4	238.5	4.5	1154.4	267.5	3.9	1129.9	304.0	3.4	1083.6	341.5	3.0	1003.4	362.3	2.6	987.4	366.2	2.5
12.0	1206.4	241.9	4.5	1185.5	269.8	4.0	1160.4	305.5	3.5	1109.5	340.9	3.0	1027.4	361.6	2.7	1011.0	365.5	2.6
13.0	1238.7	245.7	4.6	1217.3	272.4	4.1	1191.4	307.2	3.6	1135.6	340.4	3.1	1051.7	360.9	2.7	1034.9	364.8	2.7

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW

MODEL: YCIV0327E/V**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1082.7	247.9	3.9	1064.7	284.7	3.4	1044.3	326.4	3.0	1013.0	371.0	2.6	945.2	394.1	2.3	930.6	397.6	2.2
6.0	1113.5	249.6	4.0	1094.7	285.8	3.5	1073.2	327.3	3.0	1038.5	371.1	2.6	967.8	394.2	2.3	953.0	397.8	2.2
7.0	1145.0	251.6	4.1	1125.3	287.1	3.6	1102.8	328.3	3.1	1064.7	371.1	2.7	991.1	394.1	2.4	975.8	397.9	2.3
8.0	1177.1	253.9	4.2	1156.5	288.5	3.7	1133.0	329.5	3.2	1091.4	371.0	2.7	1014.9	393.9	2.4	999.0	397.7	2.4
9.0	1209.8	256.5	4.3	1188.4	290.3	3.8	1164.0	330.7	3.3	1118.6	370.9	2.8	1039.0	393.5	2.5	1022.8	397.4	2.4
10.0	1243.2	259.3	4.3	1221.0	292.3	3.8	1195.5	332.2	3.3	1146.4	370.9	2.9	1063.6	393.0	2.5	1047.0	397.0	2.5
11.0	1277.2	262.6	4.4	1254.2	294.7	3.9	1227.8	333.8	3.4	1174.3	370.9	3.0	1088.5	392.5	2.6	1071.6	396.5	2.5
12.0	1311.9	266.1	4.5	1288.1	297.2	4.0	1260.7	335.7	3.5	1201.8	370.4	3.0	1114.1	391.9	2.7	1085.7	389.4	2.6
13.0	1347.3	270.1	4.5	1322.6	300.0	4.1	1294.1	337.9	3.6	1229.8	370.1	3.1	1139.9	391.3	2.7	1095.0	379.4	2.7

MODEL: YCIV0357E/V**AIR TEMPERATURE ON - CONDENSER (°C)**

LCWT (°C)	25.0			30.0			35.0			40.0			45.0			46.0		
	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP	KWi	KWi	COP
5.0	1228.4	287.0	3.9	1206.7	325.4	3.4	1181.0	367.8	3.0	1146.5	415.9	2.6	1083.9	450.5	2.3	1070.4	456.8	2.2
6.0	1263.2	289.6	4.0	1241.1	327.6	3.5	1214.5	370.0	3.0	1177.1	417.5	2.6	1111.7	451.6	2.3	1097.6	457.9	2.3
7.0	1298.8	292.2	4.0	1276.1	330.0	3.5	1248.7	372.3	3.1	1208.5	419.0	2.7	1139.9	452.8	2.4	1125.5	459.0	2.3
8.0	1334.9	295.0	4.1	1311.8	332.6	3.6	1283.4	374.9	3.2	1240.5	420.6	2.8	1168.8	453.8	2.4	1153.8	460.1	2.4
9.0	1371.6	298.1	4.2	1348.0	335.4	3.7	1318.9	377.4	3.2	1273.1	422.2	2.8	1198.3	454.9	2.5	1183.0	461.2	2.4
10.0	1409.1	301.3	4.3	1384.9	338.3	3.8	1355.0	380.2	3.3	1306.1	424.0	2.9	1228.4	456.0	2.5	1205.0	457.4	2.5
11.0	1447.1	304.6	4.3	1422.5	341.3	3.8	1391.8	383.1	3.4	1339.8	425.7	2.9	1258.9	457.1	2.6	1215.9	446.2	2.6
12.0	1485.7	308.3	4.4	1460.6	344.7	3.9	1429.2	386.1	3.4	1372.9	427.0	3.0	1290.1	458.2	2.6	1226.3	435.1	2.6
13.0	1525.2	311.0	4.5	1499.4	348.1	4.0	1467.3	389.3	3.5	1406.5	428.4	3.1	1308.1	450.8	2.7	1236.0	424.3	2.7

NOTES:

1. kW_o = Unit kW Cooling Capacity Output
2. kW_i = Compressor kW Input
3. COP = Coefficient of Performance (includes condenser fan power)
4. LCWT = Leaving Chilled Water Temperature
5. Ratings based on 0.168 l/s cooler water per ton, and 0.018 (m² – °C)/kW

Physical Data (English - Standard Efficiency)

Refrigerant R-134a	STANDARD EFFICIENCY							
	MODEL NUMBER (YCIV S/P)							
General Unit Data	60Hz	0157	0177	0187	0207	0227	0247	0267
	50Hz	0600	0650	0720	0770	0840	0920	1000
Number of Independent Refrigerant Circuits		2	2	2	2	2	2	2
Refrigerant Charge, R-134a, Ckt.-1/Ckt.-2, lbs		162/162	170/170	185/170	192/175	192/192	230/195	230/230
Oil Charge, Ckt.-1/Ckt.-2, gal.		5/5	5/5	5/5	5/5	5/5	5/5	5/5
Compressors, Semi-hermetic Screw Qty per Chiller		2	2	2	2	2	2	2
Condensers, High Efficiency Fin/Tube with Integral Subcooler								
Total Chiller Coil Face Area, ft ²		235	235	264	264	293	323	352
Number of Rows		3	3	3	3	3	3	3
Fins per Inch		17	17	17	17	17	17	17
Condenser Fans								
Number, Ckt.-1/Ckt.-2		4/4	4/4	5/4	5/4	5/5	6/5	6/6
Low Noise Fans								
Fan Motor, HP		2	2	2	2	2	2	2
Total Chiller Airflow, cfm		104000	104000	117000	117000	130000	143000	156000
Ultra Quiet Fans								
Fan Motor, HP		2	2	2	2	2	2	2
Total Chiller Airflow, cfm		104000	104000	117000	117000	130000	143000	156000
Dual Speed Fans - Normal Speed								
Fan Motor, hp		2	2	2	2	2	2	2
Total Chiller, CFM		88000	88000	99000	99000	110000	121000	132000
Dual Speed Fans - Lower Speed								
Fan Motor, hp		2	2	2	2	2	2	2
Total Chiller, CFM		67200	67200	75600	75600	84000	92400	100800
High Static Fans								
Fan Motor, hp		5	5	5	5	5	5	5
Total Chiller, CFM		104000	104000	117000	117000	130000	143000	156000
Evaporator, Direct Expansion								
Water Volume, gals.		67.0	95.0	95.0	140.0	140.0	140.0	140.0
Maximum Water Side Pressure, PSIG ¹		150	150	150	150	150	150	150
Maximum Refrigerant Side Pressure, PSIG		235	235	235	235	235	235	235
Minimum Chilled Water Flow Rate, gpm		140	160	160	180	180	180	180
Maximum Chilled Water Flow Rate, gpm		675	750	750	800	800	800	800
Water Connections, inches		8	10	10	10	10	10	10

Contact your nearest Johnson Controls Sales Office for weight data.

Refrigerant R-134a	STANDARD EFFICIENCY				
	MODEL NUMBER (YCIV ____ S/P)				
General Unit Data	60Hz	0287	0307	0357	0397
	50Hz	1070	1180	1340	1500
Number of Independent Refrigerant Circuits		3	3	3	3
Refrigerant Charge, R-134a, Ckt.-1/Ckt.-2, lbs		185/170/170	185/185/170	185/185/230	230/230/230
Oil Charge, Ckt.-1/Ckt.-2, gal.		5/4/4	5/4/4	5/5/5	5/5/5
Glycol Charge (43% concentration), gal		5.4	5.5	6.0	6.3
Comp.s, Semihermetic Screw					
Quantity per Chiller		3	3	3	3
Condensers, High Efficiency Fin/Tube with Integral Subcooler					
Total Chiller Coil Face Area, ft ²		381	411	469	528
Number of Rows		3	3	3	3
Fins per Inch		17	17	17	17
Condenser Fans					
Number, Ckt.-1/Ckt.-2		5/4/4	5/4/4	5/5/6	6/6/6
Low Noise Fans					
Fan Motor, HP/kWi		2/1.8	2/1.8	2/1.8	2/1.8
Total Chiller Airflow, cfm		169000	182000	208000	234000
Ultra Quiet Fans					
Fan Motor, HP/kWi		2/1.50	2/1.50	2/1.50	2/1.50
Total Chiller Airflow, cfm		169000	182000	208000	234000
Dual Speed Fans - Normal Speed					
Fan Motor, hp		2	2	2	2
Total Chiller, CFM		143000	143000	165000	165000
Dual Speed Fans - Lower Speed					
Fan Motor, hp		2	2	2	2
Total Chiller, CFM		109200	109200	126000	126000
High Static Fans					
Fan Motor, hp		5	5	5	5
Total Chiller, CFM		169000	182000	208000	234000
Evaporator, Direct Expansion					
Water Volume, gals.		202.0	236.0	236.0	236.0
Maximum Water Side Pressure, PSIG		150	150	150	150
Maximum Refrigerant Side Pressure, PSIG		235	235	235	235
Minimum Chilled Water Flow Rate, gpm		250	300	300	300
Maximum Chilled Water Flow Rate, gpm		1200	1200	1200	1200
Water Connections, inches		10	10	10	10

Contact your nearest Johnson Controls Sales Office for weight data.

Physical Data (English - High Efficiency)

Refrigerant R-134a	HIGH EFFICIENCY							
	MODEL NUMBER (YCIV E/V)							
General Unit Data	60Hz	0157	0177	0187	0197	0207	0227	0247
	50Hz	0590	0630	0700	0760	0800	0830	0930
Number of Independent Refrigerant Circuits		2	2	2	2	2	2	2
Refrigerant Charge, R-134a, Ckt.-1/Ckt.-2, lbs		170/170	185/170	185/185	192/192	225/192	225/225	230/230
Oil Charge, Ckt.-1/Ckt.-2, gal.		5/5	5/5	5/5	5/5	5/5	5/5	5/5
Compressors, Semihermetic Screw Qty per Chiller		2	2	2	2	2	2	2
Condensers, High Efficiency Fin/Tube with Integral Subcooler								
Total Chiller Coil Face Area, ft ²		235	264	293	293	323	352	352
Number of Rows		3	3	3	3	3	3	3
Fins per Inch		17	17	17	17	17	17	17
Condenser Fans								
Number, Ckt.-1/Ckt.-2		4/4	5/4	5/5	5/5	6/5	6/6	6/6
Low Noise Fans								
Fan Motor, HP		2	2	2	2	2	2	2
Total Chiller Airflow, cfm		104000	117000	130000	130000	143000	156000	156000
Ultra Quiet Fans								
Fan Motor, HP		2	2	2	2	2	2	2
Total Chiller Airflow, cfm		104000	117000	130000	130000	143000	156000	156000
Dual Speed Fans - Normal Speed								
Fan Motor, hp		2	2	2	2	2	2	2
Total Chiller, CFM		88000	99000	110000	110000	121000	132000	132000
Dual Speed Fans - Lower Speed								
Fan Motor, hp		2	2	2	2	2	2	2
Total Chiller, CFM		67200	75600	84000	84000	92400	100800	100800
High Static Fans								
Fan Motor, hp		5	5	5	5	5	5	5
Total Chiller, CFM		104000	117000	130000	130000	143000	156000	156000
Evaporator, Direct Expansion								
Water Volume, gals.		95.0	95.0	95.0	110.0	110.0	110.0	140.0
Maximum Water Side Pressure, PSIG ¹		150	150	150	150	150	150	150
Maximum Refrigerant Side Pressure, PSIG		235	235	235	235	235	235	235
Minimum Chilled Water Flow Rate, gpm		160	160	160	180	180	180	180
Maximum Chilled Water Flow Rate, gpm		750	750	750	750	750	750	800
Water Connections, inches		10	10	10	10	10	10	10

Refrigerant R-134a	HIGH EFFICIENCY				
	MODEL NUMBER (YCIV____E/V)				
General Unit Data	60Hz	0267	0287	0327	0357
	50Hz	1550	1120	1220	1380
Number of Independent Refrigerant Circuits		3	3	3	3
Refrigerant Charge, R-134a, Ckt.-1/Ckt.-2, lbs		185/185/170	185/185/230	185/185/230	230/230/230
Oil Charge, Ckt.-1/Ckt.-2, gal.		5/5/4	5/5/5	5/5/5	5/5/5
Glycol Charge (43% concentration), gal		5.5	5.7	6.0	6.3
Comp.s, Semihermetic Screw					
Quantity per Chiller		3	3	3	3
Condensers, High Efficiency Fin/Tube with Integral Subcooler					
Total Chiller Coil Face Area, ft ²		411	469	469	528
Number of Rows		3	3	3	3
Fins per Inch		17	17	17	17
Condenser Fans					
Number, Ckt.-1/Ckt.-2		5/5/4	5/5/6	5/5/6	6/6/6
Low Noise Fans					
Fan Motor, HP/kWi		2/1.8	2/1.8	2/1.8	2/1.8
Total Chiller Airflow, cfm		182000	208000	208000	234000
Ultra Quiet Fans					
Fan Motor, HP/kWi		2/1.50	2/1.50	2/1.50	2/1.50
Total Chiller Airflow, cfm		182000	208000	208000	234000
Dual Speed Fans - Normal Speed					
Fan Motor, hp		2	2	2	2
Total Chiller, CFM		154000	176000	176000	198000
Dual Speed Fans - Lower Speed					
Fan Motor, hp		2	2	2	2
Total Chiller, CFM		117600	134400	134400	151200
High Static Fans					
Fan Motor, hp		5	5	5	5
Total Chiller, CFM		195000	247000	247000	273000
Evaporator, Direct Expansion					
Water Volume, gals.		202.0	202.0	236.0	236.0
Maximum Water Side Pressure, PSIG		150	150	150	150
Maximum Refrigerant Side Pressure, PSIG		235	235	235	235
Minimum Chilled Water Flow Rate, gpm		250	250	300	300
Maximum Chilled Water Flow Rate, gpm		1200	1200	1200	1200
Water Connections, inches		10	10	10	10

Contact your nearest Johnson Controls Sales Office for weight data.

Physical Data (SI - Standard Efficiency)

Refrigerant R-134a	STANDARD EFFICIENCY							
	MODEL NUMBER (YCIV ____ S/P)							
General Unit Data	60Hz	0157	0177	0187	0207	0227	0247	0267
	50Hz	0600	0650	0720	0770	0840	0920	1000
Number of Independent Refrigerant Circuits	2	2	2	2	2	2	2	2
Refrigerant Charge, R-134a, Ckt.-1/Ckt.-2, kg.	74/74	77/77	84/77	87/80	87/87	105/89	105/105	
Oil Charge, Ckt.-1/Ckt.-2, liters	19/19	19/19	19/19	19/19	19/19	19/19	19/19	19/19
Compressors, Semihermetic Screw Qty per Chiller	2	2	2	2	2	2	2	2
Condensers, High Efficiency Fin/Tube with Integral Subcooler								
Total Chiller Coil Face Area, m2	21.8	21.8	24.5	24.5	27.2	30.0	32.7	
Number of Rows	3	3	3	3	3	3	3	3
Fins per meter	669	669	669	669	669	669	669	669
Condenser Fans								
Number, Ckt.-1/Ckt.-2	4/4	4/4	5/4	5/4	5/5	6/5	6/6	
Low Noise Fans								
Fan Motor, HP/kWi	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50
Total Chiller Airflow, l/sec.	49082	49082	55218	55218	61353	67488	73624	
Ultra Quiet Fans								
Fan Motor, HP/kWi	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50
Total Chiller Airflow, l/sec.	49082	49082	55218	55218	61353	67488	73624	
Dual Speed Fans - Normal Speed								
Fan, KWi	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Total Chiller, m3/s	42	42	47	47	52	57	62	
Dual Speed Fans - Lower Speed								
Fan, KWi	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Total Chiller, m3/s	32	32	36	36	40	44	48	
High Static Fans								
Fan, KWi	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7
Total Chiller, m3/s	49	49	55	55	61	67	74	
Evaporator, Direct Expansion								
Water Volume, liters	253.6	359.6	359.6	529.9	529.9	529.9	529.9	
Maximum Water Side Pressure, Bar ¹	10	10	10	10	10	10	10	10
Maximum Refrigerant Side Pressure, Bar	16	16	16	16	16	16	16	16
Minimum Chilled Water Flow Rate, l/sec.	8.8	10.1	10.1	11.4	11.4	11.4	11.4	11.4
Maximum Chilled Water Flow Rate, l/sec.	42.6	47.3	47.3	50.5	50.5	50.5	50.5	50.5
Water Connections, inches	8	10	10	10	10	10	10	10

Refrigerant R-134a	STANDARD EFFICIENCY				
	MODEL NUMBER (YCIV ____ S/P)				
General Unit Data	60Hz	0287	0307	0357	0397
	50Hz	1070	1180	1340	1500
Number of Independent Refrigerant Circuits	3	3	3	3	3
Refrigerant Charge, R-134a, Ckt.-1/Ckt.-2, kg.	84 / 77 / 77	84 / 84 / 77	84 / 84 / 105	105 / 105 / 105	
Oil Charge, Ckt.-1/Ckt.-2, liters	19 / 15 / 15	19 / 19 / 15	19 / 19 / 19	19 / 19 / 19	
Glycol Charge (43% concentration), liters	0	0	0	0	
Compressors, Semihermetic Screw					
Quantity per Chiller	3	3	3	3	
Condensers, High Efficiency Fin/Tube with Integral Subcooler					
Total Chiller Coil Face Area, m ²	35	38	44	49	
Number of Rows	3	3	3	3	
Fins per meter	669	669	669	669	
Condenser Fans					
Number, Ckt.-1/Ckt.-2	5/4/4	5/5/4	5/5/6	6/6/6	
Low Noise Fans					
Fan Motor, HP/kWi	2/1.50	2/1.50	2/1.50	2/1.50	
Total Chiller Airflow, l/sec.	79768	85904	98176	110448	
Ultra Quiet Fans					
Fan Motor, HP/kWi	2/1.50	2/1.50	2/1.50	2/1.50	
Total Chiller Airflow, l/sec.	79768	85904	98176	110448	
Dual Speed Fans - Normal Speed					
Fan, kW	1.5	1.5	1.5	1.5	
Total Chiller, m ³ /s	67	67	78	78	
Dual Speed Fans - Lower Speed					
Fan, kW	1.5	1.5	1.5	1.5	
Total Chiller, m ³ /s	52	52	59	59	
High Static Fans					
Fan, kW	3.7	3.7	3.7	3.7	
Total Chiller, m ³ /s	80	86	98	110	
Evaporator, Direct Expansion					
Water Volume, liters	764.6	893.3	893.3	893.3	
Maximum Water Side Pressure, Bar	10	10	10	10	
Maximum Refrigerant Side Pressure, Bar	16	16	16	16	
Minimum Chilled Water Flow Rate, l/sec.	16	19	19	19	
Maximum Chilled Water Flow Rate, l/sec.	76	76	76	76	
Water Connections, mm	245	245	245	245	

Contact your nearest Johnson Controls Sales Office for weight data.

Physical Data (SI - High Efficiency)

Refrigerant R-134a	HIGH EFFICIENCY							
	MODEL NUMBER (YCIV___ E/V)							
General Unit Data	60Hz	0157	0177	0187	0197	0207	0227	0247
	50Hz	0590	0630	0700	0760	0800	0830	0930
Number of Independent Refrigerant Circuits	2	2	2	2	2	2	2	2
Refrigerant Charge, R-134a, Ckt.-1/Ckt.-2, kg.	77/77	84/77	84/84	87/87	102/87	102/102	105/105	
Oil Charge, Ckt.-1/Ckt.-2, liters	19/19	19/19	19/19	19/19	19/19	19/19	19/19	19/19
Compressors, Semihermetic Screw Qty per Chiller	2	2	2	2	2	2	2	2
Condensers, High Efficiency Fin/Tube with Integral Subcooler								
Total Chiller Coil Face Area, m2	21.8	24.5	27.2	27.2	30.0	32.7	32.7	
Number of Rows	3	3	3	3	3	3	3	3
Fins per meter	669	669	669	669	669	669	669	669
Condenser Fans								
Number, Ckt.-1/Ckt.-2	4/4	5/4	5/5	5/5	6/5	6/6	6/6	
Low Sound Fans								
Fan Motor, HP/kWi	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50
Total Chiller Airflow, l/sec.	49082	55218	61353	61353	67488	73624	73624	
Ultra Quiet Fans								
Fan Motor, HP/kWi	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50	2/1.50
Total Chiller Airflow, l/sec.	49082	55218	61353	61353	67488	73624	73624	
Dual Speed Fans - Normal Speed								
Fan, KWi	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Total Chiller, m3/s	42	47	52	52	57	62	62	
Dual Speed Fans - Lower Speed								
Fan, KWi	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Total Chiller, m3/s	32	36	40	40	44	48	48	
High Static Fans								
Fan, KWi	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7
Total Chiller, m3/s	49	55	61	61	67	74	74	
Evaporator, Direct Expansion								
Water Volume, liters	359.6	359.6	359.6	416.4	416.4	416.4	529.9	
Maximum Water Side Pressure, Bar ¹	10	10	10	10	10	10	10	10
Maximum Refrigerant Side Pressure, Bar	16	16	16	16	16	16	16	16
Minimum Chilled Water Flow Rate, l/sec.	10.1	10.1	10.1	11.4	11.4	11.4	11.4	11.4
Maximum Chilled Water Flow Rate, l/sec.	47.3	47.3	47.3	47.3	47.3	47.3	47.3	50.5
Water Connections, inches	10	10	10	10	10	10	10	10



Contact your nearest Johnson Controls Sales Office for weight data.

Refrigerant R-134a	HIGH EFFICIENCY				
	MODEL NUMBER (YCIV ____ E/V)				
General Unit Data	60Hz	0267	0287	0327	0357
	50Hz	1550	1120	1220	1380
Number of Independent Refrigerant Circuits	3	3	3	3	3
Refrigerant Charge, R-134a, Ckt.-1/Ckt.-2, kg.	84 / 84 / 77	84 / 84 / 105	84 / 84 / 105	105 / 105 / 105	
Oil Charge, Ckt.-1/Ckt.-2, liters	19 / 19 / 15	19 / 19 / 19	19 / 19 / 19	19 / 19 / 19	
Glycol Charge (43% concentration), liters	0	0	0	0	
Compressors, Semihermetic Screw					
Quantity per Chiller	3	3	3	3	
Condensers, High Efficiency Fin/Tube with Integral Subcooler					
Total Chiller Coil Face Area, m ²	38	44	44	49	
Number of Rows	3	3	3	3	
Fins per meter	669	669	669	669	
Condenser Fans					
Number, Ckt.-1/Ckt.-2	05/05/04	05/05/06	05/05/06	06/06/06	
Low Noise Fans					
Fan Motor, HP/kWi	2/1.50	2/1.50	2/1.50	2/1.50	
Total Chiller Airflow, l/sec.	85904	98176	98176	110448	
Ultra Quiet Fans					
Fan Motor, HP/kWi	2/1.50	2/1.50	2/1.50	2/1.50	
Total Chiller Airflow, l/sec.	85904	98176	98176	110448	
Dual Speed Fans - Normal Speed					
Fan, kW	1.5	1.5	1.5	1.5	
Total Chiller, m ³ /s	73	83	83	93	
Dual Speed Fans - Lower Speed					
Fan, kW	1.5	1.5	1.5	1.5	
Total Chiller, m ³ /s	56	63	63	71	
High Static Fans					
Fan, kW	3.7	3.7	3.7	3.7	
Total Chiller, m ³ /s	92	117	117	129	
Evaporator, Direct Expansion					
Water Volume, liters	764.6	764.6	893.3	893.3	
Maximum Water Side Pressure, Bar	10	10	10	10	
Maximum Refrigerant Side Pressure, Bar	16	16	16	16	
Minimum Chilled Water Flow Rate, l/sec.	16	16	19	19	
Maximum Chilled Water Flow Rate, l/sec.	76	76	76	76	
Water Connections, mm	245	245	245	245	

Contact your nearest Johnson Controls Sales Office for weight data.

Dimensions – English

Models YCIV0157E/V and YCIV0157S/P





YCIV	A	B	C	D
0157E/V	19.1"	28.1"	84.5"	112.8"
0157S/P	17.4"	29.1"	90.0"	110.1"

Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — English - continued

Models YCIV0177E/V, YCIV0177S/P, YCIV0187E/V and YCIV0187S/P





YCIV	A	B
0177E/V	88.1"	274.0"
0177S/P	80.0"	230.0"
0187E/V	88.1"	274.0"
0187S/P	88.1"	274.0"

Notes:


1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — English - continued

Models YCIV0197E/V, YCIV0207S/P, and YCIV0227S/P





YCIV	A	B	C	D
0197E/V	20.4"	28.1"	85.6"	112.3"
0207S/P	22.2"	26.0"	79.1"	113.3"
0227S/P	22.2"	26.0"	79.1"	113.3"

Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — English - continued



Models YCIV0207E/V and YCIV0227E/V



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — English - continued



Models YCIV0247S/P, YCIV0247E/V, and YCIV0267S/P



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — English - continued


Models YCIV0267E/V, and YCIV0287S/P



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — English - continued



Models YCIV0287E/V



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — English - continued


Models YCIV0307S/P



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — English - continued


Models YCIV0327E/V and YCIV0357S/P




Notes:

1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.





VIEW D-D



POWER: SINGLE POINT WITH TERMINAL BLOCK

Dimensions — English - continued


Models YCIV0357E/V and YCIV0397S/P




Notes:

1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 6'; rear to wall - 6'; control panel end to wall - 4'; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.





VIEW D-D



POWER: SINGLE POINT WITH TERMINAL BLOCK

Dimensions – SI

YCIV0590E/V and YCIV0600S/P





YCIV	A	B	C	D
0590E/V	485	714	2146	2865
0600S/P	442	739	2286	2797

Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — SI - continued

YCIV0630E/V, YCIV0650S/P, YCIV0700E/V and YCIV0720S/P





YCIV	A	B
0630E/V	2238	6960
0650S/P	2032	5842
0700E/V	2238	6960
0720S/P	2238	6960

Notes:

1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.



Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.

DIMENSIONS (mm) UNLESS OTHERWISE NOTED



Dimensions — SI - continued

YCIV0760E/V, YCIV0770S/P, and YCIV0890S/P





YCIV	A	B	C	D
0760E/V	518	714	2174	2852
0770S/P	564	660	2009	2878
0890S/P	564	660	2009	2878

Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions – SI - continued


YCIV0800E/V and YCIV0830E/V



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions – SI - continued



YCIV0920S/P, YCIV0930E/V, and YCIV1000S/P



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions – SI - continued


YCIV1050E/V and YCIV1070S/P



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — SI - continued



YCIV1120E/V



Notes:



1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions – SI - continued


YCIV1180S/P



Notes:


1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions – SI - continued



YCIV1220E/V and YCIV1340S/P



Notes:


1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Dimensions — SI - continued



YCIV1380E/V and YCIV1500S/P




Notes:

1. Placement on a level surface free of obstructions (including snow, for winter operation) or air recirculation ensures rated performance, reliable operation, and ease of maintenance. Site restrictions may compromise minimum clearances indicated below, resulting in unpredictable air patterns and possible diminished performance. Johnson Controls' unit controls will optimize the operation without nuisance high pressure safety cutouts; however, the system designer **MUST** consider potential performance degradation.

Access to the unit control center stipulates the unit is no higher than on spring isolators. Recommended minimum clearances: side to wall - 2m; rear to wall - 2m; control panel end to wall - 1.2m; top - no obstructions whatsoever; distance between adjacent units - 10'. No more than one adjacent wall may be higher than the unit.



Isolator Locations – English




STANDARD EFFICIENCY - ENGLISH

MODEL		Isolator Locations (x , y) - in. and Point Loads - lbs							
60 Hz	50 Hz		1	2	3	4	5	6	7
YCI0157S/P	YCI0600S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(211 , 86.8)			
		Al Fin Coils	1702	1592	1396	1340			
		Cu Fin Coils	1702	1704	1739	1682			
		RS&LS1 / Al Fin Coils	1881	1770	1396	1340			
		RS&LS1 / Cu Fin Coils	1881	1883	1739	1682			
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(211 , 1.3)			
		Al Fin Coils	1702	1592	1396	1340			
		Cu Fin Coils	1702	1704	1739	1682			
		RS&LS1 / Al Fin Coils	1881	1770	1396	1340			
RS&LS1 / Cu Fin Coils	1881	1883	1739	1682					
YCI0177S/P	YCI0650S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(211 , 86.8)			
		Al Fin Coils	1720	1614	1667	1609			
		Cu Fin Coils	1720	1726	2011	1951			
		RS&LS1 / Al Fin Coils	1898	1792	1667	1609			
		RS&LS1 / Cu Fin Coils	1898	1905	2011	1951			
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(211 , 1.3)			
		Al Fin Coils	1702	1594	1667	1609			
		Cu Fin Coils	1702	1706	2011	1951			
		RS&LS1 / Al Fin Coils	1881	1773	1667	1609			
RS&LS1 / Cu Fin Coils	1881	1885	2011	1951					
YCI0187S/P	YCI0720S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(195.7 , 86.8)	(265.4 , 86.8)		
		Al Fin Coils	1715	1579	1559	1274	774		
		Cu Fin Coils	1715	1700	1898	1653	935		
		RS&LS1 / Al Fin Coils	1894	1757	1559	1274	774		
		RS&LS1 / Cu Fin Coils	1894	1878	1898	1653	935		
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(195.7 , 1.3)	(265.4 , 1.3)		
		Al Fin Coils	1698	1559	1559	1241	664		
		Cu Fin Coils	1698	1680	1898	1620	825		
		RS&LS1 / Al Fin Coils	1876	1737	1559	1241	664		
RS&LS1 / Cu Fin Coils	1876	1858	1898	1620	825				
YCI0207S/P	YCI0770S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(195.7 , 86.8)	(265.4 , 86.8)		
		Al Fin Coils	1728	1680	1768	1512	915		
		Cu Fin Coils	1728	1801	2108	1892	1076		
		RS&LS1 / Al Fin Coils	1907	1858	1768	1512	915		
		RS&LS1 / Cu Fin Coils	1907	1980	2108	1892	1076		
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(195.7 , 1.3)	(265.4 , 1.3)		
		Al Fin Coils	1728	1676	1764	1475	800		
		Cu Fin Coils	1728	1797	2108	1854	961		
		RS&LS1 / Al Fin Coils	1907	1854	1764	1475	800		
RS&LS1 / Cu Fin Coils	1907	1975	2103	1854	961				
YCI0277S/P	YCI0840S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(195.7 , 86.8)	(265.4 , 86.8)		
		Al Fin Coils	1728	1680	1768	1523	959		
		Cu Fin Coils	1728	1801	2108	1903	1120		
		RS&LS1 / Al Fin Coils	1907	1858	1768	1523	959		
		RS&LS1 / Cu Fin Coils	1907	1980	2108	1903	1120		
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(195.7 , 1.3)	(265.4 , 1.3)		
		Al Fin Coils	1728	1676	1764	1519	955		
		Cu Fin Coils	1728	1797	2103	1898	1116		
		RS&LS1 / Al Fin Coils	1907	1854	1764	1519	955		
RS&LS1 / Cu Fin Coils	1907	1975	2103	1898	1116				
YCI0247S/P	YCI0920S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(97.2 , 86.8)	(161.4 , 86.8)	(210.6 , 86.8)	(307.9 , 86.8)	
		Al Fin Coils	1728	1638	1248	1160	1261	959	
		Cu Fin Coils	1728	1728	1488	1435	1609	1199	
		RS&LS1 / Al Fin Coils	1907	1817	1248	1160	1261	959	
		RS&LS1 / Cu Fin Coils	1907	1907	1488	1435	1609	1199	
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(97.2 , 1.3)	(161.4 , 1.3)	(210.6 , 1.3)	(307.9 , 1.3)	
		Al Fin Coils	1720	1625	1239	1153	1237	955	
		Cu Fin Coils	1720	1715	1479	1429	1585	1195	
		RS&LS1 / Al Fin Coils	1898	1803	1239	1153	1237	955	
RS&LS1 / Cu Fin Coils	1898	1894	1479	1429	1590	1195			

MODEL		Isolator Locations (x , y) - in. and Point Loads - lbs							
60 Hz	50 Hz		1	2	3	4	5	6	7
YCI0267S/P	YCI01000S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(97.2 , 86.8)	(161.4 , 86.8)	(210.6 , 86.8)	(307.9 , 86.8)	
		Al Fin Coils	1728	1638	1248	1160	1265	1005	
		Cu Fin Coils	1728	1728	1488	1435	1614	1246	
		RS&LS1 / Al Fin Coils	1907	1817	1248	1160	1265	1005	
		RS&LS1 / Cu Fin Coils	1907	1907	1488	1435	1614	1246	
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(97.2 , 1.3)	(161.4 , 1.3)	(210.6 , 1.3)	(307.9 , 1.3)	
		Al Fin Coils	1728	1638	1248	1160	1265	1005	
		Cu Fin Coils	1728	1728	1488	1435	1614	1246	
		RS&LS1 / Al Fin Coils	1907	1817	1248	1160	1265	1005	
		RS&LS1 / Cu Fin Coils	1907	1907	1488	1435	1618	1246	
YCI0287S/P	YCI01070S/P	LEFT - L	(9.1 , 86.8)	(58.1 , 86.8)	(111.1 , 86.8)	(204.7 , 86.8)	(284.9 , 86.8)	(368 , 86.8)	
		Al Fin Coils	1753	1585	1821	1810	2123	1175	
		Cu Fin Coils	1775	1757	2165	2156	2467	1347	
		RS&LS1 / Al Fin Coils	1929	1761	1821	1810	2189	1462	
		RS&LS1 / Cu Fin Coils	1885	1933	2165	2156	2533	1634	
		RIGHT - R	(9.1 , 1.3)	(58.1 , 1.3)	(111.1 , 1.3)	(204.7 , 1.3)	(284.9 , 1.3)	(368 , 1.3)	
		Al Fin Coils	1753	1596	2407	2414	2635	1179	
		Cu Fin Coils	1775	1768	2751	2760	2978	1351	
		RS&LS1 / Al Fin Coils	1929	1773	2407	2414	2701	1466	
		RS&LS1 / Cu Fin Coils	1951	1944	2751	2760	3045	1638	
YCI0307S/P	YCI01180S/P	LEFT - L	(9.1 , 86.8)	(58.1 , 86.8)	(111.1 , 86.8)	(204.7 , 86.8)	(284.9 , 86.8)	(368 , 86.8)	
		Al Fin Coils	1753	1585	1953	1978	2304	1184	
		Cu Fin Coils	1775	1757	2297	2324	2648	1356	
		RS&LS1 / Al Fin Coils	1929	1761	1953	1978	2370	1470	
		RS&LS1 / Cu Fin Coils	1951	1933	2297	2324	2714	1642	
		RIGHT - R	(9.1 , 1.3)	(58.1 , 1.3)	(111.1 , 1.3)	(204.7 , 1.3)	(284.9 , 1.3)	(368 , 1.3)	
		Al Fin Coils	1753	1596	2540	2632	2897	1188	
		Cu Fin Coils	1775	1768	2884	2978	3241	1338	
		RS&LS1 / Al Fin Coils	1929	1773	2540	2632	2963	1475	
		RS&LS1 / Cu Fin Coils	1951	1944	2884	2978	3307	1647	
YCI0357S/P	YCI01340S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(185.4 , 86.8)	(284.4 , 86.8)	(358.5 , 86.8)	(411.9 , 86.8)
		Al Fin Coils	1753	1585	1953	1978	1953	1140	946
		Cu Fin Coils	1775	1733	2238	2363	2339	1424	1065
		RS&LS1 / Al Fin Coils	1929	1761	1953	1978	1953	1316	1122
		RS&LS1 / Cu Fin Coils	1951	1909	2238	2363	2339	1601	1241
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(185.4 , 1.3)	(284.4 , 1.3)	(358.5 , 1.3)	(411.9 , 1.3)
		Al Fin Coils	1753	1596	2540	2632	2540	1151	946
		Cu Fin Coils	1775	1715	2824	3018	2926	1435	1065
		RS&LS1 / Al Fin Coils	1929	1773	2540	2632	2540	1327	1122
		RS&LS1 / Cu Fin Coils	1951	1892	2824	3018	2926	1612	1241
YCI0397S/P	YCI01500S/P	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(185.4 , 86.8)	(298.1 , 86.8)	(375.2 , 86.8)	(456 , 86.8)
		Al Fin Coils	1766	1607	1953	1978	2041	1404	1056
		Cu Fin Coils	1788	1755	2238	2363	2427	1689	1175
		RS&LS1 / Al Fin Coils	1942	1784	1953	1978	2041	1581	1232
		RS&LS1 / Cu Fin Coils	1964	1931	2238	2363	2427	1865	1351
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(185.4 , 1.3)	(298.1 , 1.3)	(375.2 , 1.3)	(456 , 1.3)
		Al Fin Coils	1766	1618	2540	2632	2628	1415	1056
		Cu Fin Coils	1788	1737	2824	3018	3014	1700	1175
		RS&LS1 / Al Fin Coils	1942	1795	2540	2632	2628	1592	1232
		RS&LS1 / Cu Fin Coils	1964	1914	2824	3018	3014	1876	1351

NOTES:1. RS = Reduced Sound Option, LS = Low Sound Option

Isolator Locations – English – continued




HIGH EFFICIENCY - ENGLISH

MODEL		Isolator Locations (x , y) - in. and Point Loads - lbs							
60 Hz	50 Hz		1	2	3	4	5	6	7
YCIV0157E/V	YCIV0590E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(211 , 86.8)			
		Al Fin Coils	1702	1594	1667	1609			
		Cu Fin Coils	1702	1706	2011	1951			
		RS&LS1 / Al Fin Coils	1881	1773	1667	1609			
		RS&LS1 / Cu Fin Coils	1881	1885	2011	1951			
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(211 , 1.3)			
		Al Fin Coils	1702	1594	1667	1609			
		Cu Fin Coils	1702	1706	2011	1951			
		RS&LS1 / Al Fin Coils	1881	1773	1667	1609			
RS&LS1 / Cu Fin Coils	1881	1885	2011	1951					
YCIV0177E/V	YCIV0630E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(195.7 , 86.8)	(265.4 , 86.8)		
		Al Fin Coils	1698	1559	1559	1274	774		
		Cu Fin Coils	1698	1680	1898	1653	935		
		RS&LS1 / Al Fin Coils	1876	1737	1559	1274	774		
		RS&LS1 / Cu Fin Coils	1876	1858	1898	1653	935		
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(195.7 , 1.3)	(265.4 , 1.3)		
		Al Fin Coils	1698	1559	1559	1241	664		
		Cu Fin Coils	1698	1680	1898	1620	825		
		RS&LS1 / Al Fin Coils	1876	1737	1559	1241	664		
RS&LS1 / Cu Fin Coils	1876	1858	1898	1620	825				
YCIV0187E/V	YCIV0700E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(195.7 , 86.8)	(265.4 , 86.8)		
		Al Fin Coils	1715	1581	1676	1287	820		
		Cu Fin Coils	1715	1702	2015	1667	981		
		RS&LS1 / Al Fin Coils	1894	1759	1676	1287	820		
		RS&LS1 / Cu Fin Coils	1894	1881	2015	1667	981		
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(195.7 , 1.3)	(265.4 , 1.3)		
		Al Fin Coils	1698	1561	1561	1287	820		
		Cu Fin Coils	1698	1682	1900	1667	981		
		RS&LS1 / Al Fin Coils	1876	1739	1561	1287	820		
RS&LS1 / Cu Fin Coils	1876	1861	1900	1667	981				
YCIV0197E/V	YCIV0760E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(195.7 , 86.8)	(265.4 , 86.8)		
		Al Fin Coils	1720	1609	1618	1354	860		
		Cu Fin Coils	1720	1731	1958	1733	1021		
		RS&LS1 / Al Fin Coils	1898	1788	1618	1354	860		
		RS&LS1 / Cu Fin Coils	1898	1909	1958	1733	1021		
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(195.7 , 1.3)	(265.4 , 1.3)		
		Al Fin Coils	1720	1609	1618	1354	860		
		Cu Fin Coils	1720	1731	1958	1733	1021		
		RS&LS1 / Al Fin Coils	1898	1788	1618	1354	860		
RS&LS1 / Cu Fin Coils	1898	1909	1958	1733	1021				
YCIV0207E/V	YCIV0800E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(97.2 , 86.8)	(161.4 , 86.8)	(210.6 , 86.8)	(307.9 , 86.8)	
		Al Fin Coils	1720	1614	1082	994	1093	952	
		Cu Fin Coils	1720	1704	1323	1270	1442	1193	
		RS&LS1 / Al Fin Coils	1898	1792	1082	994	1093	952	
		RS&LS1 / Cu Fin Coils	1898	1883	1323	1270	1442	1193	
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(97.2 , 1.3)	(161.4 , 1.3)	(210.6 , 1.3)	(307.9 , 1.3)	
		Al Fin Coils	1720	1614	1082	994	1078	955	
		Cu Fin Coils	1720	1704	1323	1270	1426	1195	
		RS&LS1 / Al Fin Coils	1898	1792	1082	994	1078	955	
RS&LS1 / Cu Fin Coils	1898	1883	1323	1270	1431	1195			

MODEL		Isolator Locations (x , y) - in. and Point Loads - lbs							
60 Hz	50 Hz		1	2	3	4	5	6	7
YCI0227E/V	YCI0830E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(97.2 , 86.8)	(161.4 , 86.8)	(210.6 , 86.8)	(307.9 , 86.8)	
		Al Fin Coils	1720	1616	1085	999	1102	1003	
		Cu Fin Coils	1720	1706	1325	1274	1451	1243	
		RS&LS1 / Al Fin Coils	1898	1795	1085	999	1102	1003	
		RS&LS1 / Cu Fin Coils	1898	1885	1325	1274	1451	1243	
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(97.2 , 1.3)	(161.4 , 1.3)	(210.6 , 1.3)	(307.9 , 1.3)	
		Al Fin Coils	1720	1616	1085	999	1102	1003	
		Cu Fin Coils	1720	1706	1325	1274	1451	1243	
		RS&LS1 / Al Fin Coils	1898	1795	1085	999	1102	1003	
		RS&LS1 / Cu Fin Coils	1898	1885	1325	1274	1455	1243	
YCI0247E/V	YCI0930E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(97.2 , 86.8)	(161.4 , 86.8)	(210.6 , 86.8)	(307.9 , 86.8)	
		Al Fin Coils	1728	1638	1248	1160	1265	1005	
		Cu Fin Coils	1728	1728	1488	1435	1614	1246	
		RS&LS1 / Al Fin Coils	1907	1817	1248	1160	1265	1005	
		RS&LS1 / Cu Fin Coils	1907	1907	1488	1435	1614	1246	
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(97.2 , 1.3)	(161.4 , 1.3)	(210.6 , 1.3)	(307.9 , 1.3)	
		Al Fin Coils	1720	1629	1248	1160	1265	1005	
		Cu Fin Coils	1720	1720	1488	1435	1614	1246	
		RS&LS1 / Al Fin Coils	1898	1808	1248	1160	1265	1005	
		RS&LS1 / Cu Fin Coils	1898	1898	1488	1435	1618	1246	
YCI0267E/V	YCI1050E/V	LEFT - L	(9.1 , 86.8)	(58.1 , 86.8)	(111.1 , 86.8)	(204.7 , 86.8)	(284.9 , 86.8)	(368 , 86.8)	
		Al Fin Coils	1753	1585	1821	1839	2163	1175	
		Cu Fin Coils	1775	1757	2165	2185	2507	1347	
		RS&LS1 / Al Fin Coils	1929	1761	1821	1839	2229	1396	
		RS&LS1 / Cu Fin Coils	1951	1933	2165	2185	2573	1634	
		RIGHT - R	(9.1 , 1.3)	(58.1 , 1.3)	(111.1 , 1.3)	(204.7 , 1.3)	(284.9 , 1.3)	(368 , 1.3)	
		Al Fin Coils	1753	1596	2407	2493	2756	1179	
		Cu Fin Coils	1775	1768	2751	2840	3100	1351	
		RS&LS1 / Al Fin Coils	1929	1773	2407	2493	2822	1466	
		RS&LS1 / Cu Fin Coils	1951	1944	2751	2840	3166	1638	
YCI0287E/V	YCI1120E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(185.4 , 86.8)	(284.4 , 86.8)	(358.5 , 86.8)	(411.9 , 86.8)
		Al Fin Coils	1753	1585	1847	1870	1574	1049	928
		Cu Fin Coils	1775	1733	2132	2255	1960	1334	1047
		RS&LS1 / Al Fin Coils	1929	1761	1847	1870	1574	1226	1105
		RS&LS1 / Cu Fin Coils	1885	1909	2132	2255	1960	1510	1224
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(185.4 , 1.3)	(284.4 , 1.3)	(358.5 , 1.3)	(411.9 , 1.3)
		Al Fin Coils	1753	1596	2434	2524	2344	1120	928
		Cu Fin Coils	1775	1715	2718	2910	2729	1404	1047
		RS&LS1 / Al Fin Coils	1929	1773	2434	2524	2344	1296	1105
		RS&LS1 / Cu Fin Coils	1951	1892	2718	2910	2729	1581	1224
YCI0327E/V	YCI1220E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(185.4 , 86.8)	(284.4 , 86.8)	(358.5 , 86.8)	(411.9 , 86.8)
		Al Fin Coils	1753	1585	1953	1978	1953	1140	928
		Cu Fin Coils	1775	1733	2238	2363	2339	1424	1047
		RS&LS1 / Al Fin Coils	1929	1761	1953	1978	1953	1316	1105
		RS&LS1 / Cu Fin Coils	1951	1931	2238	2363	2339	1601	1224
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(185.4 , 1.3)	(284.4 , 1.3)	(358.5 , 1.3)	(411.9 , 1.3)
		Al Fin Coils	1753	1596	2540	2632	2540	1151	928
		Cu Fin Coils	1775	1715	2824	3018	2926	1435	1047
		RS&LS1 / Al Fin Coils	1929	1773	2540	2632	2540	1327	1105
		RS&LS1 / Cu Fin Coils	1951	1892	2824	3018	2926	1612	1224
YCI0357E/V	YCI1380E/V	LEFT - L	(9.1 , 86.8)	(59.4 , 86.8)	(109.4 , 86.8)	(185.4 , 86.8)	(298.1 , 86.8)	(375.2 , 86.8)	(456 , 86.8)
		Al Fin Coils	1766	1607	1953	1978	2041	1404	1038
		Cu Fin Coils	1788	1755	2238	2363	2427	1689	1157
		RS&LS1 / Al Fin Coils	1942	1784	1953	1978	2041	1581	1215
		RS&LS1 / Cu Fin Coils	1964	1931	2238	2363	2427	1865	1334
		RIGHT - R	(9.1 , 1.3)	(59.4 , 1.3)	(109.4 , 1.3)	(185.4 , 1.3)	(298.1 , 1.3)	(375.2 , 1.3)	(456 , 1.3)
		Al Fin Coils	1766	1618	2540	2632	2628	1415	1038
		Cu Fin Coils	1788	1737	2824	3018	3014	1700	1157
		RS&LS1 / Al Fin Coils	1942	1795	2540	2632	2628	1592	1215
		RS&LS1 / Cu Fin Coils	1964	1914	2824	3018	3014	1876	1334

NOTES:1. RS = Reduced Sound Option, LS = Low Sound Option

Isolator Locations – SI




STANDARD EFFICIENCY - SI									
MODEL		Isolator Locations (x , y) - mm and Point Loads - kg							
60 Hz	50 Hz		1	2	3	4	5	6	7
YCIV0157S/P	YCIV0600S/P	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(5360 , 2204)			
		Al Fin Coils	772	722	633	608			
		Cu Fin Coils	772	773	789	763			
		RS&LS1 / Al Fin Coils	853	803	633	608			
		RS&LS1 / Cu Fin Coils	853	854	789	763			
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(5360 , 32)			
		Al Fin Coils	772	722	633	608			
		Cu Fin Coils	772	773	789	763			
YCIV0177S/P	YCIV0650S/P	RS&LS1 / Al Fin Coils	853	803	633	608			
		RS&LS1 / Cu Fin Coils	853	854	789	763			
		LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(5360 , 2204)			
		Al Fin Coils	780	732	756	730			
		Cu Fin Coils	780	783	912	885			
		RS&LS1 / Al Fin Coils	861	813	756	730			
		RS&LS1 / Cu Fin Coils	861	864	912	885			
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(5360 , 32)			
YCIV0187S/P	YCIV0720S/P	Al Fin Coils	772	723	756	730			
		Cu Fin Coils	772	774	912	885			
		RS&LS1 / Al Fin Coils	853	804	756	730			
		RS&LS1 / Cu Fin Coils	853	855	912	885			
		LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4970 , 2204)	(6740 , 2204)		
		Al Fin Coils	778	716	707	578	351		
		Cu Fin Coils	778	771	861	750	424		
		RS&LS1 / Al Fin Coils	859	797	707	578	351		
YCIV0207S/P	YCIV0770S/P	RS&LS1 / Cu Fin Coils	859	852	861	750	424		
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4970 , 32)	(6740 , 32)		
		Al Fin Coils	770	707	707	563	301		
		Cu Fin Coils	770	762	861	735	374		
		RS&LS1 / Al Fin Coils	851	788	707	563	301		
		RS&LS1 / Cu Fin Coils	851	843	861	735	374		
		LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4970 , 2204)	(6740 , 2204)		
		Al Fin Coils	784	762	802	686	415		
YCIV0277S/P	YCIV0840S/P	Cu Fin Coils	784	817	956	858	488		
		RS&LS1 / Al Fin Coils	865	843	802	686	415		
		RS&LS1 / Cu Fin Coils	865	898	956	858	488		
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4970 , 32)	(6740 , 32)		
		Al Fin Coils	784	760	800	669	363		
		Cu Fin Coils	784	815	956	841	436		
		RS&LS1 / Al Fin Coils	865	841	800	669	363		
		RS&LS1 / Cu Fin Coils	865	896	954	841	436		

MODEL		Isolator Locations (x , y) - mm and Point Loads - kg							
60 Hz	50 Hz		1	2	3	4	5	6	7
YCIV0247S/P	YCIV0920S/P	LEFT - L	(230 , 2204)	(1510 , 2204)	(2470 , 2204)	(4100 , 2204)	(5350 , 2204)	(7820 , 2204)	
		Al Fin Coils	784	743	566	526	572	435	
		Cu Fin Coils	784	784	675	651	730	544	
		RS&LS1 / Al Fin Coils	865	824	566	526	572	435	
		RS&LS1 / Cu Fin Coils	865	865	675	651	730	544	
		RIGHT - R	(230 , 32)	(1510 , 32)	(2470 , 32)	(4100 , 32)	(5350 , 32)	(7820 , 32)	
		Al Fin Coils	780	737	562	523	561	433	
		Cu Fin Coils	780	778	671	648	719	542	
		RS&LS1 / Al Fin Coils	861	818	562	523	561	433	
		RS&LS1 / Cu Fin Coils	861	859	671	648	721	542	
YCIV0267S/P	YCIV1000S/P	LEFT - L	(230 , 2204)	(1510 , 2204)	(2470 , 2204)	(4100 , 2204)	(5350 , 2204)	(7820 , 2204)	
		Al Fin Coils	784	743	566	526	574	456	
		Cu Fin Coils	784	784	675	651	732	565	
		RS&LS1 / Al Fin Coils	865	824	566	526	574	456	
		RS&LS1 / Cu Fin Coils	865	865	675	651	732	565	
		RIGHT - R	(230 , 32)	(1510 , 32)	(2470 , 32)	(4100 , 32)	(5350 , 32)	(7820 , 32)	
		Al Fin Coils	784	743	566	526	574	456	
		Cu Fin Coils	784	784	675	651	732	565	
		RS&LS1 / Al Fin Coils	865	824	566	526	574	456	
		RS&LS1 / Cu Fin Coils	865	865	675	651	734	565	
YCIV0287S/P	YCIV1070S/P	LEFT - L	(230 , 2204)	(1475 , 2204)	(2823 , 2204)	(5199 , 2204)	(7236 , 2204)	(9346 , 2204)	
		Al Fin Coils	795	719	826	821	963	533	
		Cu Fin Coils	805	797	982	978	1119	611	
		RS&LS1 / Al Fin Coils	875	799	826	821	993	663	
		RS&LS1 / Cu Fin Coils	855	877	982	978	1149	741	
		RIGHT - R	(230 , 32)	(1475 , 32)	(2823 , 32)	(5199 , 32)	(7236 , 32)	(9346 , 32)	
		Al Fin Coils	795	724	1092	1095	1195	535	
		Cu Fin Coils	805	802	1248	1252	1351	613	
		RS&LS1 / Al Fin Coils	875	804	1092	1095	1225	665	
		RS&LS1 / Cu Fin Coils	885	882	1248	1252	1381	743	
YCIV0307S/P	YCIV1180S/P	LEFT - L	(230 , 2204)	(1475 , 2204)	(2823 , 2204)	(5199 , 2204)	(7236 , 2204)	(9346 , 2204)	
		Al Fin Coils	795	719	886	897	1045	537	
		Cu Fin Coils	805	797	1042	1054	1201	615	
		RS&LS1 / Al Fin Coils	875	799	886	897	1075	667	
		RS&LS1 / Cu Fin Coils	885	877	1042	1054	1231	745	
		RIGHT - R	(230 , 32)	(1475 , 32)	(2823 , 32)	(5199 , 32)	(7236 , 32)	(9346 , 32)	
		Al Fin Coils	795	724	1152	1194	1314	539	
		Cu Fin Coils	805	802	1308	1351	1470	607	
		RS&LS1 / Al Fin Coils	875	804	1152	1194	1344	669	
		RS&LS1 / Cu Fin Coils	885	882	1308	1351	1500	747	
YCIV0357S/P	YCIV1340S/P	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4710 , 2204)	(7225 , 2204)	(9105 , 2204)	(10463 , 2204)
		Al Fin Coils	795	719	886	897	886	517	429
		Cu Fin Coils	805	786	1015	1072	1061	646	483
		RS&LS1 / Al Fin Coils	875	799	886	897	886	597	509
		RS&LS1 / Cu Fin Coils	885	866	1015	1072	1061	726	563
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4710 , 32)	(7225 , 32)	(9105 , 32)	(10463 , 32)
		Al Fin Coils	795	724	1152	1194	1152	522	429
		Cu Fin Coils	805	778	1281	1369	1327	651	483
		RS&LS1 / Al Fin Coils	875	804	1152	1194	1152	602	509
		RS&LS1 / Cu Fin Coils	885	858	1281	1369	1327	731	563
YCIV0397S/P	YCIV1500S/P	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4710 , 2204)	(7572 , 2204)	(9530 , 2204)	(11582 , 2204)
		Al Fin Coils	801	729	886	897	926	637	479
		Cu Fin Coils	811	796	1015	1072	1101	766	533
		RS&LS1 / Al Fin Coils	881	809	886	897	926	717	559
		RS&LS1 / Cu Fin Coils	891	876	1015	1072	1101	846	613
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4710 , 32)	(7572 , 32)	(9530 , 32)	(11582 , 32)
		Al Fin Coils	801	734	1152	1194	1192	642	479
		Cu Fin Coils	811	788	1281	1369	1367	771	533
		RS&LS1 / Al Fin Coils	881	814	1152	1194	1192	722	559
		RS&LS1 / Cu Fin Coils	891	868	1281	1369	1367	851	613

NOTES:

1. RS = Reduced Sound Option, LS = Low Sound Option

Isolator Locations – SI – continued



HIGH EFFICIENCY - SI

MODEL		Isolator Locations (x , y) - mm and Point Loads - kg							
60 Hz	50 Hz		1	2	3	4	5	6	7
YCIV0157E/V	YCIV0590E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(5360 , 2204)			
		Al Fin Coils	772	723	756	730			
		Cu Fin Coils	772	774	912	885			
		RS&LS1 / Al Fin Coils	853	804	756	730			
		RS&LS1 / Cu Fin Coils	853	855	912	885			
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(5360 , 32)			
		Al Fin Coils	772	723	756	730			
		Cu Fin Coils	772	774	912	885			
		RS&LS1 / Al Fin Coils	853	804	756	730			
		RS&LS1 / Cu Fin Coils	853	855	912	885			
YCIV0177E/V	YCIV0630E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4970 , 2204)	(6740 , 2204)		
		Al Fin Coils	770	707	707	578	351		
		Cu Fin Coils	770	762	861	750	424		
		RS&LS1 / Al Fin Coils	851	788	707	578	351		
		RS&LS1 / Cu Fin Coils	851	843	861	750	424		
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4970 , 32)	(6740 , 32)		
		Al Fin Coils	770	707	707	563	301		
		Cu Fin Coils	770	762	861	735	374		
		RS&LS1 / Al Fin Coils	851	788	707	563	301		
		RS&LS1 / Cu Fin Coils	851	843	861	735	374		
YCIV0187E/V	YCIV0700E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4970 , 2204)	(6740 , 2204)		
		Al Fin Coils	778	717	760	584	372		
		Cu Fin Coils	778	772	914	756	445		
		RS&LS1 / Al Fin Coils	859	798	760	584	372		
		RS&LS1 / Cu Fin Coils	859	853	914	756	445		
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4970 , 32)	(6740 , 32)		
		Al Fin Coils	770	708	708	584	372		
		Cu Fin Coils	770	763	862	756	445		
		RS&LS1 / Al Fin Coils	851	789	708	584	372		
		RS&LS1 / Cu Fin Coils	851	844	862	756	445		
YCIV0197E/V	YCIV0760E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4970 , 2204)	(6740 , 2204)		
		Al Fin Coils	780	730	734	614	390		
		Cu Fin Coils	780	785	888	786	463		
		RS&LS1 / Al Fin Coils	861	811	734	614	390		
		RS&LS1 / Cu Fin Coils	861	866	888	786	463		
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4970 , 32)	(6740 , 32)		
		Al Fin Coils	780	730	734	614	390		
		Cu Fin Coils	780	785	888	786	463		
		RS&LS1 / Al Fin Coils	861	811	734	614	390		
		RS&LS1 / Cu Fin Coils	861	866	888	786	463		
YCIV0207E/V	YCIV0800E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2470 , 2204)	(4100 , 2204)	(5350 , 2204)	(7820 , 2204)	
		Al Fin Coils	780	732	491	451	496	432	
		Cu Fin Coils	780	773	600	576	654	541	
		RS&LS1 / Al Fin Coils	861	813	491	451	496	432	
		RS&LS1 / Cu Fin Coils	861	854	600	576	654	541	
		RIGHT - R	(230 , 32)	(1510 , 32)	(2470 , 32)	(4100 , 32)	(5350 , 32)	(7820 , 32)	
		Al Fin Coils	780	732	491	451	489	433	
		Cu Fin Coils	780	773	600	576	647	542	
		RS&LS1 / Al Fin Coils	861	813	491	451	489	433	
		RS&LS1 / Cu Fin Coils	861	854	600	576	649	542	

MODEL		Isolator Locations (x , y) - mm and Point Loads - kg						
60 Hz	50 Hz	1	2	3	4	5	6	7
YCIV0227E/V	YCIV0830E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2470 , 2204)	(4100 , 2204)	(5350 , 2204)	(7820 , 2204)
		Al Fin Coils	780	733	492	453	500	455
		Cu Fin Coils	780	774	601	578	658	564
		RS&LS1 / Al Fin Coils	861	814	492	453	500	455
		RS&LS1 / Cu Fin Coils	861	855	601	578	658	564
		RIGHT - R	(230 , 32)	(1510 , 32)	(2470 , 32)	(4100 , 32)	(5350 , 32)	(7820 , 32)
		Al Fin Coils	780	733	492	453	500	455
		Cu Fin Coils	780	774	601	578	658	564
		RS&LS1 / Al Fin Coils	861	814	492	453	500	455
		RS&LS1 / Cu Fin Coils	861	855	601	578	660	564
YCIV0247E/V	YCIV0930E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2470 , 2204)	(4100 , 2204)	(5350 , 2204)	(7820 , 2204)
		Al Fin Coils	784	743	566	526	574	456
		Cu Fin Coils	784	784	675	651	732	565
		RS&LS1 / Al Fin Coils	865	824	566	526	574	456
		RS&LS1 / Cu Fin Coils	865	865	675	651	732	565
		RIGHT - R	(230 , 32)	(1510 , 32)	(2470 , 32)	(4100 , 32)	(5350 , 32)	(7820 , 32)
		Al Fin Coils	780	739	566	526	574	456
		Cu Fin Coils	780	780	675	651	732	565
		RS&LS1 / Al Fin Coils	861	820	566	526	574	456
		RS&LS1 / Cu Fin Coils	861	861	675	651	734	565
YCIV0267E/V	YCIV1050E/V	LEFT - L	(230 , 2204)	(1475 , 2204)	(2823 , 2204)	(5199 , 2204)	(7236 , 2204)	(9346 , 2204)
		Al Fin Coils	795	719	826	834	981	533
		Cu Fin Coils	805	797	982	991	1137	611
		RS&LS1 / Al Fin Coils	875	799	826	834	1011	633
		RS&LS1 / Cu Fin Coils	885	877	982	991	1167	741
		RIGHT - R	(230 , 32)	(1475 , 32)	(2823 , 32)	(5199 , 32)	(7236 , 32)	(9346 , 32)
		Al Fin Coils	795	724	1092	1131	1250	535
		Cu Fin Coils	805	802	1248	1288	1406	613
		RS&LS1 / Al Fin Coils	875	804	1092	1131	1280	665
		RS&LS1 / Cu Fin Coils	885	882	1248	1288	1436	743
YCIV0287E/V	YCIV1120E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4710 , 2204)	(7225 , 2204)	(9105 , 2204)
		Al Fin Coils	795	719	838	848	714	476
		Cu Fin Coils	805	786	967	1023	889	605
		RS&LS1 / Al Fin Coils	875	799	838	848	714	556
		RS&LS1 / Cu Fin Coils	855	866	967	1023	889	685
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4710 , 32)	(7225 , 32)	(9105 , 32)
		Al Fin Coils	795	724	1104	1145	1063	508
		Cu Fin Coils	805	778	1233	1320	1238	637
		RS&LS1 / Al Fin Coils	875	804	1104	1145	1063	588
		RS&LS1 / Cu Fin Coils	885	858	1233	1320	1238	717
YCIV0327E/V	YCIV1220E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4710 , 2204)	(7225 , 2204)	(9105 , 2204)
		Al Fin Coils	795	719	886	897	886	517
		Cu Fin Coils	805	786	1015	1072	1061	646
		RS&LS1 / Al Fin Coils	875	799	886	897	886	597
		RS&LS1 / Cu Fin Coils	885	876	1015	1072	1061	726
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4710 , 32)	(7225 , 32)	(9105 , 32)
		Al Fin Coils	795	724	1152	1194	1152	522
		Cu Fin Coils	805	778	1281	1369	1327	651
		RS&LS1 / Al Fin Coils	875	804	1152	1194	1152	602
		RS&LS1 / Cu Fin Coils	885	858	1281	1369	1327	731
YCIV0357E/V	YCIV1380E/V	LEFT - L	(230 , 2204)	(1510 , 2204)	(2780 , 2204)	(4710 , 2204)	(7572 , 2204)	(9530 , 2204)
		Al Fin Coils	801	729	886	897	926	637
		Cu Fin Coils	811	796	1015	1072	1101	766
		RS&LS1 / Al Fin Coils	881	809	886	897	926	717
		RS&LS1 / Cu Fin Coils	891	876	1015	1072	1101	846
		RIGHT - R	(230 , 32)	(1510 , 32)	(2780 , 32)	(4710 , 32)	(7572 , 32)	(9530 , 32)
		Al Fin Coils	801	734	1152	1194	1192	642
		Cu Fin Coils	811	788	1281	1369	1367	771
		RS&LS1 / Al Fin Coils	881	814	1152	1194	1192	722
		RS&LS1 / Cu Fin Coils	891	868	1281	1369	1367	851

NOTES:



1. RS = Reduced Sound Option, LS = Low Sound Option

Isolator Details

ONE INCH DEFLECTION SPRING ISOLATOR CROSS-REFERENCE


CIP-X-

Illustration shows single spring CIP-B or CIP-C mount.



NEOPRENE ISOLATOR CROSS-REFERENCE

ND-X




ENGLISH								
Size	D	H	L	T	W	BC	CS	MBD
ND-C	2 9/16	2 3/4	5 1/2	1/4	2 5/16	4 1/80	1/2- 13 x 1"	1/2"
ND-D	3 3/8	2 3/4	6 1/4	5/16	4	5	1/2- 13 x 1"	1/2"
ND-DS	3 3/8	2 3/4	6 1/4	5/16	4	5	1/2- 13 x 1"	1/2"
SI								
ND-C	65.1	69.9	139.7	6.4	58.7	101.9	1/2- 13 x 1"	1/2"
ND-D	85.7	69.9	158.8	7.9	101.6	127.0	1/2- 13 x 1"	1/2"
ND-DS	85.7	69.9	158.8	7.9	101.6	127.0	1/2- 13 x 1"	1/2"

Weight Range (lbs)	Weight Range (kg)	Model Number	Color
Up to 751 lbs	Up to 341 kg	ND-C	Yellow
751 to 1651 lbs	341 to 749 kg	ND-D	Yellow
1651 to 3226 lbs	749 to 1463 kg	ND-DS	Yellow

Isolator Details (cont'd)

TWO INCH DEFLECTION, SEISMIC SPRING ISOLATOR CROSS-REFERENCE

SLRS



ENGLISH

SIZE	H	T	D	E	L	HCL	W	HCW	MBD
2-C2	8 1/2	3/8	5/8	1 3/8	14	12 1/4	5 1/4	3 1/2	5/8"

SI

SIZE	H	T	D	E	L	HCL	W	HCW	MBD
2-C2	215.9	9.5	15.9	34.9	355.6	311.2	133.4	88.9	5/8"

*Weight Range (lbs)	Weight Range (kg)	Model Number	Color
Up to 358 lbs	Up to 162 kg	SLRS-2-C2-	Red
358 to 443 lbs	162 to 201 kg	SLRS-2-C2-	White
443 to 582 lbs	201 to 264 kg	SLRS-2-C2-	Black
582 to 783 lbs	264 to 335 kg	SLRS-2-C2-	Blue
783 to 1038 lbs	335 to 471 kg	SLRS-2-C2-	Green
1038 to 1497 lbs	471 to 679 kg	SLRS-2-C2-	Gray
1497 to 2058 lbs	679 to 933 kg	SLRS-2-C2-	Silver
2058 to 2619 lbs	933 to 1188 kg	SLRS-2-C2-	Gray w/ red
2619 to 3180 lbs	1188 to 1442 kg	SLRS-2-C2-	Silver w/ red

INTENTIONALLY LEFT BLANK

Electrical Data - 2 Comp Standard Efficiency

Standard Efficiency YCIV____ S/P

Model No./Nameplate			System 1								
			Std. & Ultra Quiet Cond. Fans			High Head/Static Cond. Fans			Two-Speed Cond. Fans		
YCIV S/P	Input Volts (9)	Input Freq	Compressor RLA (5)	Condenser Fans		Compressor RLA (5)	Condenser Fans		Compressor RLA (5)	Condenser Fans	
				Qty.	FLA (EA)		Qty.	FLA (EA)		Qty.	FLA (EA)
0157	460	60	120	4	2.8						
	380	60	152	4	3.5	152	4	9.3			
0600	400	50	144	4	3.1	144	4	9.3	152	4	3.8
0177	460	60	159	4	2.8						
	380	60	201	4	3.5	201	4	9.3			
0650	400	50	191	4	3.1	191	4	9.3	198	4	3.8
0187	460	60	162	5	2.8						
	380	60	205	5	3.5	205	5	9.3			
0720	400	50	195	5	3.1	195	5	9.3	207	5	3.8
0207	460	60	145	5	2.8						
	380	60	184	5	3.5	184	5	9.3			
0770	400	50	174	5	3.1	174	5	9.3	185	5	3.8
0227	460	60	162	5	2.8						
	380	60	205	5	3.5	205	5	9.3			
0840	400	50	194	5	3.1	194	5	9.3	206	5	3.8
0247	460	60	193	6	2.8						
	380	60	245	6	3.5	245	6	9.3			
0920	400	50	232	6	3.1	232	6	9.3	246	6	3.8
0267	460	60	191	6	2.8						
	380	60	242	6	3.5	242	6	9.3			
1000	400	50	230	6	3.1	230	6	9.3	243	6	3.8

YCIV S/P	Control KVA (7)	Unit Short Circuit Withstand (KA)		Field Wiring & Protection			
				Std. & Ultra Quiet Cond. Fans			
		Terminal Block (STD)	Circuit Breaker (OPT)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)
0157	1.8	30KA	65KA	293	350	400	400
	1.8	30KA	65KA	370	450	500	500
0600	1.8	30KA	65KA	350	400	450	450
0177	1.8	30KA	65KA	326	400	450	450
	1.8	30KA	65KA	413	500	600	600
0650	1.8	30KA	65KA	390	450	500	500
0187	1.8	30KA	65KA	348	400	500	500
	1.8	30KA	65KA	440	500	600	600
0720	1.8	30KA	65KA	416	500	600	600
0207	1.8	30KA	65KA	373	450	500	500
	1.8	30KA	65KA	472	600	600	600
0770	1.8	30KA	65KA	446	500	600	600
0227	1.8	30KA	65KA	392	450	500	500
	1.8	30KA	65KA	496	600	700	700
0840	1.8	30KA	65KA	468	600	600	600
0247	1.8	30KA	65KA	433	500	600	600
	1.8	30KA	65KA	547	700	700	700
0920	1.8	30KA	65KA	517	600	700	700
0267	1.8	30KA	65KA	464	600	600	600
	1.8	30KA	65KA	587	700	800	800
1000	1.8	30KA	65KA	555	700	700	700

See page 192 for Electrical Data footnotes.

Standard Efficiency YCIV____ S/P

System 2								
Std. & Ultra Quiet Cond. Fans			High Head/Static Cond. Fans			Two-Speed Cond. Fans		
Compressor RLA (5)	Condenser Fans		Compressor RLA (5)	Condenser Fans		Compressor RLA (5)	Condenser Fans	
	Qty.	FLA (EA)		Qty.	FLA (EA)		Qty.	FLA (EA)
120	4	2.8						
152	4	3.5	152	4	9.3			
144	4	3.1	144	4	9.3	152	4	3.8
105	4	2.8						
133	4	3.5	133	4	9.3			
127	4	3.1	127	4	9.3	132	4	3.8
120	4	2.8						
152	4	3.5	152	4	9.3			
144	4	3.1	144	4	9.3	152	4	3.8
162	4	2.8						
206	4	3.5	206	4	9.3			
195	4	3.1	195	4	9.3	201	4	3.8
162	5	2.8						
205	5	3.5	205	5	9.3			
194	5	3.1	194	5	9.3	206	5	3.8
160	5	2.8						
203	5	3.5	203	5	9.3			
192	5	3.1	192	5	9.3	204	5	3.8
191	6	2.8						
242	6	3.5	242	6	9.3			
230	6	3.1	230	6	9.3	243	6	3.8

High Head/High Static Fans				Two-Speed Cond. Fans			
Minimum Ckt. Am- pacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)	Minimum Ckt. Am- pacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)
417	500	500	500				
373	450	500	500	399	450	500	500
459	600	600	600				
410	500	600	600	440	500	600	600
492	600	700	700				
445	500	600	600	472	600	600	600
525	600	700	700				
471	600	600	600	502	600	700	700
554	700	700	700				
502	600	700	700	530	600	700	700
610	700	800	800				
553	700	800	800	585	700	800	800
657	800	800	800				
593	700	800	800	629	700	800	800

Electrical Data - 2 Comp High Efficiency

High Efficiency YCIV_ _ _ _ E/V											
Model No./Nameplate			System 1								
			Std. & Ultra Quiet Cond. Fans			High Head/Static Cond. Fans			Two-Speed Cond. Fans		
			Compressor	Condenser Fans		Compressor	Condenser Fans		Compressor	Condenser Fans	
YCIV E/V	Input Volts (9)	Input Freq	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)
0157	460	60	110	4	2.8						
	380	60	139	4	3.5	139	4	9.3			
0590	400	50	132	4	3.1	132	4	9.3	138	4	3.8
0177	460	60	111	5	2.8						
	380	60	141	5	3.5	141	5	9.3			
0630	400	50	134	5	3.1	134	5	9.3	139	5	3.8
0187	460	60	154	5	2.8						
	380	60	195	5	3.5	195	5	9.3			
0700	400	50	185	5	3.1	185	5	9.3	196	5	3.8
0197	460	60	141	5	2.8						
	380	60	179	5	3.5	179	5	9.3			
0760	400	50	170	5	3.1	170	5	9.3	180	5	3.8
0207	460	60	141	6	2.8						
	380	60	179	6	3.5	179	6	9.3			
0800	400	50	170	6	3.1	170	6	9.3	178	6	3.8
0227	460	60	150	6	2.8						
	380	60	190	6	3.5	190	6	9.3			
0830	400	50	180	6	3.1	180	6	9.3	189	6	3.8
0247	460	60	194	6	2.8						
	380	60	245	6	3.5	245	6	9.3			
0930	400	50	233	6	3.1	233	6	9.3	246	6	3.8

YCIV E/V	Control KVA (7)	Unit Short Circuit Withstand (KA)		Field Wiring & Protection			
				Std. & Ultra Quiet Cond. Fans			
		Terminal Block (STD)	Circuit Breaker (OPT)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)
0157	1.8	30KA	65KA	270	300	350	350
	1.8	30KA	65KA	341	400	450	450
0590	1.8	30KA	65KA	322	400	450	450
0177	1.8	30KA	65KA	288	350	400	400
	1.8	30KA	65KA	365	450	500	500
0630	1.8	30KA	65KA	344	400	450	450
0187	1.8	30KA	65KA	325	400	450	450
	1.8	30KA	65KA	411	500	600	600
0700	1.8	30KA	65KA	388	450	500	500
0197	1.8	30KA	65KA	345	400	450	450
	1.8	30KA	65KA	437	500	600	600
0760	1.8	30KA	65KA	412	500	500	500
0207	1.8	30KA	65KA	362	450	500	500
	1.8	30KA	65KA	458	600	600	600
0800	1.8	30KA	65KA	433	500	600	600
0227	1.8	30KA	65KA	371	450	500	500
	1.8	30KA	65KA	469	600	600	600
0830	1.8	30KA	65KA	443	500	600	600
0247	1.8	30KA	65KA	424	500	600	600
	1.8	30KA	65KA	536	700	700	700
0930	1.8	30KA	65KA	506	600	700	700

High Efficiency YCIV_ _ _ _ E/V

System 2

Std. & Ultra Quiet Cond. Fans			High Head/Static Cond. Fans			Two-Speed Cond. Fans		
Compressor	Condenser Fans		Compressor	Condenser Fans		Compressor	Condenser Fans	
RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)
110	4	2.8						
139	4	3.5	139	4	9.3			
132	4	3.1	132	4	9.3	138	4	3.8
122	4	2.8						
154	4	3.5	154	4	9.3			
146	4	3.1	146	4	9.3	154	4	3.8
105	5	2.8						
132	5	3.5	132	5	9.3			
126	5	3.1	126	5	9.3	131	5	3.8
141	5	2.8						
179	5	3.5	179	5	9.3			
170	5	3.1	170	5	9.3	180	5	3.8
152	5	2.8						
193	5	3.5	193	5	9.3			
183	5	3.1	183	5	9.3	195	5	3.8
150	6	2.8						
190	6	3.5	190	6	9.3			
180	6	3.1	180	6	9.3	189	6	3.8
149	6	2.8						
188	6	3.5	188	6	9.3			
178	6	3.1	178	6	9.3	187	6	3.8

High Head/High Static Fans				Two-Speed Cond. Fans			
Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)
388	450	500	500				
372	450	500	500	342	400	450	450
417	500	500	500				
400	450	500	500	366	450	500	500
469	600	600	600				
450	500	600	600	414	500	600	600
495	600	600	600				
474	600	600	600	442	500	600	600
522	600	700	700				
501	600	600	600	463	600	600	600
539	600	700	700				
517	600	700	700	472	600	600	600
606	700	800	800				
581	700	800	800	541	700	700	700

Electrical Data - 3 Comp Standard Efficiency

Model No./Nameplate			System 1									System 2		
			Std. & Ultra Quiet Cond. Fans			High Head/Static Cond. Fans			Two-Speed Cond. Fans			Std. & Ultra Quiet Cond. Fans		
			Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans	
YCIV S/P	Input Volts (9)	Input Freq	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)
0287	460	60	146	5	2.8							164	4	2.8
	380	60	184	5	3.5	184	5	9.3				207	4	3.5
1070	400	50	175	5	3.1	175	5	9.3	186	5	3.8	196	4	3.1
0307	460	60	147	5	2.8							147	5	2.8
	380	60	186	5	3.5	186	5	9.3				186	5	3.5
1180	400	50	177	5	3.1	177	5	9.3	188	5	3.8	177	5	3.1
0357	460	60	160	5	2.8							160	5	2.8
	380	60	202	5	3.5	202	5	9.3				202	5	3.5
1340	400	50	192	5	3.1	192	5	9.3	204	5	3.8	192	5	3.1
0397	460	60	191	6	2.8							191	6	2.8
	380	60	241	6	3.5	241	6	9.3				241	6	3.5
1500	400	50	229	6	3.1	229	6	9.3	243	6	3.8	229	6	3.1

YCIV S/P	Control KVA (7)	Unit Short Circuit Withstand (KA)		Field Wiring & Protection					
				Std. & Ultra Quiet Cond. Fans				High Head/High Static Fans	
		Terminal Block (STD)	Circuit Breaker (OPT)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)
0287	2.4	30KA	65KA	494	600	600	600		
	2.4	30KA	65KA	624	700	800	800	676	800
1070	2.4	30KA	65KA	590	700	700	700	671	800
0307	2.4	30KA	65KA	540	600	700	700		
	2.4	30KA	65KA	682	800	800	800	731	800
1180	2.4	30KA	65KA	644	700	800	800	731	800
0357	2.4	30KA	65KA	607	700	800	800		
	2.4	30KA	65KA	766	1000	1000	1000	827	1000
1340	2.4	30KA	65KA	724	800	800	800	824	1000
0397	2.4	30KA	65KA	671	800	800	800		
	2.4	30KA	65KA	847	1000	1000	1000	911	1000
1500	2.4	30KA	65KA	801	1000	1000	1000	913	1000

System 2						System 3								
High Head/Static Cond. Fans			Two-Speed Cond. Fans			Std. & Ultra Quiet Cond. Fans			High Head/Static Cond. Fans			Two-Speed Cond. Fans		
Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans	
RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)
						108	4	2.8						
207	4	9.3				136	4	3.5	136	4	9.3			
196	4	9.3	202	4	3.8	129	4	3.1	129	4	9.3	135	4	3.8
						165	4	2.8						
186	5	9.3				208	4	3.5	208	4	9.3			
177	5	9.3	188	5	3.8	198	4	3.1	198	4	9.3	203	4	3.8
						193	6	2.8						
202	5	9.3				244	6	3.5	244	6	9.3			
192	5	9.3	204	5	3.8	232	6	3.1	232	6	9.3	245	6	3.8
						191	6	2.8						
241	6	9.3				241	6	3.5	241	6	9.3			
229	6	9.3	243	6	3.8	229	6	3.1	229	6	9.3	243	6	3.8

Field Wiring & Protection						Field Wiring Lugs			
High Head/High Static Fans		Two-Speed Cond. Fans				STD Terminal Block		OPT Circuit Breaker	
Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)				
						Lugs/ Phase (1)	Lug Wire Range	Lugs/ Phase (1)	Lug Wire Range
						4	#2 - 600 KCM	4	#4/0 - 500 KCM
800	800					4	#2 - 600 KCM	4	#4/0 - 500 KCM
800	800	623	700	800	800	4	#2 - 600 KCM	4	#4/0 - 500 KCM
						4	#2 - 600 KCM	4	#4/0 - 500 KCM
800	800					4	#2 - 600 KCM	4	#4/0 - 500 KCM
800	800	683	800	800	800	4	#2 - 600 KCM	4	#4/0 - 500 KCM
						4	#2 - 600 KCM	4	#4/0 - 500 KCM
1000	1000					4	#2 - 600 KCM	4	#4/0 - 500 KCM
1000	1000	776	1000	1000	1000	4	#2 - 600 KCM	4	#4/0 - 500 KCM
						4	#2 - 600 KCM	4	#4/0 - 500 KCM
1000	1000					4	#2 - 600 KCM	4	#4/0 - 500 KCM
1000	1000	857	1000	1000	1000	4	#2 - 600 KCM	4	#4/0 - 500 KCM

Electrical Data - 3 Comp High Efficiency

Model No./Nameplate			System 1									System 2		
			Std. & Ultra Quiet Cond. Fans			High Head/Static Cond. Fans			Two-Speed Cond. Fans			Std. & Ultra Quiet Cond. Fans		
			Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans	
YCIV E/V	Input Volts (9)	Input Freq	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)
0267	460	60	142	5	2.8							142	5	2.8
	380	60	179	5	3.5	179	5	9.3				179	4	3.5
1050	400	50	170	5	3.1	170	5	9.3	180	5	3.8	170	5	3.1
0287	460	60	137	5	2.8							137	5	2.8
	380	60	173	5	3.5	173	5	9.3				173	5	3.5
1120	400	50	164	5	3.1	164	5	9.3	173	5	3.8	164	5	3.1
0327	460	60	152	5	2.8							152	5	2.8
	380	60	193	5	3.5	193	5	9.3				193	5	3.5
1220	400	50	183	5	3.1	183	5	9.3	194	5	3.8	183	5	3.1
0357	460	60	181	6	2.8							181	6	2.8
	380	60	229	6	3.5	229	6	9.3				229	6	3.5
1380	400	50	218	6	3.1	218	6	9.3	229	6	3.8	218	6	3.1

YCIV S/P	Control KVA (7)	Unit Short Circuit Withstand (KA)		Field Wiring & Protection					
				Std. & Ultra Quiet Cond. Fans				High Head/High Static Fans	
		Terminal Block (STD)	Circuit Breaker (OPT)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)
0287	2.4	30KA	65KA	463	600	600	600		
	2.4	30KA	65KA	581	700	700	700	632	800
1070	2.4	30KA	65KA	552	600	700	700	639	700
0307	2.4	30KA	65KA	486	600	600	600		
	2.4	30KA	65KA	610	700	700	700	659	800
1180	2.4	30KA	65KA	580	700	700	700	673	800
0357	2.4	30KA	65KA	528	600	600	600		
	2.4	30KA	65KA	667	800	800	800	728	800
1340	2.4	30KA	65KA	631	700	800	800	730	800
0397	2.4	30KA	65KA	598	700	700	700		
	2.4	30KA	65KA	755	800	800	800	818	1000
1500	2.4	30KA	65KA	713	800	800	800	824	1000

See page 192 for Electrical Data footnotes.

System 2						System 3								
High Head/Static Cond. Fans			Two-Speed Cond. Fans			Std. & Ultra Quiet Cond. Fans			High Head/Static Cond. Fans			Two-Speed Cond. Fans		
Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans		Comp.	Condenser Fans	
RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)	RLA (5)	Qty.	FLA (EA)
						105	4	2.8						
179	4	9.3				133	4	3.5	133	4	9.3			
170	5	9.3	180	5	3.8	126	4	3.1	126	4	9.3	132	4	3.8
						137	5	2.8						
173	5	9.3				173	4	3.5	173	4	9.3			
164	5	9.3	173	5	3.8	164	5	3.1	164	5	9.3	173	5	3.8
						141	6	2.8						
193	5	9.3				178	6	3.5	178	6	9.3			
183	5	9.3	194	5	3.8	169	6	3.1	169	6	9.3	178	6	3.8
						139	6	2.8						
229	6	9.3				176	6	3.5	176	6	9.3			
218	6	9.3	229	6	3.8	167	6	3.1	167	6	9.3	175	6	3.8

Field Wiring & Protection						Field Wiring Lugs			
High Head/High Static Fans		Two-Speed Cond. Fans				STD Terminal Block		OPT Circuit Breaker	
Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)	Minimum Ckt. Ampacity (MCA) (3)	Recommended Fuse/Ckt. Breaker Rating (4)	Max. Inverse Time Ckt. Brkr. Rating (2)	Max Dual Element Fuse Size (2)	Lugs/ Phase (1)	Lug Wire Range	Lugs/ Phase (1)	Lug Wire Range
						4	#2 - 600 KCM	4	#4/0 - 500 KCM
800	800					4	#2 - 600 KCM	4	#2 - 600 KCM
800	800	590	700	700	700	4	#2 - 600 KCM	4	#2 - 600 KCM
						4	#2 - 600 KCM	4	#2 - 600 KCM
800	800					4	#2 - 600 KCM	4	#2 - 600 KCM
800	800	621	700	700	700	4	#2 - 600 KCM	4	#2 - 600 KCM
						4	#2 - 600 KCM	4	#2 - 600 KCM
800	800					4	#2 - 600 KCM	4	#2 - 600 KCM
800	800	676	800	800	800	4	#2 - 600 KCM	4	#2 - 600 KCM
						4	#2 - 600 KCM	4	#2 - 600 KCM
1000	1000					4	#2 - 600 KCM	4	#2 - 600 KCM
1000	1000	760	800	800	800	4	#2 - 600 KCM	4	#2 - 600 KCM

Electrical Notes

1. As standard, all units have single point power connection. Contact factory for information regarding dual point power units.
2. Maximum Inverse Time Circuit Breaker or Dual Element Fuse - 225% of the largest compressor RLA plus the sum of all other loads per NEC 440.22 (A).
3. MCA - Minimum Circuit Ampacity - 125% of the largest compressor RLA plus 100% of the remaining compressor RLA's plus the sum of all condenser fan FLA's per NEC 440.33
4. Recommended time delay or dual element fuse size - 150% of the largest compressor RLA plus 100% of the remaining compressor RLA's plus the sum of all condenser fan FLA's.
5. RLA - Rated Load Amps - rated in accordance with UL standard 1995.
6. Local codes may take precedence.
7. Control KVA includes operational controls and evaporator heaters.
8. System inrush current is less than RLA due to the use of York Variable Speed Drive technology. Typical Compressor Starting Current (first four seconds of startup):

<u>Rated Voltage</u>	<u>Typical Starting Current per Compressor</u>
380-400/50/3	28A
380/60/3	29A
460/60/3	23A

9. Voltage Utilization Range:

<u>Rated Voltage</u>	<u>Utilization Range</u>
380-415/50/3	360 - 440
380/60/3	342 - 402
460/60/3	414 - 508

LEGEND

C.B.	CIRCUIT BREAKER
D.E.	DUAL ELEMENT FUSE
DISC SW	DISCONNECT SWITCH
FACT CB	FACTORY-MOUNTED CIRCUIT BREAKER
FLA	FULL LOAD AMPS
HZ	HERTZ
MAX	MAXIMUM
MCA	MINIMUM CIRCUIT AMPACITY
MIN	MINIMUM
MIN NF	MINIMUM NON-FUSED
RLA	RATED LOAD AMPS
S.P. WIRE	SINGLE-POINT WIRING

NOTES:

1. U.L. Label is provided on 50 and 60 Hz units for these electrical wiring configurations.
2. — — — — — Dashed Line = Field Provided Wiring.
3. The above recommendations are based on the National Electric Code and using copper conductors only. Field wiring must also comply with local codes. Group Rated breaker must be HACR type for cUL machines.

2 COMPRESSOR POWER WIRING CONNECTIONS




FIG. 1 – TWO COMPRESSOR WIRING DIAGRAM WITH CIRCUIT BREAKER




FIG. 2 – TWO COMPRESSOR WIRING DIAGRAM WITH TERMINAL BLOCK

Power Wiring – continued

3 COMPRESSOR POWER WIRING CONNECTIONS




FIG. 3 – THREE COMPRESSOR WIRING DIAGRAM WITH CIRCUIT BREAKER – SINGLE POINT

3 COMPRESSOR POWER WIRING CONNECTIONS






FIG. 4 – THREE COMPRESSOR WIRING DIAGRAM WITH TERMINAL BLOCK – SINGLE POINT

INTENTIONALLY LEFT BLANK

Typical Control Wiring - Two Compressor




For informational purposes only. Do not attempt to tie into wiring without a proper wiring diagram.




CONTROL ELEMENTARY DIAGRAM
2 COMPRESSOR YCAV/YCIV CHILLER
035-19905-001 REV. H

Typical Control Wiring - Three Compressor



For informational purposes only. Do not attempt to tie into wiring without a proper wiring diagram.



CONTINUED TO
035-20326-002

Application Data

UNIT LOCATION

The YCIV chillers are designed for outdoor installation. When selecting a site for installation, be guided by the following requirements:

1. Installation sites may be either on a roof or on ground level. (See FOUNDATION)
2. Select a place having an adequate supply of fresh air for the condensers. Recommended clearances for all units are shown on the DIMENSIONS pages.
3. Avoid locations near windows or structures where normal operating sounds may be objectionable.
4. The standard condenser fans are propeller-type and are not recommended for use with ductwork, filters or other impediments to airflow in the condenser air stream.
5. When it is desirable to surround the unit(s), it is recommended that the screening be able to pass the required chiller CFM without exceeding 0.1" external static pressure.
6. Protection against corrosive environments is available by supplying the units with either copper fins, or cured epoxy-coating on the condenser coils. Epoxy-coated coils should be utilized with any units being installed at the seashore, or where salt spray may hit the units, or where acid rain is prevalent (copper condenser coils are not recommended where they may be exposed to acid rain).
7. On installations where winter operation is intended and snow accumulations are expected, additional elevation must be provided to insure normal condenser air flow.

FOUNDATION

The unit should be mounted on a flat and level foundation, ground or roof, capable of supporting the entire operating weight of the equipment. Please contact your nearest Johnson Controls Sales Office for shipping and operating weights.

Roof Locations – Adequate structural strength to safely support the entire weight of the unit and service personnel must be provided. Care must be taken not to damage the roof during installation. If the roof is "bonded", consult building contractor or architect for special installation requirements. Roof installations should incorporate the use

of spring-type isolators to minimize the transmission of vibration into building structure. Additional support should be provided to the roof at the spring-isolator locations.

Ground Locations – Units must be installed on a substantial base that will not settle and cause strain on the refrigerant lines, resulting in possible leaks. A one-piece concrete slab, with footers extending below the frost line, is recommended. The slab should not be tied to the main building foundation as noises will telegraph.

Mounting holes (5/8") are provided in the base rails for bolting the unit to its foundation. See DIMENSIONS for location of the mounting holes.

For ground installations, precautions should be taken to protect the unit from tampering by, or injury to, unauthorized persons. Fasteners on access panels will prevent casual tampering; however, further safety precautions, such as unit enclosure options, a fenced-in enclosure, or locking devices on the panels may be advisable. Check local authorities for safety regulations.

CHILLED LIQUID PIPING

The chilled liquid piping system should be laid out so that the circulating pump discharges into the cooler. The inlet and outlet cooler-liquid connections are given in DIMENSIONS. Hand stop valves are recommended for use in all lines to facilitate servicing. Drain connections should be provided at all low points to permit complete drainage of the cooler and system piping.

A strainer (40 mesh) is recommended for use on the INLET line to the cooler, and must be in place at initial operation of the water pumps.

Pressure-gauge connections are recommended for installation in the inlet and outlet water lines. Gauges are not provided with the unit and are to be furnished by others.

Chilled liquid lines exposed to the weather should be wrapped with a supplemental heater cable and insulated, or glycol should be added to the chilled liquid to protect against freezing if low-ambient periods are expected.

A flow switch is available as an accessory on all units. A flow switch must be installed in the leaving water piping of the cooler and must not be used to start and stop the unit.

Guide Specifications

PART 1 — GENERAL

1.01 SCOPE

- A. The requirements of the General Conditions, Supplementary Conditions, and Drawings apply to all work herein.
- B. Provide Microprocessor controlled, twin-screw compressor, air-cooled, liquid chillers of the scheduled capacities as shown and indicated on the Drawings, including but not limited to:
 1. Chiller package
 2. Charge of refrigerant and oil.
 3. Electrical power and control connections
 4. Chilled water connections
 5. Factory start-up

1.02 QUALITY ASSURANCE

- A. Products shall be Designed, Tested, Rated and Certified IAW, and installed in compliance with applicable sections of the following Standards and Codes:
 1. ARI 550/590 – Water Chilling Packages Using the Vapor Compression Cycle
 2. ARI 70 – Sound Rating of Large Outdoor Refrigerating and Air Conditioning Equipment
 3. ANSI/ASHRAE Standard 15 – Safety Code for Mechanical Refrigeration
 4. ASHRAE 34 – Number Designation and Safety Classification of Refrigerants
 5. ASHRAE 90.1 – Energy Standard for Buildings Except Low-Rise Residential Buildings
 6. ANSI/NFPA Standard 70 – National Electrical Code (N.E.C).
 7. ASME Boiler and Pressure Vessel Code, Section VIII, Division 1.
 8. ASTM A48 – Gray Iron Castings
 9. OSHA – Occupational Safety and Health Act
 10. Manufactured in facility registered to ISO 9001
 11. Conform to Underwriters Laboratories (U.L.) for construction of chillers and provide U.L./cU.L. listing label.
- B. Factory Test: Chiller shall be pressure-tested, evacuated and fully charged with refrigerant and oil, and shall be factory operational run tested with water flowing through the vessel.
- C. Chiller manufacturer shall have a factory trained and supported service organization.

- D. Warranty: Manufacturer shall Warrant all equipment and material of its manufacture against defects in workmanship and material for a period of eighteen (18) months from date of initial start-up or date of availability.

1.03 DELIVERY AND HANDLING

- A. Unit shall be delivered to job site fully assembled and charged with refrigerant and oil by the Manufacturer.
- B. During shipment, provide protective covering over vulnerable components. Fit nozzles and open ends with plastic enclosures.
- C. Unit shall be stored and handled per Manufacturer's instructions.

PART 2 — PRODUCTS

2.01 GENERAL

- A. Manufacturers: The design shown on the drawings is based on Johnson Controls. Alternate equipment will be acceptable if their equipment meets the scheduled performance and complies with these specifications. If equipment manufactured by a manufacturer other than that scheduled is utilized, then the Mechanical Contractor shall be responsible for coordinating with the General Contractor and all affected Subcontractors to insure proper provisions for installation of the furnished unit. This coordination shall include, but not be limited to, the following:
 1. Structural supports for units.
 2. Piping size and connection/header locations.
 3. Electrical power requirements and wire/conduit and overcurrent protection sizes.
 4. Chiller physical size on plant layout.
 5. Site noise considerations.

The Mechanical Contractor shall be responsible for all costs incurred by the General Contractor, Subcontractors, and Consultants to modify the building provisions to accept the furnished units.

- B. Description: Install and commission, as shown on the schedules and plans, factory assembled, charged, and operational tested air cooled screw compressor chiller(s) as specified herein. Chiller shall include, but is not limited to: a complete system with multiple independent refrigerant circuits, semihermetic twin screw compressors, shell and tube type evaporator, air-cooled condenser, R134a refrigerant, lubrication

Guide Specifications – continued

system, interconnecting wiring, safety and operating controls including capacity controller, control center, motor starting components, and special features as specified herein or required for safe, automatic operation.

C. Operating Characteristics:

1. Provide low ambient control and high ambient options as required to ensure unit is capable of operation from 0°F to 125°F (-18°C to 52°C) ambient.
2. Provide capacity control system capable of reducing unit capacity to (10% for 2 compressor units and 7.5% for 3 compressor units) of full load. Compressor shall start in unloaded condition. Application of factory installed hot gas bypass shall be acceptable as required to meet specified minimum load.

D. Cabinet: Unit panels, structural elements, control boxes and heavy gauge structural base shall be constructed of galvanized steel. Unit panels, control boxes and structural base are finished with a baked on powder paint. All painted surfaces shall be coated with baked on powder paint which, when subject to ASTM B117, 1,000 hour, 5% salt spray test, yields minimum ASTM 1654 rating of "6".

E. Unit shall ship in one piece and shall require installer to provide only a single evaporator inlet and outlet pipe connection. If providing chiller model that ships in multiple pieces, bid shall include all the material and field labor costs for factory authorized personnel to install a trim kit to connect the pieces as well as all interconnecting piping and wiring.

2.02 COMPRESSORS AND MOTORS

- A. Compressors: Shall be direct drive, semihermetic, rotary twin-screw type, including: muffler, temperature actuated 'off-cycle' heater, rain-tight terminal box, discharge shut-off service valve, and precision machined cast iron housing mounted on neoprene isolators. Design working pressure of entire compressor, suction to discharge, shall be 350 PSIG (24 bar) or higher. Compressor shall be U.L. Recognized.
- B. Motors: Refrigerant suction gas cooled accessible hermetic compressor motor, full suction gas flow through 0.006" maximum mesh screen, with inherent internal thermal overload protection and external current overload on all three phases.
- C. Lubrication: External oil separators with no moving parts, 450 PSIG design working pressure, and UL listing. Refrigerant system differential pressure shall

provide oil flow through service replaceable, 0.5 micron, full flow, cartridge type oil filter internal to compressor. Filter bypass, less restrictive media, or oil pump not acceptable.

D. Capacity Control: Compressors shall start at minimum load. Provide Microprocessor control to command compressor capacity to balance compressor capacity with cooling load. When required to meet minimum load, hot gas bypass shall be factory installed and integrated into standard control system.

2.03 REFRIGERANT CIRCUIT COMPONENTS

- A. Each independent refrigerant circuit shall include: liquid line shutoff valve with charging port, low side pressure relief device, removable core filter-drier, sight glass with moisture indicator, and electronic expansion valve.
- B. Chiller manufacturer shall provide independent circuit for each compressor to provide maximum redundancy. If equipment does not have independent circuits per compressor, manufacturer shall provide owner one spare compressor of each unique size.
- C. Discharge lines shall be provided with manual compressor shutoff service valves. Suction line shall be covered with closed cell foam insulation.

2.04 HEAT EXCHANGERS

- A. Evaporator:
1. Direct expansion type or flooded type shell and tube evaporator with high efficiency copper tubes. Independent refrigerant circuits shall be provided per compressor.
 2. Constructed, tested, and stamped IAW applicable sections of ASME pressure vessel code for minimum 235 PSIG (16 bar) refrigerant side design working pressure and 150 PSIG (10 bar) water side design working pressure.
 3. Shell covered with 3/4" (19mm), flexible, closed-cell insulation, thermal conductivity of 0.26k (BTU/HR-Ft²-°F/in.) maximum. Water nozzles with grooves for mechanical couplings, and insulated by Contractor after pipe installation.
 4. Provide vent and drain fittings, and thermostatically controlled heaters to protect to -20°F (-29°C) ambient in off-cycle.
- B. Air Cooled Condenser:
1. Coils: Internally enhanced, seamless copper tubes, mechanically expanded into aluminum alloy fins

with full height collars. Subcooling coil an integral part of condenser. Design working pressure shall be 450 PSIG (31 bar).

2. Low Sound Fans: Shall be dynamically and statically balanced, direct drive, corrosion resistant glass fiber reinforced composite blades molded into low noise, full airfoil cross section, providing vertical air discharge from extended orifices. Guards of heavy gauge, PVC (polyvinyl chloride) coated or galvanized steel.
3. Fan Motors: High efficiency, direct drive, 3-phase, insulation class "F", current protected, Totally Enclosed Air Over (TEAO), with double sealed, permanently lubricated ball bearings.

2.05 POWER AND ELECTRICAL REQUIREMENTS

A. Power/Control Panel:

1. NEMA 3R (IP55), powder painted steel cabinets with hinged, latched, and gasket sealed outer doors equipped with wind struts for safer servicing. Provide main power connection(s), compressor starters and fan motor contactors, current overloads, and factory wiring.
2. Panel shall include control display access door.

B. Single Point Power (As standard for 2 and 3 compressor chillers)

1. Provide single point power connection to chiller, shall be 3 phase of scheduled voltage.
2. Terminal Block connections shall be provided at the point of incoming single point connection.

C. Control Transformer: Power panel shall be supplied with a factory mounted and wired control transformer that will supply all unit control voltage from the main unit power supply. Transformer shall utilize scheduled line voltage on the primary side and provide 115V/1Ø on secondary.

D. Short Circuit Withstand Rating of the chiller electrical enclosure shall be (380, 400, & 460V: 65,000 Amps). Rating shall be IAW UL508.

E. Motor Starters: Motors starters shall be reduced inrush type (Wye-Delta or Solid State) for minimum electrical inrush. Across the line type starters will not be acceptable.

F. Power Factor:

1. Provide equipment with power factor correc-

tion capacitors as required to maintain a power factor of 95% at all load conditions.

2. The installing contractor is responsible for additional cost to furnish and install power factor correction capacitors if they are not factory mounted and wired.

G. Exposed compressor and fan motor power wiring shall be routed through liquid tight conduit.

2.06 CONTROLS

A. General:

1. Provide automatic control of chiller operation including compressor start/stop and load/unload, anti-recycle timers, condenser fans, evaporator pump, evaporator heater, unit alarm contacts and run signal contacts.
2. Chiller shall automatically reset to normal chiller operation after power failure.
3. Unit operating software shall be stored in non-volatile memory. Field programmed set points shall be retained in lithium battery backed regulated time clock (RTC) memory for minimum 5 years.
4. Alarm contacts shall be provided to remote alert for any unit or system safety fault.

B. Display and Keypad:

1. Provide minimum 80 character liquid crystal display that is both viewable in direct sunlight and has LED backlighting for nighttime viewing. Provide one keypad and display panel per chiller.
2. Display and keypad shall be accessible through display access door without opening main control/electrical cabinet doors.
3. Display shall provide a minimum of unit setpoints, status, electrical data, temperature data, pressures, safety lockouts and diagnostics without the use of a coded display.
4. Descriptions in English (or available language options), numeric data in English (or Metric) units.
5. Sealed keypad shall include unit On/Off switch.

C. Programmable Setpoints (within Manufacturer limits): display language; leaving chilled liquid temperature: setpoint, control range; local or remote control; units of measure; compressor lead/lag; and maximum chilled water setpoint reset temperature range.

D. Display Data: Chiller liquid return and leaving temper-

Guide Specifications – continued

atures, ambient, lead compressor identification, clock and schedule, (variable) out of range, remote input indication, chilled liquid reset setpoint, and history data for last ten shutdown faults. Compressor suction, discharge, and oil pressures and temperatures, suction and discharge superheats, percent of full-load, operating hours, starts, and anti-recycle timer status. Status Messages for manual override, unit switch off, compressor run, run permissive, remote controlled shut down, no cooling load, daily/holiday shut down, anti-recycle timer.

- E. Predictive Control Points: Unit controls shall avoid safety shutdown when operating outside design conditions by optimizing the chiller controls and cooling load output to stay online and avoid safety limits being reached. The system shall monitor the following parameters and maintain the maximum cooling output possible without shutdown of the equipment: motor current, suction pressure and discharge pressure.
- F. System Safeties: Shall cause individual compressor systems to perform auto-reset shut down; manual reset required after the third trip in 90 minutes. Includes: high discharge pressure or temperature, low suction pressure, high / low motor current, high motor temperature, high pressure switch, high / low differential oil pressure, high oil temperature, low suction superheat, critical sensor malfunction, low or high current, phase loss/single phase power, overload of motor windings, and low voltage.
- G. Unit Safeties: Shall be automatic reset and cause compressors to shut down if: high or low ambient, low leaving chilled liquid temperature, under voltage, and flow switch operation. Contractor shall provide flow switch and wiring per chiller manufacturer requirements.
- H. Manufacturer shall provide any controls not listed above, necessary for automatic chiller operation. Mechanical Contractor shall provide field control wiring necessary to interface sensors to the chiller control system.

2.07 ACCESSORIES AND OPTIONS

Some accessories and options supersede standard product features. Your Johnson Controls representative will be pleased to provide assistance.

A. Sound Reduction

1. Provide the following options as required to

meet scheduled sound performance data at all load points.

- a. Normal speed fans and unlined compressor enclosure. **(Factory Mounted)**
- b. Two-speed fans and acoustically lined enclosure. **(Factory Mounted)**
- c. Sound power octave band data, dB per ARI standard 70 and IAW ISO3744 at 35°C ambient and 7°C leaving chilled water.

2. Provide optional control input to limit sound output of the chiller based on time of day. Shall be programmable at the chiller panel or controlled remotely via signal (4-20mA or 0-10 VDC) from BAS system. Chillers without this feature shall be provided with the necessary sound attenuation to meet the scheduled sound performance data at all load points.

B. Power Supply/Connections:

1. Circuit breaker is optional at point of incoming single point connection to provide disconnecting means AND be sized to provide the motor branch circuit protection, short circuit protection and ground fault protection for the motor branch-circuit conductors, the motor control apparatus and the motors. Circuit breaker shall be equipped with lockable operating handle that shall extend through power panel door so that power may be disconnected without opening any panel doors.

C. Condenser Coil Environmental Protection:

1. **PRE-COATED FIN CONDENSER COILS –**
The air-cooled condenser coils are constructed of epoxy-coated aluminum fins.
2. **COPPER FIN –** Provide condenser coils with copper fins in lieu of aluminum fins.
3. **POST-COATED EPOXY DIPPED CONDENSER COILS –** The unit is built with dipped-cured condenser coils.

D. Protective Chiller Panels **(Factory Mounted)**:

1. Louvered Panels (condenser coils only): Painted steel to match unit panels, over external condenser coil faces.
2. Wire Panels (full unit): Heavy gauge, welded wire mesh, coated to resist corrosion, to protect condenser coils from incidental damage and restrict unauthorized access to internal components.
3. Louvered Panels (full unit): Painted steel to match unit panels, to protect condenser coils from incidental damage, visually screen internal components, and prevent unauthorized access to internal

components.

4. Louvered/Wire Panels: Louvered steel panels on external condenser coil faces, painted to match unit panels. Heavy gauge, welded wire-mesh, coated to resist corrosion, around base of machine to restrict unauthorized access.

E. Evaporator options:

1. Provide 1-1/2" (38mm) cooler insulation in lieu of standard 3/4" (19mm).
2. Provide Raised Face Flanges for cooler nozzles:
 - a. 150 PSIG (10.3 bar), welded flanges (field kit, matching pipe flange by contractor).
 - b. 150 PSIG (10.3 bar) companion flanges. (not available with 460V units)
 - c. 150 PSIG (10.3 bar), ANSI/AWWA C-606 couplings (field kit, matching pipe flange by contractor).

- F. Flow Switch (**Field Mounted**): Vapor proof SPDT, NEMA 3R switch [____ 150 PSIG (10.3 bar) or ____ 300 PSIG (20.7 bar)], -20°F to 250°F (-28.9°C to 121.1°C).

G. Building Automation System Interface:

1. Chiller to accept 4 to 20mA or 0 to 10 VDC input to reset the leaving chilled liquid temperature. (**Factory Mounted**)

- H. Multi-Unit Sequence Control (**Field Mounted**): Separate Sequencing control center provided to permit control of up to eight chillers in parallel based on mixed liquid temperature.

I. Vibration Isolation (**Field Mounted**):

1. Neoprene Isolators.
2. 1 Inch Deflection Spring Isolators: Level adjustable, spring and cage type isolators for mounting under the unit base rails.
3. 2 Inch Deflection Seismic Isolators: Level

adjustable, restrained mounts in rugged welded steel housing with vertical and horizontal limit stops. Housings shall be designed to withstand a minimum 1.0g accelerated force in all directions to 2" (50.8 mm).

- J. Service Shut-Off Valve: Provide suction service shut-off valve for each compressor. (**Factory Mounted**)

PART 3 — EXECUTION

3.01 INSTALLATION

- A. General: Rig and Install in full accordance with Manufacturer's requirements, Project drawings, and Contract documents.
- B. Location: Locate chiller as indicated on drawings, including cleaning and service maintenance clearance per Manufacturer instructions. Adjust and level chiller on support structure.
- C. Components: Installing Contractor shall provide and install all auxiliary devices and accessories for fully operational chiller.
- D. Electrical: Coordinate electrical requirements and connections for all power feeds with Electrical Contractor (Division 16).
- E. Controls: Coordinate all control requirements and connections with Controls Contractor.
- F. Finish: Installing Contractor shall paint damaged and abraded factory finish with touch-up paint matching factory finish.







P. O. Box 1592, York, Pennsylvania USA 17504-1592
© by Johnson Controls 2006

Tele. 800-861-1001
www.york.com

Subject to change without notice. Printed in USA
ALL RIGHTS RESERVED

Form 201.23-EG1 (1007)
Supersedes: 201.23-EG1 (607)
File in ET2