RANGE COMPOSITION

Zanussi Professional have designed and produced a complete range of refrigerated tables, that combines the dual function of worktop and refrigerated table. This versatility allows notable savings in space whilst offering functional and modular solutions to kitchen requirements. The main benefit of this innovative new range is total flexibility: you have the possibility to compose your table to your exact personal requirements. You can order each individual unit and combine them together: structure, top, door, drawer and refrigeration unit. We offer a basic range of 38 models but the choice is infinite.

The range presented here consists of 3 models with rear upstand with a temperature from -2° to $+10^{\circ}$ C. Models are available with 4 doors; 3 doors and $2x\frac{1}{2}$ drawers.



PT 3 SERIES

113174

REFRIGERATED TABLES & UPSTAND 2200 ZANUSS

TECHNICAL CHARACTERISTICS

◆ Constructed entirely in AISI 304 stainless steel with satin finish and polished interior guaranteeing maximum reliability. 2" height-adjustable AISI 304 stainless steel feet (-15 to +80 mm). Completely removable grid support structure in AISI 304 stainless steel.

 The worktop has a height of 50 mm and is slotted into place for easy removal.

 High-density expanded polyurethane foam, 60 mm in thickness, with cyclopenthane injection, guarantees exceptional, long-term insulation and notable energy savings.

◆ The design of the refrigeration unit allows maximum usage of the available space in the compartment. It is also mounted on a pull-out system to facilitate maintenance and cleaning.

 The new central position of the refrigeration unit allows perfect air circulation in the different compartments and temperature uniformity.

◆ These appliances are suitable for use in tropical climates (+43°C) ensuring high performance even in extreme ambient conditions.

 The base, with water drain, is pressed and features rounded internal corners to guarantee perfect cleaning. Completely automatic defrosting and automatic evaporation of defrost water obtained by hot gas.

◆ The refrigerated tables feature: reversible, self-closing doors; recessed ergonomical handles.

◆ The drawers feature: fully removable, telescopic runners in AISI 304 stainless steel;

perforations for improved ventilation.

- Doors and drawers are interchangeable on site.
- CFC and HCFC free.

♦ All models comply with the standards required by the main international approval bodies and are H marked.

CHARACTERISTICS	MODELS	
	TRNA224A 113173	TRNA224B 113174
Operating temperature - min/max °C	-2/10	-2/10
Operating mode	Ventilated	Ventilated
Gross capacity (D.I.N. 8952) - I.	590	590
External dimensions - mm		
width	2244	2244
depth/with open doors	700, 1110	700, 1110
height	950	950
Internal dimensions - mm		
depth	580	580
height	530	530
Min/Max internal humidity - %	80/95	80/95
N° of drawers		2
N° and type of door	4	3
Door hinges	2 Left+2 Right	2 Left+1 Right
N° and type of grids (included)	4, GN 1/1	3, GN 1/1
Compressor power - HP	1/4	1/4
N° defrost in 24 hrs.	3/15'	3/15'
Refrigerant type	R134a	R134a
Refrigerant quantity - g.	290	290
Refrigeration power - W	378	378
Power - kW		
installed-electric	0.38	0.38
Noise level - dBA	56	
Net weight - kg.	187	195
Power supply - V, phases, Hz	230 V, 1N, 50	230 V, 1N, 50
INCLUDED ACCESSORIES		
1/1 GN GREY "RILSAN" GRID	4	3



	TRNA224A 113173	TRNA224B 113174
D - Water drain	16mm	16mm
EI - Electrical connection	230 V, 1N, 50	230 V, 1N, 50

TRNA224A 113173

881435

880539

881505

881506

880119

880132

880133

922166 881499

811451

881040

881038

881457

MODELS

TRNA224B 113174

881435

880539

881505

881506

880119 88<u>0132</u>

880133 922166 881499

811451

881040 881038

881457





www.zanussiprofessional.com

DBAB7

ACCESSORIES

1/1 GN GREY "RILSAN" GRID 2 WHEELS FOR REFRIGERATORS/REFRIG.TABLES CHEST OF 2 DRAWERS FOR REFRIGER.COUNTER

CHEST OF 3 DRAWERS FOR REFRIGER.COUNTER HACCP ADV.CONN.10 UNITS-DIG.REF.(ID9XX) HACCP ADV.CONN.80 UNITS-DIG.REF.(ID9XX)

HACCP ADV.CONN.PER UNIT-DIG.REF.(ID9XX)

PRINTER FOR HACCP BASIC VERSION REFRIG.

2009-07-02

KIT HACCP EKIS LOCK FOR REFRIGERATED COUNTERS

PLASTIC CONTAINER GN 1/1 H=100 MM

PLASTIC CONTAINER GN 1/1 H=150 MM PLASTIC CONTAINER GN 1/1 H=65 MM