

**RIGGMASTER COIL TETHER - FIBRE CORE**

Order no.: 1108(with swivel) and Order no.: 1105(no swivel)



The following guidelines are to be read through carefully, and strictly observed. This product has been manufactured especially for tool safety and for drop prevention. This product does not discharge users from their personal responsibility.

**Observe:** Any user of RIGGMASTER equipment of any kind is personally responsible for learning its correct application and the technique of use. The manufacturer and the retailers deny any liability in the event of misuse and improper use and/or handling of this product. The presented guidelines are made as a helpful aid on the correct use of this product. However, as it is impossible to list all instances of incorrect application and error possibilities, the guideline can never replace the user's own knowledge, training, experience and personal responsibility.

**Purpose of use:** The RIGGMASTER Coil Tether is made to safely attach tools or other objects in order to prevent drops from high places. Maximum load is 1 kilogram.

**Technical information:**

- The product is made from plastic and synthetic fibre.
- Karabiner hook and swivel are made from stainless steel
- Total length fully stretch out is 210 cm
- Weight: 130 grams

**Storage and transport:** Optimum storage condition is in a dry, dark and cool place. Protect the product from direct exposure of sunlight, chemicals, heat and mechanical stress.

**Cleaning:** Clean contaminated products in lukewarm water using a neutral soap or a mild washing agent.

**Exposure to chemicals:** As a general rule, exposure to chemicals should be avoided. This is counting particularly for acids, which can damage parts of the product, without leaving any visible traces. If the product has been exposed to acid or other aggressive chemicals it must be replaced immediately.

**Heat:** The Coil Tether must not be exposed to temperatures exciding 75°C.

**Accessories:** Only use accessories approved as tool safety equipment. Observe the corresponding guidelines for the product.

**Service life:** The service life of a product cannot be calculated precisely in advance, as it depends on many factors such as frequency of use, way of use, working environment, climate influence and solar exposure.

In principle the product is to be replaced immediately:

- After a drop, or when exposed to extreme mechanical load
- When there are visible wear, cracks or deformations.
- When malfunction occur.
- If the product is heavily and irreversibly contaminated. (e.g. with grease, crude oil, paint etc.)
- If the product have been exposed to high thermal stress.
- After contact with aggressive chemicals.

Even under optimum storage conditions with little or no use the product should be replaced after maximum 5 years.

**Manufacturer and product information** is engraved to the badge, attached to the Coil Tether.



**Warning!** Never make knots or other deformations on the line. This will significantly reduce the lines strength properties, this might still be the case after a knot is opened again.

This product must not be modified.

**BEFORE USE:** This product must be controlled for wear and damage before every use. Pay attention to the condition of the swivel, hook, ferrules and line, in particular where line is connected to the karabiner hooks. Control that the Ferrules are tightly pressed to the line.

**WHEN IN USE:** lock the screw nut in lock position in order to maintain full mechanical strength of the karabiner hook.

**Do not expose the line to open flame or heat. It may cause the plastic to deform or and be significantly weaker.**

**YOU ARE WELCOME TO VISIT OUR WEB PAGE WHERE YOU WILL FIND MORE PRODUCTS IMPROVING LIFE AT HEIGHT.**