

# 10.4" Waterproof Outdoor LCD Monitor


**Model: NGLT104WP**

**Bathroom, On the Boat, Outdoor Plant, Steam Room, SPA, Rainproof Application**  
**Inputs: PC (VGA), Composite Video Input and S-VHS**



**Waterproof LCD Monitor**  
**IP67 Underwater Test Picture**


[www.nanovdisplay.com](http://www.nanovdisplay.com)




The world's *First Underwater IP67 Water Proof Digital LCD Monitor* for the Marine, Bathroom and SPA Industry


### Features

1. **IP Grade: IP67 (Tested to work 3 ft underwater for 30 minutes)**
2. **Brightness: 250 cd/m<sup>2</sup>**
3. **12VDC with 12VAC Adapter**
4. **Tested and works inside a Steam Room**
5. **Back Cover: Aluminum to transfer heat and protect humidity**
6. **Specially treated waterproof glass to protect against scratches**
7. **Front Touch Buttons**
8. **Floating *water resistant* IT Remote Control**



## Front Cover - Waterproof & High Brightness Panel






## Features (NGLT104WP)

### Waterproof LCD for Ship and SPA builders


S.No.	Feature	Final Product
1	Panel & Brightness	10.4" LCD Panel, 250 cd/m <sup>2</sup>
2	IP Grade	IP67, Protection against dust and water (Immersion)
3	Front Glass	Re-enforced glass with touch screen function
4	Audio Out	1W x 1W Audio Out
5	Button Switch	Touch Screen
6	PC Board & Connector	PC Board : Non-Conformal Coating , Connectors : Heavy Duty, O-Ring Waterproof connectors Two Meter Connectors Included *** All connectors should be tightened for waterproof.
7	In/Out Jacks	Extension Wire type.
8	Cabinet & Vent	Front : Specially treated glass Back : Aluminum - to transfer heat from the inside and protect against salt corrosion.
9	TV Tuner, Picture Ratio	Optional ATSC or DVB-T Digital TV-Tuner, 4:3
10	Remote Control	IR LED Module, Water Floating Design, Universal remote control can be programmed
11	Picture Color	Natural Color Advanced Technology Adapted + 3D Comb Filter
12	Language	English, Spanish, French
13	Unit Weight/Dimension	6.6lbs, 10.6" x 9.5" x 2"
<p>* Disclaimer: Our device is intended for use in the moist, humid and wet environmental condition. It is recommended to put the unit in an area which has shade to protect from direct sunlight. Do not use or place the unit under extensive or direct sunlight as it would cause the liquid in the panel to overheat.</p>		



## Waterproof IP Grade in accordance with IEC 529


1 <sup>st</sup> Identity Number	Production Category (Contact & Foreign Object Production)	2 <sup>nd</sup> Identity Number	Protection Category (Water Protection)
0	No special protection	0	No special protection
1	Protection against the entry of solid foreign object, having a diameter larger than 50 mm.	1	Protection against vertically falling drip water. No harmful effects are allowed. (drip water).
2	Protection against the entry of solid foreign object, having a diameter larger than 12 mm. Protection for fingers and similar objects.	2	Protection against vertically falling drip water. When the enclosure is tipped up to an angle of 15 degree from its normal position.
3	Protection against the entry of solid foreign object, having a diameter larger than 2.5 mm. Protection for tools, wires, or similar objects which are thicker than 2.5 mm.	3	Protection against drip water that falls at an angle of up to 60 degree vertically.
4	Protection against the entry of solid foreign object, having a diameter larger than 1.0 mm. Protection for tools, wires, or similar objects which are thicker than 1.0 mm.	4	Protection against water which sprays against the equipment from all directions. No harmful effects are allowed (spray water).
5	Protection against harmful dust deposits. Complete contact protection.	5	Protection against water from a hose which is directed on the enclosure from all directions. No harmful effects are allowed (hose directed w.).
6	Protection against the entry of dust (dust proof). Complete contact protection.	6	Protection against strong seas or strong water jets.
		7	Protection against water. <b>(Immersion)</b>
		8	Protection against water. <b>(Submersion)</b>






## Specifications

	Contents		Specifications
<b>Panel</b>	Panel		10.4"
	Resolution		800 x 600
	Display Color		16,777,216 color combinations
	Pixel Pitch		0.297(H)mm x 0.297(V)mm
	Operating Temperature		-5° ~ 50° Centigrade
	Contrast Ratio		300 : 1
	Brightness		<b>250 cd/m2</b>
	Response Time	Rise Time	5 ms
		Decay Time	11 ms
	Viewing Angle		100° Horizontal / 70° Vertical
	Physical Rotation		+ 20 degree, - 5 degree up/down
	Panel Interface		LVDS
<b>Feature</b>	Dimming (Back light control by Remote control)		Yes (Mode1. Mode2.....)
	On/Off Timer		Yes
	No Signal Mute / Auto Power off		Yes
	On Screen Display		Yes
	Multi-language OSD		English, Spanish, French
	Auto Search Memory		Yes
	Selectable Picture / Sound		Yes




## Specifications (continued)

System	Contents		Specifications
	Video Input	Composite	Yes, RCA
		S-Video(Y/C)	Yes
		PC Analog	Yes
	Caption And V-Chip		Yes
	Sound System	MTS	Yes
		Standard Model	Standard, Music, Movie, Speech, User
	Audio Output		1W x 1W
Jacks	Composite Input	Video Input	Yes (RCA jack)
		S-Video Input	Yes (Din Jack)
		Audio Input	Yes (RCA Jack)
	Audio Line Out		450mV + / - 50mV
Others	Power Supply		DC 12V, 3A
	Power Consumption (Watts)		Stand-by : 1.8W / Power On : 45W
	Audio Power		1W x 1W
	Coating Level		IP – 67
	Accessories	User's Manual, Adapter, Power Cable, Remote Control, Warranty Card	
	Regulation	Safety	NRTL, TUV, CE
		EMI	FCC
	Dimensions	Unit without stand	10.6" x 9.5" x 2"
	Weight	Net	6.6 lbs



## Waterproof Connectors (Reference)




**NGLT104WP Watertight Back Connectors.**




# *MECHANICAL DRAWING*

## *(NGLT104WP)*




Width (inside)	Height (Inside)	Depth (inside)	Width (Inputs)
272.8mm	246.3mm	50.2mm	70mm



## Yacht & SPA Video Application with Waterproof Speakers, Amplifier and DVD Player






## YSPA Video Application



**IP67 Slave monitor installation**



**IP67 Waterproof Test**



**1982 NW 82<sup>nd</sup> Ave  
Miami, FL 33126**

**Phone:(305)395-6069  
Fax:(866)431-7242  
E-mail: [miajin@nanovdisplay.com](mailto:miajin@nanovdisplay.com)**

**[www.nanovdisplay.com](http://www.nanovdisplay.com)**