



1. DISPLAY CHARACTERISTICS

DIAGONAL	19"; 48cm
PANEL	TN
DISPLAY AREA H X W	256.5 x 410.4 mm; " x "
RESPONSE TIME	5 ms
CONTRAST	1000 : 1 typical
BRIGHTNESS	400 cd/m ² typical
VIEWING ZONE	horizontal/vertical: 170° / 160°; right/left: 85° / 85°; up/down: 80° / 80°
DISPLAY COLOUR	16.7 million
PIXEL PITCH H X V	0.285 x 0.285 mm
NATIVE RESOLUTION	1440 x 900 (1.3 megapixel)
HORIZONTAL SYNC	30 - 80 KHz
VERTICAL SYNC	50 - 75 Hz
BANDWIDTH	137 MHz
SYNCHRONIZATION	Separate Sync
ASPECT RATIO	16 : 10
CHANNELS PROGRAMMING TV	99
PICTURE FORMATS	Full, Normal, Panorama, Zoom1, Zoom2, WSS

2. INTERFACES & CONNECTORS

ANALOG INPUT CONNECTOR	D-Sub
DIGITAL INPUT CONNECTOR	HDMI
HDCP	yes
INPUTS	antenna, composite RCA, SCART, YPbPr component, HDMI, audio

3. SPECIAL FEATURES

APPLE - MAC	All iiyama monitors are compatible with Apple-Macintosh computers.
PLUG & PLAY	VESA DDC2B™
CONTROLS	On-Screen-Display in 8 languages (D, GB, F, I, Esp, P, NL, SE) and 7 Front controls (Volume Down (Adjust Decreasing), Volume Up (Adjust Increasing), OSD Menu Key (Back to Previous Menu), Scroll Down (Channel Down), Scroll Up (Channel Up), Input Select (Enter), Power)
USER CONTROLS	Brightness, contrast, colour temperature, colour control, tint, sharpness, aspect ratio, sound menu (bass, treble, balance, AVC), sleep, TXT language, OSD language, OSD H. position, OSD V. position, OSD time out, Canal +, auto scan, manual store, auto adjust, horizontal & vertical position, clock, phase, reset*Some user controls are dependant on which input signal is in use.
SPEAKERS	2 x 2.5 W (Stereo)
ANTI-THEFT-DEVICE	Kensington-lock™ prepared
SAFETY	CB, CE, TÜV-GS
TILT ANGLE	20° up; -° down

VESA MOUNTING	100 mm
COLOUR	Black
EXTERNAL CONTROLS	IR remote control, OSD (On Screen Display)
ORIENTATION	Simple-Text, TOP-Text Fast-Text
TV EQUIPMENT	automatic station programming, Sleep Timer
TV TUNER	Yes

4. ACCESSORIES

DRIVER	Windows 95/98/2000/ME/XP
INCLUDED ACCESSORIES	IR remote control (+ batteries), analog VGA signal cable, audio cable (PC), user manual, Power Cord, RCA A/V Cable, HDMI Cable

5. POWER MANAGEMENT

POWER SUPPLY	AC 100 - 240 V, 50 / 60 Hz
POWER SUPPLY UNIT	internal
POWER USAGE	max. 50 W in normal use; max. 2 W in Power management mode

6. DIMENSIONS & WEIGHT

DIMENSIONS W X H X D	443 x 379.7 x 210 mm
WEIGHT	4.95 kg

7. PRICE

PRICE	£ 159 SRP ex VAT
-------	------------------

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION (). ALL RIGHTS RESERVED.