



# 4432N Mega Top

Front-Breathing Self-Contained Compact Mega Top Refrigerators

Project \_\_\_\_\_  
 Item \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 CSI Section 11400  
 Approved \_\_\_\_\_  
 Date \_\_\_\_\_

4432N Mega Top

Front-Breathing Self-Contained Compact Mega Top Refrigerators

## Models

- 4432N-12M Single section with doors twelve pan capacity
- D4432N-12M Single section with drawers twelve pan capacity



4432N-12M

## Standard Features

- Patented air screen ensures product stays cold without drying it out
- 100% front breathing, which allows the unit to be pushed against a wall or built into a cabinet or an existing line up
- Durable, rugged stainless steel sides, top and front
- Features Delfield's exclusive ABS interior (on sides). ABS is extremely durable - it won't dent, chip or corrode and is backed by a limited lifetime warranty
- Delfield supplies 1/6 size pans and adapter bars for top opening
- Mega top refrigerators are standard with 8" wide, dishwasher safe polyethylene cutting board treated with antimicrobial agent
- "D" prefix models feature Delfield's new drawer system. Drawers are backed by a 10-year warranty on the track assembly
- Environmentally friendly R404A refrigerant
- High density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane keeps energy costs low
- Black recessed quick grip handle
- Standard on 2" casters for easy cleaning and installation
- 7' cord and plug supplied
- Cord spring relief - prevents cord rollover
- One epoxy coated wire shelf standard, installed per door section
- ACT solid state electronic control
- One year parts and 90 day labor standard warranty.

## Options & Accessories

- Flat lift off cover
  - 18" wide single tier overshef
  - Stainless steel finish on back
  - Plastic laminate on front
  - Additional wire shelves
  - Door lock
  - Exterior thermometer
  - Glass door(s)
  - \*220V/50 Hertz electrical system
- \*Inclusion of this option will alter electrical specifications of the unit.

## Specifications

**Exterior top** is one-piece, 22-gauge stainless steel with integral 2.12" (5.1cm) square nosing on the front. Top has two openings to accept twelve 1/6-size 4" (10.1cm) or 6" (15.2cm) deep pans or two 12" x 20" (30.5cm x 50.8cm) full size pans, 4" (10.1cm) or 6" (15.2cm) deep. Adapter bars and 1/6 size pans are supplied by Delfield. Telescoping cover is constructed of 20-gauge stainless steel. Temperature in top opening to maintain 33°F (1°C) to 41°F (5°C), with pans recessed 2.5" (6.4cm) at 86°F ambient room temperature, meeting NSF 7 requirements. One 32" x 8" x .5" (81.3cm x 20.3cm x 1.3cm) polyethylene cutting board treated with antimicrobial agent is mounted on the top at the front edge.

**Exterior back and bottom** are two-piece 24-gauge galvanized steel. Exterior ends are stainless steel.

**Interior sides** are thermoformed ABS plastic with pilaster shelf supports and clips. Base is fully insulated with high-density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane.

**Refrigeration** system uses HFC-404A refrigerant. Compressor is 1/5 H.P., with condenser coil and hot gas condensate evaporator mounted on rear of the cabinet. Evaporator coils are located on the interior rear wall of the cabinet. Refrigerant

flow is controlled by a capillary tube. Cabinet maintains an interior cabinet temperature of 36°F to 40°F (2°C to 4°C).

**ACT control.** ACT electronic, solid state control, mounted on the exterior rear of the cabinet, allows unit to maintain precise temperatures in heavy duty conditions.

**Electrical** connection is 115 volt, 60 Hertz, single phase. Unit has a 7' (2.1m) long electrical cord and NEMA 5-15P plug.

**Casters:** Equipment is mounted on 2" (5.08cm) diameter plate casters with front two locking. Equipment clearance above the floor is 2.5" (6.35cm).

**Doors** have a 24-gauge stainless steel exterior, with thermoformed ABS plastic interior liner. Cabinet has one adjustable epoxy-coated wire shelf.

**Drawers** have 24-gauge stainless steel exterior with thermoformed ABS plastic interior liner. Drawer frames are 12-gauge stainless steel. Drawer slides are 11-gauge stainless steel with Delrin bearings. Top drawer will hold two 12" x 20" (30.5cm x 50.8cm) pans 4"- 6" (10.1cm - 15.2cm) deep. Bottom drawer holds two 12" x 20" (30.5cm x 50.8cm) pans 4" (10.1cm) deep. Pans are supplied by others.





# 4432N Mega Top

Front-Breathing Self-Contained Compact Mega Top Refrigerators

**4432N-12M Elevation View**  
 1.15 (2.93) 32.13 (81.61) 1.15 (2.93) 8.54 (21.69) 36.00 (91.40) 33.59 (85.31)

**4432N-12M Right Side View**  
 31.50 (80.01) 3.88 (9.87) 23.79 (60.43) 12.98 (33.00) 7.53 (19.10) 6.11 (15.52) 17.35 (44.08) 26.86 (68.22) 21.94 (55.73) 20.75 (52.70) 2.50 (6.30)

**4432N-12M ISO View**  
 30.67 (77.98) NOSE OF UNIT TO EDGE OF DOOR 28.75 (73.03) INTERIOR DIMENSION

**D4432N-12M ISO View**  
 19.67 (49.77) NOSE OF UNIT TO EDGE OF DRAWER

**D4432N-12M Elevation View**  
 1.15 (2.93) 32.13 (81.61) 1.15 (2.93) 8.54 (21.69) 36.00 (91.40) 33.59 (85.31)

**D4432N-12M Right Side View**  
 31.50 (80.01) 3.88 (9.87) 4.00" OR 6.00" DEEP PANS ON TOP 4.00" DEEP PANS ONLY ON BOTTOM 2.50 (6.30)

**Pan Cutout Configuration**  
 32.13 1.75 13.63 1.39 21.63 4.96

**INSTALLATION NOTE:**  
 Refrigeration system is designed so that air will flow under the unit, through the compressor area and out the front of the unit. Any restriction to this air flow path will void the warranties.

**PLEASE NOTE:**  
 Air flow through the louver on the back of the unit is not necessary for operation, however, any air which passes through the louver is beneficial.

**Specifications**

Model	1/6 Size Pan Capacity	Number of Shelves	Shelf Area	Storage Capacity	H.P.	V/Hz/Ph	Amps	NEMA Plug	Ship Weight
4432N-12M	12	1	3.97ft <sup>2</sup>	6.9ft <sup>3</sup>	1/5	115/60/1	7.20	5-15P	315lbs/143kg
D4432N-12M	12	NA	NA	2.7ft <sup>3</sup>	1/5	115/60/1	7.20	5-15P	350lbs/158kg

Delfield reserves the right to make changes to the design or specifications without prior notice.

980 S. Isabella Rd.  
Mt. Pleasant, Michigan 48858

Phone: 800-733-8948 or 989-773-7981  
 Fax: 800-669-0619  
 www.delfield.com

Printed in the U.S.A.  
 DS4432N-M  
 03/08

Enodis®