

## Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	
Internet site *	www.lexmark.se / www.lexmark.com	·
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	Single Function Color Laser Printer					
Commercial name *	exmark CS410dn, Lexmark CS410dtn, Lexmark CS410n					
Model number *	S410dn, CS410dtn, CS410n					
Issue date *	Rev. June 24, 2015					
Intended market *	Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requireme	nt met	
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\boxtimes$	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model n		CS410dtn, CS410n		_			
Issue da	e * Rev. June	24, 2015	Logo	LEXM	<b>ARI</b>	K	
_							
	environmental attr	ributes - Legal requirements		Require			
Item P1	Hererdeus substan	ees and proportions		Yes	No	n.a.	
P1.1*		ces and preparations ain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% h	exavalent				
1 1.1		/brominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethe					
P1.2*	Products do not cont	ain Asbestos (see legal reference). erence has no maximum concentration value.		$\square$			
P1.3*	P1.3* Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-						
	concentration values						
P1.4*	terphenyl (PCT) in pr	ain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% po reparations (see legal reference).	-				
P1.5*		ain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 at least 48% per mass of chlorine in the SCCP (see legal reference		$\boxtimes$			
P1.6*	Tris-(aziridinyl)-phos	arts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)- phineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference has no maximum concentration values.		),			
P1.7*		arts with direct skin contact do not contain more than 0.003% Azo ee legal reference and Note B1)	colorants that split			$\boxtimes$	
P1.8*	Wooden parts do not pentachlorophenol a	t contain arsenic and chromium as a wood preservation treatment and derivatives (see legal reference). And derivatives (see legal reference). Arence has no maximum concentration values.	as well as				
P1.9*	Parts with direct and microgram/cm <sup>2</sup> /week	prolonged skin contact do not release nickel in concentrations abo ( (see legal reference). in legal reference when tested according to EN1811:1998.	ve 0.5				
P1.10*	REACH Article 33 inf	formation about substances in articles is available at (add URL or r nager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550	nail contact):				
P2	Batteries						
P2.1*	more than 0.0005% of marked with the cher	is a battery or an accumulator, it is labeled with the disposal symbol of mercury (for button cells only) by weight, or more than 0.004% of mical symbol for the metal concerned, Hg or Pb. Information on pro- nual. (See legal reference)	f lead, it shall be	5			
P2.2*	Button cells used in t	the product do not contain more than 2% by weight of mercury. Oth contain more than 0.0005% of mercury or 0.002% of cadmium. (S					
P2.3*	Batteries and accum design of the product	ulators are easily removable by either users or service providers (a t). Exception: Batteries that are permanently installed for safety, pr ons do not have to be "easily removable". (See legal reference)	s dependent on th	ie 🔀			
P3		ction to the telephone network and labeling					
P3.1*		s with legally required safety standards as specified (see legal refe	rence).				
P3.2*	The product complies reference).	s with legally required standards for electromagnetic compatibility (	see legal				
P3.3*	If product is intended	I for connection to a public telecom network or contains a radio trar standards for radio and telecommunication devices (see legal refer		es 🔀			
P3.4*		d to show conformance with applicable legal requirements (see leg		$\square$			
P4	Consumable materi	als		<u> </u>			
P4.1*	If a photo conductor legal reference and N	(drum, belt etc.) is used in the product, it does not contain cadmiur lote B1).	n max 0.01% (see	•			
P4.2*		the product, it does not contain cadmium max 0.1% by weight (se	e legal reference).	$\boxtimes$			
P4.3*	product/packaging is	lation/preparation is classified as hazardous according to applicabl adequately labeled and a Safety Data Sheet (SDS) in accordance able (see legal reference).	0 /				
P5	Product packaging						
<b>P5</b> P5.1*	Packaging and pack	kaging components do not contain more than 0.01% lead, mer n by weight of these together.	cury, cadmium a	nd 🔀			
	Packaging and pack hexavalent chromium			nd 🔀			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu		CS410dn, CS410dtn, CS410n						
Issue date *		Rev. June 24, 2015 Logo	L	EXM	ARK	TM		
Broduct	onviron	montal attributes. Market requirements. Environmental conscious design	D	oquiro	mont	mot		
Item		mental attributes - Market requirements - Environmental conscious design atory to fill in. Additional information regarding each item may be found under P14.	п	equire Yes	No			
P6		nt information		165	NU	n.a.		
P6.1*		ion for recyclers/treatment facilities is available (see legal reference).						
P7	Design							
F <i>1</i>		mbly, recycling						
P7.1*	Parts that							
P7.2*				H	H			
P7.3*	Plastic materials in covers/housing have no surface coating.       Image: Construction of the second s							
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.			╞	╞		
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly available	a tools		╶╞┽	╶┝┤		
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).	5 10013.		<u> </u>	<u> </u>		
F7.0								
P7.7*		lifetime ng can be done e.g. with processor, memory, cards or drives						
P7.8*		ig can be done using commonly available tools			<u> </u>	- 님-		
				$\boxtimes$		<u> </u>		
P7.9.		arts are available after end of production for: 5 years				<u> </u>		
P7.10		s available after end of production for: 5 years						
		and substance requirements						
P7.11*		cover/housing material type:						
P7.12		type: ABS Material type: HIPS Material type: I I cable insulation materials of power cables are PVC free.	C/ABS					
				<u> </u>		⊢⊢		
P7.13		I cable insulation materials of signal cables are PVC free		<u> </u>		<u> </u>		
P7.14		/housing plastic parts >25g are free from chlorine and bromine.		<u> </u>		<u> </u>		
P7.15	Note B2		-21. (See					
P7.16	Marking:	etarded plastic parts >25g in covers / housings are marked according ISO 1043-4:						
P7.17		al specifications of flame retardants in printed circuit boards >25g (without components): (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:						
	ISO 104	Il specifications of flame retardants in printed circuit boards (without components) >25g act 3-4: <i>FR(16)</i>	cording					
P7.18		etarded plastic parts >25g contain the following flame retardant substances/preparations above 0.1%:	ations in					
	1. Chem 2. Chem	ent: No legal limits exist, this is a market requirement. ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:						
	Alt. 2 Chemica FR(40),	Il specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50)						
P7.19	R40, R4	arts >25g are free from flame retardant substances/ preparations above 0.1% classified as 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	s R45,					
P7.20		plastic parts' weight >25g, recycled material content is <i>up to 11%</i> .						
P7.21		blastic parts' weight >25g, biobased material content is %.						
P7.22	If mercu	arces are free from mercury ry is used specify: Number of lamps: and max. mercury content per lamp: mg	9					
P8	Batterie							
P8.1*		chemical composition: Lithium Manganese Dioxide, LiMnO2				<u> </u>		
P8.2	Batteries	meet the requirements of the following voluntary program/s:						

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model num											
Issue date	*	Rev. June 24, 2015									
Product environmental attributes - Market requirements (continued) Requirement met											
	environn	nental att	ributes - Market re	quirements (coi	ntinued)			R	equir Yes	rement No	
Item P9	Enormy	oncumnti	on.						res	5 INO	n.a.
P9         Energy consumption           9.1         For the product the following power levels or energy consumptions are reported:											
-							ence /	Ctondord	for	000501	
Energy mo	ue		100 V AC	115 V AC	230 V AC		s and test		for	energy	
Printing			537 W	<b>529</b> W	<b>504</b> W	Corpo	orate Stan	dard			
Ready Mod			26.8 W	27.4 W	<b>27.0</b> W		gy Star I E				
Sleep Mod	le		<b>2.9</b> W	<b>2.9</b> W	<b>2.9</b> W	Energ	yy Star I E	V2.0			
Hibernate	Mode		0.35 W	0.37 W	0.39 W	IEC 6	2301				
Off Mode			0.0 W	0.0 W	0.0 W	IEC 6	2301				
			W	W	W						
EPS No-loa	ad		W	W	W						$\square$
(External p charger plu outlet but d the product	gged in th	ne wall									
PTEC *	0		W	W	W						$\square$
Typical Ene	ergy Cons	sumption									
TEC *			2.5 kWh/week	2.4 kWh/week	2.4 kWh/week	Energ	y Star I E	V2.0			
Typical Ene	ergy Cons	umption									
Etec *			kWh/year	kWh/year	kWh/ye	kWh/year					$\square$
Annual Ene	ergy Cons	umption									
Display res	olution*	Me	gapixels								
Print Speed			s per minute			150.2	4734 (US	( ottor)			
		0	•								
			ve mode: 30 minutes			Energ	yy Star I E	V2.0			
P9.2*			ne energy save functio	•	•				$\boxtimes$		
P9.3*			the energy requiremer ersion: 2.0 Tier: Prod			n/s:					
			L-UZ 122/RAL-UZ 171		ing Equipment					H	H
P10	Emissio	ns									
_			Declared according to	ISO 9296							
P10.1	Mode Mode description			Declared A-weighted			A-weighted				
					sound power	sound	l pressure				
				level $L_{WAd}$ (B)	Operator po	sition 🗌	Bystan	der po	ositions		
							sktop	(only if p	oroduc	t is not	
						or Desl	< side			tended)	
	Idle		Ready		* 3.2			16			
	Operatio		Duplex Mono Printing		* 6.6	51					
	Other mo		Duplex Mono Printing	_	6.2			48			
	Measure	d according		ECMA-74							
P10.2	The proc	luct monto	Other the acoustic noise req	(only if not covered					m	<u>)</u>	
1 10.2	UZ 171	act meets	The accusult house leq		nowing voluntary	piogram/s. r	ML-UZ 12	Z/NAL-	$\square$		

Model nu	Model number * CS410dn, CS410dtn, CS410n								
Issue date	e *	Rev. June 24, 2015	Logo	EXM	RK				
Product	Product environmental attributes - Market requirements (continued) Requirement me								
Item				Yes	No	n.a.			
P10.3*		al emissions from printing products							
	171	formed according to ECMA-328 (ISO/IEC 28360) standard , other specify: <b>RAL</b>	-UZ 122/RAL-UZ						
P10.4		emission rate (print phase) is (mg/h):	100 10						
P10.5		Dust <1.8 (BQL) Ozone <0.3 (BQL) Styrene 0.55 Benzene <0.05 (BQL) TV al emission requirements of the following voluntary program/s RAL-UZ 122/RAL-U		$\square$					
F 10.5									
		Dust 🛛 Ozone 🖂 Styrene 🖂 Benzene 🖂	TVOC 🔀						
P10.6		magnetic emissions er display meets the requirement for low frequency electromagnetic fields of the fol	llowing voluntary						
	program		lietung telanany						
P11		nable materials for printing products							
P11.1*	A Safety	/ Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	uired (see P4.3).	$\square$					
P11.2*	Paper c EN1228	containing post-consumer recycled fibers can be used, provided that it meets that.	ne requirements of						
P11.3*	2-sided	(duplex) printing/copying is an integrated product function.		$\boxtimes$					
P12		mics for computing products							
P12.1*	The disp	play meets the ergonomic requirements of ISO 9241-307 for visual display technology	ogies.			$\square$			
P12.2*	The phy	sical input device meets the requirements of ISO 9995 and ISO 9241-410.				$\boxtimes$			
P13		ing and documentation							
P13.1*	Product	packaging material type(s): <i>Corrugated</i> weight (kg): 2.542 packaging material type(s): <i>Polystyrene, expanded</i> weight (kg): 0.204 packaging material type(s): <i>High Density Belivethylana</i> weight (kg): 0.277							
		packaging material type(s): <i>High Density Polyethylene</i> weight (kg): 0.277 <i>nsity Polyethylene, expanded – 0.204 kg</i>							
P13.2*		plastic packaging is free from PVC.		$\boxtimes$					
P13.3*	Specify	media for user and product documentation (tick box): ic $\square$ , Paper $\square$ , Other $\square$							
P13.4*	For pape	er user and product documentation, please specify contained percentage of post-co	onsumer recycled						
Rev.	fiber: 0 User an	//o d product documentation do not contain chlorine bleached paper							
P13.5 P14	Additio	nal information (See Note B4)							
P1. 1		duct uses RoHS exemptions for lead used in small amounts for specific applications.							
P2.1	The batt	ery contained within this product should be disposed of properly with the product. The p symbol and instructions for such disposal is listed in the product User's Guide.	roduct is properly la	beled with	the W	EEE			
P2.3		ery contained within this product meets the exception listed. The battery is not intended , is designed for easy removal by recyclers and service providers.	l to be removed by t	he custom	er;				
P7.14		amount of bromine may be present in covers due to sourcing post consumer recycled com ocessing of these parts.	tent. No bromine w	as intentio	nally a	dded			
P7.20	Per IEEE	1680.2 PCR calculation.							
P9.1		tion provided in P9.1 is for products with firmware FW LW30.VY2.P300 or higher. Print sp wing table provides energy data for products with lower levels of firmware:	eed listed is Letter; /	A4 speed i	s 30 pp	m.			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

	P9         Energy consumption           9.1         For the product the following power levels or energy consumptions are reported:						
	Energy mode *	Power level at	Power level at	Reference / Standard for energy			
	<b>D</b> 1 4	100 V AC	115 V AC	230 V AC	modes and test method *		
	Printing Ready Mode	537 W 26.6 W	529 W 27.9 W	504 W 25.0 W	Corporate Standard Energy Star I E V1.2		
	Sleep Mode	4.8 W	4.9 W	4.9 W	Energy Star I E V1.2		
	Hibernate Mode	0.35 W	0.37 W	0.39 W	IEC 62301		
	Off Mode	0.0 W	0.0 W	0.0 W	IEC 62301		
		W	W	W			
	EPS No-load	W	W	W			
	(External power supply /						
	charger plugged in the wall outlet but disconnected from the product.)						
	PTEC * Typical Energy Consumption	W	W	W			
	TEC * Typical Energy Consumption	2.7 kWh/week	2.6 kWh/week	2.6 kWh/week	Energy Star I E V1.2		
	ETEC * Annual Energy Consumption	kWh/year	kWh/year	kWh/year			
	Display resolution* : Me	gapixels		1			
	Print Speed * : 32 Images				Corporate Standard		
	Default time to enter energy sav				Energy Star I E V1.2		
	P9.2* Information about th	e energy save function	n is provided with th	e product.			
		he energy requiremen ersion: 1.2 Tier: 1 Pro UZ 122				R	
P10.1	Duplex data does not a	oply to the CS41	On model.				
P10.4	Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone – <0.3 mg/h (BQL); Styrene - <0.3 mg/h (BQL); Benzene – <0.05 mg/h (BQL); Dust –<1.8 mg/h (BQL) ; and TVOC – 10 mg/h BQL = Below Quantifiable Limit						
P11.3	Duplex is not an integra	ited product fun	ction of the C	5410n model.			
P13.1	Packaging for CS410n and CS410dn displayed in 13.1 Packaging for CS410dtn: Product packaging material type(s): Corrugated weight (kg): 2.385 Product packaging material type(s): Polystyrene, expanded weight (kg): 0.304 Product packaging material type(s): High Density Polyethylene weight (kg): 0.277 Low Density Polyethylene, expanded – 0.204 kg Polypropylene - 0.065						
	Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle Lexmark Sweden is connected to REPA and El-kretsen						

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19