G-Shot P536



True 5.0 mega pixel Super CCD with 3X Optical zoom

G-Shot[™] P536 is a high performance digital camera from the Genius DSC family. The 5.0 mega pixel Super CCD enhances high resolution image quality. Total 12X zoom (3X optical zoom and 4X digital zoom) lets you bring distant objects closer.

G-Shot[™] P536 supports 12 kinds of scenic modes. Whether it is at night or you want to capture firework displays or even text, you will be impressed by the shooting results using all the options available. The bright 2.5" LTPS LCD lets you create a better image, plus, with 17 types of photo frames available, you can create funny pictures right away without complicated editing.

The elegant G-Shot[™] P536 has more innovative features like voice memo for photo, high speed USB 2.0 Web Cam and so on. Check out the following details to learn more about it. Then ask your salesperson how you can start selling the G-Shot P536.







PictBridge



Selling Points





True 5.0 Mega Pixel Super CCD

Equipped with a 5.0 Mega pixel CCD, this camera is capable of capturing images with a resolution of up to 2560 x 1920 pixels.

II 3X Optical Zoom

3x optical zoom allows capturing distant subjects closer and lets you frame shots for better composition.





	 2.5" LTPS LCD display 2.5" Full color LTPS LCD (230K pixels) monitor makes it easy to frame your subject when capturing images. It also displays the images you have captured.
	The Photo Frame Function You can select a photo frame before shooting. There are 17 types of frame-like borders already stored in the camera.
	 Voice memo A voice memo can be recorded once for 30 seconds in photography mode immediately following a still image capture or playback mode while viewing the images.
PictBridge DIRECT PRINT	 Direct Print function Connect to any PictBridge™ compatible printer with the supplied USB cable and print directly from the camera. Images can be viewed and selected for printing right on the camera's LCD, with menus for print quantity, date and index print.
	DPOF function Supports DPOF (Digital Print Order Format), makes printing your pictures extremely easy.

Multi-Scene Selection Modes

Select the scene mode suitable for the occasion or situation.

Scene mode	Description
[P] Program AE	Select this mode to capture images without having to set special functions or manual adjustments. However, this useful mode also allows you to make changes on camera settings to suit the photographic condition.
[💌] Panorama	Select this mode to take a series of shots then stitch them together with software to make a single photo.
[🛆] Portrait	Select this mode when you want to capture an image that makes the person stand out against a defocused (blurred) background.

www.geniusnet.com





Scene mode	Description
[🔺] Landscape	Select this mode to capture an image with infinity focus, hard sharpness and high saturation.
[🛠] Sport	Select this mode when you want to photograph fast-moving subjects.
[🎾] Night	Select this mode when you want to capture people in an evening or night scene background.
[🎬] Candlelight	Select this mode when you want to capture photos of a candlelit scene, without spoiling the atmosphere.
[TEXT]Text	Select this mode when you want to capture an image that contains black and white subjects like printed documents.
[🚖] Sunset	Select this mode when you want to capture photos of a sunset. This mode helps keep the deep hues in the scene.
[🚢] Sunrise	Select this mode when you want to capture photos of a sunrise. This mode helps keep the deep hues in the scene.
[继] Splash	Select this mode when you want to capture photos of splashing water.
[🏶] Fireworks	Select this mode when you want to capture fireworks clearly with optimal exposure. The shutter speed becomes slower, so using a tripod is recommended.

Bundled Software



Ulead Photo Explorer

Ulead® Photo Explorer 8.0 lets you spend more time enjoying photos, music and videos and less time finding them. It's the all-in-one solution for owners of digital cameras, camcorders, scanners or anyone who wants to make it easier to keep track of their media

Ulead Photo Express

Ulead® Photo Express® 5 is home photo creativity software that makes it easy to edit and share digital photos and create fun photo projects. Edit and enhance images, browse your photo collection and express your creativity with stunning special effects and creative photo projects.







Ulead® COOL 360SE is photo panorama software that combines ease-of-use, power and flexibility to allow even novice digital imaging enthusiasts to move beyond traditional photos into immersive imaging.

System requirements for USB Terminal	Package Contents
 Recommended environment for USB terminal: Windows[®] environment IBM PC Pentium II 400 compatible or higher Minimum 128MB hard disk drive space Windows XP/Me/2000/98SE Available USB port CD-ROM drive for software installation Mac environment Mac OS 9.0 or later CD-ROM drive for installation 	 Digital camera USB cable AV cable One Rechargeable Lithium Ion Battery AC Power Adapter AC Plug Adaptor for EU to US Battery Charger CD driver includes: USB Driver for Windows 98/98SE Web cam Driver for Windows Ulead Photo Explorer Ulead Photo Express Cool 360SE Multi-Language User's Manual Multi-Language Quick Guide Pouch and strap

Specifications

Item	Description			
Image sensor	1/2.5" CCD sensor			
Effective pixels	5.0 Mega pixels			
lana na shuttan	<still image=""> 2560x1920, 2048x1536, 1280x960, 640x480</still>			
Image resolution	< Video clip> 320x240/20fps			
LCD monitor 2.5" LTPS color LCD (High-resolution 230K pixel display)				
Departing modia	16 MB internal memory (9 MB for image storage)			
Recording media	Supports SD card (up to 1GB)			
Compression format	JPEG (Still image), Motion JPEG (AVI)			





Item	Description				
	F-no.: Wide: 2.8 / Tele: 4.8				
Lens	Focal length: 5.4mm~16.2mm (Equivalent 35 mm				
	camera: 32-96mm)				
	Normal: 50 cm-infinity,				
Focus range	Marco : Wide: 5 cm -Infinity / Tele: 35 cm -Infinity				
Self-timer	2 sec delay, 10 sec delay, 2+10 sec delay				
Exposure compensation	-2.0EV~ +2.0EV (in 0.3EV increments)				
White balance	Auto, Incandescent, Fluorescent 1, Fluorescent 2, Day				
	Light, Cloudy, Manual				
ISO	64, 100, 200, Auto				
Power supply	Lithium-ion rechargeable battery (3.7V, 650mAh)				
OSD language	English, Russian, Spanish, Italian, Arabic, Traditional Chinese				
Giftbox language	English, Russian, Italian, Spanish, Portuguese, Czech, Polish,				
	Arabic, Greek, Traditional Chinese				
Multi-Language User's Manual	English, Russian, Italian, Spanish, Portuguese, Czech, Polish,				
	Arabic, Greek, Traditional Chinese				
Multi-Language Quick Guide	English, Russian, Spanish, Italian, Arabic, Traditional Chinese				
WEEE Information					
Body Weight (g)	Approx. 120 g (without the battery and SD memory card)				
Body Dimension (LxWxH mm)	Approx. 90 x 55 x 25 mm (excluding protruding parts)				
Gift-Box Dimension	240 × 140 × 77 mm				
(LxWxH mm)	210 x 149 x 77 mm				
Shipping Information					
PCs / Carton	10 pcs / Carton				
CUFT:	1.3181cuft / CTN				
Dates available					
Sample available	September 29, 2006				
Mass Production	September 29, 2006				
Product number	32300050101				





Possible number of shots (still image)

The table shows the approximate shots that you can capture at each setting based on the capacity of the internal memory and the SD card. Built-in 16MB internal memory (9 MB available for image storage)

Image		16 MB	SD card capacity					
size	Quality	Internal Memory	64MB	128MB	256MB	512MB	1GB	
2560	Fine	3	22	44	90	181	362	
х	Standard	6	44	89	179	359	720	
1920	Economy	10	66	134	270	543	1087	
2048	Fine	5	34	69	138	278	558	
x	Standard	10	67	137	275	552	1106	
1536	Economy	16	102	207	416	836	1674	
1280	Fine	13	84	170	342	687	1377	
x	Standard	25	165	333	670	1345	2694	
960	Economy	39	253	512	1028	2063	4131	
640	Fine	49	316	640	1285	2579	5164	
x 480	Standard	98	633	1280	2571	5158	10328	
	Economy	148	950	1920	3857	7738	15493	

Possible recording time (video clip)

		16 MB	SD card capacity				
Image size	Quality	Internal Memory	64MB	128MB	256MB	512MB	1GB
320 x 240	Standard	00'41"	04'32"	09'12"	18'31"	37'09"	74'25"

* The data shows the standard testing results. The actual capacity varies according to the shooting conditions and settings.

Product Family



Web Cam and Video Product Family

		9			
Look 313Media	Look 320S	Slim 322	Look 1320	IPCam SECURE300W	T02Q
Web CAM	Web CAM	Web CAM	Web CAM	IP CAM	Video