

y user manual on CD: Czech, Danish, Dutch, English, French, German, Greek, Hungarian, Italian, ian, Polish, Spanish, Swedish, Brazilian Portuguese  
Information Guide in: English, French, Italian, German, Spanish, Brazilian Portuguese, Iberian ese, Danish, Dutch, Finnish, Norwegian, Swedish, Czech, Greek, Polish, Arabic, Hebrew, Hungarian, Slovak, Slovenian, Romanian  
50950-1 (International); IEC60825-1 (Laser); CE Mark (EU); GS Mark (Germany); SASO (Saudi Arabia); outh Africa); UL/cUL Listed (UL60950-1 US/Canada); FDA/DHHS (21CFR, Chapter 1, Subchapter J, \_aser, US); NOM (Mexico); CCC (China); other safety approvals required by individual countries.  
2 Class B; EN61000-3-2; EN 61000-3-3; EN55024; FCC CFR Title 47, Part 15 Class B (USA); ICES- rada); CE (EU countries); GOST (Russia); SABS (South Africa); CCC (China); C-tick (Australia); and other tions required by individual countries.  
Star® v1.2-qualified<sup>9</sup>; RoHS<sup>10</sup>, ErP Lot 4, ErP Lot 6, WEEE, SAP, WHQL

actly from Android mobile devices via Dell Mobile Print app<sup>5</sup>, or from an iPad®, iPhone®, iPod touch® to rint™-enabled printer<sup>4</sup>. You can also print on the go from your Smartphone or computer via compatible Cloud Print apps.

**nter Manager:** helps easily customise the printer's settings; **Dell Supplies Ordering Utility:** intelligently s toner status and proactively notifies the user in advance of running out of toner; **Firmware Download** effectively manages firmware updates; **Lite StatusMonitor:** tracks printer status  
**t via browser:** Microsoft Internet Explorer, 6, 7, 8, 9 and later; Apple Mac OS X Safari 1.0 and later veloper beta); Mozilla Firefox 2.x, 3.x, 4.x and 5.x; Google Chrome 9, 10; Opera 9.x and later;  
**atures:** Printer Configuration, Network Setup, Paper Setup, Report, Firmware, Update, gin/Password

ars Next Business Day On-site Service After Remote Diagnosis<sup>7</sup>  
irs Dell ProSupport™ available during the term of warranty

348 mm (W) x 338 mm (D) x 197 mm (H)  
y carton: 458 mm (W) x 423 mm (D) x 279 mm (H)  
7.2 kg (with toner); 6.5 kg (without toner)  
y carton: 8.6 kg  
rg: air temperature 10 to 32°C, Relative Humidity 20 - 80%, altitude 2,500 m  
(unpackaged): air temperature 0 to 40°C, Relative Humidity 10 - 80%  
(packaged): air temperature -20 to 40°C, Relative Humidity 20 - 95%, altitude 10,500 m  
(Simplex Mode/Main Tray): Sound pressure less than 50 dBA  
Mode: Sound Pressure less than 30 dBA (after more than 30 pages printing)  
models: 220 - 240 volts (V) at 50/60 ± 3 hertz (Hz) nominal.  
mode less than 45 W: Power saver mode less than 1.2 W: Off less than or equal to 0.5 W,  
Star® v1.2-qualified<sup>9</sup>

CD, Product Information Guide, placemat, power cord, retail warranty card, 1,000 page<sup>3</sup> black h toner

er), and iPod touch (3rd generation or later) running iOS 4.2 or later. iPad, iPhone, iPod, and iPod touch are trademarks of Apple Inc., mark of Apple Inc.  
ygy. Actual print speeds will vary with use.  
ogy. Yields vary with usage and environmental conditions  
y, Dell House, The Boulevard, Cain Road, Bracknell, Berkshire, RG12 1LF, UK or see [www.dell.com/warranty](http://www.dell.com/warranty). For warranty information for ts and then select the country  
mpletion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.  
e same wireless network.  
re information, visit [www.dell.com/servicesdescriptions](http://www.dell.com/servicesdescriptions)

ducts, refer to: <http://www.energystar.gov>

## laser printer



## Help boost productivity for small to medium business workgroups

### Get outstanding performance with the Dell B1260dn laser printer

Compact in design, the affordably priced Dell™ B1260dn printer offers outstanding performance with its low cost per page, excellent print quality and productivity features. Help boost productivity with its fast print speed, built-in duplexer, Ethernet networking, and a high duty cycle of up to 100,000 pages per month.

Easy-to-use and maintain, this laser printer is built with a fuser unit that is designed so the only part that has to be installed is the single black toner cartridge. The D1260dn offers the flexibility of printing from various mobile devices — print directly from Android mobile devices or from an iPad®, iPhone®, iPod touch® to this AirPrint™-enabled printer<sup>4</sup>. You can also print from your computer via compatible Cloud Print apps.

rinting, excellent  
rnet networking.  
r minute (ppm)<sup>2</sup> (A4),

its with crisp black  
0 dpi resolution

n can easily be shared  
ork

irectly from your

ng the

iPod touch® to this

u can print on the go  
sing Google Cloud Print

### Reliable and easy to maintain

Get reliable performance with this robust printer that is easy-to-use and maintain.

- Count on reliable performance with its large maximum duty cycle of up to 20,000 pages a month
- Print up to 2,500 pages with the high yield cartridge and up to 1,500 pages with the standard yield cartridge<sup>3</sup>
- Reduce work disruptions and save on maintenance costs with a fuser unit that is designed to last the life of the printer.

### Environmentally conscious

- This Energy Star qualified<sup>9</sup> printer has low energy consumption without compromising on print speeds.
- ECO Mode Button
  - Save toner and paper with one touch of the Eco button. It automatically engages two-sided printing and reduces toner usage by printing in draft mode.
- Reduce, Recycle, Renew
  - Reduce paper usage with automatic two-sided printing.

### Outstanding service and warranty

Gain peace of mind with Dell's standard 1-Year Limited Hardware Warranty<sup>4</sup> and 12 months Next Business Day On-Site Service After Remote Diagnosis.<sup>7</sup> Protect your investment even longer with an optional Limited Hardware Warranty extension for up to five years.<sup>4</sup>

### Printer specifications

Print speed	Up to 28 pages per minute (ppm) <sup>2</sup> (A4), (actual print speed will vary)
First page out time	From 'Ready' mode: Less than 8.5 seconds; From 'Sleep' mode: Le
Print resolution	600 x 600 dpi (printer default); 1200 x 1200 dpi max
User interface	Four-button operational panel
Data streams	SPL, PCL 6 (V2.1)
Processor	ARM11 (533 MHz)
Memory (RAM)	64 MB DDR2 667 MHz
Memory expansion	Not available
Maximum duty cycle	Up to 20,000 pages per month
Average monthly usage rate	208 pages per month

### Paper handling

Standard input sources	250 sheet cassette
Additional input capacity	1 sheet multipurpose tray
Maximum input capacity	251 sheets
Duplex unit	Standard two-sided printing
Standard output destination	150 sheet bin

### Supported media types, sizes and paper weights

Media types supported	1 sheet multipurpose tray: plain, thin, thick, thicker, bond, card stock, archive, transparency, label, envelope, thick envelope; Standard tray: recycled, archive
250 sheet standard tray	Media size: A4, A5, A6, US letter, US legal, executive, folio, Oficio, IS; Weight: 60 to 163g/m <sup>2</sup>
Multipurpose tray	Media size: A4, A5, A6, US letter, US legal, Oficio, folio, ISO B5, JIS 1; DL envelope, C5 envelope, C6 envelope, No. 10 envelope, postcard; Weight: 60 to 220g/m <sup>2</sup>
Duplexer	Media sizes: A4, US letter, US legal, Oficio, folio; Media types: Plain paper, thin, thick, recycled; Weight: 60 to 120g/m <sup>2</sup>
Page layout options	Portrait or landscape orientation
Printable area	Within 4.32 mm of all edges of the media

### Connectivity

Standard interfaces	High-speed USB 2.0; Ethernet 10/100 Base TX
Print languages	SPL, PCL6, Host based XPS, XPS driver can be supported by either
Print fonts	HP PCL® 6 Emulation: 93 scalable, 1 bitmap font
Operating Systems (OS) support	Microsoft® Windows® 7 (32/64 bit), Windows® 2000/XP (32/64 bit), Windows® Server® (32/64 bit) / 2008 Windows Server (32/64 bit), Windows® 2003, 4, 5, 6 (32/64 bit), Linux: RedHat® Enterprise Linux® WS 4, 5, 6 (32/64 bit), 14, 15, SuSE Linux 10.1 (32 bit); OpenSUSE 10.2, 10.3, 11.0, 11.1, 11.2, 11.3, 11.4, 11.5, 11.6, 11.7, 11.8, 11.9, 12.0, 12.1, 12.2, 12.3, 12.4, 12.5, 12.6, 12.7, 12.8, 12.9, 13.0, 13.1, 13.2, 13.3, 13.4, 13.5, 13.6, 13.7, 13.8, 13.9, 14.0, 14.1, 14.2, 14.3, 14.4, 14.5, 14.6, 14.7, 14.8, 14.9, 15.0, 15.1, 15.2, 15.3, 15.4, 15.5, 15.6, 15.7, 15.8, 15.9, 16.0, 16.1, 16.2, 16.3, 16.4, 16.5, 16.6, 16.7, 16.8, 16.9, 17.0, 17.1, 17.2, 17.3, 17.4, 17.5, 17.6, 17.7, 17.8, 17.9, 18.0, 18.1, 18.2, 18.3, 18.4, 18.5, 18.6, 18.7, 18.8, 18.9, 19.0, 19.1, 19.2, 19.3, 19.4, 19.5, 19.6, 19.7, 19.8, 19.9, 20.0, 20.1, 20.2, 20.3, 20.4, 20.5, 20.6, 20.7, 20.8, 20.9, 21.0, 21.1, 21.2, 21.3, 21.4, 21.5, 21.6, 21.7, 21.8, 21.9, 22.0, 22.1, 22.2, 22.3, 22.4, 22.5, 22.6, 22.7, 22.8, 22.9, 23.0, 23.1, 23.2, 23.3, 23.4, 23.5, 23.6, 23.7, 23.8, 23.9, 24.0, 24.1, 24.2, 24.3, 24.4, 24.5, 24.6, 24.7, 24.8, 24.9, 25.0, 25.1, 25.2, 25.3, 25.4, 25.5, 25.6, 25.7, 25.8, 25.9, 26.0, 26.1, 26.2, 26.3, 26.4, 26.5, 26.6, 26.7, 26.8, 26.9, 27.0, 27.1, 27.2, 27.3, 27.4, 27.5, 27.6, 27.7, 27.8, 27.9, 28.0, 28.1, 28.2, 28.3, 28.4, 28.5, 28.6, 28.7, 28.8, 28.9, 29.0, 29.1, 29.2, 29.3, 29.4, 29.5, 29.6, 29.7, 29.8, 29.9, 30.0, 30.1, 30.2, 30.3, 30.4, 30.5, 30.6, 30.7, 30.8, 30.9, 31.0, 31.1, 31.2, 31.3, 31.4, 31.5, 31.6, 31.7, 31.8, 31.9, 32.0, 32.1, 32.2, 32.3, 32.4, 32.5, 32.6, 32.7, 32.8, 32.9, 33.0, 33.1, 33.2, 33.3, 33.4, 33.5, 33.6, 33.7, 33.8, 33.9, 34.0, 34.1, 34.2, 34.3, 34.4, 34.5, 34.6, 34.7, 34.8, 34.9, 35.0, 35.1, 35.2, 35.3, 35.4, 35.5, 35.6, 35.7, 35.8, 35.9, 36.0, 36.1, 36.2, 36.3, 36.4, 36.5, 36.6, 36.7, 36.8, 36.9, 37.0, 37.1, 37.2, 37.3, 37.4, 37.5, 37.6, 37.7, 37.8, 37.9, 38.0, 38.1, 38.2, 38.3, 38.4, 38.5, 38.6, 38.7, 38.8, 38.9, 39.0, 39.1, 39.2, 39.3, 39.4, 39.5, 39.6, 39.7, 39.8, 39.9, 40.0, 40.1, 40.2, 40.3, 40.4, 40.5, 40.6, 40.7, 40.8, 40.9, 41.0, 41.1, 41.2, 41.3, 41.4, 41.5, 41.6, 41.7, 41.8, 41.9, 42.0, 42.1, 42.2, 42.3, 42.4, 42.5, 42.6, 42.7, 42.8, 42.9, 43.0, 43.1, 43.2, 43.3, 43.4, 43.5, 43.6, 43.7, 43.8, 43.9, 44.0, 44.1, 44.2, 44.3, 44.4, 44.5, 44.6, 44.7, 44.8, 44.9, 45.0, 45.1, 45.2, 45.3, 45.4, 45.5, 45.6, 45.7, 45.8, 45.9, 46.0, 46.1, 46.2, 46.3, 46.4, 46.5, 46.6, 46.7, 46.8, 46.9, 47.0, 47.1, 47.2, 47.3, 47.4, 47.5, 47.6, 47.7, 47.8, 47.9, 48.0, 48.1, 48.2, 48.3, 48.4, 48.5, 48.6, 48.7, 48.8, 48.9, 49.0, 49.1, 49.2, 49.3, 49.4, 49.5, 49.6, 49.7, 49.8, 49.9, 50.0, 50.1, 50.2, 50.3, 50.4, 50.5, 50.6, 50.7, 50.8, 50.9, 51.0, 51.1, 51.2, 51.3, 51.4, 51.5, 51.6, 51.7, 51.8, 51.9, 52.0, 52.1, 52.2, 52.3, 52.4, 52.5, 52.6, 52.7, 52.8, 52.9, 53.0, 53.1, 53.2, 53.3, 53.4, 53.5, 53.6, 53.7, 53.8, 53.9, 54.0, 54.1, 54.2, 54.3, 54.4, 54.5, 54.6, 54.7, 54.8, 54.9, 55.0, 55.1, 55.2, 55.3, 55.4, 55.5, 55.6, 55.7, 55.8, 55.9, 56.0, 56.1, 56.2, 56.3, 56.4, 56.5, 56.6, 56.7, 56.8, 56.9, 57.0, 57.1, 57.2, 57.3, 57.4, 57.5, 57.6, 57.7, 57.8, 57.9, 58.0, 58.1, 58.2, 58.3, 58.4, 58.5, 58.6, 58.7, 58.8, 58.9, 59.0, 59.1, 59.2, 59.3, 59.4, 59.5, 59.6, 59.7, 59.8, 59.9, 60.0, 60.1, 60.2, 60.3, 60.4, 60.5, 60.6, 60.7, 60.8, 60.9, 61.0, 61.1, 61.2, 61.3, 61.4, 61.5, 61.6, 61.7, 61.8, 61.9, 62.0, 62.1, 62.2, 62.3, 62.4, 62.5, 62.6, 62.7, 62.8, 62.9, 63.0, 63.1, 63.2, 63.3, 63.4, 63.5, 63.6, 63.7, 63.8, 63.9, 64.0, 64.1, 64.2, 64.3, 64.4, 64.5, 64.6, 64.7, 64.8, 64.9, 65.0, 65.1, 65.2, 65.3, 65.4, 65.5, 65.6, 65.7, 65.8, 65.9, 66.0, 66.1, 66.2, 66.3, 66.4, 66.5, 66.6, 66.7, 66.8, 66.9, 67.0, 67.1, 67.2, 67.3, 67.4, 67.5, 67.6, 67.7, 67.8, 67.9, 68.0, 68.1, 68.2, 68.3, 68.4, 68.5, 68.6, 68.7, 68.8, 68.9, 69.0, 69.1, 69.2, 69.3, 69.4, 69.5, 69.6, 69.7, 69.8, 69.9, 70.0, 70.1, 70.2, 70.3, 70.4, 70.5, 70.6, 70.7, 70.8, 70.9, 71.0, 71.1, 71.2, 71.3, 71.4, 71.5, 71.6, 71.7, 71.8, 71.9, 72.0, 72.1, 72.2, 72.3, 72.4, 72.5, 72.6, 72.7, 72.8, 72.9, 73.0, 73.1, 73.2, 73.3, 73.4, 73.5, 73.6, 73.7, 73.8, 73.9, 74.0, 74.1, 74.2, 74.3, 74.4, 74.5, 74.6, 74.7, 74.8, 74.9, 75.0, 75.1, 75.2, 75.3, 75.4, 75.5, 75.6, 75.7, 75.8, 75.9, 76.0, 76.1, 76.2, 76.3, 76.4, 76.5, 76.6, 76.7, 76.8, 76.9, 77.0, 77.1, 77.2, 77.3, 77.4, 77.5, 77.6, 77.7, 77.8, 77.9, 78.0, 78.1, 78.2, 78.3, 78.4, 78.5, 78.6, 78.7, 78.8, 78.9, 79.0, 79.1, 79.2, 79.3, 79.4, 79.5, 79.6, 79.7, 79.8, 79.9, 80.0, 80.1, 80.2, 80.3, 80.4, 80.5, 80.6, 80.7, 80.8, 80.9, 81.0, 81.1, 81.2, 81.3, 81.4, 81.5, 81.6, 81.7, 81.8, 81.9, 82.0, 82.1, 82.2, 82.3, 82.4, 82.5, 82.6, 82.7, 82.8, 82.9, 83.0, 83.1, 83.2, 83.3, 83.4, 83.5, 83.6, 83.7, 83.8, 83.9, 84.0, 84.1, 84.2, 84.3, 84.4, 84.5, 84.6, 84.7, 84.8, 84.9, 85.0, 85.1, 85.2, 85.3, 85.4, 85.5, 85.6, 85.7, 85.8, 85.9, 86.0, 86.1, 86.2, 86.3, 86.4, 86.5, 86.6, 86.7, 86.8, 86.9, 87.0, 87.1, 87.2, 87.3, 87.4, 87.5, 87.6, 87.7, 87.8, 87.9, 88.0, 88.1, 88.2, 88.3, 88.4, 88.5, 88.6, 88.7, 88.8, 88.9, 89.0, 89.1, 89.2, 89.3, 89.4, 89.5, 89.6, 89.7, 89.8, 89.9, 90.0, 90.1, 90.2, 90.3, 90.4, 90.5, 90.6, 90.7, 90.8, 90.9, 91.0, 91.1, 91.2, 91.3, 91.4, 91.5, 91.6, 91.7, 91.8, 91.9, 92.0, 92.1, 92.2, 92.3, 92.4, 92.5, 92.6, 92.7, 92.8, 92.9, 93.0, 93.1, 93.2, 93.3, 93.4, 93.5, 93.6, 93.7, 93.8, 93.9, 94.0, 94.1, 94.2, 94.3, 94.4, 94.5, 94.6, 94.7, 94.8, 94.9, 95.0, 95.1, 95.2, 95.3, 95.4, 95.5, 95.6, 95.7, 95.8, 95.9, 96.0, 96.1, 96.2, 96.3, 96.4, 96.5, 96.6, 96.7, 96.8, 96.9, 97.0, 97.1, 97.2, 97.3, 97.4, 97.5, 97.6, 97.7, 97.8, 97.9, 98.0, 98.1, 98.2, 98.3, 98.4, 98.5, 98.6, 98.7, 98.8, 98.9, 99.0, 99.1, 99.2, 99.3, 99.4, 99.5, 99.6, 99.7, 99.8, 99.9, 100.0
Network protocol	TCP/IP; IPv4/IPv6 (Transportation:lpsec, ICMPv6, Printing: Port 9100)

### Consumables

Toner management	Dell Supplies Ordering Utility, intelligently monitors toner status and notifies you when running out of toner
Ship-with toner cartridge capacity <sup>3</sup>	The printer ships with a toner cartridge (approx 1,000 pages)



60dn control panel



Dell B1260dn connectivity



Dell B1260dn high-capacity toner cartridge

rinter with genuine Dell options and supplies