

Model No. : WM-A379

User's Manual

Product Introduction

Thank you for using the new generation digital web cam. This web cam works with a USB port to be connected with PC. It is an ideal web cam for its plug and play and real-time transmission. Its mini size, easily carrying, huge resolution and high speed make you life more colorful and make your long distance communications fresh and vivid.

Technical Specification

- * High Resolution CMOS Color Sensor
- Resolution: 1.3M Pixel (software interpolated)
- Video Format: 24bit True Color
- * Interface: USB2.0

*Transmission Speed:

320*240	30frames/second
640*480	15frames/second
1280*960	10frames/second

- * Dynamic Range: ≥72db
- * Imaging Distance: 5CM to Infinity
- * Built-in Image Compression

- * Automatic White Balance
- * Automatic Colors Compensation
- * Manual Adjusting Focus
- * Manual Snapshot (Snapshot button is necessary for this)

System Requirement

- *IBM PC compatible computer or notebook with USB port
- * Pentium200 or Higher CPU
- * WIN98SE/ME/2000/XP System
- * Hard Drive Remaining Space≥20MB
- * CD—ROM Drive
- * Internal Storage≥68MB
- * VGA Display Card Available for DIRECTX

Driver Installation

1. Put "CD Driver" disk in the CD-Rom and then open "setup new" file and double click "Setup.exe". Wanted files will be automatically installed.

MARKED USER DC Common W Sylin	er Settep
Selar Status	1
UNEXUUSE PCSmmvVSma	a partners the second second
Solding .	
F1. Lorence File/Install/Meth23	phentie-stallagent noe
	228
	- Const 1
	Care

System runs further as displayed.



Click "NEXT"

Histoff Util IV. Camera Villier Setup		
	InstallShield Woord Complete	
10 million (10 mil	Companiation	
	Youhave established the down successfully	
	rich Tault Sutton, then replice canvelal	
	# Yes, I want to actual my computer row	
	C No.) we wrigt by computer later.	
	Remove any data limit that drives, and then disk Frenk to complete using	
	Test	

Click "Finish"

2. Connect web cam to PC by USB port. System finds the new hardware and will automatically install the software as indicated below.



New hardware appears.

System goes further as follow:



Click "NEXT"



Click "Continue Anyway"



Click "Finish"

 Click "Start"— "Process"— "VIMICRO USB PC Camera/AMCAP". You will see your image. You can click "Options" to set the image.



4. Click Video Capture Filter to adjust the effect and setup of web cam.

(and)	
Same Providence	· 王
-	-
	1
-	
	14
10000	
	in the second

5. Double click "ZOOMV". "ZOOMV" appears at the bottom-right corner of the desktop. And then click it once it will come out as picture. You can choose ZOOM to adjust the focus.

Open the webcam icon on the desktop, double click 'ZOOM', which will occur on the bottom-right corner of desktop. Then click this 'ZOOM' icon, the figure will occur as the right figure. Mark 'ZOOM' with' $\sqrt{}$ ', the focus can be adjusted via slipping the slip (adjusting image size).



6. You can select the "Capture / Snap One Image" to take the current picture.



If the computer is of WIN98, ME, 2000 system, Directx9.0 mend process would be necessary for image 1280x960. To return to 800*600 or lower format you will have to re-plug USB port. Web cam can still work as normal without Directx9.0 mend process. Windows XP doesn't need Directx9.0 for 1280*960

Properties	X
Stream Format	
Video Format	Compression
Video Standard: None	
Frame Rate: 30.000	I Frame Intervat
Flip Horizontal	P Frame Interval
Color Space / Compression:	·
P08.24 💌	
Output Size:	Quality:
320 x 240 💌	
160 x 120	
176 x 144	
352 × 200	Carca Adda
640 × 400	Providence of the second second second
800 × 600	CARLES COMMENTS OF ANY ANY ANY

Notice:

- ✤ Don't use fingers or any other sharp or coarse items to touch the camera. Soft cotton cloth is highly recommended to clean the optics parts.
- ✤ Don't use this product when ambience is too hot or cold or dusty.
- ♦ Please avoid this product dropping heavily. Heavily dropping will cause it not to work well.

10