

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5J3 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo.
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	t.html
Additional information		

	pased on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Notebook PC
Commercial name *	Lenovo IdeaPad Flex 10
Model number *	20324; 80CR
Issue date *	2015-01-16
Intended market *	☑ Global Europe Asia, Pacific & Japan Americas Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality (Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	20324; 80CR		
Issue date *	2015-01-16	Logo	lenovo.

Product	environmental attributes - Legal requirements	Require	ment	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal			
P1.2*	reference and Note B1) Products do not contain Asbestos (see legal reference).			
	Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\boxtimes		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-			
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum			
P1.4*	concentration values.			
P1.4	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the			
1 1.5	chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).		ш	
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),			X
	Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).			
	Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split			\boxtimes
	aromatic amines. (See legal reference and Note B1)			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as			\boxtimes
	pentachlorophenol and derivatives (see legal reference).			
D4.0*	Comment: Legal reference has no maximum concentration values.		_	
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).	\boxtimes		Ш
	Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):			
1 1.10	http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment		ш	ш
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains		$\overline{}$	
1 2.1	more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be		ш	ш
	marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is			
	provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or	\square		
	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the	\boxtimes		
	design of the product). Exception: Batteries that are permanently installed for safety, performance, medical			
D2	or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3 P3.1*	Safety, EMC connection to the telephone network and labeling The product complies with legally required safety standards as specified (see legal reference).		$\overline{}$	
			Щ.	Щ.
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	\boxtimes		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies	\boxtimes		
50.44	with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).		Ш	
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\square
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the	\dashv	Ħ	
1 1.0	product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).		Ш	
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and			
-	hexavalent chromium by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal		币	Ħ
	Protocol (see legal reference).			
	Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	20324; 80CR		
Issue date *	2015-01-16	Logo	lenovo.

Product	environmental attributes - Market requirements - Environmental conscious design	Require	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		
P7	Design			
	Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes		
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.	$\overline{\boxtimes}$	$\overline{\sqcap}$	
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.			Ħ
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.			H
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\square	H	-
1 7.0			<u> </u>	
P7.7*	Product lifetime Upgrading can be done e.g. with processor, memory, cards or drives			
			Н	-#-
P7.8*	Upgrading can be done using commonly available tools			_Ц
P7.9.	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type:			
D7.40	Material type: PC+ABS-FR(40) Material type: Material type:			
P7.12	Electrical cable insulation materials of power cables are PVC free.	_ <u>_</u> _	\boxtimes	
P7.13	Electrical cable insulation materials of signal cables are PVC free			
P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.	\boxtimes		
P7.15	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See		\boxtimes	
	Note B2)			
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: <i>FR</i> (40)			
P7.17	Alt. 1			
	Chemical specifications of flame retardants in printed circuit boards >25g (without components):			
	TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
	Alt. 2			
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according			
	ISO 1043-4: Brominated Epoxy Resin See P14	ш	ш	ш
P7.18	Alt. 1			
	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in	ı		
	concentrations above 0.1%:	_	_	_
	Comment: No legal limits exist, this is a market requirement.			
	Provide a list of all used flame retardants including MSDS for each flame retardant. The list must contain			
	complete chemical name, CAS number and supplier. 1. Chemical name: , CAS #: , Supplier:			
	2. Chemical name: , CAS #: , Supplier:			
	3. Chemical name: , CAS #: , Supplier:			
	Alt. 2			
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:			
	FR(40)			
P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,	\boxtimes		
	R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)			
P7.20	Of total plastic parts' weight >25g, recycled material content is 5.2%.			
P7.21	Of total plastic parts' weight >25g, biobased material content is 0%.			
P7.22	Light sources are free from mercury			
P8	Batteries Pottony chemical composition: Lithium Ion/Lithium Manageness Disvide			
P8.1*	Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide			
P8 2	Batteries meet the requirements of the following voluntary program/s: US RBRC			1 1

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *		4; 80CR							
Issue date *	2015-01-	-16			Log	jo	lenov	70 .	
Draduat anviron	mantal at	Market Market	vaguiramanta (ac	nation and			Deguiren	2004	
Item	nentai ai	tributes - Market	requirements (co	ontinuea)			Requirem Yes	No.	n.a.
	consump	tion					103	140	11.4.
9.1 For the	product the	e following power lev		mptions are reporte	ed: See P14		\square		
Energy mode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / So and test method		for energy mo	des	
Peak (On-max)		45 W	45 W	45 W	Full load				
Category A									
Idle State - WOL Er	nabled	4.3W	4.1 W	4.2 W	Use for Energy	Star V	5 registration(Pi	dle)	
Sleep (S3) - WOL E	nabled	W	W	W	Use for Energy	Star V	'5 registration(P	sleep)	
Sleep (S3) - WOL D	Disabled	1.3 W	1.2 W	1.2 W	Reference				
Off (S5) - WOL Ena	bled	0.3 W	0.3 W	0.3 W	Use for Energy	Star V	'5 registration(P	off)	
Off (S5) - WOL Disa	abled	0.251 W	0.247 W	0.280 W	Use for EuP				
EPS No-load		0.075 W	0.076 W	0.117 W					
(External power sup charger plugged in t outlet but disconnec the product.)	he wall								
TEC Typical Energy Cons	sumption	kWh/week	kWh/week	kWh/week					
ETEC * Annual Energy Cons	sumption	14.0 kWh/year	13.4 kWh/year	13.7 kWh/year	$E_{TEC} = (8760/100000000000000000000000000000000000$		$(P_{\rm off} \times 0.6 + P_{\rm sle})$	_{ep} X	
		P _{off} : Off Mode(S5) - I	NOL Enabled; P_{sleep}: 	Sleep Mode(S3) - WO	DL Enabled; P _{idle} : Id	lle State	- WOL Enabled		
Display resolution	1366*76	8 Megapixels							
Print Speed	:	Images per minu	ite					_	
Default time to enter	energy sa	ave mode: 25 minute	S					-	H
		the energy save fund		the product.			\square	П	〒
ENERG	Y STAR®	s the energy requiren version: Version 5.0 pergy Star for Extern	dated July 1, 2009	Product category:	A				
P10 Emissio									
		Declared according	to ISO 9296	Declared	Daal	arad A ·	waightad		
P10.1 Mode		Mode description		Declared A-weighted sound power			weighted vel $L_{p m Am}$ (dB)		
				level $L_{W\!\!\operatorname{Ad}}(B)$	Operator position Desktop or Desk side		Bystander posit (only if product is operator attend	not	
Idle	,	* HDD: Idle		* 3.0		23.7		.54)	ΙП

* 3.0

* HDD: Operating

Measured according to: ISO7779 ECMA-74
Other (only if no

Operation

P10.2

Other mode

m)

26.1

Chem	nmental attributes - Market requirements (continued) lical emissions from printing products performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: all emission rate (print phase) is (mg/h): Dust	Red	quire Yes		
Chem	performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: all emission rate (print phase) is (mg/h): Dust Ozone Styrene Benzene TVOC ical emission requirements of the following voluntary program/s are met for: Dust Ozone Styrene Benzene TVOC ical emission requirements of the following voluntary program/s are met for: Dust Ozone Styrene Benzene TVOC romagnetic emissions uter display meets the requirement for low frequency electromagnetic fields of the following voluntary: MPR-II				n.a.
Chem	performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: all emission rate (print phase) is (mg/h): Dust Ozone Styrene Benzene TVOC ical emission requirements of the following voluntary program/s are met for: Dust Ozone Styrene Benzene TVOC ical emission requirements of the following voluntary program/s are met for: Dust Ozone Styrene Benzene TVOC romagnetic emissions uter display meets the requirement for low frequency electromagnetic fields of the following voluntary: MPR-II				n.a.
P10.3* Test p P10.4 Typica P10.5 Chem Electromagn="	performed according to ECMA-328 (ISO/IEC 28360) standard , other specify: all emission rate (print phase) is (mg/h): Dust Ozone Styrene Benzene TVOC ical emission requirements of the following voluntary program/s are met for: Dust Ozone Styrene Benzene TVOC TOMAGE BENZENE TVOC TOM	Intary			
P10.4 Typica P10.5 Chem Electric P10.6 Comp	al emission rate (print phase) is (mg/h): Dust Ozone Styrene Benzene TVOC ical emission requirements of the following voluntary program/s are met for : Dust Ozone Styrene Benzene TVOC romagnetic emissions uter display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s: MPR-II] untarv			
P10.4 Typica P10.5 Chem Electric P10.6 Comp	al emission rate (print phase) is (mg/h): Dust Ozone Styrene Benzene TVOC ical emission requirements of the following voluntary program/s are met for : Dust Ozone Styrene Benzene TVOC romagnetic emissions uter display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s: MPR-II	Intary			
P10.6 Comp	ical emission requirements of the following voluntary program/s are met for : Dust Ozone Styrene Benzene TVOC romagnetic emissions uter display meets the requirement for low frequency electromagnetic fields of the following volum/s: MPR-II	Intary			
P10.6 Comp	Dust Ozone Styrene Benzene TVOC romagnetic emissions uter display meets the requirement for low frequency electromagnetic fields of the following volum/s: MPR-II	ıntarv			\boxtimes
P10.6 Comp	romagnetic emissions uter display meets the requirement for low frequency electromagnetic fields of the following volu am/s: MPR-II	ıntary			
P10.6 Comp	uter display meets the requirement for low frequency electromagnetic fields of the following volu am/s: MPR-II	ıntarv			
	am/s: MPR-II	ıntarv			
progra		intary			
P11 Cons	umable materials for printing products				
P11.1* A Safe	ety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see F	P4.3).			\boxtimes
P11.2* Paper EN12	containing post-consumer recycled fibers can be used, provided that it meets the requirer 281.	ments of			\boxtimes
P11.3* 2-side	d (duplex) printing/copying is an integrated product function.				\boxtimes
P12 Ergor	nomics for computing products				
P12.1* The d	isplay meets the ergonomic requirements of ISO 9241-307 for visual display technologies.		\boxtimes		
P12.2* The p	hysical input device meets the requirements of ISO 9995 and ISO 9241-410.		\boxtimes		
P13 Packa	aging and documentation				
P13.1* Produ	ct packaging material type(s): Corrugated Carton weight (kg): 0.172				
	ct packaging material type(s): Polyethylene Cushions weight (kg): 0.0225				
P13.2* Produ	ct packaging material type(s): Others weight (kg):0.119 ct plastic packaging is free from PVC.				$\overline{}$
	fy media for user and product documentation (tick box):				井
	onic X, Paper X, Other				Ш
	aper user and product documentation, please specify contained percentage of post-consumer re	cycled			$\overline{}$
	0% (Japan only 70%)	cycleu			ш
	ional information (See Note B4)				
NOT	E: Supplier makes no representations, guarantees, assurances or warranties whether express of	or implied, re	egardi	ng the)
inform	nation contained in this document. All information provided by supplier in this document is provided by supplier in the supplier in the supplier in the supplier in this document is provided by supplier in the supplier in the supplier in the s	ed based or	1 supp	lier's	
	edge available at the time of completion, and supplier shall have no obligation to update such in led here is approximate and provided for informational purposes only. See a Lenovo Account Re				ion
inform		ергеѕептану	e 101 1	liole	
	uct does not contain free TBBPA in printed circuit boards(without components)>25g.				
P9 See E	nergy Star Qualified (insert appropriate Product type; i.e. Desktop, Notebook, etc.) for the	e latest info	rmati	on:	
	/downloads.energystar.gov/bi/qplist/laptops_prod_list.xls (insert appropriate web url)				

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet

- PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo IdeaPad Flex 10	Logo
Model Number	20324, 80CR	_
Issue Date	2015-01-16	lenovo.
Additional information		

(d)	year of manufacture:	2014
(e)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are disabled and if the system is tested with switchable graphics mode with UMA driving the display:	
	Category (according to ErP Lot 3): A Etec: 14.61	
(f)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are enabled:	
	Category (according to ErP Lot 3): NA Etec: NA	
(g)	idle state power demand (Watts);	4.77
(h)	sleep mode power demand (Watts);	0.69
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	NA
(j)	off mode power demand (Watts);	0.28
(k)	off mode with WOL enabled power demand (Watts) (where enabled);	NA
(1)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable):	
	10% 20% 50% 100% Average	
(m)	external power supply efficiency (if applicable):	
	Average 45W: 87.60%,88.32%,87.58%;	
	*internal note: show values for all available external power supplies	
(o)	the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):	300 cycles
(p-1)	the measurement methodology used to determine information mentioned in points (I) – internal PSU	
	efficiency: NA	
(p-2)	the measurement methodology used to determine information mentioned in points (m) – external PSU efficiency:	
	Energy-star requirement	
(p-3)	the measurement methodology used to determine information mentioned in points (o) – loadingcycles batteries:	
	IEC 61960 measurement methodology	

(p-4)	4) the measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:				
				Energy-star requirement	
(q)	sequence of steps for achieving a stable condition with respect to power demand::				
				Based on user manual	
(r)	description of how sleep and/or off mode was selected or programmed:				
				Based on user manual	
(s)	sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:				
				Based on user manual	
(t)	the duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):				
(u)	the length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):				
(v)	the length of time before the display sleep mode is set to activate after user inactivity (in minutes):				
(w) information on the energy-saving potential of power management functionality:					
Based on user manual					
(x) user information on how to enable the power management functionality:					
Based on user manual					
(z) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:					
230V/50Hz, Total Harmonic Distortion <2 %					
Addition N	Notebook Ba	attery Information:			
Yes		No	n/a	This notebook computer is operated by battery/ies that cannot be acce by a non-professional user.	ssed and replaced
(Battery	not user	(Battery user		by a non-professional user.	
replaceabl		replaceable)		The battery[ies] in this product cannot be easily repla	aced by users
			П	themselves	
Additional information					